

Making the railway system
work better for society.

Technical document

TAF TSI — ANNEX D.2: APPENDIX F — TAF TSI DATA AND MESSAGE MODEL

*In the Document History table, version are identified as x.n where
“x” is a correlative number assigned to an approved version when reaching a main milestones
“n” is a correlative number assigned to draft versions, starting by 1. “n”=0 means version approved
Information related to previous draft versions (i.e. 0.1, 0.2 etc.) shall be deleted from the table when a
subsequent approved version is issued.*

Document History

<i>Version</i>	<i>Date</i>	<i>Comments</i>
1.0	25.01.2011	Initial version
1.1	15.05.2012	New TAF TSI baseline 5.2

2.0	08.08.2013	All the chapters were revised due to the TAF TSI Revision Process and the TAF TSI CCM WP cycle 2012 – 2013. New TAF TSI baseline 5.3.
2.0	17.10.2013	Validated by the ERA TAF CCB on 11.09.2013
2.1	10.02.2015	All the chapters were revised due to the TAF TSI CCM WP cycle 2013 – 2014. Validated by the ERA TAF CCB on 10.02.2015. New TAF TSI baseline 2.1
2.2	18.03.2018	New TAF TSI baseline 2.2
2.2.2	16.06.2018	Validated by the ERA TAF CCB on 31.05.2018.
2.3.0	30.11.2018	Validated by the ERA TAF CCB on 28.11.2018.
2.3.1	16.04.2020	Hotfix 2.3.1
2.4.0	27.05.2020	Validated by the ERA TAF CCB on 27.05.2020
2.4.1	03.09.2020	Hotfix 2.4.1
2.5.0	15.12.2020	Validated by the ERA TAF CCB on 25.11.2020
3.0.0	15.06.2021	Validated by the ERA TAF CCB on 26.05.2021
3.1.0	15.12.2021	Validated by the ERA TAF CCB on 24.11.2021
3.2.0	15.06.2022	Validated by the ERA TAF CCB on 01.06.2022
3.3.0	15.12.2022	Validated by the ERA TAF CCB on 30.11.2022

Contents

1.	Summary	4
2.	Schema taf_cat_complete.xsd	4
3.	Schema taf_cat_codelists.xsd	677

Application:

With effect from 08 March 2012.

All actors of the European Union falling under the provisions of the TAF TSI.

1. Summary

The following document is a complete list of data elements and messages defined in the TAF-TSI data catalogue. It is represented in XML format.

This catalogue shall be used as a basis for message development. During the course of the technical specifications and the implementation phase, this catalogue may be modified and/or amended.

All the elements listed in appendixes B, C and D are contained within this catalogue and described in detail.

The TAF TSI data catalogue is split into two documents:

- › The schema TAF_CAT_COMPLETE.XSD, containing the messages and the main data elements of the TAF TSI
- › The schema TAF_CAT_CODELIST.XSD, containing the code lists of the TAF TSI

In accordance with Commission Regulation (EU) 2015/302 of 25 February 2015 amending Regulation (EU) No 454/2011 on the technical specification for interoperability relating to the subsystem ‘telematics applications for passenger services’, the technical document TAP TSI Technical Document B.30 attached to TAP TSI refers to the TAF TSI data catalogue. Therefore, for TAF TSI and TAP TSI there will share a unique RU/IM communication catalogue.

2. Schema taf_cat_complete.xsd

schema location: [taf_cat_complete.xsd](#)
 attributeFormDefault: **unqualified**
 elementFormDefault: **qualified**
 targetNamespace: **http://www.era.europa.eu/schemes/TAFTSI/3.3**

Elements	Complex types	Simple types	Attributes
ActualEndDateTime	CargoCodeType	CommunicationRefID	CI_InstanceNumber
ActualETA	CompositIdentifierOperationalType	CompanyCode	
ActualETI	CompositIdentifierPlannedType	CountryIdentISO	
AdditionalInstruction	ConsignmentIdent	CurrencyCode_Type	
Address	CustomerCode	DeltaTime	
AdministrativeContactInformation	DanGoodsType	DerailmentDetectionDevice	
AffectedLocation	DimensionValue	EquipmentNumberType	
AffectedSection	LocationIdent	EquipmentTypeType	
AgainstBooked	TrainActivityType	ForwardingRestrictionType	
AgainstReferenced	WagonTelematics	FreeText	

[AgreedTimeOfDelivery](#)[AirBrake](#)[AirBrakedMass](#)[AlertMessage](#)[AllocationCompany](#)[Altitude](#)[ArrivalAtDestination](#)[ArrivalInterchangeReport](#)[ArrivalTimeAtDestination](#)[ArrivalTimeAtLocation](#)[ArrivalTimeAtLocationActual](#)[ArrivalTrackAtLocation](#)[AssociatedAttachedOTN](#)[AssociatedAttachedTimingAtLocation](#)[AssociatedAttachedTrainID](#)[AssociatedAttachedTrainServiceNumber](#)[BitmapDays](#)[BogiePitch](#)[BogieWagonsOnly](#)[BookedLocationDateTime](#)[BookedLocationTime](#)[BrakeWeight](#)[BrakingRatio](#)[CarrierStatus](#)[ChangeofTrackMessage](#)[CityTown](#)[ClosingTime](#)[Coasting](#)[Comments](#)[CommitmentETA](#)[Company](#)[ConsignmentNumber](#)[ConsignmentOrderMessage](#)[ContainerHandlingFlag](#)[ContractNumber](#)[ContractNumberMovement](#)[CoordinatingIM](#)[Core](#)[CountryCodeISO](#)[CreateDateTime](#)[Customer](#)[CustomerNumber](#)[Customers](#)[DangerousGoodsIndication](#)[DangerousGoodsIndicator](#)[DangerousGoodsVolume](#)[DangerousGoodsWeight](#)[LoadUnitNumberType](#)[Money_Type](#)[Name](#)[NHMCodeType](#)[Numeric1-5](#)[Numeric1-6](#)[Numeric2-2](#)[Numeric3-3](#)[Numeric4-4](#)[Percentage](#)[Speed](#)[String1-10](#)[String1-14](#)[String1-5](#)[String1-7](#)[String1-8](#)[String4-4](#)[String5-5](#)[String5-8](#)[Time](#)[VolumeValue](#)[WagonIdent](#)[WeightValueKilo](#)[WeightValueTonne](#)

[Date](#)[DateLastOverhaul](#)[DateNextOverhaul](#)[DatePutIntoService](#)[DeclarationText](#)[DelayCause](#)[DelayCauseTime](#)[DelayCodingDateTime](#)[DelayEventDateTime](#)[DelayEventReport](#)[DelayLocation](#)[DelayMinutes](#)[DeliveryAtDestination](#)[DeliveryReference](#)[DeliveryTimeAtDestination](#)[DeliveryTimeAtInterchange](#)[DepartureInterchangeReport](#)[DepartureJourneyTrack](#)[DepartureTimeAtLocation](#)[DepartureTrackAtLocation](#)[Destination](#)[Dimensions](#)[DwellTime](#)[eMail](#)[EmergencyBrakeOverride](#)[EndDate](#)[EndDateTime](#)[EndLocation](#)[ErrorMessage](#)[EstimatedEndDateTime](#)[ExceptionalGaugingCode](#)[ExceptionalGaugingIdent](#)[ExceptionalGaugingInd](#)[ExceptionalGaugingProfile](#)[ExceptionPoint](#)[ExceptionReason](#)[ExceptionTimeAtLocation](#)[FaxNumber](#)[FerryPermittedFlag](#)[FreeTextField](#)[FreightFlag](#)[GeographicalCoordinates](#)[GeographicCoordinates](#)[GeoLocalisation](#)[GeoLocalisationOnNetwork](#)[GNSS DynamicPosition](#)[Goods](#)[GoodsDescription](#)

[GoodsInWagon](#)
[GrossWeight](#)
[HandBrake](#)
[HandlingInstruction](#)
[HandoverPointFlag](#)
[Height](#)
[HighestPlannedSpeed](#)
[Identifiers](#)
[IM_Partner](#)
[ImpactedRU](#)
[IntermediateDestination](#)
[InternalReferenceIdentifier](#)
[InterruptionDateTime](#)
[InterruptionDescription](#)
[InterruptionInformation](#)
[InterruptionPoint](#)
[InterruptionReason](#)
[ITU](#)
[ITU_Details](#)
[ITU_Type](#)
[JourneySection](#)
[JourneySectionDestination](#)
[JourneySectionOrigin](#)
[KeeperShortNameVKM](#)
[LastModifiedDateTime](#)
[Latitude](#)
[LeadRU](#)
[Length](#)
[LengthOfSetOfCarriages](#)
[LengthOverBuffers](#)
[LoadArea](#)
[LoadingCapacity](#)
[LoadingFacility](#)
[LoadingStatus](#)
[LoadingTackles](#)
[Location](#)
[LocationActualTrack](#)
[LocationDateTime](#)
[LocationFileDatasetMessage](#)
[LocationModified](#)
[LocationPlannedTrack](#)
[LocationPrimaryCode](#)
[LocationPrimaryInformation](#)
[LocationPrimaryName](#)
[LocationSubsidiaryCode](#)
[LocationSubsidiaryIdentification](#)
[LocationSubsidiaryInformation](#)
[LocationSubsidiaryName](#)

[LocoNumber](#)

[LocoTypeNumber](#)

[Longitude](#)

[MaxAxleWeight](#)

[MaxDesignSpeed](#)

[MaxGrossWeight](#)

[MaxLengthOfLoad](#)

[MaxTemp](#)

[Measure](#)

[MessageDateTimeCreated](#)

[MessageHeader](#)

[MessageIdentifier](#)

[MessageReference](#)

[MessageRoutingID](#)

[MessageType](#)

[MessageTypeVersion](#)

[MinBrakedWeightPercent](#)

[MinCurveRadius](#)

[MinTemp](#)

[MinVerticalRadiusYardHump](#)

[ModificationReason](#)

[ModificationStatusIndicator](#)

[Name](#)

[NetworkProjectedLocation](#)

[NetworkSpecificParameter](#)

[NextIntermediateDestination](#)

[NextResponsibleRU](#)

[NHM Code](#)

[Noise](#)

[NoiseByPassLimit](#)

[Notes](#)

[NumberOfAxles](#)

[NumberOfBogies](#)

[NumberOfVehicles](#)

[ObjectType](#)

[Offset](#)

[OffsetToReference](#)

[OnDemandPath](#)

[OperationalTrainCouplingStrength](#)

[OperationalTrainNumber](#)

[OperationalTrainNumberIdentifier](#)

[OriginCountry](#)

[OverhaulValidityPeriod](#)

[ParkingBrakeForce](#)

[PassengerFlag](#)

[PathCanceledMessage](#)

[PathConfirmedMessage](#)

[PathDetailsMessage](#)

[PathDetailsRefusedMessage](#)
[PathInformation](#)
[PathNotAvailableMessage](#)
[PathRequestMessage](#)
[PermittedTolerance](#)
[PhoneNumber](#)
[PickupTimeAtLocation](#)
[PlannedCalendar](#)
[PlannedDateNextOverhaul](#)
[PlannedJourneyLocation](#)
[PlannedSpeed](#)
[PlannedTrainData](#)
[PlannedTrainTechnicalData](#)
[PlannedTransportIdentifiers](#)
[PostalCode](#)
[PreArrangedPath](#)
[PreviousConsignmentNumber](#)
[PreviousResponsibleRU](#)
[PrimaryLocationName](#)
[ProductionStation](#)
[PushPullTrain](#)
[Quantity](#)
[ReceiptConfirmationMessage](#)
[Recipient](#)
[ReferencedLocationDateTime](#)
[ReferenceNumbers](#)
[ReferenceOTN](#)
[ReferenceTrainIDSubCalendar](#)
[RelatedIdentifier](#)
[RelatedPlannedTransportIdentifiers](#)
[RelatedReference](#)
[RelatedSenderReference](#)
[RelatedTransportOperationalIdentifiers](#)
[Remarks](#)
[RequestedCalendar](#)
[RequestedPeriod](#)
[RequestedTimeframe](#)
[ResponsibilityActualSection](#)
[ResponsibilityNextSection](#)
[ResponsibleApplicant](#)
[ResponsibleIM](#)
[ResponsibleRU](#)
[RestrictionsDueToLoadOrDamage](#)
[RevisedRequest](#)
[RID](#)
[RollingRoadUnit](#)
[RollingStockDataset](#)
[RollingStockDatasetMessage](#)

[RollingStockDatasetQueryMessage](#)

[RouteInformation](#)

[Routing](#)

[RP Code](#)

[RU Partner](#)

[ScheduledDateTimeAtTransfer](#)

[ScheduledTimeAtHandover](#)

[ScheduledTimeAtLocation](#)

[Seals](#)

[Sender](#)

[SenderReference](#)

[Ship](#)

[SpecialTreatments](#)

[SRID](#)

[StartDate](#)

[StartDateTime](#)

[StartLocation](#)

[Station](#)

[StatusOfDocument](#)

[SummaryOfGoodsWithSameRID](#)

[TechnicalForwardingRestrictions](#)

[TiltingFunction](#)

[TimetableYear](#)

[TimingAtLocation](#)

[TotalLoadWeight](#)

[TotalWeight](#)

[TractionDetails](#)

[TractionPositionInTrain](#)

[TractionWeight](#)

[TrafficType](#)

[TrainActivity](#)

[TrainActivityType](#)

[TrainAtLocation](#)

[TrainCC System](#)

[TrainCompositionJourneySection](#)

[TrainCompositionMessage](#)

[TrainContactDetails](#)

[TrainDelay](#)

[TrainDelayCauseMessage](#)

[TrainForecastAtReportingLocationMessage](#)

[TrainID](#)

[TrainInformation](#)

[TrainJourneyModification](#)

[TrainJourneyModificationIndicator](#)


[TrainJourneyModificationMessage](#)

[TrainJourneyModificationTime](#)


[TrainJourneyStartTime](#)

[TrainLength](#)
[TrainLocationReport](#)
[TrainLocationStatus](#)
[TrainMaxSpeed](#)
[TrainNotAtInterruptionPoint](#)
[TrainOperationalIdentification](#)
[TrainReadyMessage](#)
[TrainReadyStatus](#)
[TrainRunningData](#)
[TrainRunningForecastMessage](#)
[TrainRunningInformationMessage](#)
[TrainRunningInterruptionMessage](#)
[TrainRunningTechData](#)
[TrainStartTime](#)
[TrainWeight](#)
[TransfereeIM](#)
[TransferPoint](#)
[TransportInstruction](#)
[TransportOperationalIdentifiers](#)
[TypeOfIMHarmonization](#)
[TypeOfInformation](#)
[TypeOfRequest](#)
[TypeOfRUHarmonization](#)
[TypeofService](#)
[UltimateDestinationCountry](#)
[UN Number](#)
[ValidityPeriod](#)
[Value](#)
[Variant](#)
[VesselIndication](#)
[VesselName](#)
[Volume](#)
[WagonArrivalNoticeMessage](#)
[WagonAtDeparture](#)
[WagonData](#)
[WagonDeliveryNoticeMessage](#)
[WagonDepartureNoticeMessage](#)
[WagonDeviationMessage](#)
[WagonETI ETA Message](#)
[WagonEventInformation](#)
[WagonExceptionMessage](#)
[WagonExceptionReasonMessage](#)
[WagonExceptionReport](#)
[WagonInformation](#)
[WagonLength](#)
[WagonLocationStatus](#)
[WagonMaxSpeed](#)
[WagonNumberFreight](#)

[WagonNumberOfAxles](#)[WagonOperationalData](#)[WagonPickupAtOrigin](#)[WagonReleaseNoticeMessage](#)[Wagons](#)[WagonTechData](#)[WagonTrainPosition](#)[WagonWeightEmpty](#)[WagonYardArrivalMessage](#)[WagonYardDepartureMessage](#)[WeightOfSetOfCarriages](#)[WheelDiameter](#)[WheelsetGauge](#)[Width](#)[WIMO Dataset](#)[YardArrival](#)[YardDeparture](#)element **ActualEndDateTime**


diagram	 <p>Identifies the actual date and time of arrival of the Wagon or Unit on the final destination of the customer siding.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation Identifies the actual date and time of arrival of the Wagon or Unit on the final destination of the customer siding.
source	<pre><xs:element name="ActualEndDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Identifies the actual date and time of arrival of the Wagon or Unit on the final destination of the customer siding.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ActualETA**


diagram	 <p>Identifies the actual ETA date and time of arrival of the Wagon or Unit on the final destination of the customer siding.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple

used by	element AlertMessage
annotation	documentation Identifies the actual ETA date and time of arrival of the Wagon or Unit on the final destination of the customer siding.
source	<pre><xs:element name="ActualETA" type="xs:dateTime"> <xs:annotation> <xs:documentation>Identifies the actual ETA date and time of arrival of the Wagon or Unit on the final destination of the customer siding.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ActualETI**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element WagonDeviationMessage
annotation	documentation Identifies the actual valid estimated date and time of interchange of the Wagon or Unit at an interchange point
source	<pre><xs:element name="ActualETI" type="xs:dateTime"> <xs:annotation> <xs:documentation>Identifies the actual valid estimated date and time of interchange of the Wagon or Unit at an interchange point</xs:documentation> </xs:annotation> </xs:element></pre>

element **AdditionalInstruction**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Additional instructions regarding the wagon or shipment in free text									
source	<pre><xs:element name="AdditionalInstruction" type="FreeText"> <xs:annotation> <xs:documentation>Additional instructions regarding the wagon or shipment in free text</xs:documentation> </xs:annotation></pre>									

	<code></xs:element></code>
--	----------------------------------

element Address

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
used by	element AdministrativeContactInformation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Generic postal address in clear text									
source	<pre><xs:element name="Address" type="FreeText"> <xs:annotation> <xs:documentation>Generic postal address in clear text</xs:documentation> </xs:annotation> </xs:element></pre>									

element AdministrativeContactInformation

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Name Address eMail PhoneNumber FaxNumber FreeTextField
used by	elements Customers ErrorMessage LoadingFacility PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage
annotation	documentation Used to define administrative contact information
source	<pre><xs:element name="AdministrativeContactInformation"> <xs:annotation></pre>

	<pre> <xs:documentation>Used to define administrative contact information</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Name"/> <xs:element ref="Address" minOccurs="0"/> <xs:element ref="eMail" minOccurs="0"/> <xs:element ref="PhoneNumber" minOccurs="0"/> <xs:element ref="FaxNumber" minOccurs="0"/> <xs:element ref="FreeTextField" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **AffectedLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location LocationDateTime OperationalTrainNumberIdentifier
used by	element ReceiptConfirmationMessage
annotation	documentation Affected location
source	<pre> <xs:element name="AffectedLocation"> <xs:annotation> <xs:documentation>Affected location </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="LocationDateTime"/> <xs:element ref="OperationalTrainNumberIdentifier" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **AffectedSection**

<p>diagram</p>	<p>Indication for the recipient if not the entire path is affected, e.g. in case of a partial cancelation for the last part of the path</p> <p>This is the calendar item for path request/path details messages - used in planning phase</p> <p>The usage of this element must be specified in national rules and has to be defined by each IM</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>StartOfSection EndOfSection OperationalTrainNumberIdentifier PlannedCalendar NetworkSpecificParameter</p>
<p>used by</p>	<p>elements PathCanceledMessage PathConfirmedMessage PathDetailsRefusedMessage PathNotAvailableMessage ReceiptConfirmationMessage</p>
<p>annotation</p>	<p>documentation Indication for the recipient if not the entire path is affected, e.g. in case of a partial cancelation for the last part of the path</p>
<p>source</p>	<pre><xs:element name="AffectedSection"> <xs:annotation> <xs:documentation>Indication for the recipient if not the entire path is affected, e.g. in case of a partial cancelation for the last part of the path</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="StartOfSection"> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"> <xs:sequence minOccurs="0"> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> <xs:element ref="BookedLocationTime" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element> <xs:element name="EndOfSection"> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"> <xs:sequence minOccurs="0"> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> <xs:element ref="BookedLocationTime" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element> <xs:element ref="OperationalTrainNumberIdentifier" minOccurs="0"/> <xs:element ref="PlannedCalendar"/> </xs:sequence> </xs:complexType> </xs:element></pre>


```
<xs:element ref="NetworkSpecificParameter" minOccurs="0"
maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:element>
```

element **AffectedSection/StartOfSection**

<p>diagram</p>	<p>The diagram illustrates the structure of the StartOfSection element. It is an extension of the LocationIdent type. The StartOfSection element contains a sequence of three child elements: LocationIdent (which is an extension of the base type), BookedLocationDateTime, and BookedLocationTime. The LocationIdent (extended) type contains four child elements: CountryCodeISO, LocationPrimaryCode, PrimaryLocationName, and LocationSubsidiaryIdentification. Each element is represented by a box with a description of its content.</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>extension of LocationIdent</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification BookedLocationDateTime BookedLocationTime</p>
<p>source</p>	<pre><xs:element name="StartOfSection"> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"> <xs:sequence minOccurs="0"> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> <xs:element ref="BookedLocationTime" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element></pre>

element **AffectedSection/EndOfSection**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification BookedLocationDateTime BookedLocationTime
source	<pre> <xs:element name="EndOfSection"> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"> <xs:sequence minOccurs="0"> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> <xs:element ref="BookedLocationTime" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element> </pre>

element **AgainstBooked**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	DeltaTime						
properties	content simple						
used by	element TrainDelay						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>5</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	5	
Kind	Value	Annotation					
length	5						
annotation	documentation Identifies the Delta delay time against the booked schedule in minutes						
source	<pre> <xs:element name="AgainstBooked" type="DeltaTime"> <xs:annotation> </pre>						

	<pre> <xs:documentation>Identifies the Delta delay time against the booked schedule in minutes</xs:documentation> </xs:annotation> </xs:element> </pre>
--	---

element **AgainstReferenced**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	DeltaTime
properties	content simple
used by	element TrainDelay
facets	Kind Value Annotation length 5
annotation	documentation Delay compared to the referenced Date/Time
source	<pre> <xs:element name="AgainstReferenced" type="DeltaTime"> <xs:annotation> <xs:documentation>Delay compared to the referenced Date/Time</xs:documentation> </xs:annotation> </xs:element> </pre>

element **AgreedTimeOfDelivery**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements ConsignmentOrderMessage/COMS/COM WIMO Dataset/ConsignmentLevelData
annotation	documentation The requested Date and Time for the delivery of a wagon/Shipment or Intermodal untis at customer sidings
source	<pre> <xs:element name="AgreedTimeOfDelivery" type="xs:dateTime"> <xs:annotation> <xs:documentation>The requested Date and Time for the delivery of a wagon/Shipment or Intermodal untis at customer sidings</xs:documentation> </xs:annotation> </xs:element> </pre>

element **AirBrake**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>NumberOfBrakes BrakeSystem AirBrakeType BrakingPowerVariationDevice AirBrakedMass LoadChangeDevice BrakeSpecialCharacteristics</p>
<p>used by</p>	<p>element RollingStockDataset/DesignDataSet</p>
<p>annotation</p>	<p>documentation Characteristics of Air Brakes</p>
<p>source</p>	<pre><xs:element name="AirBrake"> <xs:annotation> <xs:documentation>Characteristics of Air Brakes</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NumberOfBrakes" type="Numeric2-2"> <xs:annotation> <xs:documentation>Number of air brakes</xs:documentation> </xs:annotation> </xs:element> <xs:element name="BrakeSystem" minOccurs="0"> <xs:annotation> <xs:documentation>Abbreviation of air brake system. Following values are examples: Kk; Dr; Bo; Hik; Bd; Ch; O; KE; WE; DK; WU; WA; DM; MH, SW; KE 435; through brake pipe</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="AirBrakeType" type="xs:string"/> <xs:element name="BrakingPowerVariationDevice" type="xs:string"/> <xs:element name="AirBrakedMass" type="xs:float"/> <xs:element name="LoadChangeDevice" type="xs:float"/> <xs:element name="BrakeSpecialCharacteristics" type="xs:string"/> </xs:sequence> </xs:complexType> </xs:element></pre>

```

</xs:simpleType>
</xs:element>
<xs:element ref="AirBrakeType"/>
<xs:element ref="BrakingPowerVariationDevice"/>
<xs:element ref="AirBrakedMass">
  <xs:annotation>
    <xs:documentation> General braked weight for wagon without any
variation device or braked weight in position "empty" for wagons with a
variation device or maximum brake weight for wagons with a linear auto
continuous brake weight device "0" for wagons without brake system (in
tonns)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="LoadChangeDevice" minOccurs="0"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>Specific weights for change over air brake
systems</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ChangeOverWeight" type="Numeric3-3">
        <xs:annotation>
          <xs:documentation>Change over weight of braked weight in
tonns variation device</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="AirBrakedMassLoaded" type="Numeric3-3">
        <xs:annotation>
          <xs:documentation>Braked weight in tonns loaded for change
over weight</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element ref="BrakeSpecialCharacteristics"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **AirBrake/NumberOfBrakes**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric2-2									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
annotation	documentation Number of air brakes									

source	<pre><xs:element name="NumberOfBrakes" type="Numeric2-2"> <xs:annotation> <xs:documentation>Number of air brakes</xs:documentation> </xs:annotation> </xs:element></pre>
--------	--

element **AirBrake/BrakeSystem**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation maxLength 256
annotation	documentation Abbreviation of air brake system. Following values are examples: Kk; Dr; Bo; Hik; Bd; Ch; O; KE; WE; DK; WU; WA; DM; MH, SW; KE 435; through brake pipe
source	<pre><xs:element name="BrakeSystem" minOccurs="0"> <xs:annotation> <xs:documentation>Abbreviation of air brake system. Following values are examples: Kk; Dr; Bo; Hik; Bd; Ch; O; KE; WE; DK; WU; WA; DM; MH, SW; KE 435; through brake pipe</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **AirBrake/LoadChangeDevice**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc unbounded content complex
children	ChangeOverWeight AirBrakedMassLoaded
annotation	documentation Specific weights for change over air brake systems

source	<pre> <xs:element name="LoadChangeDevice" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Specific weights for change over air brake systems</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="ChangeOverWeight" type="Numeric3-3"> <xs:annotation> <xs:documentation>Change over weight of braked weight in tonns variation device</xs:documentation> </xs:annotation> </xs:element> <xs:element name="AirBrakedMassLoaded" type="Numeric3-3"> <xs:annotation> <xs:documentation>Braked weight in tonns loaded for change over weight</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--------	--

element **AirBrake/LoadChangeDevice/ChangeOverWeight**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric3-3									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
annotation	documentation Change over weight of braked weight in tonns variation device									
source	<pre> <xs:element name="ChangeOverWeight" type="Numeric3-3"> <xs:annotation> <xs:documentation>Change over weight of braked weight in tonns variation device</xs:documentation> </xs:annotation> </xs:element> </pre>									

element **AirBrake/LoadChangeDevice/AirBrakedMassLoaded**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric3-3

properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
annotation	documentation Braked weight in tonnes loaded for change over weight									
source	<pre><xs:element name="AirBrakedMassLoaded" type="Numeric3-3"> <xs:annotation> <xs:documentation>Braked weight in tonnes loaded for change over weight</xs:documentation> </xs:annotation> </xs:element></pre>									

element **AirBrakedMass**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element AirBrake									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	999									
annotation	documentation General braked weight for wagon without a variation device; Braked weight empty for wagons with a variation device; maximum braked weight for wagons with linear auto continuous device; "0" for wagons without air brake (in tons).									
source	<pre><xs:element name="AirBrakedMass"> <xs:annotation> <xs:documentation>General braked weight for wagon without a variation device; Braked weight empty for wagons with a variation device; maximum braked weight for wagons with linear auto continuous device; "0" for wagons without air brake (in tons).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **AlertMessage**


diagram	<p>Following the comparison between the actual ETA and the commitment to the customer, the Lead RU sends this Alert Message to the actual RU in charge and to all following RUs involved in t...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader CommitmentETA ActualETA WagonNumberFreight
annotation	documentation Following the comparison between the actual ETA and the commitment to the customer, the Lead RU sends this Alert Message to the actual RU in charge and to all following RUs involved in the transport chain
source	<pre><xs:element name="AlertMessage"> <xs:annotation> <xs:documentation>Following the comparison between the actual ETA and the commitment to the customer, the Lead RU sends this Alert Message to the actual RU in charge and to all following RUs involved in the transport chain</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="CommitmentETA"/> <xs:element ref="ActualETA"/> <xs:element ref="WagonNumberFreight"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **AllocationCompany**


diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	elements LocationSubsidiaryIdentification LocationSubsidiaryInformation												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												

annotation	documentation Name of company who is responsible for allocation and maintenance of codes
source	<code><xs:element name="AllocationCompany" type="CompanyCode"> <xs:annotation> <xs:documentation>Name of company who is responsible for allocation and maintenance of codes</xs:documentation> </xs:annotation> </xs:element></code>

element **Altitude**

diagram	 Altitude (in m) at the beginning of the SP. Considering ETRS89 as reference. Starting at -100...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:integer
properties	content simple
used by	element GeographicCoordinates
annotation	documentation Altitude (in m) at the beginning of the SP. Considering ETRS89 as reference. Starting at -1000m
source	<code><xs:element name="Altitude" type="xs:integer"> <xs:annotation> <xs:documentation>Altitude (in m) at the beginning of the SP. Considering ETRS89 as reference. Starting at -1000m</xs:documentation> </xs:annotation> </xs:element></code>

element **ArrivalAtDestination**


diagram	 Arrival of a wagon at its destination point with Date and Time. The location is not the final destination at customer sidings, but the location of the last RU which has to organise the final delivery of the wagon to c... Destination Location... ArrivalTimeAtDestination The actual Date and Time of the arrival of wagons by train at its final destination yard
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Destination ArrivalTimeAtDestination
used by	element WagonArrivalNoticeMessage
annotation	documentation Arrival of a wagon at its destination point with Date and Time. The location is not the final destination at customer sidings, but the location of the last RU which has to organise the final delivery of the wagon to customer sidings
source	<code><xs:element name="ArrivalAtDestination"> <xs:annotation> <xs:documentation>Arrival of a wagon at its destination point with Date and Time. The location is not the final destination at customer sidings, but the location of the last RU which has to organise the final delivery of the wagon to customer sidings</xs:documentation> </xs:annotation> </xs:element></code>

	<pre> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Destination"/> <xs:element ref="ArrivalTimeAtDestination"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **ArrivalInterchangeReport**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Source Location ArrivalTimeAtLocation TrainID
used by	element WagonETI ETA Message
annotation	documentation The arrival or interchange station where ETI end
source	<pre> <xs:element name="ArrivalInterchangeReport"> <xs:annotation> <xs:documentation>The arrival or interchange station where ETI end</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Source"> <xs:annotation> <xs:documentation>Source of information</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Experienced time of arrival"/> <xs:enumeration value="Real Time Train Situation"/> <xs:enumeration value="Estimated time of arrival"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="Location"/> <xs:element ref="ArrivalTimeAtLocation"/> <xs:element ref="TrainID" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **ArrivalInterchangeReport/Source**

diagram	 Source of informat...												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:string												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Experienced time of arrival</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Real Time Train Situation</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Estimated time of arrival</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	Experienced time of arrival		enumeration	Real Time Train Situation		enumeration	Estimated time of arrival	
Kind	Value	Annotation											
enumeration	Experienced time of arrival												
enumeration	Real Time Train Situation												
enumeration	Estimated time of arrival												
annotation	documentation Source of information												
source	<pre><xs:element name="Source"> <xs:annotation> <xs:documentation>Source of information</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Experienced time of arrival"/> <xs:enumeration value="Real Time Train Situation"/> <xs:enumeration value="Estimated time of arrival"/> </xs:restriction> </xs:simpleType> </xs:element></pre>												

element **ArrivalTimeAtDestination**


diagram	 The actual Date and Time of the arrival of wagons by train at its final destination yard
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element ArrivalAtDestination
annotation	documentation The actual Date and Time of the arrival of wagons by train at its final destination yard
source	<pre><xs:element name="ArrivalTimeAtDestination" type="xs:dateTime"> <xs:annotation> <xs:documentation>The actual Date and Time of the arrival of wagons by train at its final destination yard</xs:documentation> </xs:annotation> </xs:element></pre>

element **ArrivalTimeAtLocation**


diagram	 The actual arrival date and time at the defined location
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element ArrivalInterchangeReport
annotation	documentation The actual arrival date and time at the defined location
source	<pre><xs:element name="ArrivalTimeAtLocation" type="xs:dateTime"> <xs:annotation> <xs:documentation>The actual arrival date and time at the defined location</xs:documentation> </xs:annotation> </xs:element></pre>

element **ArrivalTimeAtLocationActual**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element YardArrival
annotation	documentation The actual arrival date and time at the defined location
source	<pre><xs:element name="ArrivalTimeAtLocationActual" type="xs:dateTime"> <xs:annotation> <xs:documentation>The actual arrival date and time at the defined location</xs:documentation> </xs:annotation> </xs:element></pre>

element **ArrivalTrackAtLocation**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex

children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Identifies the track of the arrival of a train at a reporting point. This is indicated in the LocationSubsidiaryCode in conjunction with the LocationPrimaryCode.
source	<pre><xs:element name="ArrivalTrackAtLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>Identifies the track of the arrival of a train at a reporting point. This is indicated in the LocationSubsidiaryCode in conjunction with the LocationPrimaryCode. </xs:documentation> </xs:annotation> </xs:element></pre>

element **AssociatedAttachedOTN**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	String1-8									
properties	content simple									
used by	complexType TrainActivityType									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>8</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	8	
Kind	Value	Annotation								
minLength	1									
maxLength	8									
annotation	documentation Identifies the associated train for the activity for traffic management purposes by the Dispatcher, GSMR services, etc.									
source	<pre><xs:element name="AssociatedAttachedOTN" type="String1-8"> <xs:annotation> <xs:documentation>Identifies the associated train for the activity for traffic management purposes by the Dispatcher, GSMR services, etc.</xs:documentation> </xs:annotation> </xs:element></pre>									

element **AssociatedAttachedTimingAtLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3


properties	content complex
children	TimingAtLocation
used by	complexType TrainActivityType
annotation	documentation Identifies the time at location of the associated attached train or train service number given by AssociatedAttachedTrainID or AssociatedAttachedOTN or AssociatedAttachedTrainServiceNumber. In general, the Dwell Time element of structure TimingAtLocation is not provided when using TrainActivityType
source	<pre> <xs:element name="AssociatedAttachedTimingAtLocation"> <xs:annotation> <xs:documentation>Identifies the time at location of the associated attached train or train service number given by AssociatedAttachedTrainID or AssociatedAttachedOTN or AssociatedAttachedTrainServiceNumber. In general, the Dwell Time element of structure TimingAtLocation is not provided when using TrainActivityType</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TimingAtLocation" maxOccurs="unbounded" /> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **AssociatedAttachedTrainID**


diagram	<p>The diagram illustrates the structure of the CompositIdentifierPlannedTy... class. It is composed of several sub-classes: ObjectType (Provides a possibility for differentiation between the objects: Train (TR), Route (RO), Path (PA), Case Reference (CR) and Path Request (PR)), Compa... (Identifies a railway company (RU or IM)), Core (It is the main part of identifier and is determined by the company that creates it), Variant (The variant shows a relationship between two identifiers referring to the same business case), TimetableYear (Refers to the timetable period in which the business will be carried out), and StartDate (The start of the date/time in effect). The AssociatedAttachedTrainID element is shown as a separate class with the description "TrainID of the Associated Train in an Attach Activity" and is connected to the Core class of the CompositIdentifierPlannedTy... class.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CompositIdentifierPlannedType
properties	content complex
children	ObjectType Company Core Variant TimetableYear StartDate
used by	complexType TrainActivityType

annotation	documentation TrainID of the Associated Train in an Attach Activity
source	<pre><xs:element name="AssociatedAttachedTrainID" type="CompositIdentifierPlannedType"> <xs:annotation> <xs:documentation>TrainID of the Associated Train in an Attach Activity</xs:documentation> </xs:annotation> </xs:element></pre>

element **AssociatedAttachedTrainServiceNumber**


diagram	 <p>Identifies the associated train service line number for the train activity connecting ser...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	String1-8									
properties	content simple									
used by	complexType TrainActivityType									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>8</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	8	
Kind	Value	Annotation								
minLength	1									
maxLength	8									
annotation	documentation Identifies the associated train service line number for the train activity connecting service									
source	<pre><xs:element name="AssociatedAttachedTrainServiceNumber" type="String1-8"> <xs:annotation> <xs:documentation>Identifies the associated train service line number for the train activity connecting service</xs:documentation> </xs:annotation> </xs:element></pre>									

element **BitmapDays**

diagram	 <p>Structure BitmapDays must be provided if ValidityPeriod of associated calendar contains more than one day; it is optional otherwise.</p>															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	content simple															
used by	elements PlannedCalendar ReferenceTrainIDSubCalendar RequestedCalendar															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>740</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-1]{1,740}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	740		whiteSpace	collapse		pattern	[0-1]{1,740}	
Kind	Value	Annotation														
minLength	1															
maxLength	740															
whiteSpace	collapse															
pattern	[0-1]{1,740}															
annotation	documentation Structure BitmapDays must be provided if ValidityPeriod of associated calendar contains more than one day; it is optional otherwise.															

source	<pre> <xs:element name="BitmapDays"> <xs:annotation> <xs:documentation>Structure BitmapDays must be provided if ValidityPeriod of associated calendar contains more than one day; it is optional otherwise.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="740"/> <xs:whiteSpace value="collapse"/> <xs:pattern value="[0-1]{1,740}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--------	--

element **BogiePitch**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation Bogie Wheelbase measured in mm									
source	<pre> <xs:element name="BogiePitch"> <xs:annotation> <xs:documentation>Bogie Wheelbase measured in mm</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **BogieWagonsOnly**


diagram	 <p>Indicates that the train consists of bogie wagons only or not. "Yes"/"true" means always all wagons of the train are bogie wagons. Then content of element is "no"/"false" or element isn't used means the train contains of different wagons (not homogeneous only with bo...</p>
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element PlannedTrainTechnicalData
annotation	documentation Indicates that the train consists of bogie wagons only or not. "Yes"/"true" means always all wagons of the train are bogie wagons. Then content of element is "no"/"false" or element isn't used means the train contains of different wagons (not homogeneous only with bogie wagons).
source	<pre><xs:element name="BogieWagonsOnly" type="xs:boolean"> <xs:annotation> <xs:documentation>Indicates that the train consists of bogie wagons only or not. "Yes"/"true" means always all wagons of the train are bogie wagons. Then content of element is "no"/"false" or element isn't used means the train contains of different wagons (not homogeneous only with bogie wagons).</xs:documentation> </xs:annotation> </xs:element></pre>


element **BookedLocationDateTime**

diagram	 <p>BookedLocationDateTime Scheduled Date and Time of a train at a specied location as defined in the path contract</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements ChangeofTrackMessage DelayEventReport AffectedSection/EndOfSection InterruptionPoint JourneySectionDestination JourneySectionOrigin LocationModified AffectedSection/StartOfSection TimingAtLocation/Timing TrainAtLocation TrainLocationReport
annotation	documentation Scheduled Date and Time of a train at a specied location as defined in the path contract
source	<pre><xs:element name="BookedLocationDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Scheduled Date and Time of a train at a specied location as defined in the path contract</xs:documentation> </xs:annotation> </xs:element></pre>


element **BookedLocationTime**

diagram	 <p>BookedLocationTime</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:time
properties	content simple
used by	elements AffectedSection/EndOfSection AffectedSection/StartOfSection
source	<pre><xs:element name="BookedLocationTime" type="xs:time"/></pre>

element **BrakeWeight**

diagram	 Shows the Braked mass of the wagon according to the type of the braking system, in Tonnes									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
used by	elements PlannedTrainTechnicalData TrainRunningTechData WagonOperationalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	99999									
annotation	documentation Shows the Braked mass of the wagon according to the type of the braking system, in Tonnes									
source	<pre><xs:element name="BrakeWeight"> <xs:annotation> <xs:documentation>Shows the Braked mass of the wagon according to the type of the braking system, in Tonnes</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **BrakingRatio**

diagram	 Minimum percentage of braking. Expressed as an integer value (no percent sign should be added).									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Minimum percentage of braking. Expressed as an integer value (no percent sign should be added).									
source	<pre><xs:element name="BrakingRatio"> <xs:annotation> <xs:documentation>Minimum percentage of braking. Expressed as an integer value (no percent sign should be added).</xs:documentation> </xs:annotation> <xs:simpleType></pre>									

```
<xs:restriction base="xs:integer">
  <xs:maxInclusive value="999"/>
  <xs:minInclusive value="1"/>
</xs:restriction>
</xs:simpleType>
</xs:element>
```


element **CarrierStatus**

diagram	<p>CarrierStatus Status of the carrier during the transport</p> <ul style="list-style-type: none"> 0 Contractual carrier / Lead carrier 1 Successive carrier 2 Substitute carrier 3 to be used for all other partners (e.g. subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2 (which have to be mention... 															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:token															
properties	content simple															
used by	element ConsignmentOrderMessage/COMS/COM/Carriers															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td>documentation 0: Contractual carrier</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation 1: Successive carrier</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation 2: Substitute carrier</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation 3: to be used for all other partners (e.g. subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2 (which have to be mentioned in the consignment note)</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0	documentation 0: Contractual carrier	enumeration	1	documentation 1: Successive carrier	enumeration	2	documentation 2: Substitute carrier	enumeration	3	documentation 3: to be used for all other partners (e.g. subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2 (which have to be mentioned in the consignment note)
Kind	Value	Annotation														
enumeration	0	documentation 0: Contractual carrier														
enumeration	1	documentation 1: Successive carrier														
enumeration	2	documentation 2: Substitute carrier														
enumeration	3	documentation 3: to be used for all other partners (e.g. subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2 (which have to be mentioned in the consignment note)														
annotation	<p>documentation Status of the carrier during the transport</p> <ul style="list-style-type: none"> 0 Contractual carrier / Lead carrier 1 Successive carrier 2 Substitute carrier 3 to be used for all other partners (e.g. subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2 (which have to be mentioned in the consignment note) 															
source	<pre><xs:element name="CarrierStatus"> <xs:annotation> <xs:documentation>Status of the carrier during the transport 0 Contractual carrier / Lead carrier 1 Successive carrier 2 Substitute carrier 3 to be used for all other partners (e.g. subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2 (which have to be mentioned in the consignment note)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>0: Contractual carrier</xs:documentation> </xs:annotation></pre>															

```


</xs:enumeration>
<xs:enumeration value="1">
  <xs:annotation>
    <xs:documentation>1: Successive carrier</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="2">
  <xs:annotation>
    <xs:documentation>2: Substitute carrier</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="3">
  <xs:annotation>
    <xs:documentation>3: to be used for all other partners (e.g.
subcontractors, relevant applicants) beside the carriers in role 0, 1 and 2
(which have to be mentioned in the consignment note)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **ChangeofTrackMessage**




properties	content complex
children	MessageHeader MessageStatus TrainOperationalIdentification OperationalTrainNumberIdentifier ReferenceOTN LocationPlannedTrack LocationActualTrack BookedLocationDateTime TrainLocationStatus InterruptionReason InterruptionDescription TransferPoint TransfereeIM
annotation	documentation This message is issued to show that the train is arriving at another platform to the one that was scheduled
source	<pre> <xs:element name="ChangeofTrackMessage"> <xs:annotation> <xs:documentation> This message is issued to show that the train is arriving at another platform to the one that was scheduled</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"> <xs:annotation> <xs:documentation>Assigned by the Sender 1=Creation, 2=Modification, 3=deletion </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TrainOperationalIdentification" minOccurs="0"/> <xs:element ref="OperationalTrainNumberIdentifier"/> <xs:element ref="ReferenceOTN" minOccurs="0"/> <xs:element ref="LocationPlannedTrack" minOccurs="0"/> <xs:element ref="LocationActualTrack"/> <xs:element ref="BookedLocationDateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Scheduled Date and Time of a train at a specied location as defined in the path contract</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TrainLocationStatus" minOccurs="0"/> <xs:element ref="InterruptionReason" minOccurs="0"/> <xs:element ref="InterruptionDescription" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="TransferPoint" minOccurs="0"> <xs:annotation> <xs:documentation>Transfer point or station of destination in the considered network where the Reference Train Numbers refers to </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TransfereeIM" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **CityTown**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Name of the City or Town in Clear Text									
source	<pre><xs:element name="CityTown"> <xs:annotation> <xs:documentation>Name of the City or Town in Clear Text</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ClosingTime**


diagram	 <p>The closing Date and Time of the port for the delivery of the shipment by rail to a vessel.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element VesselIndication
annotation	documentation The closing Date and Time of the port for the delivery of the shipment by rail to a vessel.
source	<pre><xs:element name="ClosingTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>The closing Date and Time of the port for the delivery of the shipment by rail to a vessel.</xs:documentation> </xs:annotation> </xs:element></pre>

element **Coasting**


diagram	 <p>IM indicates to the RU whether the driver can rely on coasting. This is of both economic and ecological interest, as in many parts of the journey the trains may have enough inertia to be able to match the calculated time of the next location r...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean

properties	content simple
used by	element PlannedTrainTechnicalData
annotation	documentation IM indicates to the RU whether the driver can rely on coasting. This is of both economic and ecological interest, as in many parts of the journey the trains may have enough inertia to be able to match the calculated time of the next location relying on coasting only.
source	<pre><xs:element name="Coasting" type="xs:boolean"> <xs:annotation> <xs:documentation>IM indicates to the RU whether the driver can rely on coasting. This is of both economic and ecological interest, as in many parts of the journey the trains may have enough inertia to be able to match the calculated time of the next location relying on coasting only.</xs:documentation> </xs:annotation> </xs:element></pre>

element **Comments**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
used by	elements LocationPrimaryInformation LocationSubsidiaryInformation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
source	<pre><xs:element name="Comments" type="FreeText"/></pre>									

element **CommitmentETA**


diagram	 <p>Identifies the commitment to the customer regarding date and time of the arrival date and time of the Wagon or Unit on the final destination of the customer siding.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element AlertMessage
annotation	documentation Identifies the commitment to the customer regarding date and time of the arrival date and time of the Wagon or Unit on the final destination of the customer siding.
source	<pre><xs:element name="CommitmentETA" type="xs:dateTime"> <xs:annotation> <xs:documentation>Identifies the commitment to the customer regarding date and time of the arrival date and time of the Wagon or Unit on the final destination of the customer siding.</xs:documentation> </xs:annotation></pre>

	<code></xs:element></code>
--	----------------------------------

element **Company**

diagram	 Identifies a railway company (RU or IM)												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	complexTypees CompositIdentifierOperationalType CompositIdentifierPlannedType												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Identifies a railway company (RU or IM)												
source	<pre><xs:element name="Company" type="CompanyCode"> <xs:annotation> <xs:documentation>Identifies a railway company (RU or IM)</xs:documentation> </xs:annotation> </xs:element></pre>												

element **ConsignmentNumber**

diagram	 Reference number assigned to a consignment by a lead RU
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	ConsignmentIdent
properties	content complex
used by	element WIMO Dataset/ConsignmentLevelData
annotation	documentation Reference number assigned to a consignment by a lead RU
source	<pre><xs:element name="ConsignmentNumber" type="ConsignmentIdent"> <xs:annotation> <xs:documentation>Reference number assigned to a consignment by a lead RU</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader COMS
annotation	documentation Consignment Order Message from Lead RU to RU
source	<pre> <xs:element name="ConsignmentOrderMessage"> <xs:annotation> <xs:documentation>Consignment Order Message from Lead RU to RU</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element name="COMS" maxOccurs="50"> <xs:annotation> <xs:documentation>Message (all bounded optional elements are bounded to to obligations of legacy systems)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="COM_Header"> <xs:annotation> <xs:documentation>Additional Header containing consignment related key data such as dossiernumber, version number and a change log for modifications</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="SendingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which created/amended the message (like 2185).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ReceivingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which is the recipient of the message (like 2185).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="MessageReferenceNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Message Reference NumberThis identification is being generated during creation of the message. This allows the tracing of the message.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="18">
      <xs:annotation>
        <xs:documentation>Use here a counter, any
system.</xs:documentation>
      </xs:annotation>
    </xs:maxLength>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="ShipmentType">
  <xs:annotation>
    <xs:documentation>Classification of the wagon order as
'CUV','CIM' or "SMGS".</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value="CIM">
        <xs:annotation>
          <xs:documentation>Regular transport, according
in basic to the CIM consignment note.</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="CUV">
        <xs:annotation>
          <xs:documentation>Transport of empty wagons. If
loaded and empty wagons are withing the same shipment, then the ShipmentType
has to be set to CIM. For the empty wagons the loading status has to be set
in the WagonDetails.</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="SMGS"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="ConsignmentOrderType"/>
<xs:element name="COM_PreparationDatetime">
  <xs:annotation>
    <xs:documentation>Date and Time of preparation of the
COM</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:dateTime"/>
  </xs:simpleType>
</xs:element>
<xs:element name="DossierNumber" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Internal identification number of
the Wo. This information is important to be able to identify the COM even
after modifications. Format: RRRYYYYMMDDNNNNNNN Where RRRR = railway code,
YYYY = year, MM = month, DD = day and NNNNNNN = running
number.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">

```

```

3]\d{8}"/>
    <xs:length value="19"/>
    <xs:pattern value="\d{4}20\d{2}[0-1][0-9][0-
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="VersionNumber">
  <xs:annotation>
    <xs:documentation>Message version number. This number
    hast to be incremented after each modification. On creation this value has
    to be set to 0.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:minInclusive value="0"/>
      <xs:maxInclusive value="100"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="PrintForm" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Which form to use for printout. CIM-
    CN or CIM-CN for combined traffic. This information assures, that the same
    paper document will be used for the 'duplicate of the consignment note' and
    the final print out of the ECN for the consignee.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value="WLT">
        <xs:annotation>
          <xs:documentation>Wagon load transport form to
          be used for print-out.</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="CT">
        <xs:annotation>
          <xs:documentation>Combined traffic form to be
          used for print-out.</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Intermodal" minOccurs="0">
  <xs:simpleType>
    <xs:restriction base="xs:byte">
      <xs:pattern value="0|1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ChangeLog" minOccurs="0"
maxOccurs="100">
  <xs:annotation>
    <xs:documentation>Log of changes made by the LeadRU /
    contractual carrier during the transport.</xs:documentation>
  </xs:annotation>
</xs:complexType>
</xs:sequence>

```

```

<xs:element name="DateTime">
  <xs:annotation>
    <xs:documentation>DateTime, when the changes
were applied.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:dateTime"/>
  </xs:simpleType>
</xs:element>
<xs:element name="NumberOfModifiedVersion">
  <xs:annotation>
    <xs:documentation>Version number of the modified
message (as also written into
COMHeader/COMVersionNumber).</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int"/>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="COM">
  <xs:annotation>
    <xs:documentation>Consignment order
message</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="AcceptancePoint">
        <xs:annotation>
          <xs:documentation>Description of location and time for
the take over of the consignment</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element ref="Station"/>
            <xs:element ref="RP_Code" minOccurs="0"/>
            <xs:element ref="ProductionStation" minOccurs="0"/>
            <xs:element name="AcceptanceDate" minOccurs="0">
              <xs:annotation>
                <xs:documentation>Date and time (month, day and
hour) at which the goods were accepted. </xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:dateTime"/>
              </xs:simpleType>
            </xs:element>
            <xs:element name="ConsignmentNumber">
              <xs:annotation>
                <xs:documentation>Running number and check digit
of the consignment between Lead RU and customer. Format: NNNNC The number
consists of NNNNN = running number C = check digit, </xs:documentation>
              </xs:annotation>
              <xs:simpleType>

```

```

        <xs:restriction base="xs:string">
            <xs:length value="6"/>
            <xs:pattern value="\d*[1-9]\d*"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="ForwardingTrainNumber"
minOccurs="0">
    <xs:annotation>
        <xs:documentation>Train number at shipping
    </xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="CarrierCode" type="CompanyCode">
    <xs:annotation>
        <xs:documentation>Code of the shipping carrier
mentioned in the consignment number.</xs:documentation>
    </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="DeliveryPoint">
    <xs:annotation>
        <xs:documentation>Description of location and time for
the hand over of the consignment</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="Station"/>
            <xs:element ref="RP_Code" minOccurs="0"/>
            <xs:element ref="ProductionStation" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element ref="Customers" minOccurs="2" maxOccurs="4">
    <xs:annotation>
        <xs:documentation>Information about the consignor,
consignee and freight payers. At least information about consignor and
consignee has to be given</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="ConsignorDeclarations" minOccurs="0"
maxOccurs="10">
    <xs:annotation>
        <xs:documentation>Consignors declarartions, this
element contains either declarations of the original consignor or
declarations of the LeadRU as consignor</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="ConsignorDeclarationCode"/>

```

```

        <xs:element ref="DeclarationText" minOccurs="0"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GeneralInformation" minOccurs="0">
    <xs:annotation>
      <xs:documentation>General information about the
complete consignment</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="ConsignorReference" minOccurs="0">
          <xs:annotation>
            <xs:documentation>Consignor's reference
concerning the complete consignment</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:minLength value="1"/>
              <xs:maxLength value="35"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="InformationConsignee"
minOccurs="0">
          <xs:annotation>
            <xs:documentation>Information from the consignor
to the consignee relating to the consignment. This information is not to
commit the carrier.</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:minLength value="1"/>
              <xs:maxLength value="350"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="WagonGroupInfo" minOccurs="0">
          <xs:annotation>
            <xs:documentation>Consignor information
regarding the whole consignment. Comparable with the element WagonInfo, but
for all wagons.</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:maxLength value="500"/>
              <xs:minLength value="1"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="AttachedDocuments" minOccurs="0"
maxOccurs="10">
    <xs:annotation>
      <xs:documentation>Paper documents accompanying the
transport</xs:documentation>

```

```

</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="DocumentType">
      <xs:annotation>
        <xs:documentation>Type code of attached
document. The UN/DIFACT 1001 list of codes is to be used to code
accompanying documents.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:int">
          <xs:minInclusive value="1"/>
          <xs:maxInclusive value="999"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="DocumentInformation"
minOccurs="0">
      <xs:annotation>
        <xs:documentation>Additional information
regarding the attached document may be entered here.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="35"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element ref="Quantity" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Amount of the documents of the
specified type.</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="DocumentTypeDescription"
minOccurs="0">
      <xs:annotation>
        <xs:documentation>Description of document type,
when it is not in the UN/EDIFACT 1001 list included.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="35"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="Filename" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Filename of embedded pdf in
legacy system</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:maxLength value="35"/>
          <xs:minLength value="1"/>
        </xs:restriction>

```



```

        </xs:simpleType>
      </xs:element>
      <xs:element ref="StatusOfDocument" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CommercialSpecifications" minOccurs="0"
maxOccurs="5">
  <xs:annotation>
    <xs:documentation>Commercial
Specification</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CommercialSpecificationCode"/>
      <xs:element name="SpecificationText" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Additional Text for codes with
free text</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="350"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CarrierCode" type="CompanyCode"
minOccurs="0" maxOccurs="10">
        <xs:annotation>
          <xs:documentation>additional carrier code
belonging to the given contract number</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="ContractNumber" minOccurs="0"
maxOccurs="10">
        <xs:annotation>
          <xs:documentation>additional contract number
according to the given carrier code.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1">
              <xs:annotation>
                <xs:documentation>has to be sent as n6
(with leading zeros if necessary)</xs:documentation>
              </xs:annotation>
            </xs:minLength>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="PrepaymentInstructions">
  <xs:annotation>
    <xs:documentation>Prepayment</xs:documentation>
  </xs:annotation>

```

```

</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="PrepaymentCustomer" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Prepaidcode (given by the
client)</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element ref="PrepaidCodeCustomer"/>
    <xs:element ref="IncotermCode"/>
    <xs:element ref="PrepaidcodeCarrier"/>
    <xs:element name="PaidUpTo" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Charges Paid Up To ... This
information is being sent by the consignor in agreement with the contractual
carrier so only one structure is needed for field 20 and 49. The carrier is
only allowed to apply changes, when ordered by the
consignor.</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="AdditionalCharges" minOccurs="0"
maxOccurs="5">
      <xs:annotation>
        <xs:documentation>Additional
Charges</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="Code">
      <xs:annotation>
        <xs:documentation>Additional charges code
according CIT GLV-CIM appendix 3</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="Description" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Additional charges
description</xs:documentation>
      </xs:annotation>
    </xs:element>
  </xs:sequence>
</xs:complexType>

```

```

        <xs:maxLength value="35"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Tariff">
  <xs:annotation>
    <xs:documentation>Number of customer agreement or
tariff</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="ContractNumber">
        <xs:annotation>
          <xs:documentation>Number of customer
agreement.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1">
              <xs:annotation>
                <xs:documentation>has to be sent as n6
(with leading zeros if necessary)</xs:documentation>
              </xs:annotation>
            </xs:minLength>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="TariffNumber">
        <xs:annotation>
          <xs:documentation>Number of the
tariff.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1">
              <xs:annotation>
                <xs:documentation>has to be sent as n6
(with leading zeros if necessary, but without check
digit)</xs:documentation>
              </xs:annotation>
            </xs:minLength>
            <xs:maxLength value="6"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
<xs:element name="SectionalInvoicing" minOccurs="0">
  <xs:annotation>

```

```

        <xs:documentation>Sectional
Invoicing</xs:documentation>
    </xs:annotation>
    <xs:complexType>
    <xs:sequence>
        <xs:element name="Section" maxOccurs="30">
            <xs:annotation>
                <xs:documentation>Sectional
Invoicing</xs:documentation>
            </xs:annotation>
            <xs:complexType>
            <xs:sequence>
                <xs:element name="InvoicingCarrierCode"
type="CompanyCode">
                    <xs:annotation>
                        <xs:documentation>Sectional invoicing
by</xs:documentation>
                    </xs:annotation>
                    </xs:element>
                    <xs:element name="InvoicedSection">
                        <xs:annotation>
                            <xs:documentation>Information about the
section to be invoiced.</xs:documentation>
                        </xs:annotation>
                        <xs:complexType>
                        <xs:choice>
                            <xs:element name="CountryCode"
type="CountryIdentISO">
                                <xs:annotation>
                                    <xs:documentation>Invoiced section
specified by country</xs:documentation>
                                </xs:annotation>
                                </xs:element>
                                <xs:element name="SectionCarrierCode"
type="CompanyCode">
                                    <xs:annotation>
                                        <xs:documentation>Invoiced section
specified by carrier</xs:documentation>
                                    </xs:annotation>
                                    </xs:element>
                                </xs:choice>
                            </xs:complexType>
                        </xs:element>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="DeclarationOfValue" minOccurs="0">
        <xs:annotation>
            <xs:documentation>Details of the value of the goods
and the currency code when the value exceeds the limit given in CIM Article
30 section 2.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
        <xs:sequence>
            <xs:element name="Amount" type="Money_Type">

```

```

        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode"
type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-
4217 alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="InterestInDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the amount and currency
code of a special interest in delivery.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode"
type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-
4217 alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CashOnDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the amount to be
collected on delivery and the currency code.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode"
type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-
4217 alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

<xs:element name="RouteSection" minOccurs="0"
maxOccurs="30">
  <xs:annotation>
    <xs:documentation>Route sequence Sequential
information about the complete routing of the consignment, the LeadRu
decides wether to provide this information or not</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="SequenceID" type="xs:int">
        <xs:annotation>
          <xs:documentation>Position of the route section
in transport chain. Used to determine the exact way of the transport for
customs purposes.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
    <xs:element name="RouteCode">
      <xs:annotation>
        <xs:documentation>Route code (International
RouteCode)</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:length value="5"/>
          <xs:pattern value="\d*[1-9]\d*0"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="RouteText" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Description of the specific
route section</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="80"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="SpecialTreatments" minOccurs="0"
maxOccurs="30"/>
<xs:element name="CustomsProcedures" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Customs
procedures</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="RU_Partner" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Code of the RU entrusted of
customs procedures. </xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element ref="Location"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CustomsData" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Customs Data</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="SimplifiedTransportProcedure"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Simplified transport procedure
is used (STP).</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:boolean"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="PrincipalRU" type="CompanyCode"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Code for the principal
RU</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CustomsSurveillance">
        <xs:annotation>
          <xs:documentation>Good under customs
surveillance</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:boolean"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CustomsEndorsements"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Reserved for endorsements by
customs or a consignor/consignee authorised by customs. Data element in
accordance with Regulation (EC) 1875/2006.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="350"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="RU_Declarations" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Carriers

```

```

declaration</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="RU_Declaration" minOccurs="0"
maxOccurs="30">
                <xs:annotation>
                    <xs:documentation>Details of the carriers
declaration.</xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="DeclaringRU"
type="CompanyCode">
                            <xs:annotation>
                                <xs:documentation>Code of carrier, who
added the declaration.</xs:documentation>
                            </xs:annotation>
                            </xs:element>
                            <xs:element ref="RU_DeclarationCode"/>
                            <xs:element ref="DeclarationText"
minOccurs="0"/>
                        </xs:sequence>
                    </xs:complexType>
                </xs:element>
                <xs:element name="DifferentAcceptance"
minOccurs="0">
                    <xs:annotation>
                        <xs:documentation>Details of the changes of the
acceptance point given by the consignor.</xs:documentation>
                    </xs:annotation>
                    <xs:complexType>
                        <xs:sequence>
                            <xs:element name="DifferentAcceptancePoint"
type="LocationIdent" minOccurs="0">
                                <xs:annotation>
                                    <xs:documentation>Variance of acceptance
point given in structure AcceptancePoint.</xs:documentation>
                                </xs:annotation>
                                </xs:element>
                                <xs:element name="DifferentAcceptanceDate"
minOccurs="0">
                                    <xs:annotation>
                                        <xs:documentation>Variance of acceptance
date given structure AcceptancePoint.</xs:documentation>
                                    </xs:annotation>
                                    <xs:simpleType>
                                        <xs:restriction base="xs:dateTime"/>
                                    </xs:simpleType>
                                </xs:element>
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Carriers" maxOccurs="30">
    <xs:complexType>

```



```

<xs:sequence>
  <xs:element ref="CarrierStatus"/>
  <xs:element name="CarrierCode" type="CompanyCode">
    <xs:annotation>
      <xs:documentation>Railway Undertaking (Railway
Code)</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="ResponsibleCarrierCode"
type="CompanyCode" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Railway Undertaking (Railway
Code) of the carrier in charge.</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="CarrierName" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Name of
Carrier</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="35"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="StreetNumber" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Streetnumber of
carrier.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="5"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="Street" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Name of street of the
carrier</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="35"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="ZIPCode" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Postal Code</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>

```

```

        <xs:maxLength value="9"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CountryCode"
type="CountryIdentISO" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO
Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SectionFrom" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>Start of section to be
performed by the carrier. This can be a station OR a border crossing
point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SectionTo" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>End of section to be performed
by the carrier. This can be a station OR a border crossing
point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SubContractNumber_SplitContract"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Number of customer agreement
between the responsible and the operating carrier</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1">
        <xs:annotation>
          <xs:documentation>has to be sent as n6
(with leading zeros if necessary)</xs:documentation>
        </xs:annotation>
      </xs:minLength>
      <xs:maxLength value="6"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
<xs:attribute name="sequenceID" type="xs:int">
  <xs:annotation>
    <xs:documentation>Position of carrier during

```

```

transport. </xs:documentation>
    </xs:annotation>
    </xs:attribute>
    </xs:complexType>
</xs:element>
<xs:element name="LeadCarrier">
    <xs:annotation>
        <xs:documentation>LeadCarrier/ Contractual
carrier</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="CarrierCode" type="CompanyCode">
                <xs:annotation>
                    <xs:documentation>Contractual carrier, railway
undertaking (Railway Code).</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="CarrierName" minOccurs="0">
                <xs:annotation>
                    <xs:documentation>Name of contractual
carrier</xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:string">
                        <xs:minLength value="1"/>
                        <xs:maxLength value="35"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
            <xs:element name="StreetNumber" minOccurs="0">
                <xs:annotation>
                    <xs:documentation>Streetnumber of
carrier.</xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:string">
                        <xs:minLength value="1"/>
                        <xs:maxLength value="5"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
            <xs:element name="Street" minOccurs="0">
                <xs:annotation>
                    <xs:documentation>Name of street of the
carrier</xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:string">
                        <xs:minLength value="1"/>
                        <xs:maxLength value="35"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
            <xs:element name="ZIPCode" minOccurs="0">
                <xs:annotation>
                    <xs:documentation>Postal Code</xs:documentation>
                </xs:annotation>

```

```

<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="9"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CountryCode"
type="CountryIdentISO" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO
Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="Signature" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Signature of the contractual
carrier. When missing, the shipment number (CIM: 62) shall be used for
signature purposes.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="MadeOut" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Made out</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Place">
        <xs:annotation>
          <xs:documentation>Place on which the consignment
note was made out</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="35"/>
            <xs:minLength value="1"/>
          </xs:restriction>
        </xs:simpleType>

```

```

</xs:element>
<xs:element name="Date" type="xs:date">
  <xs:annotation>
    <xs:documentation>Date at which the consignment
note was made out.</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ChargesNote" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Charges note</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ChargesNoteAvailable"
type="xs:boolean"/>
      <xs:element name="DateOfReturn" type="xs:date"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Date, when the destination
carrier sent the charges note back to the contractual
carrier.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TransitPeriodExtensions" minOccurs="0"
maxOccurs="30">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CodeOfCause"/>
      <xs:element name="Description" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Description for CodeOfCause
no. 9.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="180"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Place">
        <xs:annotation>
          <xs:documentation>Place of the
extension.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="180"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

<xs:element name="Beginning">
  <xs:annotation>
    <xs:documentation>Beginning of the
extension.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:dateTime"/>
  </xs:simpleType>
</xs:element>
<xs:element name="Ending">
  <xs:annotation>
    <xs:documentation>End of
extension.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:dateTime"/>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ChargingSections" maxOccurs="15">
  <xs:annotation>
    <xs:documentation>Charging section</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Start" type="LocationIdent">
        <xs:annotation>
          <xs:documentation>Start of the charging
section</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="End" type="LocationIdent">
        <xs:annotation>
          <xs:documentation>End of the charging
section</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CommercialRouteCode"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Route code (RIP) when the
customer agreement or the tariff applied provide for it. </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="3"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CurrencyCode"
type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Code for the currency of the
amounts entered in the charging section.</xs:documentation>
        </xs:annotation>

```

```

</xs:element>
<xs:element name="Tariff" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges Section
  </xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="NHMCode" type="NHMCodeType">
        <xs:annotation>
          <xs:documentation>NHM code determining the
charges applicable.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="TariffNumber">
        <xs:annotation>
          <xs:documentation>Customer agreement or
tariff applied</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ChargedMass" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Charged mass [weight in
kg]. As appropriate, area in m2 or the volume of the wagon or goods in m3 if
used as the basis for charging.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="value">
              <xs:simpleType>
                <xs:restriction base="xs:decimal">
                  <xs:minInclusive value="1"/>
                  <xs:totalDigits value="8"/>
                  <xs:fractionDigits value="1"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
            <xs:element name="measure"
minOccurs="0">
              <xs:simpleType>
                <xs:restriction base="xs:token">
                  <xs:enumeration value="kg"/>
                  <xs:enumeration value="m2"/>
                  <xs:enumeration value="m3"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="ExchangeRate" minOccurs="0">
        <xs:annotation>

```

```

<xs:documentation>Exchange rate for
amounts to be paid by the consignor or consignee which are not expressed in
the invoicing currency.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:decimal">
    <xs:totalDigits value="18"/>
    <xs:fractionDigits value="3"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Distance" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Tariff distance,
expressed in km or zones, between the stations or points corresponding to
the beginning and end of the charging section.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="KM">
        <xs:annotation>
          <xs:documentation>Tariff distance,
expressed in km, between the stations or points corresponding to the
beginning and end of the charging section.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="99999"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Zones">
        <xs:annotation>
          <xs:documentation>Tariff distance,
expressed in zones, between the stations or points corresponding to the
beginning and end of the charging section.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="99"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
<xs:element name="Fee" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Supplements, fees,
deductions</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:totalDigits value="4"/>
      <xs:minInclusive value="1"/>
    </xs:restriction>
  </xs:simpleType>

```



```

</xs:simpleType>
</xs:element>
<xs:element name="FreightCharges"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges (paid
and due)</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="Prepaid"
type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges
to be paid by the consignor in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Transferred"
type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges
to be paid by the consignee in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
<xs:element name="AdditionalCharges" minOccurs="0"
maxOccurs="10">
  <xs:annotation>
    <xs:documentation/>
    <xs:documentation>Sum of
Prepaid</xs:documentation>
    <xs:documentation>Sum of
Transferred</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Code">
        <xs:annotation>
          <xs:documentation>Additional charges
code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="2"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:choice>
    <xs:element name="Prepaid"
type="Money_Type">
      <xs:annotation>

```

```

<xs:documentation>Prepaid</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="Transferred"
type="Money_Type">
    <xs:annotation>
<xs:documentation>Transferred</xs:documentation>
    </xs:annotation>
  </xs:element>
</xs:choice>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="Wagons" minOccurs="0" maxOccurs="99">
  <xs:annotation>
    <xs:documentation>Contains list of transported Goods,
Wagons and ITU etc.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="WagonPreviousNumberFreight"
minOccurs="0" maxOccurs="20">
  <xs:annotation>
    <xs:documentation>Identifies the previous freight
wagon if a shipment or Intermodal unit has changed the wagon during its
journey</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="WagonIdent">
      <xs:length value="12"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="AgreedTimeOfDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>The requested Date and Time for the
delivery of a wagon/Shipment or Intermodal units at customer
sidings</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **ConsignmentOrderMessage/COMS**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 1 maxOcc 50 content complex</p>
<p>children</p>	<p>COM Header COM</p>
<p>annotation</p>	<p>documentation Message (all bounded optional elements are bounded to to obligations of legacy systems)</p>
<p>source</p>	<pre> <xs:element name="COMS" maxOccurs="50"> <xs:annotation> <xs:documentation>Message (all bounded optional elements are bounded to to obligations of legacy systems)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="COM_Header"> <xs:annotation> <xs:documentation>Additional Header containing consignment related key data such as dossiernumber, version number and a change log for modifications</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="SendingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which created/amended the message (like 2185).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ReceivingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which is the receipt of the message (like 2185).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="MessageReferenceNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Message Reference NumberThis identification is being generated during creation of the message. This allows the tracing of the message.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="18"> <xs:annotation> <xs:documentation>Use here a counter, any </xs:annotation> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

system.</xs:documentation>
    </xs:annotation>
    </xs:maxLength>
    </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="ShipmentType">
    <xs:annotation>
        <xs:documentation>Classification of the wagon order as
'CUV', 'CIM' or "SMGS".</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:token">
            <xs:enumeration value="CIM">
                <xs:annotation>
                    <xs:documentation>Regular transport, according in
basic to the CIM consignment note.</xs:documentation>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="CUV">
                <xs:annotation>
                    <xs:documentation>Transport of empty wagons. If loaded
and empty wagons are withing the same shipment, then the ShipmentType has to
be set to CIM. For the empty wagons the loading status has to be set in the
WagonDetails.</xs:documentation>
                </xs:annotation>
            </xs:enumeration>
            <xs:enumeration value="SMGS"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element ref="ConsignmentOrderType"/>
<xs:element name="COM_PreparationDatetime">
    <xs:annotation>
        <xs:documentation>Date and Time of preparation of the
COM</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:dateTime"/>
    </xs:simpleType>
</xs:element>
<xs:element name="DossierNumber" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Internal identification number of the Wo.
This information is important to be able to identify the COM even after
modifications. Format: RRRRYYYMMDDNNNNNNNN Where RRRR = railway code, YYYY =
year, MM = month, DD = day and NNNNNNNN = running number.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:length value="19"/>
            <xs:pattern value="\d{4}20\d{2}[0-1][0-9][0-3]\d{8}"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="VersionNumber">
    <xs:annotation>
        <xs:documentation>Message version number. This number hast

```

```

to be incremented after each modification. On creation this value has to be
set to 0.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:int">
    <xs:minInclusive value="0"/>
    <xs:maxInclusive value="100"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="PrintForm" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Which form to use for printout. CIM-CN or
CIM-CN for combined traffic. This information assures, that the same paper
document will be used for the 'duplicate of the consignment note' and the
final print out of the ECN for the consignee.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value="WLT">
        <xs:annotation>
          <xs:documentation>Wagon load transport form to be used
for print-out.</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="CT">
        <xs:annotation>
          <xs:documentation>Combined traffic form to be used for
print-out.</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Intermodal" minOccurs="0">
  <xs:simpleType>
    <xs:restriction base="xs:byte">
      <xs:pattern value="0|1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ChangeLog" minOccurs="0" maxOccurs="100">
  <xs:annotation>
    <xs:documentation>Log of changes made by the LeadRU /
contractual carrier during the transport.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DateTime">
        <xs:annotation>
          <xs:documentation>DateTime, when the changes were
applied.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:dateTime"/>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="NumberOfModifiedVersion">

```

```

        <xs:annotation>
          <xs:documentation>Version number of the modified
message (as also written into
COMHeader/COMVersionNumber).</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int"/>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="COM">
  <xs:annotation>
    <xs:documentation>Consignment order message</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="AcceptancePoint">
        <xs:annotation>
          <xs:documentation>Description of location and time for the
take over of the consignment</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element ref="Station"/>
            <xs:element ref="RP_Code" minOccurs="0"/>
            <xs:element ref="ProductionStation" minOccurs="0"/>
            <xs:element name="AcceptanceDate" minOccurs="0">
              <xs:annotation>
                <xs:documentation>Date and time (month, day and hour)
at which the goods were accepted. </xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:dateTime"/>
              </xs:simpleType>
            </xs:element>
            <xs:element name="ConsignmentNumber">
              <xs:annotation>
                <xs:documentation>Running number and check digit of
the consignment between Lead RU and customer. Format: NNNNNC The number
consists of NNNNN = running number C = check digit, </xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:string">
                  <xs:length value="6"/>
                  <xs:pattern value="\d*[1-9]\d*"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
            <xs:element name="ForwardingTrainNumber" minOccurs="0">
              <xs:annotation>
                <xs:documentation>Train number at shipping
</xs:documentation>
              </xs:annotation>

```

```

        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CarrierCode" type="CompanyCode">
        <xs:annotation>
          <xs:documentation>Code of the shipping carrier
mentioned in the consignment number.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeliveryPoint">
  <xs:annotation>
    <xs:documentation>Description of location and time for the
hand over of the consignment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="Station"/>
      <xs:element ref="RP_Code" minOccurs="0"/>
      <xs:element ref="ProductionStation" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element ref="Customers" minOccurs="2" maxOccurs="4">
  <xs:annotation>
    <xs:documentation>Information about the consignor, consignee
and freight payers. At least information about consignor and consignee has
to be given</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="ConsignorDeclarations" minOccurs="0"
maxOccurs="10">
  <xs:annotation>
    <xs:documentation>Consignors declarartions, this element
contains either declarations of the original consignor or declarations of
the LeadRU as consignor</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ConsignorDeclarationCode"/>
      <xs:element ref="DeclarationText" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GeneralInformation" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Geneeral information about the complete
consignment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ConsignorReference" minOccurs="0">

```

```

        <xs:annotation>
          <xs:documentation>Consignor's reference concerning the
complete consignment</xs:documentation>
        </xs:annotation>
      </xs:simpleType>
    </xs:restriction>
  </xs:element>
  <xs:element name="InformationConsignee" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Information from the consignor to
the consignee relating to the consignment. This information is not to commit
the carrier.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="350"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="WagonGroupInfo" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Consignor information regarding the
whole consignment. Comparable with the element WagonInfo, but for all
wagons.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:maxLength value="500"/>
        <xs:minLength value="1"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
  <xs:element name="AttachedDocuments" minOccurs="0"
maxOccurs="10">
    <xs:annotation>
      <xs:documentation>Paper documents accompanying the
transport</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="DocumentType">
          <xs:annotation>
            <xs:documentation>Type code of attached document. The
UN/DIFACT 1001 list of codes is to be used to code accompanying
documents.</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:int">
              <xs:minInclusive value="1"/>
              <xs:maxInclusive value="999"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```



```

        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="DocumentInformation" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Additional information regarding the
attached document may be entered here.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="35"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element ref="Quantity" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Amount of the documents of the
specified type.</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="DocumentTypeDescription" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Description of document type, when
it is not in the UN/EDIFACT 1001 list included.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="35"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="Filename" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Filename of embedded pdf in legacy
system</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:maxLength value="35"/>
          <xs:minLength value="1"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element ref="StatusOfDocument" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CommercialSpecifications" minOccurs="0"
maxOccurs="5">
  <xs:annotation>
    <xs:documentation>Commercial
Specification</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CommercialSpecificationCode"/>

```

```

<xs:element name="SpecificationText" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Additional Text for codes with free
text</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="350"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CarrierCode" type="CompanyCode"
minOccurs="0" maxOccurs="10">
  <xs:annotation>
    <xs:documentation>additional carrier code belonging to
the given contract number</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="ContractNumber" minOccurs="0"
maxOccurs="10">
  <xs:annotation>
    <xs:documentation>additional contract number according
to the given carrier code.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1">
        <xs:annotation>
          <xs:documentation>has to be sent as n6 (with
leading zeros if necessary)</xs:documentation>
        </xs:annotation>
      </xs:minLength>
      <xs:maxLength value="6"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="PrepaymentInstructions">
  <xs:annotation>
    <xs:documentation>Prepayment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="PrepaymentCustomer" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Prepaidcode (given by the
client)</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:choice>
            <xs:element ref="PrepaidCodeCustomer"/>
            <xs:element ref="IncotermCode"/>
          </xs:choice>
        </xs:complexType>
      </xs:element>

```

```

</xs:element ref="PrepaidcodeCarrier"/>
<xs:element name="PaidUpTo" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Charges Paid Up To ... This
information is being sent by the consignor in agreement with the contractual
carrier so only one structure is needed for field 20 and 49. The carrier is
only allowed to apply changes, when ordered by the
consignor.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:complexContent>
      <xs:extension base="LocationIdent"/>
    </xs:complexContent>
  </xs:complexType>
</xs:element>
<xs:element name="AdditionalCharges" minOccurs="0"
maxOccurs="5">
  <xs:annotation>
    <xs:documentation>Additional
Charges</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Code">
        <xs:annotation>
          <xs:documentation>Additional charges code
according CIT GLV-CIM appendix 3</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="2"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Description" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Additional charges
description</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Tariff">
  <xs:annotation>
    <xs:documentation>Number of customer agreement or
tariff</xs:documentation>
  </xs:annotation>

```

```

        <xs:complexType>
          <xs:choice>
            <xs:element name="ContractNumber">
              <xs:annotation>
                <xs:documentation>Number of customer
agreement.</xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:string">
                  <xs:minLength value="1">
                    <xs:annotation>
                      <xs:documentation>has to be sent as n6 (with
leading zeros if necessary)</xs:documentation>
                    </xs:annotation>
                  </xs:minLength>
                  <xs:maxLength value="6"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
            <xs:element name="TariffNumber">
              <xs:annotation>
                <xs:documentation>Number of the
tariff.</xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:string">
                  <xs:minLength value="1">
                    <xs:annotation>
                      <xs:documentation>has to be sent as n6 (with
leading zeros if necessary, but without check digit)</xs:documentation>
                    </xs:annotation>
                  </xs:minLength>
                  <xs:maxLength value="6"/>
                  <xs:pattern value="\d*[1-9]\d*"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
          </xs:choice>
        </xs:complexType>
      </xs:element>
      <xs:element name="SectionalInvoicing" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Sectional Invoicing</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="Section" maxOccurs="30">
              <xs:annotation>
                <xs:documentation>Sectional
Invoicing</xs:documentation>
              </xs:annotation>
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="InvoicingCarrierCode"
type="CompanyCode">
                    <xs:annotation>
                      <xs:documentation>Sectional invoicing
by</xs:documentation>

```

```

        </xs:annotation>
      </xs:element>
    <xs:element name="InvoicedSection">
      <xs:annotation>
        <xs:documentation>Information about the section
to be invoiced.</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:choice>
          <xs:element name="CountryCode"
type="CountryIdentISO">
            <xs:annotation>
              <xs:documentation>Invoiced section
specified by country</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="SectionCarrierCode"
type="CompanyCode">
            <xs:annotation>
              <xs:documentation>Invoiced section
specified by carrier</xs:documentation>
            </xs:annotation>
          </xs:element>
        </xs:choice>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="DeclarationOfValue" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the value of the goods and the
currency code when the value exceeds the limit given in CIM Article 30
section 2.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode" type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-4217
alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="InterestInDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the amount and currency code of
a special interest in delivery.</xs:documentation>

```

```

</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="Amount" type="Money_Type">
      <xs:annotation>
        <xs:documentation>Amount</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="CurrencyCode" type="CurrencyCode_Type">
      <xs:annotation>
        <xs:documentation>Currency abbreviation (ISO-4217
alphanumeric)</xs:documentation>
      </xs:annotation>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CashOnDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the amount to be collected on
delivery and the currency code.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode" type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-4217
alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="RouteSection" minOccurs="0" maxOccurs="30">
  <xs:annotation>
    <xs:documentation>Route sequence Sequential information
about the complete routing of the consignment, the LeadRu decides wether to
provide this information or not</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="SequenceID" type="xs:int">
        <xs:annotation>
          <xs:documentation>Position of the route section in
transport chain. Used to determine the exact way of the transport for
customs purposes.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
    <xs:element name="RouteCode">
      <xs:annotation>
        <xs:documentation>Route code (International
RouteCode)</xs:documentation>
      </xs:annotation>
    </xs:element>
  </xs:complexType>
</xs:element>

```

```

</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:length value="5"/>
    <xs:pattern value="\d*[1-9]\d*0"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="RouteText" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Description of the specific route
section</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="80"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="SpecialTreatments" minOccurs="0"
maxOccurs="30"/>
<xs:element name="CustomsProcedures" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Customs procedures</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="RU_Partner" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Code of the RU entrusted of customs
procedures. </xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element ref="Location"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CustomsData" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Customs Data</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="SimplifiedTransportProcedure"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Simplified transport procedure is
used (STP).</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:boolean"/>
        </xs:simpleType>
      </xs:element>

```

```

<xs:element name="PrincipalRU" type="CompanyCode"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Code for the principal
RU</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="CustomsSurveillance">
  <xs:annotation>
    <xs:documentation>Good under customs
surveillance</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:boolean"/>
  </xs:simpleType>
</xs:element>
<xs:element name="CustomsEndorsements" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Reserved for endorsements by customs
or a consignor/consignee authorised by customs. Data element in accordance
with Regulation (EC) 1875/2006).</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="350"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="RU_Declarations" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Carriers declaration</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="RU_Declaration" minOccurs="0"
maxOccurs="30">
        <xs:annotation>
          <xs:documentation>Details of the carriers
declaration.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="DeclaringRU" type="CompanyCode">
              <xs:annotation>
                <xs:documentation>Code of carrier, who added the
declaration.</xs:documentation>
              </xs:annotation>
            </xs:element>
            <xs:element ref="RU_DeclarationCode"/>
            <xs:element ref="DeclarationText" minOccurs="0"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DifferentAcceptance" minOccurs="0">

```



```

        <xs:annotation>
          <xs:documentation>Details of the changes of the
acceptance point given by the consignor.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="DifferentAcceptancePoint"
type="LocationIdent" minOccurs="0">
              <xs:annotation>
                <xs:documentation>Variance of acceptance point
given in structure AcceptancePoint.</xs:documentation>
              </xs:annotation>
            </xs:element>
            <xs:element name="DifferentAcceptanceDate"
minOccurs="0">
              <xs:annotation>
                <xs:documentation>Variance of acceptance date
given structure AcceptancePoint.</xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:dateTime"/>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
<xs:element name="Carriers" maxOccurs="30">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CarrierStatus"/>
      <xs:element name="CarrierCode" type="CompanyCode">
        <xs:annotation>
          <xs:documentation>Railway Undertaking (Railway
Code)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="ResponsibleCarrierCode"
type="CompanyCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Railway Undertaking (Railway Code)
of the carrier in charge.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CarrierName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of Carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="StreetNumber" minOccurs="0">

```

```

        <xs:annotation>
          <xs:documentation>Streetnumber of
carrier.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="5"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Street" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of street of the
carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ZIPCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Postal Code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="9"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="City" minOccurs="0">
        <xs:annotation>
          <xs:documentation>City/Town</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CountryCode" type="CountryIdentISO"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Country Code (ISO
Code)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="SectionFrom" type="LocationIdent">
        <xs:annotation>
          <xs:documentation>Start of section to be performed by
the carrier. This can be a station OR a border crossing
point.</xs:documentation>
        </xs:annotation>

```

```

</xs:element>
<xs:element name="SectionTo" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>End of section to be performed by
the carrier. This can be a station OR a border crossing
point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SubContractNumber_SplitContract"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Number of customer agreement between
the responsible and the operating carrier</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1">
        <xs:annotation>
          <xs:documentation>has to be sent as n6 (with
leading zeros if necessary)</xs:documentation>
        </xs:annotation>
      </xs:minLength>
      <xs:maxLength value="6"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
<xs:attribute name="sequenceID" type="xs:int">
  <xs:annotation>
    <xs:documentation>Position of carrier during transport.
</xs:documentation>
  </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>
<xs:element name="LeadCarrier">
  <xs:annotation>
    <xs:documentation>LeadCarrier/ Contractual
carrier</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CarrierCode" type="CompanyCode">
        <xs:annotation>
          <xs:documentation>Contractual carrier, railway
undertaking (Railway Code).</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CarrierName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of contractual
carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

</xs:simpleType>
</xs:element>
<xs:element name="StreetNumber" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Streetnumber of
carrier.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="5"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Street" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Name of street of the
carrier</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ZIPCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Postal Code</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="9"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CountryCode" type="CountryIdentISO"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO
Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="Signature" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Signature of the contractual

```

```

carrier. When missing, the shipment number (CIM: 62) shall be used for
signature purposes.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="35"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="MadeOut" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Made out</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Place">
        <xs:annotation>
          <xs:documentation>Place on which the consignment note
was made out</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="35"/>
            <xs:minLength value="1"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Date" type="xs:date">
        <xs:annotation>
          <xs:documentation>Date at which the consignment note
was made out.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ChargesNote" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Charges note</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ChargesNoteAvailable"
type="xs:boolean"/>
      <xs:element name="DateOfReturn" type="xs:date"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Date, when the destination carrier
sent the charges note back to the contractual carrier.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

<xs:element name="TransitPeriodExtensions" minOccurs="0"
maxOccurs="30">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CodeOfCause"/>
      <xs:element name="Description" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Description for CodeOfCause no.
9.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="180"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Place">
        <xs:annotation>
          <xs:documentation>Place of the
extension.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="180"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Beginning">
        <xs:annotation>
          <xs:documentation>Beginning of the
extension.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:dateTime"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Ending">
        <xs:annotation>
          <xs:documentation>End of extension.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:dateTime"/>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ChargingSections" maxOccurs="15">
  <xs:annotation>
    <xs:documentation>Charging section</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Start" type="LocationIdent">
        <xs:annotation>
          <xs:documentation>Start of the charging

```

```

section</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="End" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>End of the charging
section</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="CommercialRouteCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Route code (RIP) when the customer
agreement or the tariff applied provide for it. </xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:length value="3"/>
      <xs:pattern value="\d*[1-9]\d*" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CurrencyCode" type="CurrencyCode_Type">
  <xs:annotation>
    <xs:documentation>Code for the currency of the amounts
entered in the charging section.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="Tariff" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges Section
Tariff</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="NHMCode" type="NHMCodeType">
        <xs:annotation>
          <xs:documentation>NHM code determining the
charges applicable.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="TariffNumber">
        <xs:annotation>
          <xs:documentation>Customer agreement or tariff
applied</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ChargedMass" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Charged mass [weight in kg].
As appropriate, area in m2 or the volume of the wagon or goods in m3 if used
as the basis for charging.</xs:documentation>
        </xs:annotation>

```

```

<xs:complexType>
  <xs:sequence>
    <xs:element name="value">
      <xs:simpleType>
        <xs:restriction base="xs:decimal">
          <xs:minInclusive value="1"/>
          <xs:totalDigits value="8"/>
          <xs:fractionDigits value="1"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="measure" minOccurs="0">
      <xs:simpleType>
        <xs:restriction base="xs:token">
          <xs:enumeration value="kg"/>
          <xs:enumeration value="m2"/>
          <xs:enumeration value="m3"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ExchangeRate" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Exchange rate for amounts to
be paid by the consignor or consignee which are not expressed in the
invoicing currency.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:decimal">
      <xs:totalDigits value="18"/>
      <xs:fractionDigits value="3"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Distance" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Tariff distance, expressed in
km or zones, between the stations or points corresponding to the beginning
and end of the charging section.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="KM">
        <xs:annotation>
          <xs:documentation>Tariff distance,
expressed in km, between the stations or points corresponding to the
beginning and end of the charging section.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="99999"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Zones">

```



```

        <xs:annotation>
          <xs:documentation>Tariff distance,
expressed in zones, between the stations or points corresponding to the
beginning and end of the charging section.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="99"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
<xs:element name="Fee" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Supplements, fees,
deductions</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:totalDigits value="4"/>
      <xs:minInclusive value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="FreightCharges" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges (paid and
due)</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="Prepaid" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be
paid by the consignor in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Transferred"
type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be
paid by the consignee in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
<xs:sequence>
  <xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="AdditionalCharges" minOccurs="0"
maxOccurs="10">
  <xs:annotation>
    <xs:documentation/>
    <xs:documentation>Sum of Prepaid</xs:documentation>

```

```

        <xs:documentation>Sum of
Transferred</xs:documentation>
    </xs:annotation>
    <xs:complexType>
    <xs:sequence>
        <xs:element name="Code">
        <xs:annotation>
        <xs:documentation>Additional charges
code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
        <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="2"/>
        </xs:restriction>
        </xs:simpleType>
        </xs:element>
        <xs:choice>
        <xs:element name="Prepaid" type="Money_Type">
        <xs:annotation>
        <xs:documentation>Prepaid</xs:documentation>
        </xs:annotation>
        </xs:element>
        <xs:element name="Transferred" type="Money_Type">
        <xs:annotation>

<xs:documentation>Transferred</xs:documentation>
        </xs:annotation>
        </xs:element>
        </xs:choice>
        </xs:sequence>
        </xs:complexType>
        </xs:element>
        </xs:sequence>
        </xs:complexType>
        </xs:element>
        <xs:element ref="Wagons" minOccurs="0" maxOccurs="99">
        <xs:annotation>
        <xs:documentation>Contains list of transported Goods, Wagons
and ITU etc.</xs:documentation>
        </xs:annotation>
        </xs:element>
        <xs:element name="WagonPreviousNumberFreight" minOccurs="0"
maxOccurs="20">
        <xs:annotation>
        <xs:documentation>Identifies the previous freight wagon if a
shipment or Intermodal unit has changed the wagon during its
journey</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
        <xs:restriction base="WagonIdent">
        <xs:length value="12"/>
        </xs:restriction>
        </xs:simpleType>
        </xs:element>
        <xs:element ref="AgreedTimeOfDelivery" minOccurs="0">
        <xs:annotation>
        <xs:documentation>The requested Date and Time for the

```

	<pre> delivery of a wagon/Shipment or Intermodal units at customer sidings</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **ConsignmentOrderMessage/COMS/COM_Header**

<p>diagram</p>	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	SendingRU ReceivingRU MessageReferenceNumber ShipmentType ConsignmentOrderType COM_PreparationDatetime DossierNumber VersionNumber PrintForm Intermodal ChangeLog
annotation	<p>documentation</p> <p>Additional Header containing consignment related key data such as dossier number, version number and a change</p>

	log for modifications
source	<pre> <xs:element name="COM_Header"> <xs:annotation> <xs:documentation>Additional Header containing consignment related key data such as dossiernumber, version number and a change log for modifications</xs:documentation> </xs:annotation> </xs:complexType> <xs:sequence> <xs:element name="SendingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which created/amended the message (like 2185).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ReceivingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which is the recipient of the message (like 2185).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="MessageReferenceNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Message Reference NumberThis identification is being generated during creation of the message. This allows the tracing of the message.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="18"> <xs:annotation> <xs:documentation>Use here a counter, any system.</xs:documentation> </xs:annotation> </xs:maxLength> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ShipmentType"> <xs:annotation> <xs:documentation>Classification of the wagon order as 'CUV','CIM' or "SMGS".</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="CIM"> <xs:annotation> <xs:documentation>Regular transport, according in basic to the CIM consignment note.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CUV"> <xs:annotation> <xs:documentation>Transport of empty wagons. If loaded and </pre>

empty wagons are withing the same shipment, then the ShipmentType has to be set to CIM. For the empty wagons the loading status has to be set in the WagonDetails.

```

</xs:documentation>
  </xs:annotation>
</xs:enumeration>
  <xs:enumeration value="SMGS"/>
</xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element ref="ConsignmentOrderType"/>
<xs:element name="COM_PreparationDatetime">
  <xs:annotation>
    <xs:documentation>Date and Time of preparation of the
COM</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:dateTime"/>
  </xs:simpleType>
</xs:element>
<xs:element name="DossierNumber" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Internal identification number of the Wo. This
information is important to be able to identify the COM even after
modifications. Format: RRRRYYYMMDDNNNNNNNN Where RRRR = railway code, YYYY =
year, MM = month, DD = day and NNNNNNNN = running number.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:length value="19"/>
      <xs:pattern value="\d{4}20\d{2}[0-1][0-9][0-3]\d{8}"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="VersionNumber">
  <xs:annotation>
    <xs:documentation>Message version number. This number hast to be
incremented after each modification. On creation this value has to be set to
0.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:minInclusive value="0"/>
      <xs:maxInclusive value="100"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="PrintForm" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Which form to use for printout. CIM-CN or CIM-CN
for combined traffic. This information assures, that the same paper document
will be used for the 'duplicate of the consignment note' and the final print
out of the ECN for the consignee.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value="WLT">
        <xs:annotation>
          <xs:documentation>Wagon load transport form to be used for


```

```


print-out.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
  <xs:enumeration value="CT">
    <xs:annotation>
      <xs:documentation>Combined traffic form to be used for
print-out.</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Intermodal" minOccurs="0">
  <xs:simpleType>
    <xs:restriction base="xs:byte">
      <xs:pattern value="0|1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ChangeLog" minOccurs="0" maxOccurs="100">
  <xs:annotation>
    <xs:documentation>Log of changes made by the LeadRU / contractual
carrier during the transport.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DateTime">
        <xs:annotation>
          <xs:documentation>DateTime, when the changes were
applied.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:dateTime"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="NumberOfModifiedVersion">
        <xs:annotation>
          <xs:documentation>Version number of the modified message (as
also written into COMHeader/COMVersionNumber).</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int"/>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```


element **ConsignmentOrderMessage/COMS/COM_Header/SendingRU**

diagram	 <p>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which created/amended the message (like 2185).</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	<p>documentation</p> <p>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which created/amended the message (like 2185).</p>												
source	<pre><xs:element name="SendingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which created/amended the message (like 2185).</xs:documentation> </xs:annotation> </xs:element></pre>												


element **ConsignmentOrderMessage/COMS/COM_Header/ReceivingRU**

diagram	 <p>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which is the recipient of the message (like 2185).</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	<p>documentation</p> <p>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which is the recipient of the message (like 2185).</p>												
source	<pre><xs:element name="ReceivingRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Use here the 4 digit code according to UIC leaflet 920-1 of the railway, which is the recipient of the message (like 2185).</xs:documentation> </xs:annotation> </xs:element></pre>												

element **ConsignmentOrderMessage/COMS/COM_Header/MessageReferenceNumber**


diagram	 Message Reference Number This identification is being generated during creation of the message. This allows the tracing of the message.
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 18 documentation Use here a counter, any system.
annotation	documentation Message Reference Number This identification is being generated during creation of the message. This allows the tracing of the message.
source	<pre><xs:element name="MessageReferenceNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Message Reference NumberThis identification is being generated during creation of the message. This allows the tracing of the message.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="18"> <xs:annotation> <xs:documentation>Use here a counter, any system.</xs:documentation> </xs:annotation> </xs:maxLength> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM_Header/ShipmentType**


diagram	 ShipmentType Classification of the wagon order as "CUV", "CIM" or "SMGS".
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:token
properties	content simple
facets	Kind Value Annotation enumeration CIM documentation Regular transport, according in basic to the CIM consignment note. enumeration CUV documentation Transport of empty wagons. If loaded and empty wagons are withing the same shipment, then the ShipmentType has to be set to CIM. For the empty wagons the loading status has to be set in the WagonDetails. enumeration SMGS
annotation	documentation

	Classification of the wagon order as 'CUV','CIM' or "SMGS".
source	<pre> <xs:element name="ShipmentType"> <xs:annotation> <xs:documentation>Classification of the wagon order as 'CUV','CIM' or "SMGS".</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="CIM"> <xs:annotation> <xs:documentation>Regular transport, according in basic to the CIM consignment note.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CUV"> <xs:annotation> <xs:documentation>Transport of empty wagons. If loaded and empty wagons are withing the same shipment, then the ShipmentType has to be set to CIM. For the empty wagons the loading status has to be set in the WagonDetails.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="SMGS"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>


element **ConsignmentOrderMessage/COMS/COM_Header/COM_PreparationDatetime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:dateTime
properties	content simple
annotation	documentation Date and Time of preparation of the COM
source	<pre> <xs:element name="COM_PreparationDatetime"> <xs:annotation> <xs:documentation>Date and Time of preparation of the COM</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM_Header/DossierNumber**


diagram	 <p>Internal identification number of the Wo. This information is important to be able to identify the COM even after modifications. Format: RRRYYYYMMDDNNNNNNN N Where RRRR = railway code, YYYY = year, MM = month, DD = day and NN...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation length 19 pattern \d{4}20\d{2}[0-1][0-9][0-3]\d{8}
annotation	documentation Internal identification number of the Wo. This information is important to be able to identify the COM even after modifications. Format: RRRYYYYMMDDNNNNNNN Where RRRR = railway code, YYYY = year, MM = month, DD = day and NNNNNNN = running number.
source	<pre><xs:element name="DossierNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Internal identification number of the Wo. This information is important to be able to identify the COM even after modifications. Format: RRRYYYYMMDDNNNNNNN Where RRRR = railway code, YYYY = year, MM = month, DD = day and NNNNNNN = running number.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="19"/> <xs:pattern value="\d{4}20\d{2}[0-1][0-9][0-3]\d{8}"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM_Header/VersionNumber**

diagram	 <p>Message version number. This number has to be incremented after each modification. On creation this value has to be set to 0.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int
properties	content simple
facets	Kind Value Annotation minInclusive 0 maxInclusive 100
annotation	documentation Message version number. This number has to be incremented after each modification. On creation this value has to be set to 0.
source	<pre><xs:element name="VersionNumber"> <xs:annotation></pre>

	<pre> <xs:documentation>Message version number. This number has to be incremented after each modification. On creation this value has to be set to 0.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:maxInclusive value="100"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM_Header/PrintForm**

diagram	 <p>Which form to use for printout, CIM-CN or CIM-CN for combined traffic. This information assures, that the same paper document will be used for the 'duplicate of the consignment note' and the ...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:token									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>WLT</td> <td>documentation Wagon load transport form to be used for print-out.</td> </tr> <tr> <td>enumeration</td> <td>CT</td> <td>documentation Combined traffic form to be used for print-out.</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	WLT	documentation Wagon load transport form to be used for print-out.	enumeration	CT	documentation Combined traffic form to be used for print-out.
Kind	Value	Annotation								
enumeration	WLT	documentation Wagon load transport form to be used for print-out.								
enumeration	CT	documentation Combined traffic form to be used for print-out.								
annotation	documentation Which form to use for printout. CIM-CN or CIM-CN for combined traffic. This information assures, that the same paper document will be used for the 'duplicate of the consignment note' and the final print out of the ECN for the consignee.									
source	<pre> <xs:element name="PrintForm" minOccurs="0"> <xs:annotation> <xs:documentation>Which form to use for printout. CIM-CN or CIM-CN for combined traffic. This information assures, that the same paper document will be used for the 'duplicate of the consignment note' and the final print out of the ECN for the consignee.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="WLT"> <xs:annotation> <xs:documentation>Wagon load transport form to be used for print- out.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CT"> <xs:annotation> <xs:documentation>Combined traffic form to be used for print- out.</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

	<pre></xs:simpleType> </xs:element></pre>
--	---

element **ConsignmentOrderMessage/COMS/COM_Header/Intermodal**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:byte
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation pattern 0 1
source	<pre><xs:element name="Intermodal" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:byte"> <xs:pattern value="0 1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM_Header/ChangeLog**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 100 content complex
children	DateTime NumberOfModifiedVersion
annotation	documentation Log of changes made by the LeadRU / contractual carrier during the transport.
source	<pre><xs:element name="ChangeLog" minOccurs="0" maxOccurs="100"> <xs:annotation> <xs:documentation>Log of changes made by the LeadRU / contractual carrier during the transport.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DateTime"> <xs:annotation> <xs:documentation>DateTime, when the changes were applied.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element></pre>

	<pre> <xs:element name="NumberOfModifiedVersion"> <xs:annotation> <xs:documentation>Version number of the modified message (as also written into COMHeader/COMVersionNumber).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"/> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM_Header/ChangeLog/DateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:dateTime
properties	content simple
annotation	documentation DateTime, when the changes were applied.
source	<pre> <xs:element name="DateTime"> <xs:annotation> <xs:documentation>DateTime, when the changes were applied.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM_Header/ChangeLog/NumberOfModifiedVersion**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int
properties	content simple
annotation	documentation Version number of the modified message (as also written into COMHeader/COMVersionNumber).
source	<pre> <xs:element name="NumberOfModifiedVersion"> <xs:annotation> <xs:documentation>Version number of the modified message (as also written into COMHeader/COMVersionNumber).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"/> </xs:simpleType> </xs:element> </pre>

`</xs:element>`

element **ConsignmentOrderMessage/COMS/COM**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>AcceptancePoint DeliveryPoint Customers ConsignorDeclarations GeneralInformation AttachedDocuments CommercialSpecifications PrepaymentInstructions Tariff SectionalInvoicing DeclarationOfValue InterestInDelivery CashOnDelivery RouteSection SpecialTreatments CustomsProcedures CustomsData RU Declarations Carriers LeadCarrier MadeOut ChargesNote TransitPeriodExtensions ChargingSections Wagons WagonPreviousNumberFreight AgreedTimeOfDelivery</p>
<p>annotation</p>	<p>documentation Consignment order message</p>
<p>source</p>	<pre><xs:element name="COM"> <xs:annotation> <xs:documentation>Consignment order message</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence></pre>

```

<xs:element name="AcceptancePoint">
  <xs:annotation>
    <xs:documentation>Description of location and time for the take
over of the consignment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="Station"/>
      <xs:element ref="RP_Code" minOccurs="0"/>
      <xs:element ref="ProductionStation" minOccurs="0"/>
      <xs:element name="AcceptanceDate" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Date and time (month, day and hour) at
which the goods were accepted. </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:dateTime"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ConsignmentNumber">
        <xs:annotation>
          <xs:documentation>Running number and check digit of the
consignment between Lead RU and customer. Format: NNNNNC The number consists
of NNNNN = running number C = check digit, </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="6"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ForwardingTrainNumber" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Train number at shipping
</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CarrierCode" type="CompanyCode">
        <xs:annotation>
          <xs:documentation>Code of the shipping carrier mentioned in
the consignment number.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeliveryPoint">
  <xs:annotation>
    <xs:documentation>Description of location and time for the hand
over of the consignment</xs:documentation>
  </xs:annotation>

```

```

<xs:complexType>
  <xs:sequence>
    <xs:element ref="Station"/>
    <xs:element ref="RP_Code" minOccurs="0"/>
    <xs:element ref="ProductionStation" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="Customers" minOccurs="2" maxOccurs="4">
  <xs:annotation>
    <xs:documentation>Information about the consignor, consignee and
freight payers. At least information about consignor and consignee has to be
given</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="ConsignorDeclarations" minOccurs="0" maxOccurs="10">
  <xs:annotation>
    <xs:documentation>Consignors declarartions, this element contains
either declarations of the original consignor or declarations of the LeadRU
as consignor</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="ConsignorDeclarationCode"/>
      <xs:element ref="DeclarationText" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GeneralInformation" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Genearal information about the complete
consignment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ConsignorReference" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Consignor's reference concerning the
complete consignment</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="InformationConsignee" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Information from the consignor to the
consignee relating to the consignment. This information is not to commit the
carrier.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="350"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```



```

</xs:simpleType>
</xs:element>
<xs:element name="WagonGroupInfo" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Consignor information regarding the whole
consignment. Comparable with the element WagonInfo, but for all
wagons.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:maxLength value="500"/>
      <xs:minLength value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="AttachedDocuments" minOccurs="0" maxOccurs="10">
  <xs:annotation>
    <xs:documentation>Paper documents accompanying the
transport</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DocumentType">
        <xs:annotation>
          <xs:documentation>Type code of attached document. The
UN/DIFACT 1001 list of codes is to be used to code accompanying
documents.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="999"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="DocumentInformation" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Additional information regarding the
attached document may be entered here.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="Quantity" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Amount of the documents of the specified
type.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="DocumentTypeDescription" minOccurs="0">
        <xs:annotation>

```

```

        <xs:documentation>Description of document type, when it is
not in the UN/EDIFACT 1001 list included.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="Filename" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Filename of embedded pdf in legacy
system</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:maxLength value="35"/>
            <xs:minLength value="1"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element ref="StatusOfDocument" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CommercialSpecifications" minOccurs="0"
maxOccurs="5">
    <xs:annotation>
        <xs:documentation>Commercial Specification</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="CommercialSpecificationCode"/>
            <xs:element name="SpecificationText" minOccurs="0">
                <xs:annotation>
                    <xs:documentation>Additional Text for codes with free
text</xs:documentation>
                </xs:annotation>
                <xs:simpleType>
                    <xs:restriction base="xs:string">
                        <xs:minLength value="1"/>
                        <xs:maxLength value="350"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
            <xs:element name="CarrierCode" type="CompanyCode" minOccurs="0"
maxOccurs="10">
                <xs:annotation>
                    <xs:documentation>additional carrier code belonging to the
given contract number</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:element name="ContractNumber" minOccurs="0" maxOccurs="10">
                <xs:annotation>
                    <xs:documentation>additional contract number according to
the given carrier code.</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1">
              <xs:annotation>
                <xs:documentation>has to be sent as n6 (with leading
zeros if necessary)</xs:documentation>
              </xs:annotation>
            </xs:minLength>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="PrepaymentInstructions">
  <xs:annotation>
    <xs:documentation>Prepayment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="PrepaymentCustomer" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Prepaidcode (given by the
client)</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:choice>
            <xs:element ref="PrepaidCodeCustomer"/>
            <xs:element ref="IncotermCode"/>
          </xs:choice>
        </xs:complexType>
      </xs:element>
      <xs:element ref="PrepaidcodeCarrier"/>
      <xs:element name="PaidUpTo" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Charges Paid Up To ... This information is
being sent by the consignor in agreement with the contractual carrier so
only one structure is needed for field 20 and 49. The carrier is only
allowed to apply changes, when ordered by the consignor.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:complexContent>
            <xs:extension base="LocationIdent"/>
          </xs:complexContent>
        </xs:complexType>
      </xs:element>
      <xs:element name="AdditionalCharges" minOccurs="0"
maxOccurs="5">
        <xs:annotation>
          <xs:documentation>Additional Charges</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="Code">
              <xs:annotation>
                <xs:documentation>Additional charges code according
CIT GLV-CIM appendix 3</xs:documentation>

```

```

</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:length value="2"/>
    <xs:pattern value="\d*[1-9]\d*" />
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Description" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Additional charges
description</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Tariff">
  <xs:annotation>
    <xs:documentation>Number of customer agreement or
tariff</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="ContractNumber">
        <xs:annotation>
          <xs:documentation>Number of customer
agreement.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1">
              <xs:annotation>
                <xs:documentation>has to be sent as n6 (with leading
zeros if necessary)</xs:documentation>
              </xs:annotation>
            </xs:minLength>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="TariffNumber">
        <xs:annotation>
          <xs:documentation>Number of the tariff.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1">
              <xs:annotation>

```

```

        <xs:documentation>has to be sent as n6 (with leading
zeros if necessary, but without check digit)</xs:documentation>
    </xs:annotation>
</xs:minLength>
<xs:maxLength value="6"/>
<xs:pattern value="\d*[1-9]\d*"/>
</xs:restriction>
</xs:simpleType>
</xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
<xs:element name="SectionalInvoicing" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Sectional Invoicing</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Section" maxOccurs="30">
                <xs:annotation>
                    <xs:documentation>Sectional Invoicing</xs:documentation>
                </xs:annotation>
                <xs:complexType>
                    <xs:sequence>
                        <xs:element name="InvoicingCarrierCode"
type="CompanyCode">
                            <xs:annotation>
                                <xs:documentation>Sectional invoicing
by</xs:documentation>
                            </xs:annotation>
                        </xs:element>
                        <xs:element name="InvoicedSection">
                            <xs:annotation>
                                <xs:documentation>Information about the section to be
invoiced.</xs:documentation>
                            </xs:annotation>
                            <xs:complexType>
                                <xs:choice>
                                    <xs:element name="CountryCode"
type="CountryIdentISO">
                                        <xs:annotation>
                                            <xs:documentation>Invoiced section specified by
country</xs:documentation>
                                        </xs:annotation>
                                    </xs:element>
                                    <xs:element name="SectionCarrierCode"
type="CompanyCode">
                                        <xs:annotation>
                                            <xs:documentation>Invoiced section specified by
carrier</xs:documentation>
                                        </xs:annotation>
                                    </xs:element>
                                </xs:choice>
                            </xs:complexType>
                        </xs:element>
                    </xs:sequence>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeclarationOfValue" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the value of the goods and the
currency code when the value exceeds the limit given in CIM Article 30
section 2.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode" type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-4217
alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="InterestInDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the amount and currency code of a
special interest in delivery.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CurrencyCode" type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Currency abbreviation (ISO-4217
alphanumeric)</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CashOnDelivery" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Details of the amount to be collected on
delivery and the currency code.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Amount" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Amount</xs:documentation>
        </xs:annotation>
      </xs:element>

```

```

        <xs:element name="CurrencyCode" type="CurrencyCode_Type">
            <xs:annotation>
                <xs:documentation>Currency abbreviation (ISO-4217
alphanumeric)</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="RouteSection" minOccurs="0" maxOccurs="30">
    <xs:annotation>
        <xs:documentation>Route sequence Sequential information about the
complete routing of the consignment, the LeadRu decides wether to provide
this information or not</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="SequenceID" type="xs:int">
                <xs:annotation>
                    <xs:documentation>Position of the route section in transport
chain. Used to determine the exact way of the transport for customs
purposes.</xs:documentation>
                </xs:annotation>
            </xs:element>
            <xs:sequence>
                <xs:element name="RouteCode">
                    <xs:annotation>
                        <xs:documentation>Route code (International
RouteCode)</xs:documentation>
                    </xs:annotation>
                    <xs:simpleType>
                        <xs:restriction base="xs:string">
                            <xs:length value="5"/>
                            <xs:pattern value="\d*[1-9]\d*0"/>
                        </xs:restriction>
                    </xs:simpleType>
                </xs:element>
                <xs:element name="RouteText" minOccurs="0">
                    <xs:annotation>
                        <xs:documentation>Description of the specific route
section</xs:documentation>
                    </xs:annotation>
                    <xs:simpleType>
                        <xs:restriction base="xs:string">
                            <xs:minLength value="1"/>
                            <xs:maxLength value="80"/>
                        </xs:restriction>
                    </xs:simpleType>
                </xs:element>
            </xs:sequence>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element ref="SpecialTreatments" minOccurs="0" maxOccurs="30"/>
<xs:element name="CustomsProcedures" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Customs procedures</xs:documentation>
    </xs:annotation>

```

```

<xs:complexType>
  <xs:sequence>
    <xs:element ref="RU_Partner" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Code of the RU entrusted of customs
procedures. </xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element ref="Location"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="CustomsData" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Customs Data</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="SimplifiedTransportProcedure" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Simplified transport procedure is used
(STP).</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:boolean"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="PrincipalRU" type="CompanyCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Code for the principal
RU</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CustomsSurveillance">
        <xs:annotation>
          <xs:documentation>Good under customs
surveillance</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:boolean"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CustomsEndorsements" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Reserved for endorsements by customs or a
consignor/consignee authorised by customs. Data element in accordance with
Regulation (EC) 1875/2006.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="350"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```



```

<xs:element name="RU_Declarations" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Carriers declaration</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="RU_Declaration" minOccurs="0" maxOccurs="30">
        <xs:annotation>
          <xs:documentation>Details of the carriers
declaration.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="DeclaringRU" type="CompanyCode">
              <xs:annotation>
                <xs:documentation>Code of carrier, who added the
declaration.</xs:documentation>
              </xs:annotation>
              </xs:element>
            <xs:element ref="RU_DeclarationCode"/>
            <xs:element ref="DeclarationText" minOccurs="0"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="DifferentAcceptance" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Details of the changes of the acceptance
point given by the consignor.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="DifferentAcceptancePoint"
type="LocationIdent" minOccurs="0">
              <xs:annotation>
                <xs:documentation>Variance of acceptance point given
in structure AcceptancePoint.</xs:documentation>
              </xs:annotation>
              </xs:element>
            <xs:element name="DifferentAcceptanceDate" minOccurs="0">
              <xs:annotation>
                <xs:documentation>Variance of acceptance date given
structure AcceptancePoint.</xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:dateTime"/>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="Carriers" maxOccurs="30">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CarrierStatus"/>
      <xs:element name="CarrierCode" type="CompanyCode">

```

```

        <xs:annotation>
          <xs:documentation>Railway Undertaking (Railway
Code)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="ResponsibleCarrierCode" type="CompanyCode"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Railway Undertaking (Railway Code) of the
carrier in charge.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CarrierName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of Carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="StreetNumber" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Streetnumber of
carrier.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="5"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Street" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of street of the
carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ZIPCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Postal Code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="9"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>

```

```

<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CountryCode" type="CountryIdentISO"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SectionFrom" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>Start of section to be performed by the
carrier. This can be a station OR a border crossing
point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SectionTo" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>End of section to be performed by the
carrier. This can be a station OR a border crossing
point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SubContractNumber_SplitContract"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Number of customer agreement between the
responsible and the operating carrier</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1">
        <xs:annotation>
          <xs:documentation>has to be sent as n6 (with leading
zeros if necessary)</xs:documentation>
        </xs:annotation>
      </xs:minLength>
      <xs:maxLength value="6"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
<xs:attribute name="sequenceID" type="xs:int">
  <xs:annotation>
    <xs:documentation>Position of carrier during transport.
</xs:documentation>
  </xs:annotation>
</xs:attribute>
</xs:complexType>
</xs:element>

```

```

<xs:element name="LeadCarrier">
  <xs:annotation>
    <xs:documentation>LeadCarrier/ Contractual
carrier</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CarrierCode" type="CompanyCode">
        <xs:annotation>
          <xs:documentation>Contractual carrier, railway undertaking
(Railway Code).</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CarrierName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of contractual
carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="StreetNumber" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Streetnumber of
carrier.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="5"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Street" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of street of the
carrier</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ZIPCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Postal Code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="9"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

</xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CountryCode" type="CountryIdentISO"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="Signature" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Signature of the contractual carrier. When
missing, the shipment number (CIM: 62) shall be used for signature
purposes.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="MadeOut" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Made out</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Place">
        <xs:annotation>
          <xs:documentation>Place on which the consignment note was
made out</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="35"/>
            <xs:minLength value="1"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Date" type="xs:date">
        <xs:annotation>
          <xs:documentation>Date at which the consignment note was
made out.</xs:documentation>
        </xs:annotation>

```

```

    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ChargesNote" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Charges note</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ChargesNoteAvailable" type="xs:boolean"/>
      <xs:element name="DateOfReturn" type="xs:date" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Date, when the destination carrier sent
the charges note back to the contractual carrier.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TransitPeriodExtensions" minOccurs="0"
maxOccurs="30">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="CodeOfCause"/>
      <xs:element name="Description" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Description for CodeOfCause no.
9.</xs:documentation>
        </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="180"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:sequence>
  </xs:complexType>
  <xs:annotation>
    <xs:documentation>Place of the extension.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="180"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Beginning">
  <xs:annotation>
    <xs:documentation>Beginning of the
extension.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:dateTime"/>
  </xs:simpleType>
</xs:element>
<xs:element name="Ending">

```

```

        <xs:annotation>
          <xs:documentation>End of extension.</xs:documentation>
        </xs:annotation>
      </xs:simpleType>
      <xs:restriction base="xs:dateTime"/>
    </xs:simpleType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ChargingSections" maxOccurs="15">
  <xs:annotation>
    <xs:documentation>Charging section</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Start" type="LocationIdent">
        <xs:annotation>
          <xs:documentation>Start of the charging
section</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="End" type="LocationIdent">
        <xs:annotation>
          <xs:documentation>End of the charging
section</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CommercialRouteCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Route code (RIP) when the customer
agreement or the tariff applied provide for it. </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="3"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CurrencyCode" type="CurrencyCode_Type">
        <xs:annotation>
          <xs:documentation>Code for the currency of the amounts
entered in the charging section.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Tariff" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Freight Charges Section
Tariff</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="NHMCode" type="NHMCodeType">
              <xs:annotation>
                <xs:documentation>NHM code determining the charges
applicable.</xs:documentation>
              </xs:annotation>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

</xs:element>
<xs:element name="TariffNumber">
  <xs:annotation>
    <xs:documentation>Customer agreement or tariff
applied</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="6"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ChargedMass" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Charged mass [weight in kg]. As
appropriate, area in m2 or the volume of the wagon or goods in m3 if used as
the basis for charging.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="value">
        <xs:simpleType>
          <xs:restriction base="xs:decimal">
            <xs:minInclusive value="1"/>
            <xs:totalDigits value="8"/>
            <xs:fractionDigits value="1"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="measure" minOccurs="0">
        <xs:simpleType>
          <xs:restriction base="xs:token">
            <xs:enumeration value="kg"/>
            <xs:enumeration value="m2"/>
            <xs:enumeration value="m3"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ExchangeRate" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Exchange rate for amounts to be paid
by the consignor or consignee which are not expressed in the invoicing
currency.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:decimal">
      <xs:totalDigits value="18"/>
      <xs:fractionDigits value="3"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Distance" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Tariff distance, expressed in km or

```



```

zones, between the stations or points corresponding to the beginning and end
of the charging section.</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:choice>
    <xs:element name="KM">
      <xs:annotation>
        <xs:documentation>Tariff distance, expressed in
km, between the stations or points corresponding to the beginning and end of
the charging section.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:int">
          <xs:minInclusive value="1"/>
          <xs:maxInclusive value="99999"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="Zones">
      <xs:annotation>
        <xs:documentation>Tariff distance, expressed in
zones, between the stations or points corresponding to the beginning and end
of the charging section.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:int">
          <xs:minInclusive value="1"/>
          <xs:maxInclusive value="99"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:choice>
</xs:complexType>
</xs:element>
<xs:element name="Fee" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Supplements, fees,
deductions</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:totalDigits value="4"/>
      <xs:minInclusive value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="FreightCharges" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges (paid and
due)</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="Prepaid" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be paid by
the consignor in the tariff currency.</xs:documentation>
        </xs:annotation>

```

```

        </xs:element>
        <xs:element name="Transferred" type="Money_Type">
          <xs:annotation>
            <xs:documentation>Carriage charges to be paid by
the consignee in the tariff currency.</xs:documentation>
          </xs:annotation>
        </xs:element>
      </xs:choice>
    </xs:complexType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="AdditionalCharges" minOccurs="0"
maxOccurs="10">
  <xs:annotation>
    <xs:documentation/>
    <xs:documentation>Sum of Prepaid</xs:documentation>
    <xs:documentation>Sum of Transferred</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Code">
        <xs:annotation>
          <xs:documentation>Additional charges
code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="2"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:choice>
        <xs:element name="Prepaid" type="Money_Type">
          <xs:annotation>
            <xs:documentation>Prepaid</xs:documentation>
          </xs:annotation>
        </xs:element>
        <xs:element name="Transferred" type="Money_Type">
          <xs:annotation>
            <xs:documentation>Transferred</xs:documentation>
          </xs:annotation>
        </xs:element>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="Wagons" minOccurs="0" maxOccurs="99">
  <xs:annotation>
    <xs:documentation>Contains list of transported Goods, Wagons and
ITU etc.</xs:documentation>
  </xs:annotation>
</xs:element>

```

	<pre> <xs:element name="WagonPreviousNumberFreight" minOccurs="0" maxOccurs="20"> <xs:annotation> <xs:documentation>Identifies the previous freight wagon if a shipment or Intermodal unit has changed the wagon during its journey</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="WagonIdent"> <xs:length value="12"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="AgreedTimeOfDelivery" minOccurs="0"> <xs:annotation> <xs:documentation>The requested Date and Time for the delivery of a wagon/Shipment or Intermodal units at customer sidings</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/AcceptancePoint**

diagram	<pre> classDiagram class AcceptancePoint { Description of location and time for the take over of the consignment } class Station { Details of station serving the point } class RP_Code { Routing point code of the production station of the acceptance or delivery poi... } class ProductionStation { Details of production station serving the point, this element is used if the productional station differs from the commercial station } class AcceptanceDate { Date and time (month, day and hour) at which the goods were accepted. } class ConsignmentNumber { Running number and check digit of the consignment between Lead RU and customer. Format: NNNNNC The number consists of NNNNN = running number C = chec... } class ForwardingTrainNumber { Train number at shippi... } class CarrierCode { Code of the shipping carrier mentioned in the consignment number. } AcceptancePoint -- Station AcceptancePoint -- RP_Code AcceptancePoint -- ProductionStation AcceptancePoint -- AcceptanceDate AcceptancePoint -- ConsignmentNumber AcceptancePoint -- ForwardingTrainNumber AcceptancePoint -- CarrierCode </pre>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Station RP_Code ProductionStation AcceptanceDate ConsignmentNumber ForwardingTrainNumber CarrierCode
annotation	documentation Description of location and time for the take over of the consignment


source

```


<xs:element name="AcceptancePoint">
  <xs:annotation>
    <xs:documentation>Description of location and time for the take over of
the consignment</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="Station"/>
      <xs:element ref="RP_Code" minOccurs="0"/>
      <xs:element ref="ProductionStation" minOccurs="0"/>
      <xs:element name="AcceptanceDate" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Date and time (month, day and hour) at which the
goods were accepted. </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:dateTime"/>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ConsignmentNumber">
        <xs:annotation>
          <xs:documentation>Running number and check digit of the
consignment between Lead RU and customer. Format: NNNNNC The number consists
of NNNNN = running number C = check digit, </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="6"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ForwardingTrainNumber" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Train number at shipping </xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CarrierCode" type="CompanyCode">
        <xs:annotation>
          <xs:documentation>Code of the shipping carrier mentioned in the
consignment number.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```


element **ConsignmentOrderMessage/COMS/COM/AcceptancePoint/AcceptanceDate**

diagram	 Date and time (month, day and hour) at which the goods were accepted.
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:dateTime
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Date and time (month, day and hour) at which the goods were accepted.
source	<pre><xs:element name="AcceptanceDate" minOccurs="0"> <xs:annotation> <xs:documentation>Date and time (month, day and hour) at which the goods were accepted. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element></pre>


element **ConsignmentOrderMessage/COMS/COM/AcceptancePoint/ConsignmentNumber**

diagram	 Running number and check digit of the consignment between Lead RU and customer. Format: NNNNNC The number consists of NNNNN = running number C = chec...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple
used by	element WIMO Dataset/ConsignmentLevelData
facets	Kind Value Annotation length 6 pattern \d*[1-9]\d*
annotation	documentation Running number and check digit of the consignment between Lead RU and customer. Format: NNNNNC The number consists of NNNNN = running number C = check digit,
source	<pre><xs:element name="ConsignmentNumber"> <xs:annotation> <xs:documentation>Running number and check digit of the consignment between Lead RU and customer. Format: NNNNNC The number consists of NNNNN = running number C = check digit, </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="6"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/AcceptancePoint/ForwardingTrainNumber**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 6
annotation	documentation Train number at shipping
source	<pre><xs:element name="ForwardingTrainNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Train number at shipping </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/AcceptancePoint/CarrierCode**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CompanyCode
properties	content simple
facets	Kind Value Annotation minLength 4 maxLength 4 pattern [0-9A-Z]{4}
annotation	documentation Code of the shipping carrier mentioned in the consignment number.
source	<pre><xs:element name="CarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Code of the shipping carrier mentioned in the consignment number.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/DeliveryPoint**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Station RP_Code ProductionStation
annotation	documentation Description of location and time for the hand over of the consignment
source	<pre> <xs:element name="DeliveryPoint"> <xs:annotation> <xs:documentation>Description of location and time for the hand over of the consignment</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Station"/> <xs:element ref="RP_Code" minOccurs="0"/> <xs:element ref="ProductionStation" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/ConsignorDeclarations**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 10 content complex
children	ConsignorDeclarationCode DeclarationText
annotation	documentation Consignors declarartions, this element contains either declarations of the original consignor or declarations of the LeadRU as consignor
source	<pre> <xs:element name="ConsignorDeclarations" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>Consignors declarartions, this element contains either declarations of the original consignor or declarations of the LeadRU as consignor</xs:documentation> </xs:annotation> <xs:complexType> </pre>


	<pre> <xs:sequence> <xs:element ref="ConsignorDeclarationCode"/> <xs:element ref="DeclarationText" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/GeneralInformation**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	ConsignorReference InformationConsignee WagonGroupInfo
annotation	documentation General information about the complete consignment
source	<pre> <xs:element name="GeneralInformation" minOccurs="0"> <xs:annotation> <xs:documentation>General information about the complete consignment</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="ConsignorReference" minOccurs="0"> <xs:annotation> <xs:documentation>Consignor's reference concerning the complete consignment</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="InformationConsignee" minOccurs="0"> <xs:annotation> <xs:documentation>Information from the consignor to the consignee relating to the consignment. This information is not to commit the carrier.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

	<pre> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre> <p><xs:element name="WagonGroupInfo" minOccurs="0"> <xs:annotation> <xs:documentation>Consignor information regarding the whole consignment. Comparable with the element WagonInfo, but for all wagons.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="500"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></p>
--	---


element **ConsignmentOrderMessage/COMS/COM/GeneralInformation/ConsignorReference**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Consignor's reference concerning the complete consignment									
source	<pre> <xs:element name="ConsignorReference" minOccurs="0"> <xs:annotation> <xs:documentation>Consignor's reference concerning the complete consignment</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/GeneralInformation/InformationConsignee**

diagram	 Information from the consignor to the consignee relating to the consignment. This information is not to commit the carrier.
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 350
annotation	documentation Information from the consignor to the consignee relating to the consignment. This information is not to commit the carrier.
source	<pre><xs:element name="InformationConsignee" minOccurs="0"> <xs:annotation> <xs:documentation>Information from the consignor to the consignee relating to the consignment. This information is not to commit the carrier.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/GeneralInformation/WagonGroupInfo**

diagram	 Consignor information regarding the whole consignment. Comparable with the element WagonInfo, but for all wagons.
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 500
annotation	documentation Consignor information regarding the whole consignment. Comparable with the element WagonInfo, but for all wagons.
source	<pre><xs:element name="WagonGroupInfo" minOccurs="0"> <xs:annotation> <xs:documentation>Consignor information regarding the whole consignment. Comparable with the element WagonInfo, but for all wagons.</xs:documentation> </xs:annotation></pre>

```

<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:maxLength value="500"/>
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **ConsignmentOrderMessage/COMS/COM/AttachedDocuments**


<p>diagram</p>	<p>AttachedDocuments 0..10 Paper documents accompanying the transport...</p> <ul style="list-style-type: none"> DocumentType: Type code of attached document. The UN/DIFACT 1001 list of codes is to be used to code accompanying documents. DocumentInformation: Additional information regarding the attached document may be entered here. Quantity: Amount of the documents of the specified type. DocumentTypeDescription: Description of document type, when it is not in the UN/EDIFACT 1001 list included. Filename: Filename of embedded pdf in legacy system StatusOfDocument: Enumerated value for the status of the attached document 1 = not electronical attached 2 embedded in ECTD, EC...
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 10 content complex</p>
<p>children</p>	<p>DocumentType DocumentInformation Quantity DocumentTypeDescription Filename StatusOfDocument</p>
<p>annotation</p>	<p>documentation Paper documents accompanying the transport</p>
<p>source</p>	<pre> <xs:element name="AttachedDocuments" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>Paper documents accompanying the transport</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DocumentType"> <xs:annotation> <xs:documentation>Type code of attached document. The UN/DIFACT 1001 list of codes is to be used to code accompanying documents.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> </pre>

```


        <xs:minInclusive value="1"/>
        <xs:maxInclusive value="999"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="DocumentInformation" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Additional information regarding the attached
document may be entered here.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element ref="Quantity" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Amount of the documents of the specified
type.</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="DocumentTypeDescription" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Description of document type, when it is not in
the UN/EDIFACT 1001 list included.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="Filename" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Filename of embedded pdf in legacy
system</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:maxLength value="35"/>
            <xs:minLength value="1"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
    <xs:element ref="StatusOfDocument" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **ConsignmentOrderMessage/COMS/COM/AttachedDocuments/DocumentType**

diagram	 <p>Type code of attached document. The UN/DIFACT 1001 list of codes is to be used to code accompanying documents.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	<p>documentation</p> <p>Type code of attached document. The UN/DIFACT 1001 list of codes is to be used to code accompanying documents.</p>									
source	<pre><xs:element name="DocumentType"> <xs:annotation> <xs:documentation>Type code of attached document. The UN/DIFACT 1001 list of codes is to be used to code accompanying documents.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/AttachedDocuments/DocumentInformation**


diagram	 <p>Additional information regarding the attached document may be entered here.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	<p>documentation</p> <p>Additional information regarding the attached document may be entered here.</p>									
source	<pre><xs:element name="DocumentInformation" minOccurs="0"> <xs:annotation> <xs:documentation>Additional information regarding the attached document may be entered here.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

```


<xs:maxLength value="35"/>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element `ConsignmentOrderMessage/COMS/COM/AttachedDocuments/DocumentTypeDescription`

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Description of document type, when it is not in the UN/EDIFACT 1001 list included.									
source	<pre> <xs:element name="DocumentTypeDescription" minOccurs="0"> <xs:annotation> <xs:documentation>Description of document type, when it is not in the UN/EDIFACT 1001 list included.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element `ConsignmentOrderMessage/COMS/COM/AttachedDocuments/Filename`

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Filename of embedded pdf in legacy system									
source	<pre> <xs:element name="Filename" minOccurs="0"> <xs:annotation> <xs:documentation>Filename of embedded pdf in legacy system</xs:documentation> </pre>									

```

</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:maxLength value="35"/>
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **ConsignmentOrderMessage/COMS/COM/CommercialSpecifications**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 5 content complex</p>
<p>children</p>	<p>CommercialSpecificationCode SpecificationText CarrierCode ContractNumber</p>
<p>annotation</p>	<p>documentation Commercial Specification</p>
<p>source</p>	<pre> <xs:element name="CommercialSpecifications" minOccurs="0" maxOccurs="5"> <xs:annotation> <xs:documentation>Commercial Specification</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="CommercialSpecificationCode"/> <xs:element name="SpecificationText" minOccurs="0"> <xs:annotation> <xs:documentation>Additional Text for codes with free text</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="CarrierCode" type="CompanyCode" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>additional carrier code belonging to the given contract number</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ContractNumber" type="ContractNumber" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>additional contract number according to the given carrier code.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

	<pre> </xs:annotation> </xs:element> <xs:element name="ContractNumber" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>additional contract number according to the given carrier code.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---


element **ConsignmentOrderMessage/COMS/COM/CommercialSpecifications/SpecificationText**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>350</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	350	
Kind	Value	Annotation								
minLength	1									
maxLength	350									
annotation	documentation Additional Text for codes with free text									
source	<pre> <xs:element name="SpecificationText" minOccurs="0"> <xs:annotation> <xs:documentation>Additional Text for codes with free text</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/CommercialSpecifications/CarrierCode**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	minOcc 0 maxOcc 10 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation additional carrier code belonging to the given contract number												
source	<pre><xs:element name="CarrierCode" type="CompanyCode" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>additional carrier code belonging to the given contract number</xs:documentation> </xs:annotation> </xs:element></pre>												

element **ConsignmentOrderMessage/COMS/COM/CommercialSpecifications/ContractNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 10 content simple									
used by	element WIMO Dataset/ConsignmentLevelData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td>documentation has to be sent as n6 (with leading zeros if necessary)</td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)	maxLength	6	
Kind	Value	Annotation								
minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)								
maxLength	6									
annotation	documentation additional contract number according to the given carrier code.									
source	<pre><xs:element name="ContractNumber" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>additional contract number according to the given carrier code.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if</pre>									

	<pre>necessary)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element></pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	PrepaymentCustomer PrepaidcodeCarrier PaidUpTo AdditionalCharges
annotation	documentation Prepayment
source	<pre><xs:element name="PrepaymentInstructions"> <xs:annotation> <xs:documentation>Prepayment</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="PrepaymentCustomer" minOccurs="0"> <xs:annotation> <xs:documentation>Prepaidcode (given by the client)</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element ref="PrepaidCodeCustomer"/> <xs:element ref="IncotermCode"/> </xs:choice> </xs:complexType> </xs:element> <xs:element ref="PrepaidcodeCarrier"/> <xs:element name="PaidUpTo" minOccurs="0"> <xs:annotation> <xs:documentation>Charges Paid Up To ... This information is being sent by the consignor in agreement with the contractual carrier so only one structure is needed for field 20 and 49. The carrier is only allowed to apply changes, when ordered by the consignor.</xs:documentation></pre>

```

</xs:annotation>
<xs:complexType>
  <xs:complexContent>
    <xs:extension base="LocationIdent"/>
  </xs:complexContent>
</xs:complexType>
</xs:element>
<xs:element name="AdditionalCharges" minOccurs="0" maxOccurs="5">
  <xs:annotation>
    <xs:documentation>Additional Charges</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Code">
        <xs:annotation>
          <xs:documentation>Additional charges code according CIT GLV-
CIM appendix 3</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="2"/>
            <xs:pattern value="\d*[1-9]\d*"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Description" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Additional charges
description</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

element **ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions/PrepaymentCustomer**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 1 content complex</p>

children	PrepaidCodeCustomer IncotermCode
annotation	documentation Prepaidcode (given by the client)
source	<pre><xs:element name="PrepaymentCustomer" minOccurs="0"> <xs:annotation> <xs:documentation>Prepaidcode (given by the client)</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element ref="PrepaidCodeCustomer"/> <xs:element ref="IncotermCode"/> </xs:choice> </xs:complexType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions/PaidUpTo**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of LocationIdent
properties	minOcc 0 maxOcc 1 content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Charges Paid Up To ... This information is being sent by the consignor in agreement with the contractual carrier so only one structure is needed for field 20 and 49. The carrier is only allowed to apply changes, when ordered by the consignor.
source	<pre><xs:element name="PaidUpTo" minOccurs="0"> <xs:annotation> <xs:documentation>Charges Paid Up To ... This information is being sent by the consignor in agreement with the contractual carrier so only one structure is needed for field 20 and 49. The carrier is only allowed to apply changes, when ordered by the consignor.</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"/> </xs:complexContent> </xs:complexType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions/AdditionalCharges**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 5 content complex
children	Code Description
annotation	documentation Additional Charges
source	<pre> <xs:element name="AdditionalCharges" minOccurs="0" maxOccurs="5"> <xs:annotation> <xs:documentation>Additional Charges</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Code"> <xs:annotation> <xs:documentation>Additional charges code according CIT GLV-CIM appendix 3</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="2"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Description" minOccurs="0"> <xs:annotation> <xs:documentation>Additional charges description</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions/AdditionalCharges/Code**

diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>2</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	2		pattern	\d*[1-9]\d*	
Kind	Value	Annotation								
length	2									
pattern	\d*[1-9]\d*									
annotation	documentation Additional charges code according CIT GLV-CIM appendix 3									
source	<pre><xs:element name="Code"> <xs:annotation> <xs:documentation>Additional charges code according CIT GLV-CIM appendix 3</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="2"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element


ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions/AdditionalCharges/Description

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Additional charges description									
source	<pre><xs:element name="Description" minOccurs="0"> <xs:annotation> <xs:documentation>Additional charges description</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									


element **ConsignmentOrderMessage/COMS/COM/Tariff**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	ContractNumber TariffNumber
annotation	documentation Number of customer agreement or tariff
source	<pre> <xs:element name="Tariff"> <xs:annotation> <xs:documentation>Number of customer agreement or tariff</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element name="ContractNumber"> <xs:annotation> <xs:documentation>Number of customer agreement.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="TariffNumber"> <xs:annotation> <xs:documentation>Number of the tariff.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary, but without check digit)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element> </xs:choice> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/Tariff/ContractNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	element WIMO Dataset/ConsignmentLevelData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td>documentation has to be sent as n6 (with leading zeros if necessary)</td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)	maxLength	6	
Kind	Value	Annotation								
minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)								
maxLength	6									
annotation	documentation Number of customer agreement.									
source	<pre><xs:element name="ContractNumber"> <xs:annotation> <xs:documentation>Number of customer agreement.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/Tariff/TariffNumber**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:string												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td>documentation has to be sent as n6 (with leading zeros if necessary, but without check digit)</td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1	documentation has to be sent as n6 (with leading zeros if necessary, but without check digit)	maxLength	6		pattern	\d*[1-9]\d*	
Kind	Value	Annotation											
minLength	1	documentation has to be sent as n6 (with leading zeros if necessary, but without check digit)											
maxLength	6												
pattern	\d*[1-9]\d*												
annotation	documentation Number of the tariff.												
source	<pre><xs:element name="TariffNumber"> <xs:annotation> <xs:documentation>Number of the tariff.</xs:documentation> </xs:annotation> <xs:simpleType></pre>												

	<pre> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary, but without check digit)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **ConsignmentOrderMessage/COMS/COM/SectionalInvoicing**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	Section
annotation	documentation Sectional Invoicing
source	<pre> <xs:element name="SectionalInvoicing" minOccurs="0"> <xs:annotation> <xs:documentation>Sectional Invoicing</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Section" maxOccurs="30"> <xs:annotation> <xs:documentation>Sectional Invoicing</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="InvoicingCarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Sectional invoicing by</xs:documentation> </xs:annotation> </xs:element> <xs:element name="InvoicedSection"> <xs:annotation> <xs:documentation>Information about the section to be invoiced.</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element name="CountryCode" type="CountryIdentISO"> <xs:annotation> <xs:documentation>Invoiced section specified by country</xs:documentation> </xs:annotation> </xs:element> </xs:choice> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

	<pre> <xs:element name="SectionCarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Invoiced section specified by carrier</xs:documentation> </xs:annotation> </xs:element> </xs:choice> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 1 maxOcc 30 content complex
children	InvoicingCarrierCode InvoicedSection
annotation	documentation Sectional Invoicing
source	<pre> <xs:element name="Section" maxOccurs="30"> <xs:annotation> <xs:documentation>Sectional Invoicing</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="InvoicingCarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Sectional invoicing by</xs:documentation> </xs:annotation> </xs:element> <xs:element name="InvoicedSection"> <xs:annotation> <xs:documentation>Information about the section to be invoiced.</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element name="CountryCode" type="CountryIdentISO"> <xs:annotation> <xs:documentation>Invoiced section specified by country</xs:documentation> </xs:annotation> </xs:element> <xs:element name="SectionCarrierCode" type="CompanyCode"> </pre>

	<pre> <xs:annotation> <xs:documentation>Invoiced section specified by carrier</xs:documentation> </xs:annotation> </xs:element> </xs:choice> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicingCarrierCode**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Sectional invoicing by												
source	<pre> <xs:element name="InvoicingCarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Sectional invoicing by</xs:documentation> </xs:annotation> </xs:element> </pre>												


element **ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicedSection**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	CountryCode SectionCarrierCode
annotation	documentation Information about the section to be invoiced.
source	<pre> <xs:element name="InvoicedSection"> <xs:annotation> <xs:documentation>Information about the section to be invoiced.</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> </pre>

	<pre> <xs:element name="CountryCode" type="CountryIdentISO"> <xs:annotation> <xs:documentation>Invoiced section specified by country</xs:documentation> </xs:annotation> </xs:element> <xs:element name="SectionCarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Invoiced section specified by carrier</xs:documentation> </xs:annotation> </xs:element> </xs:choice> </xs:complexType> </xs:element> </pre>
--	--


element

ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicedSection/CountryCode

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CountryIdentISO									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2	
Kind	Value	Annotation								
minLength	2									
maxLength	2									
annotation	documentation Invoiced section specified by country									
source	<pre> <xs:element name="CountryCode" type="CountryIdentISO"> <xs:annotation> <xs:documentation>Invoiced section specified by country</xs:documentation> </xs:annotation> </xs:element> </pre>									

element

ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicedSection/SectionCarrierCode

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CompanyCode									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4	
Kind	Value	Annotation								
minLength	4									
maxLength	4									

	pattern [0-9A-Z]{4}
annotation	documentation Invoiced section specified by carrier
source	<pre><xs:element name="SectionCarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Invoiced section specified by carrier</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/DeclarationOfValue**

diagram	<p>The diagram shows a dashed box labeled 'DeclarationOfValue' with a small icon. A line connects it to a solid box labeled 'Amount' with a small icon and the text 'Amo...'. Another line connects it to a solid box labeled 'CurrencyCode' with a small icon and the text 'Currency abbreviation (ISO-4217 alphanume...'. The 'Amount' box has a small icon and the text 'Amo...'. The 'CurrencyCode' box has a small icon and the text 'Currency abbreviation (ISO-4217 alphanume...'.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	Amount CurrencyCode
annotation	documentation Details of the value of the goods and the currency code when the value exceeds the limit given in CIM Article 30 section 2.
source	<pre><xs:element name="DeclarationOfValue" minOccurs="0"> <xs:annotation> <xs:documentation>Details of the value of the goods and the currency code when the value exceeds the limit given in CIM Article 30 section 2.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Amount" type="Money_Type"> <xs:annotation> <xs:documentation>Amount</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Currency abbreviation (ISO-4217 alphanumeric)</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/DeclarationOfValue/Amount**

diagram	<p>The diagram shows a solid box labeled 'Amount' with a small icon and the text 'Amo...'.</p>
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Money Type									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									
annotation	documentation Amount									
source	<pre><xs:element name="Amount" type="Money_Type"> <xs:annotation> <xs:documentation>Amount</xs:documentation> </xs:annotation> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/DeclarationOfValue/CurrencyCode**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	CurrencyCode Type						
properties	content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[A-Z][A-Z][A-Z]</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	pattern	[A-Z][A-Z][A-Z]	
Kind	Value	Annotation					
pattern	[A-Z][A-Z][A-Z]						
annotation	documentation Currency abbreviation (ISO-4217 alphanumeric)						
source	<pre><xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Currency abbreviation (ISO-4217 alphanumeric)</xs:documentation> </xs:annotation> </xs:element></pre>						

element **ConsignmentOrderMessage/COMS/COM/InterestInDelivery**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	complex
minOcc	0						
maxOcc	1						
content	complex						
children	Amount CurrencyCode						
annotation	documentation Details of the amount and currency code of a special interest in delivery.						
source	<pre><xs:element name="InterestInDelivery" minOccurs="0"> <xs:annotation> <xs:documentation>Details of the amount and currency code of a special</pre>						

	<pre> interest in delivery.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Amount" type="Money_Type"> <xs:annotation> <xs:documentation>Amount</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Currency abbreviation (ISO-4217 alphanumeric)</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/InterestInDelivery/Amount**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Money_Type									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									
annotation	documentation Amount									
source	<pre> <xs:element name="Amount" type="Money_Type"> <xs:annotation> <xs:documentation>Amount</xs:documentation> </xs:annotation> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/InterestInDelivery/CurrencyCode**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	CurrencyCode_Type						
properties	content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[A-Z][A-Z][A-Z]</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	pattern	[A-Z][A-Z][A-Z]	
Kind	Value	Annotation					
pattern	[A-Z][A-Z][A-Z]						
annotation	documentation Currency abbreviation (ISO-4217 alphanumeric)						
source	<pre> <xs:element name="CurrencyCode" type="CurrencyCode_Type"> </pre>						

	<pre> <xs:annotation> <xs:documentation>Currency abbreviation (ISO-4217 alphanumeric)</xs:documentation> </xs:annotation> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/CashOnDelivery**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	Amount CurrencyCode
annotation	documentation Details of the amount to be collected on delivery and the currency code.
source	<pre> <xs:element name="CashOnDelivery" minOccurs="0"> <xs:annotation> <xs:documentation>Details of the amount to be collected on delivery and the currency code.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Amount" type="Money_Type"> <xs:annotation> <xs:documentation>Amount</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Currency abbreviation (ISO-4217 alphanumeric)</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/CashOnDelivery/Amount**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	Money_Type						
properties	content simple						
facets	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18	
Kind	Value	Annotation					
totalDigits	18						

	fractionDigits 2
annotation	documentation Amount
source	<pre><xs:element name="Amount" type="Money_Type"> <xs:annotation> <xs:documentation>Amount</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/CashOnDelivery/CurrencyCode**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	CurrencyCode Type						
properties	content simple						
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>pattern</td> <td>[A-Z][A-Z][A-Z]</td> <td></td> </tr> </table>	Kind	Value	Annotation	pattern	[A-Z][A-Z][A-Z]	
Kind	Value	Annotation					
pattern	[A-Z][A-Z][A-Z]						
annotation	documentation Currency abbreviation (ISO-4217 alphanumeric)						
source	<pre><xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Currency abbreviation (ISO-4217 alphanumeric)</xs:documentation> </xs:annotation> </xs:element></pre>						

element **ConsignmentOrderMessage/COMS/COM/RouteSection**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
properties	<table border="0"> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>30</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	minOcc	0	maxOcc	30	content	complex
minOcc	0						
maxOcc	30						
content	complex						
children	SequenceID RouteCode RouteText						
annotation	documentation Route sequence Sequential information about the complete routing of the consignment, the LeadRu decides wether to provide this information or not						
source	<pre><xs:element name="RouteSection" minOccurs="0" maxOccurs="30"> <xs:annotation> <xs:documentation>Route sequence Sequential information about the complete routing of the consignment, the LeadRu decides wether to provide</pre>						

```

this information or not</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="SequenceID" type="xs:int">
      <xs:annotation>
        <xs:documentation>Position of the route section in transport
chain. Used to determine the exact way of the transport for customs
purposes.</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:sequence>
      <xs:element name="RouteCode">
        <xs:annotation>
          <xs:documentation>Route code (International
RouteCode)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:length value="5"/>
            <xs:pattern value="\d*[1-9]\d*0"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="RouteText" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Description of the specific route
section</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="80"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:sequence>
</xs:complexType>
</xs:element>


```

element **ConsignmentOrderMessage/COMS/COM/RouteSection/SequenceID**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:int
properties	content simple
annotation	documentation Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.
source	<xs:element name="SequenceID" type="xs:int">

	<pre> <xs:annotation> <xs:documentation>Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.</xs:documentation> </xs:annotation> </xs:element> </pre>
--	---

element **ConsignmentOrderMessage/COMS/COM/RouteSection/RouteCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>5</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*0</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	5		pattern	\d*[1-9]\d*0	
Kind	Value	Annotation								
length	5									
pattern	\d*[1-9]\d*0									
annotation	documentation Route code (International RouteCode)									
source	<pre> <xs:element name="RouteCode"> <xs:annotation> <xs:documentation>Route code (International RouteCode)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="5"/> <xs:pattern value="\d*[1-9]\d*0"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/RouteSection/RouteText**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>80</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	80	
Kind	Value	Annotation								
minLength	1									
maxLength	80									
annotation	documentation Description of the specific route section									
source	<pre> <xs:element name="RouteText" minOccurs="0"> <xs:annotation> <xs:documentation>Description of the specific route </pre>									

	<pre> section</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="80"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/CustomsProcedures**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	RU Partner Location
annotation	documentation Customs procedures
source	<pre> <xs:element name="CustomsProcedures" minOccurs="0"> <xs:annotation> <xs:documentation>Customs procedures</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="RU_Partner" minOccurs="0"> <xs:annotation> <xs:documentation>Code of the RU entrusted of customs procedures. </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Location"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/CustomsData**


<p>diagram</p>	<pre> classDiagram class CustomsData { SimplifiedTransportProcedure PrincipalRU CustomsSurveillance CustomsEndorsements } </pre> <p>SimplifiedTransportProcedure Simplified transport procedure is used (STP).</p> <p>PrincipalRU Code for the principal ...</p> <p>CustomsSurveillance Good under customs surveillance</p> <p>CustomsEndorsements Reserved for endorsements by customs or a consignor/consignee authorised by customs. Data element in accordance with Regulation (EC) 1875/2006).</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 1 content complex</p>
<p>children</p>	<p>SimplifiedTransportProcedure PrincipalRU CustomsSurveillance CustomsEndorsements</p>
<p>annotation</p>	<p>documentation Customs Data</p>
<p>source</p>	<pre> <xs:element name="CustomsData" minOccurs="0"> <xs:annotation> <xs:documentation>Customs Data</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="SimplifiedTransportProcedure" minOccurs="0"> <xs:annotation> <xs:documentation>Simplified transport procedure is used (STP).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:boolean"/> </xs:simpleType> </xs:element> <xs:element name="PrincipalRU" type="CompanyCode" minOccurs="0"> <xs:annotation> <xs:documentation>Code for the principal RU</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CustomsSurveillance"> <xs:annotation> <xs:documentation>Good under customs surveillance</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:boolean"/> </xs:simpleType> </xs:element> <xs:element name="CustomsEndorsements" minOccurs="0"> <xs:annotation> <xs:documentation>Reserved for endorsements by customs or a consignor/consignee authorised by customs. Data element in accordance with Regulation (EC) 1875/2006).</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

	<pre> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **ConsignmentOrderMessage/COMS/COM/CustomsData/SimplifiedTransportProcedure**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:boolean
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Simplified transport procedure is used (STP).
source	<pre> <xs:element name="SimplifiedTransportProcedure" minOccurs="0"> <xs:annotation> <xs:documentation>Simplified transport procedure is used (STP).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:boolean"/> </xs:simpleType> </xs:element> </pre>


element **ConsignmentOrderMessage/COMS/COM/CustomsData/PrincipalRU**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	minOcc 0 maxOcc 1 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Code for the principal RU												
source	<pre> <xs:element name="PrincipalRU" type="CompanyCode" minOccurs="0"> <xs:annotation> <xs:documentation>Code for the principal RU</xs:documentation> </xs:annotation> </xs:element> </pre>												

element **ConsignmentOrderMessage/COMS/COM/CustomsData/CustomsSurveillance**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:boolean
properties	content simple
annotation	documentation Good under customs surveillance
source	<pre><xs:element name="CustomsSurveillance"> <xs:annotation> <xs:documentation>Good under customs surveillance</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:boolean"/> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/CustomsData/CustomsEndorsements**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 350
annotation	documentation Reserved for endorsements by customs or a consignor/consignee authorised by customs. Data element in accordance with Regulation (EC) 1875/2006).
source	<pre><xs:element name="CustomsEndorsements" minOccurs="0"> <xs:annotation> <xs:documentation>Reserved for endorsements by customs or a consignor/consignee authorised by customs. Data element in accordance with Regulation (EC) 1875/2006).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/RU_Declarations**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	RU_Declaration DifferentAcceptance
annotation	documentation Carriers declaration
source	<pre> <xs:element name="RU_Declarations" minOccurs="0"> <xs:annotation> <xs:documentation>Carriers declaration</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="RU_Declaration" minOccurs="0" maxOccurs="30"> <xs:annotation> <xs:documentation>Details of the carriers declaration.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DeclaringRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Code of carrier, who added the declaration.</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="RU_DeclarationCode"/> <xs:element ref="DeclarationText" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> <xs:element name="DifferentAcceptance" minOccurs="0"> <xs:annotation> <xs:documentation>Details of the changes of the acceptance point given by the consignor.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DifferentAcceptancePoint" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Variance of acceptance point given in structure AcceptancePoint.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="DifferentAcceptanceDate" minOccurs="0"> <xs:annotation> </pre>

	<pre> <xs:documentation>Variance of acceptance date given structure AcceptancePoint.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---


element **ConsignmentOrderMessage/COMS/COM/RU_Declarations/RU_Declaration**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 30 content complex
children	DeclaringRU RU_DeclarationCode DeclarationText
annotation	documentation Details of the carriers declaration.
source	<pre> <xs:element name="RU_Declaration" minOccurs="0" maxOccurs="30"> <xs:annotation> <xs:documentation>Details of the carriers declaration.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DeclaringRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Code of carrier, who added the declaration.</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="RU_DeclarationCode"/> <xs:element ref="DeclarationText" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/RU_Declarations/RU_Declaration/DeclaringRU**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Code of carrier, who added the declaration.												
source	<pre><xs:element name="DeclaringRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Code of carrier, who added the declaration.</xs:documentation> </xs:annotation> </xs:element></pre>												

element **ConsignmentOrderMessage/COMS/COM/RU_Declarations/DifferentAcceptance**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	complex
minOcc	0						
maxOcc	1						
content	complex						
children	DifferentAcceptancePoint DifferentAcceptanceDate						
annotation	documentation Details of the changes of the acceptance point given by the consignor.						
source	<pre><xs:element name="DifferentAcceptance" minOccurs="0"> <xs:annotation> <xs:documentation>Details of the changes of the acceptance point given by the consignor.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DifferentAcceptancePoint" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Variance of acceptance point given in structure AcceptancePoint.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="DifferentAcceptanceDate" minOccurs="0"> <xs:annotation> <xs:documentation>Variance of acceptance date given structure AcceptancePoint.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>						

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element

ConsignmentOrderMessage/COMS/COM/RU_Declarations/DifferentAcceptance/DifferentAcceptancePoint

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	minOcc 0 maxOcc 1 content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Variance of acceptance point given in structure AcceptancePoint.
source	<pre> <xs:element name="DifferentAcceptancePoint" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Variance of acceptance point given in structure AcceptancePoint.</xs:documentation> </xs:annotation> </xs:element> </pre>

element

ConsignmentOrderMessage/COMS/COM/RU_Declarations/DifferentAcceptance/DifferentAcceptanceDate

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:dateTime
properties	minOcc 0 maxOcc 1

content	simple
annotation	documentation Variance of acceptance date given structure AcceptancePoint.
source	<pre> <xs:element name="DifferentAcceptanceDate" minOccurs="0"> <xs:annotation> <xs:documentation>Variance of acceptance date given structure AcceptancePoint.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 1 maxOcc 30 content complex

children	CarrierStatus CarrierCode ResponsibleCarrierCode CarrierName StreetNumber Street ZIPCode City CountryCode SectionFrom SectionTo SubContractNumber SplitContract					
attributes	Name sequenceID	Type xs:int	Use	Default	Fixed	Annotation documentation Position of carrier during transport.
source	<pre> <xs:element name="Carriers" maxOccurs="30"> <xs:complexType> <xs:sequence> <xs:element ref="CarrierStatus"/> <xs:element name="CarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Railway Undertaking (Railway Code)</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ResponsibleCarrierCode" type="CompanyCode" minOccurs="0"> <xs:annotation> <xs:documentation>Railway Undertaking (Railway Code) of the carrier in charge.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CarrierName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of Carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="StreetNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Streetnumber of carrier.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Street" minOccurs="0"> <xs:annotation> <xs:documentation>Name of street of the carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>					

```

<xs:element name="ZIPCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Postal Code</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="9"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="CountryCode" type="CountryIdentISO" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SectionFrom" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>Start of section to be performed by the carrier.
This can be a station OR a border crossing point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SectionTo" type="LocationIdent">
  <xs:annotation>
    <xs:documentation>End of section to be performed by the carrier.
This can be a station OR a border crossing point.</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SubContractNumber_SplitContract" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Number of customer agreement between the
responsible and the operating carrier</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1">
        <xs:annotation>
          <xs:documentation>has to be sent as n6 (with leading zeros
if necessary)</xs:documentation>
        </xs:annotation>
      </xs:minLength>
      <xs:maxLength value="6"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
<xs:attribute name="sequenceID" type="xs:int">


```

	<pre> <xs:annotation> <xs:documentation>Position of carrier during transport. </xs:documentation> </xs:annotation> </xs:attribute> </xs:complexType> </xs:element> </pre>
--	---


attribute **ConsignmentOrderMessage/COMS/COM/Carriers/@sequenceID**

type	xs:int
annotation	documentation Position of carrier during transport.
source	<pre> <xs:attribute name="sequenceID" type="xs:int"> <xs:annotation> <xs:documentation>Position of carrier during transport. </xs:documentation> </xs:annotation> </xs:attribute> </pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/CarrierCode**


diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Railway Undertaking (Railway Code)												
source	<pre> <xs:element name="CarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Railway Undertaking (Railway Code)</xs:documentation> </xs:annotation> </xs:element> </pre>												

element **ConsignmentOrderMessage/COMS/COM/Carriers/ResponsibleCarrierCode**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	CompanyCode						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple
minOcc	0						
maxOcc	1						
content	simple						

facets	Kind	Value	Annotation
	minLength	4	
	maxLength	4	
	pattern	[0-9A-Z]{4}	
annotation	documentation	Railway Undertaking (Railway Code) of the carrier in charge.	
source	<pre><xs:element name="ResponsibleCarrierCode" type="CompanyCode" minOccurs="0"> <xs:annotation> <xs:documentation>Railway Undertaking (Railway Code) of the carrier in charge.</xs:documentation> </xs:annotation> </xs:element></pre>		

element **ConsignmentOrderMessage/COMS/COM/Carriers/CarrierName**


diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:string		
properties	minOcc 0 maxOcc 1 content simple		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	35	
annotation	documentation	Name of Carrier	
source	<pre><xs:element name="CarrierName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of Carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>		

element **ConsignmentOrderMessage/COMS/COM/Carriers/StreetNumber**


diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:string		
properties	minOcc 0 maxOcc 1 content simple		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	5	

annotation	documentation Streetnumber of carrier.
source	<pre><xs:element name="StreetNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Streetnumber of carrier.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/Street**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Name of street of the carrier									
source	<pre><xs:element name="Street" minOccurs="0"> <xs:annotation> <xs:documentation>Name of street of the carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/Carriers/ZIPCode**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	minOcc 0 maxOcc 1 content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1	
Kind	Value	Annotation					
minLength	1						

	maxLength 9
annotation	documentation Postal Code
source	<pre><xs:element name="ZIPCode" minOccurs="0"> <xs:annotation> <xs:documentation>Postal Code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="9"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/City**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation City/Town
source	<pre><xs:element name="City" minOccurs="0"> <xs:annotation> <xs:documentation>City/Town</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/CountryCode**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CountryIdentISO
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation

	minLength 2 maxLength 2
annotation	documentation Country Code (ISO Code)
source	<pre><xs:element name="CountryCode" type="CountryIdentISO" minOccurs="0"> <xs:annotation> <xs:documentation>Country Code (ISO Code)</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/SectionFrom**


diagram	<p>The diagram shows a 'SectionFrom' element connected to a 'LocationIdent' complex type. The 'LocationIdent' type is enclosed in a dashed box and contains four sub-elements: 'CountryCodeISO' (Identifies a County or State by code (ISO 316...)), 'LocationPrimaryCode', 'PrimaryLocationName' (Location Name in an offication language of the Country using the ISO Unicode alph...), and 'LocationSubsidiaryIdentification' (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Start of section to be performed by the carrier. This can be a station OR a border crossing point.
source	<pre><xs:element name="SectionFrom" type="LocationIdent"> <xs:annotation> <xs:documentation>Start of section to be performed by the carrier. This can be a station OR a border crossing point.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/SectionTo**

diagram	<p>The diagram shows a 'SectionTo' element connected to a 'LocationIdent' complex type. The 'LocationIdent' type is enclosed in a dashed box and contains four sub-elements: 'CountryCodeISO' (Identifies a County or State by code (ISO 316...)), 'LocationPrimaryCode', 'PrimaryLocationName' (Location Name in an offication language of the Country using the ISO Unicode alph...), and 'LocationSubsidiaryIdentification' (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation End of section to be performed by the carrier. This can be a station OR a border crossing point.
source	<pre><xs:element name="SectionTo" type="LocationIdent"> <xs:annotation> <xs:documentation>End of section to be performed by the carrier. This can be a station OR a border crossing point.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/Carriers/SubContractNumber_SplitContract**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="0"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td>documentation has to be sent as n6 (with leading zeros if necessary)</td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)	maxLength	6	
Kind	Value	Annotation								
minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)								
maxLength	6									
annotation	documentation Number of customer agreement between the responsible and the operating carrier									
source	<pre><xs:element name="SubContractNumber_SplitContract" minOccurs="0"> <xs:annotation> <xs:documentation>Number of customer agreement between the responsible and the operating carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/LeadCarrier**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CarrierCode CarrierName StreetNumber Street ZIPCode City CountryCode Signature</p>
<p>annotation</p>	<p>documentation LeadCarrier/ Contractual carrier</p>
<p>source</p>	<pre><xs:element name="LeadCarrier"> <xs:annotation> <xs:documentation>LeadCarrier/ Contractual carrier</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="CarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Contractual carrier, railway undertaking (Railway Code).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CarrierName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of contractual carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="StreetNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Streetnumber of carrier.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>


```

        <xs:minLength value="1"/>
        <xs:maxLength value="5"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Street" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Name of street of the carrier</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="ZIPCode" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Postal Code</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="9"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
    <xs:annotation>
        <xs:documentation>City/Town</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="CountryCode" type="CountryIdentISO" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Country Code (ISO Code)</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="Signature" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Signature of the contractual carrier. When
missing, the shipment number (CIM: 62) shall be used for signature
purposes.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="35"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>


```

	<code></xs:element></code>
--	----------------------------------


element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/CarrierCode**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Contractual carrier, railway undertaking (Railway Code).												
source	<pre><xs:element name="CarrierCode" type="CompanyCode"> <xs:annotation> <xs:documentation>Contractual carrier, railway undertaking (Railway Code).</xs:documentation> </xs:annotation> </xs:element></pre>												


element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/CarrierName**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Name of contractual carrier									
source	<pre><xs:element name="CarrierName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of contractual carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									


element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/StreetNumber**

diagram	 Streetnumber of carri...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 5
annotation	documentation Streetnumber of carrier.
source	<pre><xs:element name="StreetNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Streetnumber of carrier.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/Street**

diagram	 Name of street of the car...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation Name of street of the carrier
source	<pre><xs:element name="Street" minOccurs="0"> <xs:annotation> <xs:documentation>Name of street of the carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/ZIPCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>9</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	9	
Kind	Value	Annotation								
minLength	1									
maxLength	9									
annotation	documentation Postal Code									
source	<pre><xs:element name="ZIPCode" minOccurs="0"> <xs:annotation> <xs:documentation>Postal Code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="9"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									


element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/City**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation City/Town									
source	<pre><xs:element name="City" minOccurs="0"> <xs:annotation> <xs:documentation>City/Town</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/CountryCode**

diagram	 Country Code (ISO C...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CountryIdentISO
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 2 maxLength 2
annotation	documentation Country Code (ISO Code)
source	<pre><xs:element name="CountryCode" type="CountryIdentISO" minOccurs="0"> <xs:annotation> <xs:documentation>Country Code (ISO Code)</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/LeadCarrier/Signature**

diagram	 Signature of the contractual carrier. When missing, the shipment number (CIM: 62) shall be used for signature purposes.
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation Signature of the contractual carrier. When missing, the shipment number (CIM: 62) shall be used for signature purposes.
source	<pre><xs:element name="Signature" minOccurs="0"> <xs:annotation> <xs:documentation>Signature of the contractual carrier. When missing, the shipment number (CIM: 62) shall be used for signature purposes.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/MadeOut**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	Place Date
annotation	documentation Made out
source	<pre> <xs:element name="MadeOut" minOccurs="0"> <xs:annotation> <xs:documentation>Made out</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Place"> <xs:annotation> <xs:documentation>Place on which the consignment note was made out</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Date" type="xs:date"> <xs:annotation> <xs:documentation>Date at which the consignment note was made out.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/MadeOut/Place**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple

facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	<p>documentation</p> <p>Place on which the consignment note was made out</p>									
source	<pre><xs:element name="Place"> <xs:annotation> <xs:documentation>Place on which the consignment note was made out</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/MadeOut/Date**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
annotation	<p>documentation</p> <p>Date at which the consignment note was made out.</p>
source	<pre><xs:element name="Date" type="xs:date"> <xs:annotation> <xs:documentation>Date at which the consignment note was made out.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargesNote**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	complex
minOcc	0						
maxOcc	1						
content	complex						
children	ChargesNoteAvailable DateOfReturn						
annotation	<p>documentation</p> <p>Charges note</p>						
source	<pre><xs:element name="ChargesNote" minOccurs="0"> <xs:annotation></pre>						

	<pre> <xs:documentation>Charges note</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="ChargesNoteAvailable" type="xs:boolean"/> <xs:element name="DateOfReturn" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date, when the destination carrier sent the charges note back to the contractual carrier.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **ConsignmentOrderMessage/COMS/COM/ChargesNote/ChargesNoteAvailable**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
source	<pre><xs:element name="ChargesNoteAvailable" type="xs:boolean"/></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargesNote/DateOfReturn**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Date, when the destination carrier sent the charges note back to the contractual carrier.
source	<pre> <xs:element name="DateOfReturn" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date, when the destination carrier sent the charges note back to the contractual carrier.</xs:documentation> </xs:annotation> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/TransitPeriodExtensions**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 30 content complex
children	CodeOfCause Description Place Beginning Ending
source	<pre> <xs:element name="TransitPeriodExtensions" minOccurs="0" maxOccurs="30"> <xs:complexType> <xs:sequence> <xs:element ref="CodeOfCause"/> <xs:element name="Description" minOccurs="0"> <xs:annotation> <xs:documentation>Description for CodeOfCause no. 9.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="180"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Place"> <xs:annotation> <xs:documentation>Place of the extension.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="180"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Beginning"> <xs:annotation> <xs:documentation>Beginning of the extension.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> <xs:element name="Ending"> <xs:annotation> <xs:documentation>End of extension.</xs:documentation> </pre>

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/TransitPeriodExtensions/Description**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>180</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	180	
Kind	Value	Annotation								
minLength	1									
maxLength	180									
annotation	documentation Description for CodeOfCause no. 9.									
source	<pre> <xs:element name="Description" minOccurs="0"> <xs:annotation> <xs:documentation>Description for CodeOfCause no. 9.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="180"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/TransitPeriodExtensions/Place**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>180</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	180	
Kind	Value	Annotation								
minLength	1									
maxLength	180									
annotation	documentation Place of the extension.									
source	<pre> <xs:element name="Place"> <xs:annotation> <xs:documentation>Place of the extension.</xs:documentation> </xs:annotation> </xs:element> </pre>									

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="180"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/TransitPeriodExtensions/Beginning**

diagram	 Beginning of the extensi...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:dateTime
properties	content simple
annotation	documentation Beginning of the extension.
source	<pre> <xs:element name="Beginning"> <xs:annotation> <xs:documentation>Beginning of the extension.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/TransitPeriodExtensions/Ending**

diagram	 End of extensi...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:dateTime
properties	content simple
annotation	documentation End of extension.
source	<pre> <xs:element name="Ending"> <xs:annotation> <xs:documentation>End of extension.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:dateTime"/> </xs:simpleType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 1 maxOcc 15 content complex
children	Start End CommercialRouteCode CurrencyCode Tariff AdditionalCharges
annotation	documentation Charging section
source	<pre> <xs:element name="ChargingSections" maxOccurs="15"> <xs:annotation> <xs:documentation>Charging section</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Start" type="LocationIdent"> <xs:annotation> <xs:documentation>Start of the charging section</xs:documentation> </xs:annotation> </xs:element> <xs:element name="End" type="LocationIdent"> <xs:annotation> <xs:documentation>End of the charging section</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CommercialRouteCode" minOccurs="0"> <xs:annotation> <xs:documentation>Route code (RIP) when the customer agreement or the tariff applied provide for it. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="3"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Code for the currency of the amounts entered in the charging section.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="Tariff" type="string" minOccurs="0"> <xs:annotation> <xs:documentation>Freight Charges Section T... </xs:annotation> </xs:element> <xs:element name="AdditionalCharges" type="string" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>AdditionalCharges </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

</xs:element>
<xs:element name="Tariff" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges Section
  Tariff</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="NHMCode" type="NHMCodeType">
        <xs:annotation>
          <xs:documentation>NHM code determining the charges
        applicable.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="TariffNumber">
        <xs:annotation>
          <xs:documentation>Customer agreement or tariff
        applied</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="6"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="ChargedMass" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Charged mass [weight in kg]. As
        appropriate, area in m2 or the volume of the wagon or goods in m3 if used as
        the basis for charging.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="value">
              <xs:simpleType>
                <xs:restriction base="xs:decimal">
                  <xs:minInclusive value="1"/>
                  <xs:totalDigits value="8"/>
                  <xs:fractionDigits value="1"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
            <xs:element name="measure" minOccurs="0">
              <xs:simpleType>
                <xs:restriction base="xs:token">
                  <xs:enumeration value="kg"/>
                  <xs:enumeration value="m2"/>
                  <xs:enumeration value="m3"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="ExchangeRate" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Exchange rate for amounts to be paid by

```

the consignor or consignee which are not expressed in the invoicing currency.</xs:documentation>

```

</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:decimal">
    <xs:totalDigits value="18"/>
    <xs:fractionDigits value="3"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Distance" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Tariff distance, expressed in km or zones,
between the stations or points corresponding to the beginning and end of the
charging section.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="KM">
        <xs:annotation>
          <xs:documentation>Tariff distance, expressed in km,
between the stations or points corresponding to the beginning and end of the
charging section.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="99999"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="Zones">
        <xs:annotation>
          <xs:documentation>Tariff distance, expressed in zones,
between the stations or points corresponding to the beginning and end of the
charging section.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:int">
            <xs:minInclusive value="1"/>
            <xs:maxInclusive value="99"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
<xs:element name="Fee" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Supplements, fees,
deductions</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:totalDigits value="4"/>
      <xs:minInclusive value="1"/>
    </xs:restriction>
  </xs:simpleType>

```

```

</xs:element>
<xs:element name="FreightCharges" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges (paid and
due)</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="Prepaid" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be paid by the
consignor in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Transferred" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be paid by the
consignee in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:choice>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="AdditionalCharges" minOccurs="0" maxOccurs="10">
  <xs:annotation>
    <xs:documentation/>
    <xs:documentation>Sum of Prepaid</xs:documentation>
    <xs:documentation>Sum of Transferred</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="Code">
        <xs:annotation>
          <xs:documentation>Additional charges code</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="2"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:choice>
        <xs:element name="Prepaid" type="Money_Type">
          <xs:annotation>
            <xs:documentation>Prepaid</xs:documentation>
          </xs:annotation>
        </xs:element>
        <xs:element name="Transferred" type="Money_Type">
          <xs:annotation>
            <xs:documentation>Transferred</xs:documentation>
          </xs:annotation>
        </xs:element>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Start**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Start of the charging section
source	<pre> <xs:element name="Start" type="LocationIdent"> <xs:annotation> <xs:documentation>Start of the charging section</xs:documentation> </xs:annotation> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/End**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification

annotation	documentation End of the charging section
source	<pre><xs:element name="End" type="LocationIdent"> <xs:annotation> <xs:documentation>End of the charging section</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/CommercialRouteCode**

diagram	 <p>CommercialRouteCode Route code (RIP) when the customer agreement or the tariff applied provide...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation length 3 pattern \d*[1-9]\d*
annotation	documentation Route code (RIP) when the customer agreement or the tariff applied provide for it.
source	<pre><xs:element name="CommercialRouteCode" minOccurs="0"> <xs:annotation> <xs:documentation>Route code (RIP) when the customer agreement or the tariff applied provide for it. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="3"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/CurrencyCode**

diagram	 <p>CurrencyCode Code for the currency of the amounts entered in the charging section.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CurrencyCode Type
properties	content simple
facets	Kind Value Annotation pattern [A-Z][A-Z][A-Z]
annotation	documentation Code for the currency of the amounts entered in the charging section.
source	<pre><xs:element name="CurrencyCode" type="CurrencyCode_Type"> <xs:annotation> <xs:documentation>Code for the currency of the amounts entered in the</pre>

	<pre>charging section.</xs:documentation> </xs:annotation> </xs:element></pre>
--	--

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	NHMCode TariffNumber ChargedMass ExchangeRate Distance Fee FreightCharges
annotation	documentation Freight Charges Section Tariff
source	<pre><xs:element name="Tariff" minOccurs="0"> <xs:annotation> <xs:documentation>Freight Charges Section Tariff</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NHMCode" type="NHMCodeType"> <xs:annotation> <xs:documentation>NHM code determining the charges applicable.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TariffNumber"> <xs:annotation> <xs:documentation>Customer agreement or tariff applied</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>

```

        <xs:minLength value="1"/>
        <xs:maxLength value="6"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="ChargedMass" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Charged mass [weight in kg]. As appropriate,
area in m2 or the volume of the wagon or goods in m3 if used as the basis
for charging.</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element name="value">
                <xs:simpleType>
                    <xs:restriction base="xs:decimal">
                        <xs:minInclusive value="1"/>
                        <xs:totalDigits value="8"/>
                        <xs:fractionDigits value="1"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
            <xs:element name="measure" minOccurs="0">
                <xs:simpleType>
                    <xs:restriction base="xs:token">
                        <xs:enumeration value="kg"/>
                        <xs:enumeration value="m2"/>
                        <xs:enumeration value="m3"/>
                    </xs:restriction>
                </xs:simpleType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ExchangeRate" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Exchange rate for amounts to be paid by the
consignor or consignee which are not expressed in the invoicing
currency.</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:decimal">
            <xs:totalDigits value="18"/>
            <xs:fractionDigits value="3"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="Distance" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Tariff distance, expressed in km or zones,
between the stations or points corresponding to the beginning and end of the
charging section.</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:choice>
            <xs:element name="KM">
                <xs:annotation>
                    <xs:documentation>Tariff distance, expressed in km, between

```




```

the stations or points corresponding to the beginning and end of the
charging section.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:int">
    <xs:minInclusive value="1"/>
    <xs:maxInclusive value="99999"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Zones">
  <xs:annotation>
    <xs:documentation>Tariff distance, expressed in zones,
between the stations or points corresponding to the beginning and end of the
charging section.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:minInclusive value="1"/>
      <xs:maxInclusive value="99"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
<xs:element name="Fee" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Supplements, fees, deductions</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:totalDigits value="4"/>
      <xs:minInclusive value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="FreightCharges" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Freight Charges (paid and
due)</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:choice>
      <xs:element name="Prepaid" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be paid by the
consignor in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Transferred" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Carriage charges to be paid by the
consignee in the tariff currency.</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:choice>
  </xs:complexType>


```

	<pre> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/NHMCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	NHMCodeType									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>6</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	6		pattern	\d*[1-9]\d*	
Kind	Value	Annotation								
length	6									
pattern	\d*[1-9]\d*									
annotation	documentation NHM code determining the charges applicable.									
source	<pre> <xs:element name="NHMCode" type="NHMCodeType"> <xs:annotation> <xs:documentation>NHM code determining the charges applicable.</xs:documentation> </xs:annotation> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/TariffNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	6	
Kind	Value	Annotation								
minLength	1									
maxLength	6									
annotation	documentation Customer agreement or tariff applied									
source	<pre> <xs:element name="TariffNumber"> <xs:annotation> <xs:documentation>Customer agreement or tariff applied</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/ChargedMass**


diagram	<p>Charged mass [weight in kg]. As appropriate, area in m² or the volume of the wagon or goods in m³ if used as the basis for charging.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	value measure
annotation	documentation Charged mass [weight in kg]. As appropriate, area in m ² or the volume of the wagon or goods in m ³ if used as the basis for charging.
source	<pre> <xs:element name="ChargedMass" minOccurs="0"> <xs:annotation> <xs:documentation>Charged mass [weight in kg]. As appropriate, area in m² or the volume of the wagon or goods in m³ if used as the basis for charging.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="value"> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="1"/> <xs:totalDigits value="8"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="measure" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="kg"/> <xs:enumeration value="m2"/> <xs:enumeration value="m3"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/ChargedMass/value**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:decimal
properties	content simple

facets	Kind	Value	Annotation
	minInclusive	1	
	totalDigits	8	
	fractionDigits	1	
source	<pre><xs:element name="value"> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="1"/> <xs:totalDigits value="8"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>		

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/ChargedMass/measure**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:token
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation enumeration kg enumeration m2 enumeration m3
source	<pre><xs:element name="measure" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="kg"/> <xs:enumeration value="m2"/> <xs:enumeration value="m3"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/ExchangeRate**

diagram	 <p>Exchange rate for amounts to be paid by the consignor or consignee which are not expressed in the invoicing currency.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:decimal
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation totalDigits 18 fractionDigits 3


annotation	documentation Exchange rate for amounts to be paid by the consignor or consignee which are not expressed in the invoicing currency.
source	<pre><xs:element name="ExchangeRate" minOccurs="0"> <xs:annotation> <xs:documentation>Exchange rate for amounts to be paid by the consignor or consignee which are not expressed in the invoicing currency.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="18"/> <xs:fractionDigits value="3"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/Distance**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	KM Zones
annotation	documentation Tariff distance, expressed in km or zones, between the stations or points corresponding to the beginning and end of the charging section.
source	<pre><xs:element name="Distance" minOccurs="0"> <xs:annotation> <xs:documentation>Tariff distance, expressed in km or zones, between the stations or points corresponding to the beginning and end of the charging section.</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element name="KM"> <xs:annotation> <xs:documentation>Tariff distance, expressed in km, between the stations or points corresponding to the beginning and end of the charging section.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:choice> </xs:complexType> </xs:element></pre>

	<pre> </xs:element> <xs:element name="Zones"> <xs:annotation> <xs:documentation>Tariff distance, expressed in zones, between the stations or points corresponding to the beginning and end of the charging section.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:choice> </xs:complexType> </xs:element> </pre>
--	--


element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/Distance/KM**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation Tariff distance, expressed in km, between the stations or points corresponding to the beginning and end of the charging section.									
source	<pre> <xs:element name="KM"> <xs:annotation> <xs:documentation>Tariff distance, expressed in km, between the stations or points corresponding to the beginning and end of the charging section.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/Distance/Zones**

diagram	 Tariff distance, expressed in zones, between the stations or points corresponding to the beginning and end of the charging section.
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int
properties	content simple
facets	Kind Value Annotation minInclusive 1 maxInclusive 99
annotation	documentation Tariff distance, expressed in zones, between the stations or points corresponding to the beginning and end of the charging section.
source	<pre><xs:element name="Zones"> <xs:annotation> <xs:documentation>Tariff distance, expressed in zones, between the stations or points corresponding to the beginning and end of the charging section.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/Fee**

diagram	 Supplements, fees, deductions
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minInclusive 1 totalDigits 4
annotation	documentation Supplements, fees, deductions
source	<pre><xs:element name="Fee" minOccurs="0"> <xs:annotation> <xs:documentation>Supplements, fees, deductions</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:totalDigits value="4"/> <xs:minInclusive value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

	<pre></xs:simpleType> </xs:element></pre>
--	---

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/FreightCharges**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	Prepaid Transferred
annotation	documentation Freight Charges (paid and due)
source	<pre><xs:element name="FreightCharges" minOccurs="0"> <xs:annotation> <xs:documentation>Freight Charges (paid and due)</xs:documentation> </xs:annotation> <xs:complexType> <xs:choice> <xs:element name="Prepaid" type="Money_Type"> <xs:annotation> <xs:documentation>Carriage charges to be paid by the consignor in the tariff currency.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="Transferred" type="Money_Type"> <xs:annotation> <xs:documentation>Carriage charges to be paid by the consignee in the tariff currency.</xs:documentation> </xs:annotation> </xs:element> </xs:choice> </xs:complexType> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/FreightCharges/Prepaid**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Money_Type									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									

annotation	documentation Carriage charges to be paid by the consignor in the tariff currency.
source	<pre><xs:element name="Prepaid" type="Money_Type"> <xs:annotation> <xs:documentation>Carriage charges to be paid by the consignor in the tariff currency.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/FreightCharges/Transferred**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Money_Type									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									
annotation	documentation Carriage charges to be paid by the consignee in the tariff currency.									
source	<pre><xs:element name="Transferred" type="Money_Type"> <xs:annotation> <xs:documentation>Carriage charges to be paid by the consignee in the tariff currency.</xs:documentation> </xs:annotation> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/AdditionalCharges**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>10</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </tbody> </table>	minOcc	0	maxOcc	10	content	complex
minOcc	0						
maxOcc	10						
content	complex						
children	Code Prepaid Transferred						
annotation	documentation Sum of Prepaid documentation Sum of Transferred						
source	<pre><xs:element name="AdditionalCharges" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation/> <xs:documentation>Sum of Prepaid</xs:documentation> <xs:documentation>Sum of Transferred</xs:documentation> </xs:annotation> </xs:element></pre>						

```


</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="Code">
      <xs:annotation>
        <xs:documentation>Additional charges code</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="2"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:choice>
      <xs:element name="Prepaid" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Prepaid</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Transferred" type="Money_Type">
        <xs:annotation>
          <xs:documentation>Transferred</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
</xs:element>

```


element **ConsignmentOrderMessage/COMS/COM/ChargingSections/AdditionalCharges/Code**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	2	
Kind	Value	Annotation								
minLength	1									
maxLength	2									
annotation	documentation Additional charges code									
source	<pre> <xs:element name="Code"> <xs:annotation> <xs:documentation>Additional charges code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="2"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									


element **ConsignmentOrderMessage/COMS/COM/ChargingSections/AdditionalCharges/Prepaid**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Money_Type									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									
annotation	documentation Prepaid									
source	<pre><xs:element name="Prepaid" type="Money_Type"> <xs:annotation> <xs:documentation>Prepaid</xs:documentation> </xs:annotation> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/ChargingSections/AdditionalCharges/Transferred**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Money_Type									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									
annotation	documentation Transferred									
source	<pre><xs:element name="Transferred" type="Money_Type"> <xs:annotation> <xs:documentation>Transferred</xs:documentation> </xs:annotation> </xs:element></pre>									

element **ConsignmentOrderMessage/COMS/COM/WagonPreviousNumberFreight**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of WagonIdent						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>20</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	20	content	simple
minOcc	0						
maxOcc	20						
content	simple						

facets	Kind	Value	Annotation
	length	12	
	maxLength	12	
	pattern	[0-9]{12}	
annotation	documentation	Identifies the previous freight wagon if a shipment or Intermodal unit has changed the wagon during its journey	
source	<pre><xs:element name="WagonPreviousNumberFreight" minOccurs="0" maxOccurs="20"> <xs:annotation> <xs:documentation>Identifies the previous freight wagon if a shipment or Intermodal unit has changed the wagon during its journey</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="WagonIdent"> <xs:length value="12"/> </xs:restriction> </xs:simpleType> </xs:element></pre>		

element **ContainerHandlingFlag**


diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	xs:boolean		
properties	content	simple	
used by	element	LocationPrimaryInformation	
annotation	documentation	This establishment is able to handle container traffic	
source	<pre><xs:element name="ContainerHandlingFlag" type="xs:boolean"> <xs:annotation> <xs:documentation>This establishment is able to handle container traffic</xs:documentation> </xs:annotation> </xs:element></pre>		

element **ContractNumber**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:string		
properties	content	simple	
used by	element	WIMO Dataset/ConsignmentLevelData	
facets	Kind	Value	Annotation
	minLength	1	documentation has to be sent as n6 (with leading zeros if necessary)
	maxLength	6	

annotation	documentation Number of agreement between LeadRU and Responsible RU
source	<pre> <xs:element name="ContractNumber"> <xs:annotation> <xs:documentation>Number of agreement between LeadRU and Responsible RU</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"> <xs:annotation> <xs:documentation>has to be sent as n6 (with leading zeros if necessary)</xs:documentation> </xs:annotation> </xs:minLength> <xs:maxLength value="6"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **ContractNumberMovement**


diagram	 <p>Identifies the contract between LeadRU and RU involved in the transport</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Identifies the contract between LeadRU and RU involved in the transport									
source	<pre> <xs:element name="ContractNumberMovement" type="FreeText"> <xs:annotation> <xs:documentation>Identifies the contract between LeadRU and RU involved in the transport</xs:documentation> </xs:annotation> </xs:element> </pre>									

element **CoordinatingIM**

diagram	 <p>The coordinating (leading) IM coordinates the agreement process for the IM's. It is the primary point of contact for the RU's. Certain critical stages in the international timetabling process are initiated by the leading IM, such as transfer the path request to path elaboration to involved IMs in order to prepare the offer with the ...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	CompanyCode												
properties	content simple												
used by	elements PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage												
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td colspan="2">[0-9A-Z]{4}</td> </tr> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	<p>documentation</p> <p>The coordinating (leading) IM coordinates the agreement process for the IM's. It is the primary point of contact for the RU's. Certain critical stages in the international timetabling process are initiated by the leading IM, such as transfer the path request to path elaboration to involved IMs in order to prepare the offer with the partner-IMs.</p>												
source	<pre><xs:element name="CoordinatingIM" type="CompanyCode"> <xs:annotation> <xs:documentation>The coordinating (leading) IM coordinates the agreement process for the IM's. It is the primary point of contact for the RU's. Certain critical stages in the international timetabling process are initiated by the leading IM, such as transfer the path request to path elaboration to involved IMs in order to prepare the offer with the partner- IMs. </xs:documentation> </xs:annotation> </xs:element></pre>												

element **Core**


diagram																
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	content simple															
used by	complexTypees CompositIdentifierOperationalType CompositIdentifierPlannedType															
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>12</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td colspan="2">replace</td> </tr> <tr> <td>pattern</td> <td colspan="2">[\-*0-9A-Z]{12}</td> </tr> </table>	Kind	Value	Annotation	minLength	12		maxLength	12		whiteSpace	replace		pattern	[\-*0-9A-Z]{12}	
Kind	Value	Annotation														
minLength	12															
maxLength	12															
whiteSpace	replace															
pattern	[\-*0-9A-Z]{12}															
annotation	<p>documentation</p> <p>It is the main part of identifier and is determined by the company that creates it.</p>															
source	<pre><xs:element name="Core"> <xs:annotation> <xs:documentation>It is the main part of identifier and is determined by the company that creates it.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="12"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="12"/> <xs:pattern value="[\-*0-9A-Z]{12}"/> </xs:restriction> </xs:simpleType> </xs:element></pre>															

	<pre></xs:simpleType> </xs:element></pre>
--	---


element **CountryCodeISO**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	extension of CountryIdentISO									
properties	content complex									
used by	<p>elements RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber RollingRoadUnit/RollingRoadUnitDetails/Haulier LocationFileDatasetMessage RollingRoadUnit/RollingRoadUnitDetails/Vehicles</p> <p>complexTypees CustomerCode LocationIdent</p>									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2	
Kind	Value	Annotation								
minLength	2									
maxLength	2									
annotation	documentation Identifies a County or State by code (ISO 3166-1)									
source	<pre><xs:element name="CountryCodeISO"> <xs:annotation> <xs:documentation>Identifies a County or State by code (ISO 3166-1)</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="CountryIdentISO"/> </xs:simpleContent> </xs:complexType> </xs:element></pre>									

element **CreateDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation Date and Time of creation of data
source	<pre><xs:element name="CreateDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date and Time of creation of data </xs:documentation> </xs:annotation> </xs:element></pre>

element **Customer**



namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of CustomerCode
properties	content complex
children	CountryCodeISO PrimaryCode AdditionalCode Type CustomerCode Name AdditionalInformation VAT POBox StreetNumber Street Country ZIPCode City Signature Contacts ContractualCarrierCode
used by	element WIMO Dataset/ConsignmentLevelData
annotation	documentation Consignor or Consignee
source	<pre> <xs:element name="Customer"> <xs:annotation> <xs:documentation>Consignor or Consignee</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="CustomerCode"> <xs:sequence> <xs:element name="Type" minOccurs="0"> </pre>


```

    <xs:annotation>
      <xs:documentation>Customer Type: CR Consignor, CE
Consignee</xs:documentation>
    </xs:annotation>
  </xs:simpleType>
  <xs:restriction base="xs:token">
    <xs:enumeration value="CR"/>
    <xs:enumeration value="CE"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="CustomerCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>CODE: Customer Code of the Contractal
Carrier</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="16"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="Name" minOccurs="0"/>
<xs:element name="AdditionalInformation" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Additional Information supplied by
Customer</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="45"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="VAT" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Value Added Tax</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="25"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="POBox" minOccurs="0">
  <xs:annotation>
    <xs:documentation>P.O. Box</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

```

```

<xs:element name="StreetNumber" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Street Number</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="5"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Street" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Street</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Country" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code ISO</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:length value="2"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ZIPCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Postal Code</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="9"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City / Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Signature" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Signature</xs:documentation>
  </xs:annotation>


```

```

<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="35"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Contacts" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Contact information</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="PhonNumber" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Telephone Number</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="30"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="FaxNumber" minOccurs="0"/>
      <xs:element ref="eMail" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ContractualCarrierCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Contractual Carrier Code</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:length value="4"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
</xs:element>

```

element **Customer/Type**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:token
properties	minOcc 0 maxOcc 1 content simple

facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>CR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CE</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	CR		enumeration	CE	
Kind	Value	Annotation								
enumeration	CR									
enumeration	CE									
annotation	documentation Customer Type: CR Consignor, CE Consignee									
source	<pre> <xs:element name="Type" minOccurs="0"> <xs:annotation> <xs:documentation>Customer Type: CR Consignor, CE Consignee</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="CR"/> <xs:enumeration value="CE"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Customer/CustomerCode**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>16</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	16	
Kind	Value	Annotation								
minLength	1									
maxLength	16									
annotation	documentation CODE: Customer Code of the Contractal Carrier									
source	<pre> <xs:element name="CustomerCode" minOccurs="0"> <xs:annotation> <xs:documentation>CODE: Customer Code of the Contractal Carrier</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="16"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Customer/AdditionalInformation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 45
annotation	documentation Additional Information supplied by Customer
source	<pre><xs:element name="AdditionalInformation" minOccurs="0"> <xs:annotation> <xs:documentation>Additional Information supplied by Customer</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="45"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Customer/VAT**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 25
annotation	documentation Value Added Tax
source	<pre><xs:element name="VAT" minOccurs="0"> <xs:annotation> <xs:documentation>Value Added Tax</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="25"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Customer/POBox**

diagram	
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation P.O. Box
source	<pre><xs:element name="POBox" minOccurs="0"> <xs:annotation> <xs:documentation>P.O. Box</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **Customer/StreetNumber**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 5
annotation	documentation Street Number
source	<pre><xs:element name="StreetNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Street Number</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **Customer/Street**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation Street
source	<pre><xs:element name="Street" minOccurs="0"> <xs:annotation> <xs:documentation>Street</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **Customer/Country**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation length 2
annotation	documentation Country Code ISO
source	<pre><xs:element name="Country" minOccurs="0"> <xs:annotation> <xs:documentation>Country Code ISO</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="2"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **Customer/ZIPCode**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 9
annotation	documentation Postal Code
source	<pre><xs:element name="ZIPCode" minOccurs="0"> <xs:annotation> <xs:documentation>Postal Code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="9"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **Customer/City**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation City / Town
source	<pre><xs:element name="City" minOccurs="0"> <xs:annotation> <xs:documentation>City / Town</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Customer/Signature**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation Signature
source	<pre><xs:element name="Signature" minOccurs="0"> <xs:annotation> <xs:documentation>Signature</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Customer/Contacts**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	PhonNumber FaxNumber eMail
annotation	documentation Contact information
source	<pre><xs:element name="Contacts" minOccurs="0"> <xs:annotation> <xs:documentation>Contact information</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="PhonNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Telephone Number</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="30"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="FaxNumber" minOccurs="0"/> <xs:element ref="eMail" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **Customer/Contacts/PhonNumber**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 30
annotation	documentation Telephone Number
source	<pre> <xs:element name="PhonNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Telephone Number</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="30"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **Customer/ContractualCarrierCode**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation length 4
annotation	documentation Contractual Carrier Code

source	<pre><xs:element name="ContractualCarrierCode" minOccurs="0"> <xs:annotation> <xs:documentation>Contractual Carrier Code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="4"/> </xs:restriction> </xs:simpleType> </xs:element></pre>
--------	--

element **CustomerNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	elements Customers LoadingFacility									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>16</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	16	
Kind	Value	Annotation								
minLength	1									
maxLength	16									
annotation	documentation The customer number of the COM differs from the customer code used in TAF/TSI, its format may not accord to the TAF element									
source	<pre><xs:element name="CustomerNumber"> <xs:annotation> <xs:documentation>The customer number of the COM differs from the customer code used in TAF/TSI, its format may not accord to the TAF element</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="16"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Customers**

<p>diagram</p> 	<p>Information about the consignor, consignee and freight payers.</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CustomerType CustomerNumber Name AdditionalInformation VAT POBox StreetNumber Street Country ZIPCode City Signature AdministrativeContactInformation Contacts</p>
<p>used by</p>	<p>elements ConsignmentOrderMessage/COMS/COM WagonDeliveryNoticeMessage WagonDepartureNoticeMessage WagonReleaseNoticeMessage</p>
<p>annotation</p>	<p>documentation Information about the consignor, consignee and freight payers.</p>
<p>source</p>	<pre><xs:element name="Customers"> <xs:annotation> <xs:documentation>Information about the consignor, consignee and freight payers.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="CustomerType"/> <xs:element ref="CustomerNumber" minOccurs="0"> <xs:annotation> <xs:documentation>CustomerNumber</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Name" minOccurs="0"/> <xs:element name="AdditionalInformation" minOccurs="0"/> <xs:element name="VAT" minOccurs="0"></pre>

```

    <xs:annotation>
      <xs:documentation>VAT identification Nr of
customer</xs:documentation>
    </xs:annotation>
  </xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="25"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="POBox" minOccurs="0">
  <xs:annotation>
    <xs:documentation>P.O. Box</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="StreetNumber" minOccurs="0">
  <xs:annotation>
    <xs:documentation>House number</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="5"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Street" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Street</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Country" type="CountryIdentISO" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Country Code (ISO Code)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="ZIPCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Postal Code</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="9"/>
    </xs:restriction>


```

```


</xs:simpleType>
</xs:element>
<xs:element name="City" minOccurs="0">
  <xs:annotation>
    <xs:documentation>City/Town</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Signature" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Signature</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="35"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="AdministrativeContactInformation"/>
<xs:element name="Contacts" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Contact information</xs:documentation>
    <xs:documentation>RULE: Transmission of empty tag is
prohibited.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="PhoneNumber" type="CommunicationRefID"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Telephone number</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="FaxNumber" type="CommunicationRefID"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Fax number</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Email" type="CommunicationRefID"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Email address</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```


element **Customers/AdditionalInformation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1
source	<code><xs:element name="AdditdionalInformation" minOccurs="0"/></code>

element **Customers/VAT**


diagram	 VAT VAT identification Nr of customer
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 25
annotation	documentation VAT identification Nr of customer
source	<pre><xs:element name="VAT" minOccurs="0"> <xs:annotation> <xs:documentation>VAT identification Nr of customer</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="25"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Customers/POBox**


diagram	 P.O. ...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation P.O. Box

source	<pre><xs:element name="POBox" minOccurs="0"> <xs:annotation> <xs:documentation>P.O. Box</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>
--------	---

element **Customers/StreetNumber**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>5</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	5	
Kind	Value	Annotation								
minLength	1									
maxLength	5									
annotation	documentation House number									
source	<pre><xs:element name="StreetNumber" minOccurs="0"> <xs:annotation> <xs:documentation>House number</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Customers/Street**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation									

	Street
source	<pre><xs:element name="Street" minOccurs="0"> <xs:annotation> <xs:documentation>Street</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Customers/Country**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CountryIdentISO									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2	
Kind	Value	Annotation								
minLength	2									
maxLength	2									
annotation	documentation Country Code (ISO Code)									
source	<pre><xs:element name="Country" type="CountryIdentISO" minOccurs="0"> <xs:annotation> <xs:documentation>Country Code (ISO Code)</xs:documentation> </xs:annotation> </xs:element></pre>									

element **Customers/ZIPCode**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>9</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	9	
Kind	Value	Annotation								
minLength	1									
maxLength	9									
annotation	documentation Postal Code									
source	<pre><xs:element name="ZIPCode" minOccurs="0"> <xs:annotation> <xs:documentation>Postal Code</xs:documentation> </xs:annotation></pre>									

	<pre> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="9"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **Customers/City**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation City/Town
source	<pre> <xs:element name="City" minOccurs="0"> <xs:annotation> <xs:documentation>City/Town</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **Customers/Signature**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation Signature
source	<pre> <xs:element name="Signature" minOccurs="0"> <xs:annotation> <xs:documentation>Signature</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---


element **Customers/Contacts**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	PhoneNumber FaxNumber Email
annotation	documentation Contact information documentation RULE: Transmission of empty tag is prohibited.
source	<pre> <xs:element name="Contacts" minOccurs="0"> <xs:annotation> <xs:documentation>Contact information</xs:documentation> <xs:documentation>RULE: Transmission of empty tag is prohibited.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="PhoneNumber" type="CommunicationRefID" minOccurs="0"> <xs:annotation> <xs:documentation>Telephone number</xs:documentation> </xs:annotation> </xs:element> <xs:element name="FaxNumber" type="CommunicationRefID" minOccurs="0"> <xs:annotation> <xs:documentation>Fax number</xs:documentation> </xs:annotation> </xs:element> <xs:element name="Email" type="CommunicationRefID" minOccurs="0"> <xs:annotation> <xs:documentation>Email address</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **Customers/Contacts/PhoneNumber**

diagram	 Telephone num...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CommunicationRefID
properties	minOcc 0 maxOcc 1 content simple
used by	element AdministrativeContactInformation
facets	Kind Value Annotation minLength 1 maxLength 70
annotation	documentation Telephone number
source	<pre><xs:element name="PhoneNumber" type="CommunicationRefID" minOccurs="0"> <xs:annotation> <xs:documentation>Telephone number</xs:documentation> </xs:annotation> </xs:element></pre>

element **Customers/Contacts/FaxNumber**

diagram	 Fax num...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CommunicationRefID
properties	minOcc 0 maxOcc 1 content simple
used by	elements AdministrativeContactInformation Customer/Contacts
facets	Kind Value Annotation minLength 1 maxLength 70
annotation	documentation Fax number
source	<pre><xs:element name="FaxNumber" type="CommunicationRefID" minOccurs="0"> <xs:annotation> <xs:documentation>Fax number</xs:documentation> </xs:annotation> </xs:element></pre>

element **Customers/Contacts/Email**

diagram	 Email addr...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CommunicationRefID


properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 70
annotation	documentation Email address
source	<xs:element name="Email" type="CommunicationRefID" minOccurs="0"> <xs:annotation> <xs:documentation>Email address</xs:documentation> </xs:annotation> </xs:element>

element **DangerousGoodsIndication**


diagram	<p>DangerousGoodsIndicati... Identifies dangerous go...</p> <p>DanGoodsTy...</p> <ul style="list-style-type: none"> HazardIdentificationNumber UN_Numb... The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC..." DangerLabel 0..5 All Danger Label of this dangerous good according to the RID chapter 3.2, table A, column 5, excepting the shunting labels Model 13 and 15 (CODE: OTIF RID-Specification). RID_Class The Class of the dangerous good according to the RID chapter 3.2, table A, column 3a. PackingGro... The Packing Group according to the RID chapter 3.2, table A, column 4. Possible values are "I", "II" or "III", otherwise the Packing Group have to be omitted. Mandatory, if it's foreseen in column 4, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC..." DangerousGoodsWeig... The weight of the dangerous goods in Kilogr... DangerousGoodsVolu... The volume of the dangerous goods in cubic ... LimitedQuantityIndicator Indicator for labelled dangerous goods in limited quantity according to chapter 3.4 RID
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	DanGoodsType

properties	content complex
children	HazardIdentificationNumber UN Number DangerLabel RID Class PackingGroup DangerousGoodsWeight DangerousGoodsVolume LimitedQuantityIndicator
used by	elements WIMO Dataset/ConsignmentLevelData WagonOperationalData/DangerousGoodsDetails PlannedTrainData RID WagonExceptionMessage WagonExceptionReasonMessage
annotation	documentation Identifies dangerous goods
source	<pre><xs:element name="DangerousGoodsIndication" type="DanGoodsType"> <xs:annotation> <xs:documentation>Identifies dangerous goods</xs:documentation> </xs:annotation> </xs:element></pre>

element **DangerousGoodsIndicator**


diagram	 <p>Indicates whether Dangerous Goods are allowed (Yes/No Indicator) If "0", then no dangerous goods are allowed. If "1", then the restricted goods are described in DangerousGoodsIndication</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element TrainRunningData
annotation	documentation Indicates whether Dangerous Goods are allowed (Yes/No Indicator) If "0", then no dangerous goods are allowed. If "1", then the restricted goods are described in DangerousGoodsIndication
source	<pre><xs:element name="DangerousGoodsIndicator" type="xs:boolean"> <xs:annotation> <xs:documentation>Indicates whether Dangerous Goods are allowed (Yes/No Indicator) If "0", then no dangerous goods are allowed. If "1", then the restricted goods are described in DangerousGoodsIndication</xs:documentation> </xs:annotation> </xs:element></pre>

element **DangerousGoodsVolume**


diagram	 <p>The volume of the dangerous goods in cubic ...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	VolumeValue
properties	content simple
used by	element SummaryOFGoodsWithSameRID
annotation	documentation The volume of the dangerous goods in cubic meters
source	<pre><xs:element name="DangerousGoodsVolume" type="VolumeValue"> <xs:annotation></pre>

	<pre> <xs:documentation>The volume of the dangerous goods in cubic meters</xs:documentation> </xs:annotation> </xs:element> </pre>
--	--

element **DangerousGoodsWeight**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	WeightValueKilo
properties	content simple
used by	element SummaryOFGoodsWithSameRID complexType DanGoodsType
facets	Kind Value Annotation minInclusive 0 maxInclusive 999999 whiteSpace collapse
annotation	documentation The weight of dangerous goods in kilograms
source	<pre> <xs:element name="DangerousGoodsWeight" type="WeightValueKilo"> <xs:annotation> <xs:documentation>The weight of dangerous goods in kilograms</xs:documentation> </xs:annotation> </xs:element> </pre>

element **Date**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
annotation	documentation Date
source	<pre> <xs:element name="Date" type="xs:date"> <xs:annotation> <xs:documentation>Date</xs:documentation> </xs:annotation> </xs:element> </pre>

element **DateLastOverhaul**


diagram	
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
used by	element RollingStockDataset/DesignDataSet
annotation	documentation Date of the last overhaul. For wagons newly placed on the market, the date put into service must be used.
source	<pre><xs:element name="DateLastOverhaul" type="xs:date"> <xs:annotation> <xs:documentation> Date of the last overhaul. For wagons newly placed on the market, the date put into service must be used. </xs:documentation> </xs:annotation> </xs:element></pre>


element **DateNextOverhaul**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
source	<pre><xs:element name="DateNextOverhaul" type="xs:date"/></pre>

element **DatePutIntoService**

diagram	 Original Date of first operation
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
used by	element RollingStockDataset/AdministrativeDataSet
annotation	documentation Original Date of first operation
source	<pre><xs:element name="DatePutIntoService" type="xs:date"> <xs:annotation> <xs:documentation>Original Date of first operation</xs:documentation> </xs:annotation> </xs:element></pre>

element **DeclarationText**

diagram	 Additional Text for codes with free text
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string

properties	content simple
used by	elements ConsignmentOrderMessage/COMS/COM/ConsignorDeclarations ConsignmentOrderMessage/COMS/COM/RU_Declarations/RU_Declaration
facets	Kind Value Annotation minLength 1 maxLength 350
annotation	documentation Additional Text for codes with free text
source	<pre><xs:element name="DeclarationText"> <xs:annotation> <xs:documentation>Additional Text for codes with free text</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **DelayCause**

diagram																																											
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																										
type	DelayCode																																										
properties	content simple																																										
used by	elements DelayCauseTime TrainReadyMessage/TrainReadyStatus TrainReadyStatus																																										
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>11</td> <td>documentation Formation of trains if managed by infrastructure manager</td> </tr> <tr> <td>enumeration</td> <td>10</td> <td>documentation Timetable compilation</td> </tr> <tr> <td>enumeration</td> <td>12</td> <td>documentation Mistakes in operational procedures</td> </tr> <tr> <td>enumeration</td> <td>13</td> <td>documentation Wrong application of priority rules</td> </tr> <tr> <td>enumeration</td> <td>14</td> <td></td> </tr> <tr> <td>enumeration</td> <td>18</td> <td>documentation Staff</td> </tr> <tr> <td>enumeration</td> <td>19</td> <td>documentation Other causes related to the operational planning and management</td> </tr> <tr> <td>enumeration</td> <td>20</td> <td>documentation Signalling installations</td> </tr> <tr> <td>enumeration</td> <td>21</td> <td>documentation Signalling installations at level crossings</td> </tr> <tr> <td>enumeration</td> <td>22</td> <td>documentation Telecommunication installations</td> </tr> <tr> <td>enumeration</td> <td>23</td> <td>documentation Power supply equipment</td> </tr> <tr> <td>enumeration</td> <td>24</td> <td>documentation Track</td> </tr> <tr> <td>enumeration</td> <td>25</td> <td>documentation</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	11	documentation Formation of trains if managed by infrastructure manager	enumeration	10	documentation Timetable compilation	enumeration	12	documentation Mistakes in operational procedures	enumeration	13	documentation Wrong application of priority rules	enumeration	14		enumeration	18	documentation Staff	enumeration	19	documentation Other causes related to the operational planning and management	enumeration	20	documentation Signalling installations	enumeration	21	documentation Signalling installations at level crossings	enumeration	22	documentation Telecommunication installations	enumeration	23	documentation Power supply equipment	enumeration	24	documentation Track	enumeration	25	documentation
Kind	Value	Annotation																																									
enumeration	11	documentation Formation of trains if managed by infrastructure manager																																									
enumeration	10	documentation Timetable compilation																																									
enumeration	12	documentation Mistakes in operational procedures																																									
enumeration	13	documentation Wrong application of priority rules																																									
enumeration	14																																										
enumeration	18	documentation Staff																																									
enumeration	19	documentation Other causes related to the operational planning and management																																									
enumeration	20	documentation Signalling installations																																									
enumeration	21	documentation Signalling installations at level crossings																																									
enumeration	22	documentation Telecommunication installations																																									
enumeration	23	documentation Power supply equipment																																									
enumeration	24	documentation Track																																									
enumeration	25	documentation																																									

		Structures
enumeration	28	documentation
		Staff
enumeration	29	documentation
		Other causes related to infrastructure installations
enumeration	31	documentation
		Irregularities in execution of construction work
enumeration	30	documentation
		Planned construction work
enumeration	32	documentation
		Speed restrictions due to defective track
enumeration	39	documentation
		Other causes related to Civil engineering
enumeration	40	documentation
		Delay caused by next IM
enumeration	41	documentation
		Delay caused by previous IM
enumeration	50	documentation
		exceeding the stop time
enumeration	51	documentation
		Request of the RU
enumeration	52	documentation
		Loading operations
enumeration	53	documentation
		Loading irregularities
enumeration	54	documentation
		Commercial preparation of the train
enumeration	58	documentation
		Staff
enumeration	59	documentation
		Other causes related to commercial causes
enumeration	60	documentation
		Roster planning/re-rostering
enumeration	61	documentation
		Formation of trains by the RU
enumeration	62	documentation
		Problems affecting coaches
enumeration	63	documentation
		Problems affecting wagons
enumeration	64	documentation
		Problems affecting traction units
enumeration	68	documentation
		Staff
enumeration	69	documentation
		Other causes related to Rolling Stock
enumeration	70	documentation
		Delay caused by next RU
enumeration	71	documentation
		Delay caused by previous RU
enumeration	80	documentation
		Strike
enumeration	81	documentation
		Administrative formalites
enumeration	82	documentation
		Outside influence
enumeration	83	documentation
		Effects of weather and natural causes
enumeration	84	documentation
		Delay caused by external reasons on the next network
enumeration	89	documentation
		Other external causes
enumeration	90	documentation
		Dangerous incidents, accidents and hazards


	enumeration 91	documentation Track occupation caused by the lateness of the same train
	enumeration 92	documentation Track occupation caused by the lateness of another train
	enumeration 93	documentation Turn round
	enumeration 94	documentation Connection
	enumeration 95	documentation Further investigation needed
annotation	documentation	This element identifies the reason for a delay (modified DelayReason)
source	<pre><xs:element name="DelayCause" type="DelayCode"> <xs:annotation> <xs:documentation>This element identifies the reason for a delay (modified DelayReason)</xs:documentation> </xs:annotation> </xs:element></pre>	

element **DelayCauseTime**


diagram		
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3	
properties	content complex	
children	DelayCause DelayMinutes DelayEventDateTime InternalReferencelIdentifier DelayCodingDateTime Remarks	
used by	element DelayEventReport	
annotation	documentation Identifies the delay of a train due to a specified reason. In addition it allows to put in a more detailed description (Changed from DelayReasonTime)	
source	<pre><xs:element name="DelayCauseTime"> <xs:annotation> <xs:documentation>Identifies the delay of a train due to a specified reason. In addition it allows to put in a more detailed description (Changed from DelayReasonTime)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="DelayCause"> <xs:annotation> <xs:documentation>Describes the reason for a</pre>	

	<pre> delay</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="DelayMinutes"/> <xs:element ref="DelayEventDateTime"/> <xs:element ref="InternalReferenceIdentifier" minOccurs="0"> <xs:annotation> <xs:documentation>The link to the System Reference</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="DelayCodingDateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Date and Time of the ocding of the delay</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Remarks" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **DelayCodingDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element DelayCauseTime
annotation	documentation Date and Time of the coding of the delay
source	<pre> <xs:element name="DelayCodingDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date and Time of the coding of the delay</xs:documentation> </xs:annotation> </xs:element> </pre>

element **DelayEventDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element DelayCauseTime
annotation	documentation

	Date and Time of delay event
source	<pre><xs:element name="DelayEventDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date and Time of delay event </xs:documentation> </xs:annotation> </xs:element></pre>

element **DelayEventReport**

diagram	<pre> classDiagram class DelayEventReport { +DelayLocation +TrainLocationStatus +DelayCauseTime ..BookedLocationDateTime ..ReferencedLocationDateTime } DelayEventReport -- DelayLocation DelayEventReport -- TrainLocationStatus DelayEventReport -- DelayCauseTime DelayEventReport .. BookedLocationDateTime DelayEventReport .. ReferencedLocationDateTime </pre>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	DelayLocation TrainLocationStatus DelayCauseTime BookedLocationDateTime ReferencedLocationDateTime
used by	element TrainDelayCauseMessage
annotation	documentation Provides the detailed information about a single delay event (Replaced DelayReasonReport)
source	<pre><xs:element name="DelayEventReport"> <xs:annotation> <xs:documentation>Provides the detailed information about a single delay event (Replaced DelayReasonReport)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="DelayLocation"/> <xs:element ref="TrainLocationStatus"/> <xs:element ref="DelayCauseTime"/> <xs:element ref="BookedLocationDateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Scheduled Date and Time of a train at a specified location as defined in the path contract</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="ReferencedLocationDateTime" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **DelayLocation**

diagram	<p>The diagram shows a class DelayLocation (Location where the Delay occurred) which is a complex type containing four elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
used by	element DelayEventReport
annotation	documentation Location where the Delay occurred
source	<pre><xs:element name="DelayLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>Location where the Delay occurred</xs:documentation> </xs:annotation> </xs:element></pre>

element **DelayMinutes**

diagram	<p>The diagram shows a class DelayMinutes (Identifieis the delay (in minutes) of a train for a specified cause).</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	String1-5									
properties	content simple									
used by	element DelayCauseTime									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>5</td> <td></td> </tr> </table>	Kind	Value	Annotation	minLength	1		maxLength	5	
Kind	Value	Annotation								
minLength	1									
maxLength	5									
annotation	documentation Identifieis the delay (in minutes) of a train for a specified cause									
source	<pre><xs:element name="DelayMinutes" type="String1-5"> <xs:annotation> <xs:documentation>Identifieis the delay (in minutes) of a train for a specified cause</xs:documentation> </xs:annotation> </xs:element></pre>									


element **DeliveryAtDestination**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Destination DeliveryTimeAtDestination
used by	element WagonDeliveryNoticeMessage
annotation	documentation Place, Date and Time when the wagon is ready to be picked up by the customer
source	<pre> <xs:element name="DeliveryAtDestination"> <xs:annotation> <xs:documentation>Place, Date and Time when the wagon is ready to be picked up by the customer</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Destination"/> <xs:element ref="DeliveryTimeAtDestination"/> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **DeliveryReference**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	elements ITU Details Wagons/WagonDetails									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>30</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	30	
Kind	Value	Annotation								
minLength	1									
maxLength	30									
source	<pre> <xs:element name="DeliveryReference"> <xs:annotation/> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="30"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **DeliveryTimeAtDestination**

diagram	 <p>The actual Date and Time when the wagon is delivered to the customer siding or when the wagon is ready for pick-up by the customer</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element DeliveryAtDestination
annotation	documentation The actual Date and Time when the wagon is delivered to the customer siding or when the wagon is ready for pick-up by the customer
source	<pre><xs:element name="DeliveryTimeAtDestination" type="xs:dateTime"> <xs:annotation> <xs:documentation>The actual Date and Time when the wagon is delivered to the customer siding or when the wagon is ready for pick-up by the customer</xs:documentation> </xs:annotation> </xs:element></pre>

element **DeliveryTimeAtInterchange**

diagram	 <p>The scheduled departure date and time or the scheduled handover date and time of wagons at an interchange point, where the responsibility of the wagons will ch...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element NextIntermediateDestination
annotation	documentation The scheduled departure date and time or the scheduled handover date and time of wagons at an interchange point, where the responsibility of the wagons will change to another RU
source	<pre><xs:element name="DeliveryTimeAtInterchange" type="xs:dateTime"> <xs:annotation> <xs:documentation>The scheduled departure date and time or the scheduled handover date and time of wagons at an interchange point, where the responsibility of the wagons will change to another RU</xs:documentation> </xs:annotation> </xs:element></pre>

element **DepartureInterchangeReport**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location DepartureTimeAtLocation TrainID
used by	element WagonETI ETA Message
annotation	documentation Departure or interchange station ETI Origin
source	<pre> <xs:element name="DepartureInterchangeReport"> <xs:annotation> <xs:documentation>Departure or interchange station ETI Origin</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="DepartureTimeAtLocation"/> <xs:element ref="TrainID" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **DepartureJourneyTrack**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Indicates the track ID on which the train will start its journey.
source	<pre> <xs:element name="DepartureJourneyTrack" type="LocationIdent"> <xs:annotation> <xs:documentation>Indicates the track ID on which the train will start </pre>

	<pre> its journey.</xs:documentation> </xs:annotation> </xs:element> </pre>
--	---

element `DepartureTimeAtLocation`

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements DepartureInterchangeReport WagonAtDeparture WagonPickupAtOrigin YardDeparture
annotation	documentation the scheduled departure date and time at a defined location
source	<pre> <xs:element name="DepartureTimeAtLocation" type="xs:dateTime"> <xs:annotation> <xs:documentation>the scheduled departure date and time at a defined location</xs:documentation> </xs:annotation> </xs:element> </pre>

element `DepartureTrackAtLocation`

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Indicates the track ID on which the train runs. The track of the departure of a train at a reporting point. This is indicated in the LocationSubsidiaryCode in conjunction with the LocationPrimaryCode.
source	<pre> <xs:element name="DepartureTrackAtLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>Indicates the track ID on which the train runs. The track of the departure of a train at a reporting point. This is indicated in the LocationSubsidiaryCode in conjunction with the LocationPrimaryCode.</xs:documentation> </xs:annotation> </xs:element> </pre>

`</xs:element>`

element Destination


diagram	<p>The diagram illustrates the structure of the <code>Destination</code> element. It is a complex type containing a <code>LocationIdent</code> element. The <code>LocationIdent</code> element is further composed of four sub-elements: <code>CountryCodeISO</code> (Identifies a Country or State by code (ISO 316...)), <code>LocationPrimaryCode</code>, <code>PrimaryLocationName</code> (Location Name in an offication language of the Country using the ISO Unicode alph...), and <code>LocationSubsidiaryIdentification</code> (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
used by	elements ArrivalAtDestination WIMO Dataset/ConsignmentLevelData DeliveryAtDestination
annotation	documentation Destination Location
source	<pre><xs:element name="Destination" type="LocationIdent"> <xs:annotation> <xs:documentation>Destination Location</xs:documentation> </xs:annotation> </xs:element></pre>

element Dimensions


diagram	<p>The diagram illustrates the structure of the <code>Dimensions</code> element. It is a complex type containing four sub-elements: <code>LengthCode</code> (Length code according to UTC leaflet 592-2), <code>Length</code> (Length of I...), <code>Width</code> (Width of I...), and <code>Height</code> (Height of I...).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	LengthCode Length Width Height
used by	element ITU Details
annotation	documentation Dimensions of the UTI.
source	<pre><xs:element name="Dimensions"> <xs:annotation> <xs:documentation>Dimensions of the UTI.</xs:documentation> </xs:annotation> </xs:element></pre>

	<pre> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="LengthCode"> <xs:annotation> <xs:documentation>Length code according to UIC leaflet 592- 2</xs:documentation> <xs:documentation>CODE: UIC leaflet 592-2</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:totalDigits value="2"/> <xs:minInclusive value="10"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="Length" minOccurs="0"/> <xs:element ref="Width" minOccurs="0"/> <xs:element ref="Height" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---


element **Dimensions/LengthCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>10</td> <td></td> </tr> <tr> <td>totalDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	10		totalDigits	2	
Kind	Value	Annotation								
minInclusive	10									
totalDigits	2									
annotation	documentation Length code according to UIC leaflet 592-2 documentation CODE: UIC leaflet 592-2									
source	<pre> <xs:element name="LengthCode"> <xs:annotation> <xs:documentation>Length code according to UIC leaflet 592- 2</xs:documentation> <xs:documentation>CODE: UIC leaflet 592-2</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:totalDigits value="2"/> <xs:minInclusive value="10"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									


element **DwellTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:decimal
properties	content simple
used by	element TimingAtLocation
facets	Kind Value Annotation fractionDigits 1
annotation	documentation The minimum duration of dwell time expressed in minutes
source	<pre><xs:element name="DwellTime"> <xs:annotation> <xs:documentation>The minimum duration of dwell time expressed in minutes </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


element **eMail**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CommunicationRefID
properties	content simple
used by	elements AdministrativeContactInformation Customer/Contacts
facets	Kind Value Annotation minLength 1 maxLength 70
annotation	documentation Generic eMail address in Free text
source	<pre><xs:element name="eMail" type="CommunicationRefID"> <xs:annotation> <xs:documentation>Generic eMail address in Free text</xs:documentation> </xs:annotation> </xs:element></pre>


element **EmergencyBrakeOverride**

diagram	 Ability of the whole train (all wagons and traction units) to override the emergency brake signal
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element PlannedTrainTechnicalData
annotation	documentation Ability of the whole train (all wagons and traction units) to override the emergency brake signal
source	<pre><xs:element name="EmergencyBrakeOverride" type="xs:boolean"> <xs:annotation> <xs:documentation>Ability of the whole train (all wagons and traction units) to override the emergency brake signal</xs:documentation> </xs:annotation> </xs:element></pre>

element **EndDate**


diagram	 The end date/time in eff...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
annotation	documentation The end date/time in effect
source	<pre><xs:element name="EndDate" type="xs:date"> <xs:annotation> <xs:documentation>The end date/time in effect</xs:documentation> </xs:annotation> </xs:element></pre>

element **EndDateTime**


diagram	 The end date/time in eff...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements RequestedPeriod RequestedTimeframe ValidityPeriod
annotation	documentation The end date/time in effect
source	<pre><xs:element name="EndDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>The end date/time in effect</xs:documentation> </xs:annotation> </xs:element></pre>

```
</xs:element>
```

element **EndLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation End point of a section or segment
source	<pre><xs:element name="EndLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>End point of a section or segment</xs:documentation> </xs:annotation> </xs:element></pre>

element **ErrorMessage**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader MessageStatus AdministrativeContactInformation ErrorCauseReference Error

	PlannedTransportIdentifiers TransportOperationalIdentifiers
annotation	<p>documentation</p> <p>This message should be sent from the receiver to the sender after the processing of the previously sent TAF/TAP message in the backend (legacy) system of the receiver has failed.</p>
source	<pre> <xs:element name="ErrorMessage"> <xs:annotation> <xs:documentation>This message should be sent from the receiver to the sender after the processing of the previously sent TAF/TAP message in the backend (legacy) system of the receiver has failed.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"/> <xs:element ref="AdministrativeContactInformation"/> <xs:element name="ErrorCauseReference" minOccurs="0"> <xs:annotation> <xs:documentation>The reference to the message and its particular element(s) that caused the error is provided here</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageReference"/> <xs:element name="MessageSenderReference" type="FreeText" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> <xs:element name="Error" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element name="TagReference" type="xs:string" minOccurs="0"> <xs:annotation> <xs:documentation>This is a placeholder for XPath expression indicating the element of the original message which caused the error.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TypeOfError"> <xs:annotation> <xs:documentation>It is an enumerated type to indicate if the error was caused due to a bussines rule violation (1 = FUNCTIONAL) or due to a system failure (2 = TECHNICAL) or both (0 = BOTH)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> <xs:enumeration value="2"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Severity"> <xs:annotation> <xs:documentation>1 = WARNING 2 = FATAL 3 = SEVER 4 = SEVER- FATAL The senders and receivers should agree about the severity levels and </pre>

	<p>their interpretation: should the process stop, should the message be resent etc.</p> <pre> </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="1"/> <xs:enumeration value="2"/> <xs:enumeration value="3"/> <xs:enumeration value="4"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ErrorCode"> <xs:annotation> <xs:documentation>To be defined: code list from 1 to 9999. Proposal from PathDossierErrorCode: "Standard values are between 5000 and 6000 (central maintained list). The values greater than 6000 can be used on national level. "</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="FreeTextField"/> </xs:sequence> </xs:complexType> </xs:element> <xs:element ref="PlannedTransportIdentifiers" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="TransportOperationalIdentifiers" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **ErrorMessage/ErrorCauseReference**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	MessageReference MessageSenderReference
annotation	documentation The reference to the message and its particular element(s) that caused the error is provided here
source	<pre> <xs:element name="ErrorCauseReference" minOccurs="0"> <xs:annotation> <xs:documentation>The reference to the message and its particular </pre>

	<pre> element(s) that caused the error is provided here</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageReference"/> <xs:element name="MessageSenderReference" type="FreeText" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **ErrorMessage/ErrorMessageReference/MessageSenderReference**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 255
source	<code><xs:element name="MessageSenderReference" type="FreeText" minOccurs="0"/></code>


element **ErrorMessage/Error**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 1 maxOcc unbounded content complex


children	TagReference TypeOfError Severity ErrorCode FreeTextField
source	<pre> <xs:element name="Error" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element name="TagReference" type="xs:string" minOccurs="0"> <xs:annotation> <xs:documentation>This is a placeholder for XPath expression indicating the element of the original message which caused the error.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TypeOfError"> <xs:annotation> <xs:documentation>It is an enumerated type to indicate if the error was caused due to a bussines rule violation (1 = FUNCTIONAL) or due to a system failure (2 = TECHNICAL) or both (0 = BOTH)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> <xs:enumeration value="2"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Severity"> <xs:annotation> <xs:documentation>1 = WARNING 2 = FATAL 3 = SEVER 4 = SEVER-FATAL The senders and receivers should agree about the severity levels and their interpretation: should the process stop, should the message be resent etc.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="1"/> <xs:enumeration value="2"/> <xs:enumeration value="3"/> <xs:enumeration value="4"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ErrorCode"> <xs:annotation> <xs:documentation>To be defined: code list from 1 to 9999. Proposal from PathDossierErrorCode: "Standard values are between 5000 and 6000 (central maintained list). The values greater than 6000 can be used on national level. "</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="FreeTextField"/> </xs:sequence> </pre>

	<pre></xs:complexType> </xs:element></pre>
--	--

element **ErrorMessage/Error/TagReference**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:string
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation This is a placeholder for XPath expression indicating the element of the original message which caused the error.
source	<pre><xs:element name="TagReference" type="xs:string" minOccurs="0"> <xs:annotation> <xs:documentation>This is a placeholder for XPath expression indicating the element of the original message which caused the error.</xs:documentation> </xs:annotation> </xs:element></pre>

element **ErrorMessage/Error/TypeOfError**


diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:integer												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0		enumeration	1		enumeration	2	
Kind	Value	Annotation											
enumeration	0												
enumeration	1												
enumeration	2												
annotation	documentation It is an enumerated type to indicate if the error was caused due to a bussines rule violation (1 = FUNCTIONAL) or due to a system failure (2 = TECHNICAL) or both (0 = BOTH)												
source	<pre><xs:element name="TypeOfError"> <xs:annotation> <xs:documentation>It is an enumerated type to indicate if the error was caused due to a bussines rule violation (1 = FUNCTIONAL) or due to a system failure (2 = TECHNICAL) or both (0 = BOTH)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/></pre>												

	<pre> <xs:enumeration value="2"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **ErrorMessage/Error/Severity**


diagram	 <p>1 = WARNING 2 = FATAL 3 = SEVER 4 = SEVER-FATAL The senders and receivers should agree about the severity levels and their interpretation: should the process stop, should the me...</p>															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:integer															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2</td> <td></td> </tr> <tr> <td>enumeration</td> <td>3</td> <td></td> </tr> <tr> <td>enumeration</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1		enumeration	2		enumeration	3		enumeration	4	
Kind	Value	Annotation														
enumeration	1															
enumeration	2															
enumeration	3															
enumeration	4															
annotation	documentation 1 = WARNING 2 = FATAL 3 = SEVER 4 = SEVER-FATAL The senders and receivers should agree about the severity levels and their interpretation: should the process stop, should the message be resent etc.															
source	<pre> <xs:element name="Severity"> <xs:annotation> <xs:documentation>1 = WARNING 2 = FATAL 3 = SEVER 4 = SEVER-FATAL The senders and receivers should agree about the severity levels and their interpretation: should the process stop, should the message be resent etc.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="1"/> <xs:enumeration value="2"/> <xs:enumeration value="3"/> <xs:enumeration value="4"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>															

element **ErrorMessage/Error/ErrorCode**

diagram	 <p>To be defined: code list from 1 to 9999. Proposal from PathDossier/ErrorCodes Standard values are between 5000 and 6000 (central maintained list). The values greater than 6000 c...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer

properties	content simple
facets	Kind Value Annotation minInclusive 1 maxInclusive 9999
annotation	documentation To be defined: code list from 1 to 9999. Proposal from PathDossierErrorCode: "Standard values are between 5000 and 6000 (central maintained list). The values greater than 6000 can be used on national level. "
source	<pre><xs:element name="ErrorCode"> <xs:annotation> <xs:documentation>To be defined: code list from 1 to 9999. Proposal from PathDossierErrorCode: "Standard values are between 5000 and 6000 (central maintained list). The values greater than 6000 can be used on national level. "</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **EstimatedEndTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
source	<pre><xs:element name="EstimatedEndTime" type="xs:dateTime"/></pre>

element **ExceptionalGaugingCode**

diagram	 Acceptance agreement number, based on guidelines of IM_Part...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple
used by	element ExceptionalGaugingIdent
facets	Kind Value Annotation minLength 1 maxLength 24
annotation	documentation Acceptance agreement number, based on guidelines of IM_Partner
source	<pre><xs:element name="ExceptionalGaugingCode"> <xs:annotation> <xs:documentation>Acceptance agreement number, based on guidelines of IM_Partner</xs:documentation> </xs:annotation> </xs:element></pre>

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **ExceptionalGaugingIdent**

diagram	<p>Indicates that an exceptional Gauging is in the train or for the wagon</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	IM_Partner ExceptionalGaugingCode
used by	elements PlannedTrainData WagonOperationalData
annotation	documentation Indicates that an exceptional Gauging is in the train or for the wagon
source	<pre> <xs:element name="ExceptionalGaugingIdent"> <xs:annotation> <xs:documentation>Indicates that an exceptional Gauging is in the train or for the wagon </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="IM_Partner"/> <xs:element ref="ExceptionalGaugingCode"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ExceptionalGaugingInd**

diagram	<p>Indicates that an exceptional gauging is in the train or for the wagon - (true/false)</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element TrainRunningData
annotation	documentation Indicates that an exceptional gauging is in the train or for the wagon - (true/false)
source	<pre> <xs:element name="ExceptionalGaugingInd" type="xs:boolean"> </pre>

	<pre> <xs:annotation> <xs:documentation>Indicates that an exceptional gauging is in the train or for the wagon - (true/false)</xs:documentation> </xs:annotation> </xs:element> </pre>
--	--

element **ExceptionalGaugingProfile**

diagram	<p>ExceptionalGaugingProf... Identification of special load. Coding found in 404-2 chapter 4.9.1 (4AN + 3N)</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	element WagonOperationalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>7</td> <td></td> </tr> <tr> <td>maxLength</td> <td>7</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	7		maxLength	7	
Kind	Value	Annotation								
minLength	7									
maxLength	7									
annotation	documentation Identification of special load. Coding found in 404-2 chapter 4.9.1 (4AN + 3N)									
source	<pre> <xs:element name="ExceptionalGaugingProfile"> <xs:annotation> <xs:documentation>Identification of special load. Coding found in 404-2 chapter 4.9.1 (4AN + 3N)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="7"/> <xs:maxLength value="7"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ExceptionPoint**

diagram	<p>ExceptionPoi... Describes the interruption points with location and the time of the interruption</p> <p>Location Identifies a Location using a LocationIdent</p> <p>Responsible... RU Responsible for the physical operation of the train or wagon</p> <p>WagonLocationStat... identifies the status of a wagon, related to the actual time at a reporting ...</p> <p>ScheduledTimeAtLocation Scheduled Date and Time at a location related to the status of the train or wagon at the given loca...</p> <p>ExceptionTimeAtLocation The Date and Time when something unexpected happens during the transportation related to a location</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

properties	content complex
children	Location ResponsibleRU WagonLocationStatus ScheduledTimeAtLocation ExceptionTimeAtLocation
used by	element WagonExceptionReport
annotation	documentation Describes the interruption points with location and the time of the interruption
source	<pre><xs:element name="ExceptionPoint"> <xs:annotation> <xs:documentation>Describes the interruption points with location and the time of the interruption</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="ResponsibleRU"/> <xs:element ref="WagonLocationStatus"/> <xs:element ref="ScheduledTimeAtLocation"/> <xs:element ref="ExceptionTimeAtLocation"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **ExceptionReason**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	WagonInterruptionReason InterruptionDescription InterruptionType
used by	element WagonExceptionReport
annotation	documentation Identifies the reason of an unexpected interruption for a wagon during the transportation. In addition it allows to put in a more detailed description
source	<pre><xs:element name="ExceptionReason"> <xs:annotation> <xs:documentation>Identifies the reason of an unexpected interruption for a wagon during the transportation. In addition it allows to put in a more detailed description</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="WagonInterruptionReason" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="wagon damaged"/> <xs:enumeration value="change of route"/> <xs:enumeration value="other"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="InterruptionDescription"/> <xs:element ref="InterruptionType"/> </xs:sequence> </xs:complexType> </xs:element></pre>


```

</xs:simpleType>
</xs:element>
<xs:element ref="InterruptionDescription" minOccurs="0"/>
<xs:element name="InterruptionType" minOccurs="0">
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:length value="1"/>
      <xs:enumeration value="0">
        <xs:annotation>
          <xs:documentation>Damage does not cause an interruption of
transport run</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="1">
        <xs:annotation>
          <xs:documentation>Damage causes an interruption of transport
run</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="2">
        <xs:annotation>
          <xs:documentation>other (no damage)</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```


element **ExceptionReason/WagonInterruptionReason**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:token
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation enumeration wagon damaged enumeration change of route enumeration other
source	<pre> <xs:element name="WagonInterruptionReason" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="wagon damaged"/> <xs:enumeration value="change of route"/> <xs:enumeration value="other"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **ExceptionReason/InterruptionType**


diagram																
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:token															
properties	minOcc 0 maxOcc 1 content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>0</td> <td>documentation Damage does not cause an interruption of transport run</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation Damage causes an interruption of transport run</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation other (no damage)</td> </tr> </tbody> </table>	Kind	Value	Annotation	length	1		enumeration	0	documentation Damage does not cause an interruption of transport run	enumeration	1	documentation Damage causes an interruption of transport run	enumeration	2	documentation other (no damage)
Kind	Value	Annotation														
length	1															
enumeration	0	documentation Damage does not cause an interruption of transport run														
enumeration	1	documentation Damage causes an interruption of transport run														
enumeration	2	documentation other (no damage)														
source	<pre><xs:element name="InterruptionType" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:length value="1"/> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>Damage does not cause an interruption of transport run</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Damage causes an interruption of transport run</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>other (no damage)</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element></pre>															

element **ExceptionTimeAtLocation**


diagram	 <p>The Date and Time when something unexpected happens during the transportation related to a location</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element ExceptionPoint

annotation	documentation The Date and Time when something unexpected happens during the transportation related to a location
source	<pre><xs:element name="ExceptionTimeAtLocation" type="xs:dateTime"> <xs:annotation> <xs:documentation>The Date and Time when something unexpected happens during the transportation related to a location</xs:documentation> </xs:annotation> </xs:element></pre>


element **FaxNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CommunicationRefID									
properties	content simple									
used by	elements AdministrativeContactInformation Customer/Contacts									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>70</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	70	
Kind	Value	Annotation								
minLength	1									
maxLength	70									
annotation	documentation Generic Fax number in Free text									
source	<pre><xs:element name="FaxNumber" type="CommunicationRefID"> <xs:annotation> <xs:documentation>Generic Fax number in Free text</xs:documentation> </xs:annotation> </xs:element></pre>									

element **FerryPermittedFlag**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element RollingStockDataset/DesignDataSet
source	<pre><xs:element name="FerryPermittedFlag" type="xs:boolean"/></pre>

element **FreeTextField**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple

used by	elements AdministrativeContactInformation ErrorMessage/Error PathCanceledMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage PlannedJourneyLocation
	complexType TrainActivityType
facets	Kind Value Annotation minLength 1 maxLength 255
annotation	documentation Free Text
source	<pre><xs:element name="FreeTextField" type="FreeText"> <xs:annotation> <xs:documentation>Free Text</xs:documentation> </xs:annotation> </xs:element></pre>

element **FreightFlag**

diagram	 Identifies that the Entity or Location is for Freight Acti...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element LocationPrimaryInformation
annotation	documentation Identifies that the Entity or Location is for Freight Activity
source	<pre><xs:element name="FreightFlag" type="xs:boolean"> <xs:annotation> <xs:documentation>Identifies that the Entity or Location is for Freight Activity</xs:documentation> </xs:annotation> </xs:element></pre>

element **GeographicalCoordinates**

diagram	 Longitude and latitude as defined in UIC Leafle 920-2
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:string
properties	content simple
annotation	documentation Longitude and latitude as defined in UIC Leafle 920-2
source	<pre><xs:element name="GeographicalCoordinates" type="xs:string"> <xs:annotation> <xs:documentation>Longitude and latitude as defined in UIC Leafle 920- 2</xs:documentation> </xs:annotation> </xs:element></pre>

element **GeographicCoordinates**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>Latitude Longitude Altitude SRID</p>
<p>used by</p>	<p>elements GNSS DynamicPosition LocationPrimaryInformation LocationSubsidiaryInformation</p>
<p>annotation</p>	<p>documentation Latitude and Longitude of location</p>
<p>source</p>	<pre><xs:element name="GeographicCoordinates"> <xs:annotation> <xs:documentation>Latitude and Longitude of location</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Latitude"> <xs:annotation> <xs:documentation>SRID field has not been fulfilled, value of this field will be considered as in WGS84 norm</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Longitude"> <xs:annotation> <xs:documentation>If SRID field has not been fulfilled, value of this field will be considered as in WGS84 norm</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Altitude" minOccurs="0"/> <xs:element ref="SRID" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **GeoLocalisation**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>

properties	content complex
children	GNSS_DynamicPosition LocalisationPrecision
used by	element GeoLocalisationOnNetwork
annotation	documentation Geolocalisation that may be between two identified locations.
source	<pre> <xs:element name="GeoLocalisation"> <xs:annotation> <xs:documentation>Geolocalisation that may be between two identified locations. </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="GNSS_DynamicPosition"/> <xs:element name="LocalisationPrecision" type="xs:float" minOccurs="0"> <xs:annotation> <xs:documentation>Precision of the position. Expressed in metres.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **GeoLocalisation/LocalisationPrecision**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:float
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Precision of the position. Expressed in metres.
source	<pre> <xs:element name="LocalisationPrecision" type="xs:float" minOccurs="0"> <xs:annotation> <xs:documentation>Precision of the position. Expressed in metres.</xs:documentation> </xs:annotation> </xs:element> </pre>

element **GeoLocalisationOnNetwork**

diagram	
---------	---


namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	GeoLocalisation NetworkProjectedLocation
used by	element TrainLocationReport
annotation	documentation Geolocalisation information crossed with network data.
source	<pre> <xs:element name="GeoLocalisationOnNetwork"> <xs:annotation> <xs:documentation>Geolocalisation information crossed with network data. </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="GeoLocalisation" minOccurs="0"/> <xs:element ref="NetworkProjectedLocation" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **GNSS_DynamicPosition**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	GeographicCoordinates CurrentSpeed Heading AntennaDistanceFromFrontOfTrain
used by	element GeoLocalisation
source	<pre> <xs:element name="GNSS_DynamicPosition"> <xs:complexType> <xs:sequence> <xs:element ref="GeographicCoordinates"/> <xs:element name="CurrentSpeed" type="Speed" minOccurs="0"/> <xs:element name="Heading" type="xs:integer" minOccurs="0"> <xs:annotation> <xs:documentation>Direction towards which the train is going. Expressed in degrees from North (examples : 0 = North, 90 = South, 270 = West)</xs:documentation> </xs:annotation> </xs:element> <xs:element name="AntennaDistanceFromFrontOfTrain" type="xs:float" minOccurs="0"> <xs:annotation> </pre>

	<pre> <xs:documentation>Distance of GNSS antenna from the front of the train, in meters.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **GNSS_DynamicPosition/CurrentSpeed**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Speed
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minInclusive 001 maxInclusive 999
source	<pre><xs:element name="CurrentSpeed" type="Speed" minOccurs="0"/></pre>

element **GNSS_DynamicPosition/Heading**

diagram	 <p>Direction towards which the train is going. Expressed in degrees from North (examples : 0 = North, 90 = East, 180 = South, 270 = West)</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:integer
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Direction towards which the train is going. Expressed in degrees from North (examples : 0 = North, 90 = East, 180 = South, 270 = West)
source	<pre> <xs:element name="Heading" type="xs:integer" minOccurs="0"> <xs:annotation> <xs:documentation>Direction towards which the train is going. Expressed in degrees from North (examples : 0 = North, 90 = East, 180 = South, 270 = West)</xs:documentation> </xs:annotation> </xs:element> </pre>

element **GNSS_DynamicPosition/AntennaDistanceFromFrontOfTrain**

diagram	 <p>Distance of GNSS antenna from the front of the train, in meters.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	xs:float
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Distance of GNSS antenna from the front of the train, in meters.
source	<pre><xs:element name="AntennaDistanceFromFrontOfTrain" type="xs:float" minOccurs="0"> <xs:annotation> <xs:documentation>Distance of GNSS antenna from the front of the train, in meters.</xs:documentation> </xs:annotation> </xs:element></pre>

element **Goods**

diagram	<p>NoGoodsOfClass Element has to be filled with the class of the dangerous goods which are mentioned in Table 3.2 RID but are not dangerous according to chapter 2 (5.4.1.5 RID)</p> <p>RID The requirement (optional/mandatory) of the RID detail tags depend on the dangerous good and the regarding RID regulations. In contrast to the element "DangerousGoodsIndication" which only provides information to be provided to the IM according to chapter 1.4 RID, "RID" contains all information demanded in chapter 5.4 RID in order to provide all information use...</p> <p>Packing Packing informat...</p> <p>NHM_Code NHM code of the go...</p> <p>PreviousLoadedGoods</p> <p>GoodsDescription This element describes the goods of the shipment as free text</p> <p>AdditionalGoodInformation Additional information regarding the loaded good, given by the custo...</p> <p>GrossWeight Total weight of the goods either in a wagon or a transportation unit. It is the booked weight of the goods including packing</p> <p>HS_Code HS-Code for sensible goods (appendix 44c of cod) 10 digits are needed. If a good code was already assigned for 'Zollanmeldung'. In this case this good code has to be taken. These good codes m...</p> <p>EWC_Key Numeric key according to the European Waste Catal...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex

children	NoGoodsOfClassX RID Packing NHM Code PreviousLoadedGood GoodsDescription AdditionalGoodInformation GrossWeight HS Code EWC Key
used by	elements WIMO Dataset/ConsignmentLevelData ITU RollingRoadUnit Wagons
annotation	documentation Describes the goods inside the means of transport
source	<pre> <xs:element name="Goods"> <xs:annotation> <xs:documentation>Describes the goods inside the means of transport</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NoGoodsOfClassX" minOccurs="0"> <xs:annotation> <xs:documentation>Element has to be filled with the class of the dangerous goods which are mentioned in Table 3.2 RID but are not dangerous according to chapter 2 (5.4.1.5 RID)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="RID" minOccurs="0"/> <xs:element name="Packing" minOccurs="0"> <xs:annotation> <xs:documentation>Packing information</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NatureOfPacking" minOccurs="0"> <xs:annotation> <xs:documentation>Nature of packing according to the UN/ECE Recommandation No 21</xs:documentation> <xs:documentation>CODE: UN/ECE-Recommendation No. 21</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="2"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="NumberOfPackages" minOccurs="0"> <xs:annotation> <xs:documentation>Number of packages.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

</xs:element>
<xs:element name="PackageIdentification" minOccurs="0"
maxOccurs="99">
  <xs:annotation>
    <xs:documentation>Particular marks and numbers to identify
less than wagon load assignments.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:maxLength value="35"/>
      <xs:minLength value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="NHM_Code" minOccurs="0"/>
<xs:element name="PreviousLoadedGood" type="NHMCodeType"
minOccurs="0"/>
<xs:element ref="GoodsDescription" minOccurs="0"/>
<xs:element name="AdditionalGoodInformation" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Additional information regarding the loaded
good, given by the customer.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="350"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="GrossWeight"/>
<xs:element name="HS_Code" minOccurs="0">
  <xs:annotation>
    <xs:documentation>HS-Code for sensible goods (appendix 44c of
ccip) 10 digits are needed, if a good code was already assigned for
'Zollanmeldung'. In this case this good code has to be taken. These good
codes may have more than 6 digits.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="6"/>
      <xs:maxLength value="10"/>
      <xs:pattern value="\d*[1-9]\d*" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="EWC_Key" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Numeric key according to the European Waste
Catalogue</xs:documentation>
    <xs:documentation>CODE: European waste catalogue (EWC)
2000/532/EC</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">

```

	<pre> <xs:minLength value="2"/> <xs:maxLength value="6"/> <xs:pattern value="\d*" /> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **Goods/NoGoodsOfClassX**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	4	
Kind	Value	Annotation								
minLength	1									
maxLength	4									
annotation	documentation Element has to be filled with the class of the dangerous goods which are mentioned in Table 3.2 RID but are not dangerous according to chapter 2 (5.4.1.5 RID)									
source	<pre> <xs:element name="NoGoodsOfClassX" minOccurs="0"> <xs:annotation> <xs:documentation>Element has to be filled with the class of the dangerous goods which are mentioned in Table 3.2 RID but are not dangerous according to chapter 2 (5.4.1.5 RID)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Goods/Packing**


diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	NatureOfPacking NumberOfPackages PackageIdentification
annotation	documentation Packing information
source	<pre> <xs:element name="Packing" minOccurs="0"> <xs:annotation> <xs:documentation>Packing information</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NatureOfPacking" minOccurs="0"> <xs:annotation> <xs:documentation>Nature of packing according to the UN/ECE Recommmandation No 21</xs:documentation> <xs:documentation>CODE: UN/ECE-Recommendation No. 21</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="2"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="NumberOfPackages" minOccurs="0"> <xs:annotation> <xs:documentation>Number of packages.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="PackageIdentification" minOccurs="0" maxOccurs="99"> <xs:annotation> <xs:documentation>Particular marks and numbers to identify less than wagon load assignments.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **Goods/Packing/NatureOfPacking**

diagram	 Nature of packing according to the UN/ECE Recommendation No 21
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 2
annotation	documentation Nature of packing according to the UN/ECE Recommendation No 21 documentation CODE: UN/ECE-Recommendation No. 21
source	<pre><xs:element name="NatureOfPacking" minOccurs="0"> <xs:annotation> <xs:documentation>Nature of packing according to the UN/ECE Recommendation No 21</xs:documentation> <xs:documentation>CODE: UN/ECE-Recommendation No. 21</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="2"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Goods/Packing/NumberOfPackages**

diagram	 Number of packag...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minInclusive 1 maxInclusive 99999
annotation	documentation Number of packages.
source	<pre><xs:element name="NumberOfPackages" minOccurs="0"> <xs:annotation> <xs:documentation>Number of packages.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

	<pre> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---


element **Goods/Packing/PackageIdentification**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 99 content simple
facets	Kind Value Annotation minLength 1 maxLength 35
annotation	documentation Particular marks and numbers to identify less than wagon load assignments.
source	<pre> <xs:element name="PackageIdentification" minOccurs="0" maxOccurs="99"> <xs:annotation> <xs:documentation>Particular marks and numbers to identify less than wagon load assignments.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>


element **Goods/PreviousLoadedGood**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	NHMCodeType
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation length 6 pattern \d*[1-9]\d*
source	<pre> <xs:element name="PreviousLoadedGood" type="NHMCodeType" minOccurs="0"/> </pre>

element **Goods/AdditionalGoodInformation**

diagram	 Additional information regarding the loaded good, given by the custo...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 350
annotation	documentation Additional information regarding the loaded good, given by the customer.
source	<pre><xs:element name="AdditionalGoodInformation" minOccurs="0"> <xs:annotation> <xs:documentation>Additional information regarding the loaded good, given by the customer.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Goods/HS_Code**


diagram	 HS-Code for sensible goods (appendix 44c of ccip) 10 digits are needed, if a good code was already assigned for 'Zollanmeldung'. In this case this good code has to be taken. These good codes m...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 6 maxLength 10 pattern \d*[1-9]\d*
annotation	documentation HS-Code for sensible goods (appendix 44c of ccip) 10 digits are needed, if a good code was already assigned for 'Zollanmeldung'. In this case this good code has to be taken. These good codes may have more than 6 digits.
source	<pre><xs:element name="HS_Code" minOccurs="0"> <xs:annotation> <xs:documentation>HS-Code for sensible goods (appendix 44c of ccip) 10 digits are needed, if a good code was already assigned for 'Zollanmeldung'. In this case this good code has to be taken. These good codes may have more than 6 digits.</xs:documentation> </xs:annotation> </xs:element></pre>

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="6"/> <xs:maxLength value="10"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **Goods/EWC_Key**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:string												
properties	minOcc 0 maxOcc 1 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	6		pattern	\d*	
Kind	Value	Annotation											
minLength	2												
maxLength	6												
pattern	\d*												
annotation	documentation Numeric key according to the European Waste Catalogue documentation CODE: European waste catalogue (EWC) 2000/532/EC												
source	<pre> <xs:element name="EWC_Key" minOccurs="0"> <xs:annotation> <xs:documentation>Numeric key according to the European Waste Catalogue</xs:documentation> <xs:documentation>CODE: European waste catalogue (EWC) 2000/532/EC</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:maxLength value="6"/> <xs:pattern value="\d*" /> </xs:restriction> </xs:simpleType> </xs:element> </pre>												

element **GoodsDescription**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText

properties	content simple									
used by	element Goods									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation This element describes the goods of the shipment as free text									
source	<pre><xs:element name="GoodsDescription" type="FreeText"> <xs:annotation> <xs:documentation>This element describes the goods of the shipment as free text</xs:documentation> </xs:annotation> </xs:element></pre>									

element [GoodsInWagon](#)

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	NHM Code GrossWeight ContainerNumber GoodsInContainer
used by	element WagonInformation
annotation	documentation Goods
source	<pre><xs:element name="GoodsInWagon"> <xs:annotation> <xs:documentation>Goods</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="NHM_Code"/> <xs:element ref="GrossWeight" minOccurs="0"/> <xs:element name="ContainerNumber" type="EquipmentNumberType" minOccurs="0"/> <xs:element name="GoodsInContainer" minOccurs="0" maxOccurs="99"> <xs:complexType> <xs:sequence> <xs:element ref="NHM_Code" minOccurs="0"/> <xs:element ref="GrossWeight" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType></pre>

	<code></xs:element></code>
--	----------------------------------

element GoodsInWagon/ContainerNumber

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	EquipmentNumberType
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 13
source	<code><xs:element name="ContainerNumber" type="EquipmentNumberType" minOccurs="0"/></code>

element GoodsInWagon/GoodsInContainer

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 99 content complex
children	NHM Code GrossWeight
source	<code><xs:element name="GoodsInContainer" minOccurs="0" maxOccurs="99"> <xs:complexType> <xs:sequence> <xs:element ref="NHM_Code" minOccurs="0"/> <xs:element ref="GrossWeight" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></code>

element GrossWeight


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	WeightValueKilo
properties	content simple

used by	elements Goods GoodsInWagon/GoodsInContainer GoodsInWagon												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation Total weight of the goods either in a wagon or a transportation unit. It is the booked weight of the goods including packing												
source	<pre><xs:element name="GrossWeight" type="WeightValueKilo"> <xs:annotation> <xs:documentation>Total weight of the goods either in a wagon or a transportation unit. It is the booked weight of the goods including packing </xs:documentation> </xs:annotation> </xs:element></pre>												


element **HandBrake**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	HandBrakeType HandBrakedWeight ParkingBrakeForce
used by	element RollingStockDataset/DesignDataSet
source	<pre><xs:element name="HandBrake"> <xs:complexType> <xs:sequence> <xs:element ref="HandBrakeType"/> <xs:element name="HandBrakedWeight" minOccurs="0"> <xs:annotation> <xs:documentation>Braked weight of the hand brake in tons</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="4"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="ParkingBrakeForce" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **HandBrake/HandBrakedWeight**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:decimal
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation totalDigits 4 fractionDigits 1
annotation	documentation Braked weight of the hand brake in tons
source	<pre><xs:element name="HandBrakedWeight" minOccurs="0"> <xs:annotation> <xs:documentation>Braked weight of the hand brake in tons</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="4"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **HandlingInstruction**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple
facets	Kind Value Annotation minLength 1 maxLength 255
annotation	documentation Special instructions regarding the handling of the wagon or shipment in free text
source	<pre><xs:element name="HandlingInstruction" type="FreeText"> <xs:annotation> <xs:documentation>Special instructions regarding the handling of the wagon or shipment in free text</xs:documentation> </xs:annotation> </xs:element></pre>

element **HandoverPointFlag**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
used by	element LocationPrimaryInformation
annotation	documentation Identifies if the location is a Handover Point from IM to IM
source	<pre><xs:element name="HandoverPointFlag"> <xs:annotation> <xs:documentation>Identifies if the location is a Handover Point from IM to IM</xs:documentation> </xs:annotation> </xs:element></pre>

element **Height**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Value Measure
used by	element Dimensions complexType DimensionValue
annotation	documentation Height of ITU
source	<pre><xs:element name="Height"> <xs:annotation> <xs:documentation>Height of ITU</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Value"/> <xs:element ref="Measure"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **HighestPlannedSpeed**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Speed
properties	content simple

used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
annotation	documentation IM may inform the RA (Responsible applicant) on the speed which was the basis for path construction									
source	<pre><xs:element name="HighestPlannedSpeed" type="Speed"> <xs:annotation> <xs:documentation>IM may inform the RA (Responsible applicant) on the speed which was the basis for path construction</xs:documentation> </xs:annotation> </xs:element></pre>									


element **Identifiers**

diagram




namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	PlannedTransportIdentifiers RelatedPlannedTransportIdentifiers ReasonOfReference
used by	elements PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage ReceiptConfirmationMessage
source	<pre><xs:element name="Identifiers"> <xs:complexType> <xs:sequence> <xs:element ref="PlannedTransportIdentifiers" minOccurs="0" maxOccurs="unbounded"/> <xs:sequence minOccurs="0" maxOccurs="unbounded"> <xs:element ref="RelatedPlannedTransportIdentifiers"/> <xs:element ref="ReasonOfReference" minOccurs="0"/> </xs:sequence> </xs:sequence> </xs:complexType> </xs:element></pre>

element **IM_Partner**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	elements Wagons/WagonDetails/ExceptionalConsignment ExceptionalGaugingIdent												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Infrastructure Manager												
source	<pre><xs:element name="IM_Partner" type="CompanyCode"> <xs:annotation> <xs:documentation>Infrastructure Manager</xs:documentation> </xs:annotation> </xs:element></pre>												

element **ImpactedRU**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	CompanyCode						
properties	content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4	
Kind	Value	Annotation					
minLength	4						

	<p>maxLength 4</p> <p>pattern [0-9A-Z]{4}</p>
annotation	<p>documentation</p> <p>The RU impacted by a restriction</p>
source	<pre><xs:element name="ImpactedRU" type="CompanyCode"> <xs:annotation> <xs:documentation>The RU impacted by a restriction</xs:documentation> </xs:annotation> </xs:element></pre>

element **IntermediateDestination**


diagram	<p>The diagram shows the structure of the IntermediateDestination element. It is a complex type that contains four child elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location). The IntermediateDestination is described as "A location on the route of a tr...".</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
used by	element NextIntermediateDestination
annotation	<p>documentation</p> <p>A location on the route of a train</p>
source	<pre><xs:element name="IntermediateDestination" type="LocationIdent"> <xs:annotation> <xs:documentation>A location on the route of a train</xs:documentation> </xs:annotation> </xs:element></pre>

element **InternalReferencIdentifier**


diagram	<p>The diagram shows the InternalReferencIdentifier element as a simple type. Its description is "The link to the IM System Refer...".</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple
used by	elements DelayCauseTime InterruptionPoint/Interruption InterruptionInformation ReceiptConfirmationMessage TrainJourneyModificationMessage
facets	<p>Kind Value Annotation</p> <p>minLength 1</p> <p>maxLength 255</p>

annotation	documentation The link to the IM System Reference
source	<pre><xs:element name="InternalReferenceIdentifier" type="FreeText"> <xs:annotation> <xs:documentation>The link to the IM System Reference</xs:documentation> </xs:annotation> </xs:element></pre>

element **InterruptionDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements InterruptionPoint/Interruption InterruptionInformation
annotation	documentation Date and Time when the Train was interrupted
source	<pre><xs:element name="InterruptionDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date and Time when the Train was interrupted</xs:documentation> </xs:annotation> </xs:element></pre>

element **InterruptionDescription**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
used by	elements ChangeofTrackMessage ExceptionReason InterruptionPoint/Interruption InterruptionInformation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation The free text description of an interruption									
source	<pre><xs:element name="InterruptionDescription" type="FreeText"> <xs:annotation> <xs:documentation>The free text description of an interruption</xs:documentation> </xs:annotation> </xs:element></pre>									

element **InterruptionInformation**

<p>diagram</p>	<p>The main part of this complex element is Interruption Reason (Code list for Train Interruption): A list of codes that denote the reason why a path is no longer available by an IM e.g. Flooding Note: This list is the same as the Code List given by the IM during an interruption of a train during its operation. It is therefore a code that is reused during the interruption caused in planning. The other subelements help describing the interruption infor...</p> <ul style="list-style-type: none"> InterruptionDescription: The free text description of an interruption InterruptionDateTime: Date and Time when the Train was interrupted InterruptionReason: This element identifies the reason for an interruption of the train running InternalReferenceIdentifier: The link to the IM System Refer...
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>InterruptionDescription InterruptionDateTime InterruptionReason InternalReferenceIdentifier</p>
<p>used by</p>	<p>element PathNotAvailableMessage</p>
<p>annotation</p>	<p>documentation The main part of this complex element is Interruption Reason (Code list for Train Interruption): A list of codes that denote the reason why a path is no longer available by an IM e.g. Flooding Note: This list is the same as the Code List given by the IM during an interruption of a train during its operation. It is therefore a code that is reused during the interruption caused in planning. The other subelements help describing the interruption information more precisely.</p>
<p>source</p>	<pre><xs:element name="InterruptionInformation"> <xs:annotation> <xs:documentation>The main part of this complex element is Interruption Reason (Code list for Train Interruption): A list of codes that denote the reason why a path is no longer available by an IM e.g. Flooding Note: This list is the same as the Code List given by the IM during an interruption of a train during its operation. It is therefore a code that is reused during the interruption caused in planning. The other subelements help describing the interruption information more precisely.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="InterruptionDescription" minOccurs="0"/> <xs:element ref="InterruptionDateTime" minOccurs="0"/> <xs:element ref="InterruptionReason" minOccurs="0"/> <xs:element ref="InternalReferenceIdentifier" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **InterruptionPoint**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>Location DetailedDescriptionOfLocation Interruption BookedLocationDateTime ReferencedLocationDateTime InterruptionDuration Remarks</p>
<p>used by</p>	<p>element TrainRunningInterruptionMessage</p>
<p>annotation</p>	<p>documentation describes the interruption points with location and the reason for the interruption</p>
<p>source</p>	<pre><xs:element name="InterruptionPoint"> <xs:annotation> <xs:documentation>describes the interruption points with location and the reason for the interruption</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element name="DetailedDescriptionOfLocation" type="FreeText" minOccurs="0"/> <xs:element name="Interruption"> <xs:complexType> <xs:sequence> <xs:element ref="InterruptionReason" minOccurs="0"/> <xs:element ref="InterruptionDateTime"/> <xs:element ref="InterruptionDescription" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="InternalReferenceIdentifier" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> <xs:element ref="BookedLocationDateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Scheduled Date and Time of a train at a specified location as defined in the path contract</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="ReferencedLocationDateTime" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

```


<xs:element name="InterruptionDuration" minOccurs="0">
  <xs:annotation>
    <xs:documentation>To specify the probable duration of the
interruption</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="EarliestEndTime" type="xs:dateTime"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Forecasted earliest time for end of
interruption</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="LatestEndTime" type="xs:dateTime"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Forecasted latest time for end of
interruption</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:element ref="Remarks" minOccurs="0" maxOccurs="unbounded">
    <xs:annotation>
      <xs:documentation>To provide any additional information to the RU
or next IM (e.g. contact person, next steps, etc)</xs:documentation>
    </xs:annotation>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```


element **InterruptionPoint/DetailedDescriptionOfLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 255
source	<xs:element name="DetailedDescriptionOfLocation" type="FreeText" minOccurs="0"/>

element **InterruptionPoint/Interruption**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>InterruptionReason InterruptionDateTime InterruptionDescription InternalReferenceIdentifier</p>
<p>source</p>	<pre><xs:element name="Interruption"> <xs:complexType> <xs:sequence> <xs:element ref="InterruptionReason" minOccurs="0"/> <xs:element ref="InterruptionDateTime"/> <xs:element ref="InterruptionDescription" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="InternalReferenceIdentifier" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **InterruptionPoint/InterruptionDuration**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 1 content complex</p>
<p>children</p>	<p>EarliestEndDateTime LatestEndDateTime</p>
<p>annotation</p>	<p>documentation To specify the probable duration of the interruption</p>
<p>source</p>	<pre><xs:element name="InterruptionDuration" minOccurs="0"> <xs:annotation> <xs:documentation>To specify the probable duration of the interruption</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="EarliestEndDateTime" type="xs:dateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Forecasted earliest time for end of</pre>

	<pre> interruption</xs:documentation> </xs:annotation> </xs:element> <xs:element name="LatestEndDateTime" type="xs:dateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Forecasted latest time for end of interruption</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **InterruptionPoint/InterruptionDuration/EarliestEndDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Forecasted earliest time for end of interruption
source	<pre> <xs:element name="EarliestEndDateTime" type="xs:dateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Forecasted earliest time for end of interruption</xs:documentation> </xs:annotation> </xs:element> </pre>

element **InterruptionPoint/InterruptionDuration/LatestEndDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Forecasted latest time for end of interruption
source	<pre> <xs:element name="LatestEndDateTime" type="xs:dateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Forecasted latest time for end of interruption</xs:documentation> </xs:annotation> </xs:element> </pre>

element **InterruptionReason**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	DelayCode		
properties	content simple		
used by	elements ChangeofTrackMessage InterruptionPoint/Interruption InterruptionInformation		
facets	Kind	Value	Annotation
	enumeration	11	documentation Formation of trains if managed by infrastructure manager
	enumeration	10	documentation Timetable compilation
	enumeration	12	documentation Mistakes in operational procedures
	enumeration	13	documentation Wrong application of priority rules
	enumeration	14	
	enumeration	18	documentation Staff
	enumeration	19	documentation Other causes related to the operational planning and management
	enumeration	20	documentation Signalling installations
	enumeration	21	documentation Signalling installations at level crossings
	enumeration	22	documentation Telecommunication installations
	enumeration	23	documentation Power supply equipment
	enumeration	24	documentation Track
	enumeration	25	documentation Structures
	enumeration	28	documentation Staff
	enumeration	29	documentation Other causes related to infrastructure installations
	enumeration	31	documentation Irregularities in execution of construction work
	enumeration	30	documentation Planned construction work
	enumeration	32	documentation Speed restrictions due to defective track
	enumeration	39	documentation Other causes related to Civil engineering
	enumeration	40	documentation Delay caused by next IM
	enumeration	41	documentation Delay caused by previous IM
	enumeration	50	documentation exceeding the stop time
	enumeration	51	documentation Request of the RU
	enumeration	52	documentation Loading operations
	enumeration	53	documentation Loading irregularities
	enumeration	54	documentation

	enumeration 58	Commercial preparation of the train documentation Staff
	enumeration 59	documentation Other causes related to commercial causes
	enumeration 60	documentation Roster planning/re-rostering
	enumeration 61	documentation Formation of trains by the RU
	enumeration 62	documentation Problems affecting coaches
	enumeration 63	documentation Problems affecting wagons
	enumeration 64	documentation Problems affecting traction units
	enumeration 68	documentation Staff
	enumeration 69	documentation Other causes related to Rolling Stock
	enumeration 70	documentation Delay caused by next RU
	enumeration 71	documentation Delay caused by previous RU
	enumeration 80	documentation Strike
	enumeration 81	documentation Administrative formalites
	enumeration 82	documentation Outside influence
	enumeration 83	documentation Effects of weather and natural causes
	enumeration 84	documentation Delay caused by external reasons on the next network
	enumeration 89	documentation Other external causes
	enumeration 90	documentation Dangerous incidents, accidents and hazards
	enumeration 91	documentation Track occupation caused by the lateness of the same train
	enumeration 92	documentation Track occupation caused by the lateness of another train
	enumeration 93	documentation Turn round
	enumeration 94	documentation Connection
	enumeration 95	documentation Further investigation needed
annotation	documentation	This element identifies the reason for an interruption of the train running
source	<pre><xs:element name="InterruptionReason" type="DelayCode"> <xs:annotation> <xs:documentation>This element identifies the reason for an interruption of the train running</xs:documentation> </xs:annotation> </xs:element></pre>	

element ITU

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>ITU Details Goods SummaryOFGoodsWithSameRID</p>
<p>used by</p>	<p>element Wagons</p>
<p>annotation</p>	<p>documentation Describes the type and content of an IntermodalTransportUnit</p>
<p>source</p>	<pre> <xs:element name="ITU"> <xs:annotation> <xs:documentation>Describes the type and content of an IntermodalTransportUnit</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="ITU_Details"> <xs:annotation> <xs:documentation>Details for Intermodal Transport Unit on wagon</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Goods" maxOccurs="99"/> <xs:element ref="SummaryOFGoodsWithSameRID" minOccurs="0" maxOccurs="25"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ITU_Details**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>ITU_Type Number LoadingStatus ITU_TypeDetail Prefix Checkdigit Dimensions TareWeight SwapBodyCodification Forwarding Ship TurnInNumber DeliveryReference OriginCountry DepartureCountry UltimateDestinationCountry Seals ReferenceNumbers</p>
<p>used by</p>	<p>element ITU</p>
<p>annotation</p>	<p>documentation Details for ITU on wagon</p>
<p>source</p>	<pre><xs:element name="ITU_Details"> <xs:annotation> <xs:documentation>Details for ITU on wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="ITU_Type"> <xs:annotation> <xs:documentation>Type of Intermodal Transport Unit. Further information is given for each enumeration element.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

```

</xs:annotation>
</xs:element>
<xs:element name="Number">
  <xs:annotation>
    <xs:documentation>ITU number</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="EquipmentNumberType"/>
  </xs:simpleType>
</xs:element>
<xs:element ref="LoadingStatus"/>
<xs:element name="ITU_TypeDetail">
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value="BX"/>
      <xs:enumeration value="BK"/>
      <xs:enumeration value="FL"/>
      <xs:enumeration value="HT"/>
      <xs:enumeration value="HC"/>
      <xs:enumeration value="IN"/>
      <xs:enumeration value="OT"/>
      <xs:enumeration value="HH"/>
      <xs:enumeration value="PW"/>
      <xs:enumeration value="OS"/>
      <xs:enumeration value="RF"/>
      <xs:enumeration value="SD"/>
      <xs:enumeration value="SL"/>
      <xs:enumeration value="VE"/>
      <xs:enumeration value="TC"/>
      <xs:enumeration value="RH"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Prefix" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Prefix</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="5"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Checkdigit" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Check digit</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:int">
      <xs:totalDigits value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="Dimensions"/>
<xs:element name="TareWeight" type="WeightValueKilo">
  <xs:annotation>
    <xs:documentation>Tare weight [kg] of UTI.</xs:documentation>
  </xs:annotation>


```

```


</xs:annotation>
</xs:element>
<xs:element name="SwapBodyCodification" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Codification used for swap bodies according to
    UIC/UIRR regulations </xs:documentation>
    <xs:documentation>CODE:</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="3"/>
      <xs:maxLength value="4"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="Forwarding" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Final destination of the UTI.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:maxLength value="80"/>
      <xs:minLength value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="Ship" minOccurs="0">
  <xs:annotation/>
</xs:element>
<xs:element name="TurnInNumber" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Reference number used for empty containers in
    depots of shipping company.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:maxLength value="30"/>
      <xs:minLength value="1"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="DeliveryReference" minOccurs="0"/>
<xs:element ref="OriginCountry" minOccurs="0"/>
<xs:element name="DepartureCountry" type="CountryIdentISO"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Code of departure country of the
    UTI.</xs:documentation>
    <xs:documentation>CODE: ISO-3166-2</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="UltimateDestinationCountry" minOccurs="0"/>
<xs:element ref="Seals" minOccurs="0"/>
<xs:element ref="ReferenceNumbers" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```


element **ITU_Details/Number**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of EquipmentNumberType									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>13</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	13	
Kind	Value	Annotation								
minLength	1									
maxLength	13									
annotation	documentation ITU number									
source	<pre><xs:element name="Number"> <xs:annotation> <xs:documentation>ITU number</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="EquipmentNumberType"/> </xs:simpleType> </xs:element></pre>									

element **ITU_Details/ITU_TypeDetail**


diagram																																																				
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																			
type	restriction of xs:token																																																			
properties	content simple																																																			
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>BX</td><td></td></tr> <tr><td>enumeration</td><td>BK</td><td></td></tr> <tr><td>enumeration</td><td>FL</td><td></td></tr> <tr><td>enumeration</td><td>HT</td><td></td></tr> <tr><td>enumeration</td><td>HC</td><td></td></tr> <tr><td>enumeration</td><td>IN</td><td></td></tr> <tr><td>enumeration</td><td>OT</td><td></td></tr> <tr><td>enumeration</td><td>HH</td><td></td></tr> <tr><td>enumeration</td><td>PW</td><td></td></tr> <tr><td>enumeration</td><td>OS</td><td></td></tr> <tr><td>enumeration</td><td>RF</td><td></td></tr> <tr><td>enumeration</td><td>SD</td><td></td></tr> <tr><td>enumeration</td><td>SL</td><td></td></tr> <tr><td>enumeration</td><td>VE</td><td></td></tr> <tr><td>enumeration</td><td>TC</td><td></td></tr> <tr><td>enumeration</td><td>RH</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	BX		enumeration	BK		enumeration	FL		enumeration	HT		enumeration	HC		enumeration	IN		enumeration	OT		enumeration	HH		enumeration	PW		enumeration	OS		enumeration	RF		enumeration	SD		enumeration	SL		enumeration	VE		enumeration	TC		enumeration	RH	
Kind	Value	Annotation																																																		
enumeration	BX																																																			
enumeration	BK																																																			
enumeration	FL																																																			
enumeration	HT																																																			
enumeration	HC																																																			
enumeration	IN																																																			
enumeration	OT																																																			
enumeration	HH																																																			
enumeration	PW																																																			
enumeration	OS																																																			
enumeration	RF																																																			
enumeration	SD																																																			
enumeration	SL																																																			
enumeration	VE																																																			
enumeration	TC																																																			
enumeration	RH																																																			
source	<pre><xs:element name="ITU_TypeDetail"> <xs:simpleType></pre>																																																			

	<pre> <xs:restriction base="xs:token"> <xs:enumeration value="BX"/> <xs:enumeration value="BK"/> <xs:enumeration value="FL"/> <xs:enumeration value="HT"/> <xs:enumeration value="HC"/> <xs:enumeration value="IN"/> <xs:enumeration value="OT"/> <xs:enumeration value="HH"/> <xs:enumeration value="PW"/> <xs:enumeration value="OS"/> <xs:enumeration value="RF"/> <xs:enumeration value="SD"/> <xs:enumeration value="SL"/> <xs:enumeration value="VE"/> <xs:enumeration value="TC"/> <xs:enumeration value="RH"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **ITU_Details/Prefix**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 5
annotation	documentation Prefix
source	<pre> <xs:element name="Prefix" minOccurs="0"> <xs:annotation> <xs:documentation>Prefix</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **ITU_Details/Checkdigit**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	restriction of xs:int
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation totalDigits 1
annotation	documentation Check digit
source	<pre><xs:element name="Checkdigit" minOccurs="0"> <xs:annotation> <xs:documentation>Check digit</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:totalDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element ITU_Details/TareWeight


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	WeightValueKilo
properties	content simple
facets	Kind Value Annotation minInclusive 0 maxInclusive 999999 whiteSpace collapse
annotation	documentation Tare weight [kg] of UTI.
source	<pre><xs:element name="TareWeight" type="WeightValueKilo"> <xs:annotation> <xs:documentation>Tare weight [kg] of UTI.</xs:documentation> </xs:annotation> </xs:element></pre>

element ITU_Details/SwapBodyCodification


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 3

	maxLength 4
annotation	documentation Codification used for swap bodies according to UIC/UIRR regulations documentation CODE:
source	<pre> <xs:element name="SwapBodyCodification" minOccurs="0"> <xs:annotation> <xs:documentation>Codification used for swap bodies according to UIC/UIRR regulations </xs:documentation> <xs:documentation>CODE:</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="3"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element ITU_Details/Forwarding


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>80</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	80	
Kind	Value	Annotation								
minLength	1									
maxLength	80									
annotation	documentation Final destination of the UTI.									
source	<pre> <xs:element name="Forwarding" minOccurs="0"> <xs:annotation> <xs:documentation>Final destination of the UTI.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="80"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element ITU_Details/TurnInNumber

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 30
annotation	documentation Reference number used for empty containers in depots of shipping company.
source	<pre><xs:element name="TurnInNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Reference number used for empty containers in depots of shipping company.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="30"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ITU_Details/DepartureCountry**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CountryIdentISO
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 2 maxLength 2
annotation	documentation Code of departure country of the UTI. documentation CODE: ISO-3166-2
source	<pre><xs:element name="DepartureCountry" type="CountryIdentISO" minOccurs="0"> <xs:annotation> <xs:documentation>Code of departure country of the UTI.</xs:documentation> <xs:documentation>CODE: ISO-3166-2</xs:documentation> </xs:annotation> </xs:element></pre>

element **ITU_Type**

diagram	
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of EquipmentTypeType		
properties	content	simple	
used by	element	ITU_Details	
facets	Kind	Value	Annotation
	enumeration	cn	documentation Container
	enumeration	sw	documentation swap body
	enumeration	te	documentation Trailer (RollingRoad)
annotation	documentation Type of ITU. Further information is given for each enumeration element.		
source	<pre><xs:element name="ITU_Type"> <xs:annotation> <xs:documentation>Type of ITU. Further information is given for each enumeration element.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="EquipmentTypeType"/> </xs:simpleType> </xs:element></pre>		

element **JourneySection**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	JourneySectionOrigin JourneySectionDestination ResponsibilityActualSection ResponsibilityNextSection
used by	element TrainCompositionJourneySection
annotation	documentation Defines the data provided by the IM for a journey section
source	<pre><xs:element name="JourneySection"> <xs:annotation> <xs:documentation>Defines the data provided by the IM for a journey section</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="JourneySectionOrigin"/> <xs:element ref="JourneySectionDestination"/> <xs:element ref="ResponsibilityActualSection"/> <xs:element ref="ResponsibilityNextSection" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:annotation> <xs:documentation>Only optional for the last section</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **JourneySectionDestination**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification BookedLocationDateTime
used by	element JourneySection
annotation	documentation Destination of the section on which train composition is unchanged
source	<pre> <xs:element name="JourneySectionDestination"> <xs:annotation> <xs:documentation>Destination of the section on which train composition is unchanged</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"> <xs:sequence minOccurs="0"> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element> </pre>

element **JourneySectionOrigin**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>extension of LocationIdent</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification BookedLocationDateTime</p>
<p>used by</p>	<p>element JourneySection</p>
<p>annotation</p>	<p>documentation Origin of the section on which train composition is unchanged</p>
<p>source</p>	<pre><xs:element name="JourneySectionOrigin"> <xs:annotation> <xs:documentation>Origin of the section on which train composition is unchanged</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"> <xs:sequence minOccurs="0"> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> </xs:sequence> </xs:extension> </xs:complexContent> </xs:complexType> </xs:element></pre>

element **KeeperShortNameVKM**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>restriction of xs:string</p>
<p>properties</p>	<p>content simple</p>
<p>used by</p>	<p>elements RollingStockDataset/AdministrativeDataSet RollingStockDatasetMessage/RefusedWagonNumbers</p>

facets	Kind Value Annotation maxLength 10
annotation	documentation Free text, short name/vehicle keeper marking of the wagon keeper
source	<pre><xs:element name="KeeperShortNameVKM"> <xs:annotation> <xs:documentation>Free text, short name/vehicle keeper marking of the wagon keeper</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="10"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **LastModifiedDateTime**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation Date and Time of last update or modification of data
source	<pre><xs:element name="LastModifiedDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date and Time of last update or modification of data</xs:documentation> </xs:annotation> </xs:element></pre>

element **Latitude**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:float
properties	content simple
used by	element GeographicCoordinates
annotation	documentation Latitudinal Coordinates as expressed in decimal degrees with a precision of 6 decimals.
source	<pre><xs:element name="Latitude" type="xs:float"> <xs:annotation> <xs:documentation>Latitudinal Coordinates as expressed in decimal degrees with a precision of 6 decimals.</xs:documentation> </xs:annotation></pre>

	<code></xs:element></code>
--	----------------------------------


element LeadRU

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CompanyCode
properties	content simple
used by	elements PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage
facets	Kind Value Annotation minLength 4 maxLength 4 pattern [0-9A-Z]{4}
annotation	documentation Lead Railway Undertaking
source	<pre><xs:element name="LeadRU" type="CompanyCode"> <xs:annotation> <xs:documentation>Lead Railway Undertaking</xs:documentation> </xs:annotation> </xs:element></pre>


element Length

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Value Measure
used by	elements Dimensions TractionDetails complexType DimensionValue
annotation	documentation Length of ITU.
source	<pre><xs:element name="Length"> <xs:annotation> <xs:documentation>Length of ITU.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Value"/> <xs:element ref="Measure"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **LengthOfSetOfCarriages**

diagram	 <p>The calculated and rounded up maximum length of all wagons/coaches of the train (sum of all length over buffer of the wagons) expressed in metres. This is made optional together with TrainLength, but it could be implemented by applications as...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric4-4									
properties	content simple									
used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0001		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0001									
maxInclusive	9999									
annotation	documentation The calculated and rounded up maximum length of all wagons/coaches of the train (sum of all length over buffer of the wagons) expressed in metres. This is made optional together with TrainLength, but it could be implemented by applications as mandatory.									
source	<pre><xs:element name="LengthOfSetOfCarriages" type="Numeric4-4"> <xs:annotation> <xs:documentation>The calculated and rounded up maximum length of all wagons/coaches of the train (sum of all length over buffer of the wagons) expressed in metres. This is made optional together with TrainLength, but it could be implemented by applications as mandatory.</xs:documentation> </xs:annotation> </xs:element></pre>									

element **LengthOverBuffers**


diagram	 <p>Length over buffers is expressed in cm.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	elements RollingStockDataset/DesignDataSet WagonTechData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999999									
annotation	documentation Length over buffers is expressed in cm.									
source	<pre><xs:element name="LengthOverBuffers"> <xs:annotation> <xs:documentation>Length over buffers is expressed in cm.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

```


</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **LoadArea**

diagram	 Payload Area - measured in M2									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:decimal									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>5</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	5		fractionDigits	1	
Kind	Value	Annotation								
totalDigits	5									
fractionDigits	1									
annotation	documentation Payload Area - measured in M2									
source	<pre> <xs:element name="LoadArea"> <xs:annotation> <xs:documentation>Payload Area - measured in M2</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="5"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **LoadingCapacity**

diagram	 Usable Cube - measured in M3									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:decimal									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>5</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	5		fractionDigits	1	
Kind	Value	Annotation								
totalDigits	5									
fractionDigits	1									
annotation	documentation Usable Cube - measured in M3									
source	<pre> <xs:element name="LoadingCapacity"> <xs:annotation> <xs:documentation>Usable Cube - measured in M3</xs:documentation> </xs:annotation> <xs:simpleType> </pre>									

	<pre> <xs:restriction base="xs:decimal"> <xs:totalDigits value="5"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element LoadingFacility

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	CustomerNumber AdministrativeContactInformation
annotation	documentation Identifies the loading facility (in case of message type = ORU)
source	<pre> <xs:element name="LoadingFacility"> <xs:annotation> <xs:documentation>Identifies the loading facility (in case of message type = ORU)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="CustomerNumber" minOccurs="0"/> <xs:element ref="AdministrativeContactInformation"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element LoadingStatus

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	elements ITU Details RollingRoadUnit/RollingRoadUnitDetails Wagons/WagonDetails WagonInformation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0		enumeration	1	
Kind	Value	Annotation								
enumeration	0									
enumeration	1									
annotation	documentation Loading status of the equipment. 0=Empty, 1=Loaded									
source	<pre> <xs:element name="LoadingStatus"> <xs:annotation> </pre>									


	<pre> <xs:documentation>Loading status of the equipment. 0=Empty, 1=Loaded</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **LoadingTackles**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	LoadingTackleType Quantity TotalWeightLoadingTackles TypeDescription
used by	element Wagons
annotation	documentation Describes the loading tackles used inside the wagon
source	<pre> <xs:element name="LoadingTackles"> <xs:annotation> <xs:documentation>Describes the loading tackles used inside the wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="LoadingTackleType"> <xs:annotation> <xs:documentation>Loading tackle according toUN/EDIFACT Data Element 8053 UN/CEFACT Revision 2004B. Additional dummy code 'ZZZ' may be used in case the loading tackle is not included in the list. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"/> </xs:simpleType> </xs:element> <xs:element ref="Quantity"/> <xs:element name="TotalWeightLoadingTackles" type="WeightValueKilo"> <xs:annotation> </pre>

	<pre> <xs:documentation>Total weight of the loading tackles (kg) of the specified type</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TypeDescription" minOccurs="0"> <xs:annotation> <xs:documentation>Description of loading tackle, which is not included in the UN/EDIFACT 8053 list.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **LoadingTackles/LoadingTackleType**


diagram	 <p>Loading tackle according to UN/EDIFACT Data Element 8053 UN/CEFACT Revision 2004B. Additional dummy code 'ZZZ' may be used in case the loading tackle is not included in th...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple
annotation	documentation Loading tackle according to UN/EDIFACT Data Element 8053 UN/CEFACT Revision 2004B. Additional dummy code 'ZZZ' may be used in case the loading tackle is not included in the list.
source	<pre> <xs:element name="LoadingTackleType"> <xs:annotation> <xs:documentation>Loading tackle according to UN/EDIFACT Data Element 8053 UN/CEFACT Revision 2004B. Additional dummy code 'ZZZ' may be used in case the loading tackle is not included in the list. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"/> </xs:simpleType> </xs:element> </pre>

element **LoadingTackles/TotalWeightLoadingTackles**

diagram	 <p>Total weight of the loading tackles (kg) of the specified type</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	WeightValueKilo

properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation Total weight of the loading tackles (kg) of the specified type												
source	<pre><xs:element name="TotalWeightLoadingTackles" type="WeightValueKilo"> <xs:annotation> <xs:documentation>Total weight of the loading tackles (kg) of the specified type</xs:documentation> </xs:annotation> </xs:element></pre>												

element **LoadingTackles/TypeDescription**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Description of loading tackle, which is not included in the UN/EDIFACT 8053 list.									
source	<pre><xs:element name="TypeDescription" minOccurs="0"> <xs:annotation> <xs:documentation>Description of loading tackle, which is not included in the UN/EDIFACT 8053 list.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="35"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Location**


<p>diagram</p>	<p>The diagram shows a class Location with the description "Identifies a Location using a LocationIdent". It has a composition relationship with a complex type LocationIdent. The LocationIdent complex type contains four elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>LocationIdent</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification</p>
<p>used by</p>	<p>elements AffectedLocation ArrivalInterchangeReport ConsignmentOrderMessage/COMS/COM/CustomsProcedures DepartureInterchangeReport ExceptionPoint InterruptionPoint LocationModified ProductionStation SpecialTreatments TrainForecastAtReportingLocationMessage TrainLocationReport WagonAtDeparture WagonEventInformation WagonPickupAtOrigin YardArrival YardDeparture</p>
<p>annotation</p>	<p>documentation Identifies a Location using a LocationIdent</p>
<p>source</p>	<pre><xs:element name="Location" type="LocationIdent"> <xs:annotation> <xs:documentation>Identifies a Location using a LocationIdent</xs:documentation> </xs:annotation> </xs:element></pre>

element **LocationActualTrack**


<p>diagram</p>	<p>The diagram shows a class LocationActualTrack with the description "Identifies a Location using a LocationIdent". It has a composition relationship with a complex type LocationIdent. The LocationIdent complex type contains four elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>LocationIdent</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification</p>
<p>used by</p>	<p>element ChangeofTrackMessage</p>

source	<code><xs:element name="LocationActualTrack" type="LocationIdent"/></code>
--------	--

element LocationDateTime

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements AffectedLocation TrainAtLocation TrainLocationReport
annotation	documentation Identifies the actual or forecasted Date / Time at a specific reporting point
source	<pre><xs:element name="LocationDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Identifies the actual or forecasted Date / Time at a specific reporting point</xs:documentation> </xs:annotation> </xs:element></pre>

element LocationFileDatasetMessage

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader MessageStatus CountryCodeISO LocationPrimaryCode LocationPrimaryInformation LocationSubsidiaryInformation
annotation	documentation Used to Create, Modify or Update the LocationIdent Reference File
source	<pre><xs:element name="LocationFileDatasetMessage"> <xs:annotation> <xs:documentation> Used to Create, Modify or Update the LocationIdent Reference File</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence></pre>

	<pre> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"/> <xs:element ref="CountryCodeISO"/> <xs:element ref="LocationPrimaryCode"/> <xs:choice> <xs:element ref="LocationPrimaryInformation"/> <xs:element ref="LocationSubsidiaryInformation"/> </xs:choice> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **LocationModified**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location ModificationStatusIndicator TrainLocationStatus BookedLocationDateTime
used by	element TrainJourneyModification
annotation	documentation This element shows the Location that has been changed for the train run
source	<pre> <xs:element name="LocationModified"> <xs:annotation> <xs:documentation>This element shows the Location that has been changed for the train run </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="ModificationStatusIndicator"/> <xs:element ref="TrainLocationStatus" minOccurs="0"/> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **LocationPlannedTrack**

diagram	<p>The diagram shows the structure of the LocationPlannedTrack element. It contains a LocationIdent complex type. LocationIdent is composed of four child elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
used by	element ChangeofTrackMessage
source	<code><xs:element name="LocationPlannedTrack" type="LocationIdent"/></code>

element **LocationPrimaryCode**

diagram	<p>The diagram shows the LocationPrimaryCode element as a simple numeric type.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric1-5
properties	content simple
used by	element LocationFileDatasetMessage complexType LocationIdent
facets	Kind Value Annotation minInclusive 1 maxInclusive 99999
source	<code><xs:element name="LocationPrimaryCode" type="Numeric1-5"/></code>

element **LocationPrimaryInformation**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>LocationPrimaryName ResponsibleIM PrimaryLocationNameASCII ValidityPeriod ContainerHandlingFlag HandoverPointFlag FreightFlag PassengerFlag GeographicCoordinates NUTS Code Comments</p>
<p>used by</p>	<p>element LocationFileDatasetMessage</p>
<p>annotation</p>	<p>documentation Required for Primary Location Add, Update, of a Location Primary Code</p>
<p>source</p>	<pre><xs:element name="LocationPrimaryInformation"> <xs:annotation> <xs:documentation>Required for Primary Location Add, Update, of a Location Primary Code</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LocationPrimaryName"/> <xs:element ref="ResponsibleIM"/> <xs:element name="PrimaryLocationNameASCII"> <xs:annotation></pre>

```

<xs:documentation>the location name in free text, using ASCII
character set</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element ref="ValidityPeriod"/>
<xs:element ref="ContainerHandlingFlag" minOccurs="0"/>
<xs:element ref="HandoverPointFlag" minOccurs="0"/>
<xs:sequence minOccurs="0">
  <xs:element ref="FreightFlag"/>
  <xs:element ref="ValidityPeriod" minOccurs="0"/>
</xs:sequence>
<xs:sequence minOccurs="0">
  <xs:element ref="PassengerFlag"/>
  <xs:element ref="ValidityPeriod" minOccurs="0"/>
</xs:sequence>
<xs:element ref="GeographicCoordinates" minOccurs="0"/>
<xs:element name="NUTS_Code" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Nomenclature for Territorial Units for
Statistics. A NUTS code begins with a two-letter code referencing the
country, which is identical to the ISO 3166-1 alpha-2 code
</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="50"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="Comments" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>


```

element **LocationPrimaryInformation/PrimaryLocationNameASCII**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation the location name in free text, using ASCII character set									

source	<pre> <xs:element name="PrimaryLocationNameASCII"> <xs:annotation> <xs:documentation>the location name in free text, using ASCII character set</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="255"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--------	--

element **LocationPrimaryInformation/NUTS_Code**

diagram	 <p>NUTS_Code</p> <p>Nomenclature for Territorial Units for Statistics. A NUTS code begins with a two-letter code referencing the country, which is identical to the ISO 3166-1 alpha-2 code</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>50</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	50	
Kind	Value	Annotation								
minLength	1									
maxLength	50									
annotation	documentation Nomenclature for Territorial Units for Statistics. A NUTS code begins with a two-letter code referencing the country, which is identical to the ISO 3166-1 alpha-2 code									
source	<pre> <xs:element name="NUTS_Code" minOccurs="0"> <xs:annotation> <xs:documentation>Nomenclature for Territorial Units for Statistics. A NUTS code begins with a two-letter code referencing the country, which is identical to the ISO 3166-1 alpha-2 code </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="50"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **LocationPrimaryName**


diagram	 <p>LocationPrimaryName</p> <p>Location Name in an offication language of the Country using the ISO Unicode alph...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
used by	element LocationPrimaryInformation

annotation	documentation Location Name in an offication language of the Country using the ISO Unicode alphabet
source	<pre><xs:element name="LocationPrimaryName"> <xs:annotation> <xs:documentation>Location Name in an offication language of the Country using the ISO Unicode alphabet</xs:documentation> </xs:annotation> </xs:element></pre>


element **LocationSubsidiaryCode**

diagram	<p>this element identifies a location as a part of primary location e.g. a junction, a signal, a passing loop etc., It is unique when used in combination with a "LocationPrimaryCode"</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	extension of String1-10												
properties	content complex												
used by	elements LocationSubsidiaryIdentification LocationSubsidiaryInformation												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>10</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	10				
Kind	Value	Annotation											
minLength	1												
maxLength	10												
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>LocationSubsidiaryTypeCode</td> <td>derived by: xs:token</td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	LocationSubsidiaryTypeCode	derived by: xs:token	required			
Name	Type	Use	Default	Fixed	Annotation								
LocationSubsidiaryTypeCode	derived by: xs:token	required											
annotation	documentation this element identifies a location as a part of primary location e.g. a junction, a signal, a passing loop etc., It is unique when used in combination with a "LocationPrimaryCode"												
source	<pre><xs:element name="LocationSubsidiaryCode"> <xs:annotation> <xs:documentation>this element identifies a location as a part of primary location e.g. a junction, a signal, a passing loop etc., It is unique when used in combination with a "LocationPrimaryCode"</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="String1-10"> <xs:attribute ref="LocationSubsidiaryTypeCode" use="required"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>												

element **LocationSubsidiaryIdentification**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>LocationSubsidiaryCode AllocationCompany LocationSubsidiaryName</p>
<p>used by</p>	<p>complexType LocationIdent</p>
<p>annotation</p>	<p>documentation Code, Name and allocation company of Subsidiary Location</p>
<p>source</p>	<pre><xs:element name="LocationSubsidiaryIdentification"> <xs:annotation> <xs:documentation>Code, Name and allocation company of Subsidiary Location</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LocationSubsidiaryCode"/> <xs:element ref="AllocationCompany"/> <xs:element ref="LocationSubsidiaryName" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **LocationSubsidiaryInformation**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>

children	LocationSubsidiaryCode LocationSubsidiaryName AllocationCompany ValidityPeriod Comments GeographicCoordinates
used by	element LocationFileDatasetMessage
annotation	documentation Required for Add, Update of a Location Subsidiary Code (modified to global element)
source	<pre><xs:element name="LocationSubsidiaryInformation"> <xs:annotation> <xs:documentation>Required for Add, Update of a Location Subsidiary Code (modified to global element)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LocationSubsidiaryCode"/> <xs:element ref="LocationSubsidiaryName"/> <xs:element ref="AllocationCompany"/> <xs:element ref="ValidityPeriod"/> <xs:element ref="Comments" minOccurs="0"/> <xs:element ref="GeographicCoordinates" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **LocationSubsidiaryName**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
used by	elements LocationSubsidiaryIdentification LocationSubsidiaryInformation									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation To be completed in an official language of the Country using the ISO Unicode alphabet									
source	<pre><xs:element name="LocationSubsidiaryName" type="FreeText"> <xs:annotation> <xs:documentation>To be completed in an official language of the Country using the ISO Unicode alphabet</xs:documentation> </xs:annotation> </xs:element></pre>									

element **LocoNumber**

diagram	
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	element TrainCompositionJourneySection/LocIdent									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> </table>	Kind	Value	Annotation	minLength	4		maxLength	12	
Kind	Value	Annotation								
minLength	4									
maxLength	12									
annotation	documentation Identifies the number of the locomotive, usually the European Vehicle Number on 12N. It is currently not restricted only to numeric values.									
source	<pre><xs:element name="LocoNumber"> <xs:annotation> <xs:documentation>Identifies the number of the locomotive, usually the European Vehicle Number on 12N. It is currently not restricted only to numeric values.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="12"/> <xs:minLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **LocoTypeNumber**

diagram	<p>The diagram illustrates the structure of the LocoTypeNumber element. It is a composite identifier for loco types and locomotives, consisting of six parts: TypeCode1, TypeCode2, CountryCode, SeriesNumber, SerialNumber, and ControlDigit. Each part is described as follows:</p> <ul style="list-style-type: none"> TypeCode1: Value is 9 as it's written in Part 0 of the Appendix 6 of the decision 2007/756 TypeCode2: Type of tractive rolling stock as in Part 8 of the Appendix 6 of the decision 2007/756 CountryCode: Numerical country code as in Part 4 of the Appendix 6 of the decision 2007/756 SeriesNumber: 4 digits representing the type according to the country rules and based on the national vehicle register of the country indicated with the CountryCode SerialNumber: Three digits representing the serial number of the traction of the series. Optionally used in Planning to identify the subseries. Composite identifier should be unique with the series number wit... ControlDigit: 1 control digit as usual at the end of the 12 digit UIC identifier. Not used in Planning <p>Composite identifier for the loco types and locomotives. First four elements identify the series of the loco, rest can identify the exact individ...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TypeCode1 TypeCode2 CountryCode SeriesNumber SerialNumber ControlDigit


used by	elements TrainCompositionJourneySection/Locoldent TractionDetails
annotation	documentation Composite identifier for the loco types and locomotives. First four elements identify the series of the loco, rest can identify the exact individual locomotive
source	<pre> <xs:element name="LocoTypeNumber"> <xs:annotation> <xs:documentation>Composite identifier for the loco types and locomotives. First four elements identify the series of the loco, rest can identify the exact individual locomotive</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="TypeCode1"> <xs:annotation> <xs:documentation>Value is 9 as it's written in Part 0 of the Appendix 6 of the decision 2007/756</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="1"/> <xs:pattern value="[9]"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="TypeCode2"> <xs:annotation> <xs:documentation>Type of tractive rolling stock as in Part 8 of the Appendix 6 of the decision 2007/756</xs:documentation> </xs:annotation> <!--In PCS the following types are differentiated: Eletric, Diesel, Steam, Hybrid:--> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="1"/> <xs:pattern value="[0-9]"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="CountryCode"> <xs:annotation> <xs:documentation>Numerical country code as in Part 4 of the Appendix 6 of the decision 2007/756</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="2"/> <xs:pattern value="[0-9]{2}"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```


    <xs:annotation>
      <xs:documentation>4 digits representing the type according to the
country rules and based on the national vehicle register of the country
indicated with the CountryCode</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="4"/>
        <xs:whiteSpace value="replace"/>
        <xs:maxLength value="4"/>
        <xs:pattern value="[0-9]{4}"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="SerialNumber" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Three digits representing the serial number of
the traction of the series. Optionally used in Planning to identify the
subseries. Composite identifier should be unique with the series number
within a country.</xs:documentation>
    </xs:annotation>
    <!--Not necessary for Planning. Composite identifier should be
unique with the series number inside one country:-->
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="3"/>
        <xs:whiteSpace value="replace"/>
        <xs:maxLength value="3"/>
        <xs:pattern value="[0-9]{3}"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="ControlDigit" minOccurs="0">
    <xs:annotation>
      <xs:documentation>1 control digit as usual at the end of the 12
digit UIC identifier. Not used in Planning</xs:documentation>
    </xs:annotation>
    <!--Not necessary for Planning. Composite identifier should be
unique with the series number inside one country:-->
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:whiteSpace value="replace"/>
        <xs:maxLength value="1"/>
        <xs:pattern value="[0-9]"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **LocoTypeNumber/TypeCode1**

diagram	 Value is 9 as it's written in Part 0 of the Appendix 6 of the decision 2007/756															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>1</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>replace</td> <td></td> </tr> <tr> <td>pattern</td> <td>[9]</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	1		whiteSpace	replace		pattern	[9]	
Kind	Value	Annotation														
minLength	1															
maxLength	1															
whiteSpace	replace															
pattern	[9]															
annotation	documentation Value is 9 as it's written in Part 0 of the Appendix 6 of the decision 2007/756															
source	<pre><xs:element name="TypeCode1"> <xs:annotation> <xs:documentation>Value is 9 as it's written in Part 0 of the Appendix 6 of the decision 2007/756</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="1"/> <xs:pattern value="[9]"/> </xs:restriction> </xs:simpleType> </xs:element></pre>															

element **LocoTypeNumber/TypeCode2**


diagram	 Type of tractive rolling stock as in Part 8 of the Appendix 6 of the decision 2007/756															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>1</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>replace</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	1		whiteSpace	replace		pattern	[0-9]	
Kind	Value	Annotation														
minLength	1															
maxLength	1															
whiteSpace	replace															
pattern	[0-9]															
annotation	documentation Type of tractive rolling stock as in Part 8 of the Appendix 6 of the decision 2007/756															
source	<pre><xs:element name="TypeCode2"> <xs:annotation> <xs:documentation>Type of tractive rolling stock as in Part 8 of the Appendix 6 of the decision 2007/756</xs:documentation> </xs:annotation> <!--In PCS the following types are differentiated: Eletric, Diesel, Steam,</pre>															

	<pre> Hybrid:--> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="1"/> <xs:pattern value="[0-9]"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **LocoTypeNumber/CountryCode**


diagram	 <p>Numerical country code as in Part 4 of the Appendix 6 of the decision 2007/756</p>															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>replace</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{2}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2		whiteSpace	replace		pattern	[0-9]{2}	
Kind	Value	Annotation														
minLength	2															
maxLength	2															
whiteSpace	replace															
pattern	[0-9]{2}															
annotation	documentation Numerical country code as in Part 4 of the Appendix 6 of the decision 2007/756															
source	<pre> <xs:element name="CountryCode"> <xs:annotation> <xs:documentation>Numerical country code as in Part 4 of the Appendix 6 of the decision 2007/756</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="2"/> <xs:pattern value="[0-9]{2}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>															

element **LocoTypeNumber/SeriesNumber**

diagram	 <p>4 digits representing the type according to the country rules and based on the national vehicle register of the country indicated with the CountryCode</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string


properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>replace</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		whiteSpace	replace		pattern	[0-9]{4}	
Kind	Value	Annotation														
minLength	4															
maxLength	4															
whiteSpace	replace															
pattern	[0-9]{4}															
annotation	<p>documentation</p> <p>4 digits representing the type according to the country rules and based on the national vehicle register of the country indicated with the CountryCode</p>															
source	<pre><xs:element name="SeriesNumber"> <xs:annotation> <xs:documentation>4 digits representing the type according to the country rules and based on the national vehicle register of the country indicated with the CountryCode</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="4"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="4"/> <xs:pattern value="[0-9]{4}"/> </xs:restriction> </xs:simpleType> </xs:element></pre>															

element **LocoTypeNumber/SerialNumber**

diagram	 <p>Three digits representing the serial number of the traction of the series. Optionally used in Planning to identify the subseries. Composite identifier should be unique with the series number wit...</p>															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple									
minOcc	0															
maxOcc	1															
content	simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>3</td> <td></td> </tr> <tr> <td>maxLength</td> <td>3</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>replace</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{3}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	3		maxLength	3		whiteSpace	replace		pattern	[0-9]{3}	
Kind	Value	Annotation														
minLength	3															
maxLength	3															
whiteSpace	replace															
pattern	[0-9]{3}															
annotation	<p>documentation</p> <p>Three digits representing the serial number of the traction of the series. Optionally used in Planning to identify the subseries. Composite identifier should be unique with the series number within a country.</p>															
source	<pre><xs:element name="SerialNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Three digits representing the serial number of the traction of the series. Optionally used in Planning to identify the subseries. Composite identifier should be unique with the series number within a country.</xs:documentation> </xs:annotation></pre>															

	<pre> <!--Not necessary for Planning. Composite identifier should be unique with the series number inside one country:--> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="3"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="3"/> <xs:pattern value="[0-9]{3}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **LocoTypeNumber/ControlDigit**


diagram																
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:string															
properties	minOcc 0 maxOcc 1 content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>1</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>replace</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	1		whiteSpace	replace		pattern	[0-9]	
Kind	Value	Annotation														
minLength	1															
maxLength	1															
whiteSpace	replace															
pattern	[0-9]															
annotation	documentation 1 control digit as usual at the end of the 12 digit UIC identifier. Not used in Planning															
source	<pre> <xs:element name="ControlDigit" minOccurs="0"> <xs:annotation> <xs:documentation>1 control digit as usual at the end of the 12 digit UIC identifier. Not used in Planning</xs:documentation> </xs:annotation> <!--Not necessary for Planning. Composite identifier should be unique with the series number inside one country:--> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:whiteSpace value="replace"/> <xs:maxLength value="1"/> <xs:pattern value="[0-9]"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>															

element **Longitude**


diagram	
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:float
properties	content simple
used by	element GeographicCoordinates
annotation	documentation Longitudinal Coordinates as expressed in decimal degrees with a precision of 6 decimals.
source	<pre><xs:element name="Longitude" type="xs:float"> <xs:annotation> <xs:documentation>Longitudinal Coordinates as expressed in decimal degrees with a precision of 6 decimals.</xs:documentation> </xs:annotation> </xs:element></pre>

element **MaxAxleWeight**


diagram	 Indicates the maximum design axle weight (to).									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:decimal									
properties	content simple									
used by	elements RollingStockDataset/DesignDataSet PlannedTrainTechnicalData TrainRunningTechData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0.1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99.9</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0.1		maxInclusive	99.9	
Kind	Value	Annotation								
minInclusive	0.1									
maxInclusive	99.9									
annotation	documentation Indicates the maximum design axle weight (to).									
source	<pre><xs:element name="MaxAxleWeight"> <xs:annotation> <xs:documentation>Indicates the maximum design axle weight (to).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="0.1"/> <xs:maxInclusive value="99.9"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **MaxDesignSpeed**


diagram	 Maximum approved speed of the wagon (km/h)
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer
properties	content simple

used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Maximum approved speed of the wagon (km/h)									
source	<pre><xs:element name="MaxDesignSpeed"> <xs:annotation> <xs:documentation>Maximum approved speed of the wagon (km/h)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **MaxGrossWeight**


diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	WeightValueKilo												
properties	content simple												
used by	element RollingStockDataset/DesignDataSet												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation Weight of max Gross Load Weight plus the tare weight of the equipment												
source	<pre><xs:element name="MaxGrossWeight" type="WeightValueKilo"> <xs:annotation> <xs:documentation>Weight of max Gross Load Weight plus the tare weight of the equipment</xs:documentation> </xs:annotation> </xs:element></pre>												

element **MaxLengthOfLoad**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer
properties	content simple

used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999999									
annotation	documentation Measured in mm									
source	<pre><xs:element name="MaxLengthOfLoad"> <xs:annotation> <xs:documentation>Measured in mm</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **MaxTemp**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet/TemperatureRange									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	99									
annotation	documentation Maximum Temperature in °Celsius									
source	<pre><xs:element name="MaxTemp"> <xs:annotation> <xs:documentation>Maximum Temperature in °Celsius</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Measure**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	restriction of xs:token									
properties	content simple									
used by	elements Height Length Width									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>ft</td> <td></td> </tr> <tr> <td>enumeration</td> <td>mm</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	ft		enumeration	mm	
Kind	Value	Annotation								
enumeration	ft									
enumeration	mm									
annotation	documentation Measure used, either ft or mm									
source	<pre><xs:element name="Measure"> <xs:annotation> <xs:documentation>Measure used, either ft or mm</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="ft"/> <xs:enumeration value="mm"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **MessageDateTimeCreated**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element MessageHeader
annotation	documentation Date and time when the message was created by the legacy system
source	<pre><xs:element name="MessageDateTimeCreated" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date and time when the message was created by the legacy system</xs:documentation> </xs:annotation> </xs:element></pre>

element **MessageHeader**

<p>diagram</p>	<p>The diagram shows the MessageHeader element as a container for several sub-elements. The sub-elements are: MessageReference (This element identifies the message), MessageRoutingID (Additional information used to route the message to the correct receiving application (if needed)), SenderReference (reference used by the sender (e.g. FTP file name)), Sender (The sender of the mess...), MessageDateTimeCreated (Date and time when the message was created by the l...), and Recipient (Receiver of the mess...).</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageReference MessageRoutingID SenderReference Sender MessageDateTimeCreated Recipient</p>
<p>used by</p>	<p>elements AlertMessage ChangeofTrackMessage ConsignmentOrderMessage ErrorMessage LocationFileDatasetMessage PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage ReceiptConfirmationMessage RollingStockDatasetMessage RollingStockDatasetQueryMessage TrainCompositionMessage TrainDelayCauseMessage TrainForecastAtReportingLocationMessage TrainJourneyModificationMessage TrainReadyMessage TrainRunningForecastMessage TrainRunningInterruptionMessage WagonArrivalNoticeMessage WagonDeliveryNoticeMessage WagonDepartureNoticeMessage WagonDeviationMessage WagonETI ETA Message WagonExceptionMessage WagonExceptionReasonMessage WagonReleaseNoticeMessage WagonYardArrivalMessage WagonYardDepartureMessage</p>
<p>annotation</p>	<p>documentation Used for all messages</p>
<p>source</p>	<pre><xs:element name="MessageHeader"> <xs:annotation> <xs:documentation>Used for all messages</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageReference"/> <xs:element ref="MessageRoutingID" minOccurs="0"/> <xs:element ref="SenderReference" minOccurs="0"/> <xs:element ref="Sender"/> <xs:element ref="MessageDateTimeCreated" minOccurs="0"/> <xs:element ref="Recipient"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **MessageIdentifier**

<p>diagram</p>	<p>The diagram shows the MessageIdentifier element as a container for a sub-element: MessageIdentifier (Identification of the Mess...).</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>


type	FreeText									
properties	content simple									
used by	element MessageReference									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Identification of the Message									
source	<pre><xs:element name="MessageIdentifier" type="FreeText"> <xs:annotation> <xs:documentation>Identification of the Message</xs:documentation> </xs:annotation> </xs:element></pre>									

element **MessageReference**


diagram	<p>The diagram shows a class hierarchy and relationships. At the top is 'MessageReference' with a 'MessageIdentifier' attribute. Below it are several other classes, including 'MessageReference' (multiple instances), 'MessageReference', and 'MessageReference'. The diagram is somewhat complex and partially obscured by a large vertical text block.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

properties	content complex
children	MessageType MessageTypeVersion MessageIdentifier MessageDateTime
used by	elements ErrorMessage/ErrorCauseReference MessageHeader
annotation	documentation This element identifies the message
source	<pre> <xs:element name="MessageReference"> <xs:annotation> <xs:documentation>This element identifies the message</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageType"/> <xs:element ref="MessageTypeVersion"/> <xs:element ref="MessageIdentifier"/> <xs:element name="MessageDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Generated by the common Interface</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element [MessageReference/MessageDateTime](#)

diagram	 <p>Generated by the common Interface</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation Generated by the common Interface
source	<pre> <xs:element name="MessageDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Generated by the common Interface</xs:documentation> </xs:annotation> </xs:element> </pre>

element [MessageRoutingID](#)

diagram	 <p>Additional information used to route the message to the correct receiving application (if needed)</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric2-2
properties	content simple

used by	element MessageHeader									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
annotation	<p>documentation</p> <p>Additional information used to route the message to the correct receiving application (if needed)</p>									
source	<pre><xs:element name="MessageRoutingID" type="Numeric2-2"> <xs:annotation> <xs:documentation>Additional information used to route the message to the correct receiving application (if needed)</xs:documentation> </xs:annotation> </xs:element></pre>									

element **MessageType**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple

used by	element MessageReference																																																																																								
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	4																																																																																
Kind	Value	Annotation																																																																																							
minLength	1																																																																																								
maxLength	4																																																																																								
annotation	<p>documentation</p> <p>To indicate the message type transmitted or referred to. The following list was agreed within the sector:</p> <table border="1"> <tbody> <tr> <td>1000</td> <td>ConsignmentOrderMessage</td> </tr> <tr> <td>2001</td> <td>PathCanceledMessage</td> </tr> <tr> <td>2002</td> <td>PathConfirmedMessage</td> </tr> <tr> <td>2003</td> <td>PathDetailsMessage</td> </tr> <tr> <td>2004</td> <td>PathDetailsRefusedMessage</td> </tr> <tr> <td>2005</td> <td>PathNotAvailableMessage</td> </tr> <tr> <td>2006</td> <td>PathRequestMessage</td> </tr> <tr> <td>2007</td> <td>ReceiptConfirmationMessage</td> </tr> <tr> <td colspan="2">-- sector messages (Planning) --</td> </tr> <tr> <td>2500</td> <td>PathCoordinationMessage</td> </tr> <tr> <td>2501</td> <td>PathSectionNotificationMessage</td> </tr> <tr> <td colspan="2">-- sector message end --</td> </tr> <tr> <td>3003</td> <td>TrainCompositionMessage</td> </tr> <tr> <td>3006</td> <td>TrainReadyMessage</td> </tr> <tr> <td>4001</td> <td>TrainDelayCauseMessage</td> </tr> <tr> <td>4004</td> <td>TrainRunningForecastMessage</td> </tr> <tr> <td>4005</td> <td>TrainRunningInformationMessage</td> </tr> <tr> <td>4006</td> <td>TrainRunningInterruptionMessage</td> </tr> <tr> <td colspan="2">-- sector message (Operations) --</td> </tr> <tr> <td>4500</td> <td>PassengerTrainCompositionProcessMessage</td> </tr> <tr> <td>4501</td> <td>RollingStockRestrictionMessage</td> </tr> <tr> <td>4504</td> <td>ChangeOfTrackMessage</td> </tr> <tr> <td>4505</td> <td>TrainJourneyModificationMessage</td> </tr> <tr> <td colspan="2">-- sector message end --</td> </tr> <tr> <td>5001</td> <td>AlertMessage</td> </tr> <tr> <td>5002</td> <td>WagonArrivalNoticeMessage</td> </tr> <tr> <td>5003</td> <td>WagonDeliveryNoticeMessage</td> </tr> <tr> <td>5004</td> <td>WagonDepartureNoticeMessage</td> </tr> <tr> <td>5006</td> <td>WagonETI_ETA_Message</td> </tr> <tr> <td>5007</td> <td>WagonExceptionMessage</td> </tr> <tr> <td>5008</td> <td>WagonExceptionReasonMessage</td> </tr> <tr> <td colspan="2">-- sector message (Wagon interchange) --</td> </tr> <tr> <td>5009</td> <td>WagonInterchangeNoticeMessage</td> </tr> <tr> <td>5012</td> <td>WagonReceivedAtInterchangeMessage</td> </tr> <tr> <td>5013</td> <td>WagonRefusedAtInterchangeMessage</td> </tr> <tr> <td colspan="2">-- sector message end --</td> </tr> <tr> <td>5014</td> <td>WagonReleaseNoticeMessage</td> </tr> <tr> <td>5015</td> <td>WagonYardArrivalMessage</td> </tr> <tr> <td>5016</td> <td>WagonYardDepartureMessage</td> </tr> <tr> <td>6002</td> <td>LocationFileDatasetMessage</td> </tr> <tr> <td>6003</td> <td>RollingStockDatasetMessage</td> </tr> <tr> <td colspan="2">--sector (RU-RU) ---</td> </tr> <tr> <td>5500</td> <td>WagonPerformanceMessage</td> </tr> <tr> <td colspan="2">-- sector end---</td> </tr> </tbody> </table>	1000	ConsignmentOrderMessage	2001	PathCanceledMessage	2002	PathConfirmedMessage	2003	PathDetailsMessage	2004	PathDetailsRefusedMessage	2005	PathNotAvailableMessage	2006	PathRequestMessage	2007	ReceiptConfirmationMessage	-- sector messages (Planning) --		2500	PathCoordinationMessage	2501	PathSectionNotificationMessage	-- sector message end --		3003	TrainCompositionMessage	3006	TrainReadyMessage	4001	TrainDelayCauseMessage	4004	TrainRunningForecastMessage	4005	TrainRunningInformationMessage	4006	TrainRunningInterruptionMessage	-- sector message (Operations) --		4500	PassengerTrainCompositionProcessMessage	4501	RollingStockRestrictionMessage	4504	ChangeOfTrackMessage	4505	TrainJourneyModificationMessage	-- sector message end --		5001	AlertMessage	5002	WagonArrivalNoticeMessage	5003	WagonDeliveryNoticeMessage	5004	WagonDepartureNoticeMessage	5006	WagonETI_ETA_Message	5007	WagonExceptionMessage	5008	WagonExceptionReasonMessage	-- sector message (Wagon interchange) --		5009	WagonInterchangeNoticeMessage	5012	WagonReceivedAtInterchangeMessage	5013	WagonRefusedAtInterchangeMessage	-- sector message end --		5014	WagonReleaseNoticeMessage	5015	WagonYardArrivalMessage	5016	WagonYardDepartureMessage	6002	LocationFileDatasetMessage	6003	RollingStockDatasetMessage	--sector (RU-RU) ---		5500	WagonPerformanceMessage	-- sector end---	
1000	ConsignmentOrderMessage																																																																																								
2001	PathCanceledMessage																																																																																								
2002	PathConfirmedMessage																																																																																								
2003	PathDetailsMessage																																																																																								
2004	PathDetailsRefusedMessage																																																																																								
2005	PathNotAvailableMessage																																																																																								
2006	PathRequestMessage																																																																																								
2007	ReceiptConfirmationMessage																																																																																								
-- sector messages (Planning) --																																																																																									
2500	PathCoordinationMessage																																																																																								
2501	PathSectionNotificationMessage																																																																																								
-- sector message end --																																																																																									
3003	TrainCompositionMessage																																																																																								
3006	TrainReadyMessage																																																																																								
4001	TrainDelayCauseMessage																																																																																								
4004	TrainRunningForecastMessage																																																																																								
4005	TrainRunningInformationMessage																																																																																								
4006	TrainRunningInterruptionMessage																																																																																								
-- sector message (Operations) --																																																																																									
4500	PassengerTrainCompositionProcessMessage																																																																																								
4501	RollingStockRestrictionMessage																																																																																								
4504	ChangeOfTrackMessage																																																																																								
4505	TrainJourneyModificationMessage																																																																																								
-- sector message end --																																																																																									
5001	AlertMessage																																																																																								
5002	WagonArrivalNoticeMessage																																																																																								
5003	WagonDeliveryNoticeMessage																																																																																								
5004	WagonDepartureNoticeMessage																																																																																								
5006	WagonETI_ETA_Message																																																																																								
5007	WagonExceptionMessage																																																																																								
5008	WagonExceptionReasonMessage																																																																																								
-- sector message (Wagon interchange) --																																																																																									
5009	WagonInterchangeNoticeMessage																																																																																								
5012	WagonReceivedAtInterchangeMessage																																																																																								
5013	WagonRefusedAtInterchangeMessage																																																																																								
-- sector message end --																																																																																									
5014	WagonReleaseNoticeMessage																																																																																								
5015	WagonYardArrivalMessage																																																																																								
5016	WagonYardDepartureMessage																																																																																								
6002	LocationFileDatasetMessage																																																																																								
6003	RollingStockDatasetMessage																																																																																								
--sector (RU-RU) ---																																																																																									
5500	WagonPerformanceMessage																																																																																								
-- sector end---																																																																																									

	<pre> 6004 RollingStockDatasetQueryMessage -- sector (TrainID) begin -- 8500 UdateLinkMessage 8501 ObjectInfoMessage -- sector end -- 9000 ErrorMessage --Reserved: (IM-RU for SFERA) --- SF00 to SF99 for SFERA messages (see IRS90940) - Reserved end - </pre>
source	<pre> <xs:element name="MessageType"> <xs:annotation> <xs:documentation>To indicate the message type transmitted or referred to. The following list was agreed within the sector: 1000 ConsignmentOrderMessage 2001 PathCanceledMessage 2002 PathConfirmedMessage 2003 PathDetailsMessage 2004 PathDetailsRefusedMessage 2005 PathNotAvailableMessage 2006 PathRequestMessage 2007 ReceiptConfirmationMessage -- sector messages (Planning) -- 2500 PathCoordinationMessage 2501 PathSectionNotificationMessage -- sector message end -- 3003 TrainCompositionMessage 3006 TrainReadyMessage 4001 TrainDelayCauseMessage 4004 TrainRunningForecastMessage 4005 TrainRunningInformationMessage 4006 TrainRunningInterruptionMessage -- sector message (Operations) -- 4500 PassengerTrainCompositionProcessMessage 4501 RollingStockRestrictionMessage 4504 ChangeOfTrackMessage 4505 TrainJourneyModificationMessage -- sector message end -- 5001 AlertMessage 5002 WagonArrivalNoticeMessage 5003 WagonDeliveryNoticeMessage 5004 WagonDepartureNoticeMessage 5006 WagonETI_ETA_Message 5007 WagonExceptionMessage 5008 WagonExceptionReasonMessage -- sector message (Wagon interchange) -- 5009 WagonInterchangeNoticeMessage </pre>


	<pre> 5012 WagonReceivedAtInterchangeMessage 5013 WagonRefusedAtInterchangeMessage -- sector message end -- 5014 WagonReleaseNoticeMessage 5015 WagonYardArrivalMessage 5016 WagonYardDepartureMessage 6002 LocationFileDatasetMessage 6003 RollingStockDatasetMessage --sector (RU-RU) --- 5500 WagonPerformanceMessage -- sector end--- 6004 RollingStockDatasetQueryMessage -- sector (TrainID) begin -- 8500 UpateLinkMessage 8501 ObjectInfoMessage -- sector end -- 9000 ErrorMessage --Reserved: (IM-RU for SFERA) --- SF00 to SF99 for SFERA messages (see IRS90940) - Reserved end - </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **MessageTypeVersion**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
used by	element MessageReference						
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>maxLength</td> <td>25</td> <td></td> </tr> </table>	Kind	Value	Annotation	maxLength	25	
Kind	Value	Annotation					
maxLength	25						
annotation	documentation Version of the Message Type						
source	<pre> <xs:element name="MessageTypeVersion"> <xs:annotation> </pre>						

	<pre> <xs:documentation>Version of the Message Type</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="25"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **MinBrakedWeightPercent**


diagram	 <p>Minimum percentage of braking claimed by IM for safety reasons.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Minimum percentage of braking claimed by IM for safety reasons.									
source	<pre> <xs:element name="MinBrakedWeightPercent"> <xs:annotation> <xs:documentation>Minimum percentage of braking claimed by IM for safety reasons.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **MinCurveRadius**


diagram	 <p>Measured in Metres.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Measured in Metres									

source	<pre> <xs:element name="MinCurveRadius"> <xs:annotation> <xs:documentation>Measured in Metres</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--------	--

element **MinTemp**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet/TemperatureRange									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>-99</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>0</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	-99		maxInclusive	0	
Kind	Value	Annotation								
minInclusive	-99									
maxInclusive	0									
annotation	documentation Minimum temperature in ° Celsius									
source	<pre> <xs:element name="MinTemp"> <xs:annotation> <xs:documentation>Minimum temperature in ° Celsius</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="-99"/> <xs:maxInclusive value="0"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **MinVerticalRadiusYardHump**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:integer						
properties	content simple						
used by	element RollingStockDataset/DesignDataSet						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1	
Kind	Value	Annotation					
minInclusive	1						

	maxInclusive 999
annotation	documentation Minimum allowed vertical radius over yard humps. Measured in meters.
source	<pre> <xs:element name="MinVerticalRadiusYardHump"> <xs:annotation> <xs:documentation>Minimum allowed vertical radius over yard humps. Measured in meters.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>


element **ModificationReason**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	DelayCode		
properties	content	simple	
used by	element	TrainJourneyModificationMessage	
facets	Kind	Value	Annotation
	enumeration	11	documentation Formation of trains if managed by infrastructure manager
	enumeration	10	documentation Timetable compilation
	enumeration	12	documentation Mistakes in operational procedures
	enumeration	13	documentation Wrong application of priority rules
	enumeration	14	
	enumeration	18	documentation Staff
	enumeration	19	documentation Other causes related to the operational planning and management
	enumeration	20	documentation Signalling installations
	enumeration	21	documentation Signalling installations at level crossings
	enumeration	22	documentation Telecommunication installations
	enumeration	23	documentation Power supply equipment
	enumeration	24	documentation Track
	enumeration	25	documentation Structures
	enumeration	28	documentation Staff
	enumeration	29	documentation Other causes related to infrastructure installations
	enumeration	31	documentation


	enumeration	30	Irregularities in execution of construction work documentation
	enumeration	32	Planned construction work documentation
	enumeration	39	Speed restrictions due to defective track documentation
	enumeration	40	Other causes related to Civil engineering documentation
	enumeration	41	Delay caused by next IM documentation
	enumeration	50	Delay caused by previous IM documentation
	enumeration	51	exceeding the stop time documentation
	enumeration	52	Request of the RU documentation
	enumeration	53	Loading operations documentation
	enumeration	54	Loading irregularities documentation
	enumeration	58	Commercial preparation of the train documentation
	enumeration	59	Staff documentation
	enumeration	60	Other causes related to commercial causes documentation
	enumeration	61	Roster planning/re-rostering documentation
	enumeration	62	Formation of trains by the RU documentation
	enumeration	63	Problems affecting coaches documentation
	enumeration	64	Problems affecting wagons documentation
	enumeration	68	Problems affecting traction units documentation
	enumeration	69	Staff documentation
	enumeration	70	Other causes related to Rolling Stock documentation
	enumeration	71	Delay caused by next RU documentation
	enumeration	80	Delay caused by previous RU documentation
	enumeration	81	Strike documentation
	enumeration	82	Administrative formalites documentation
	enumeration	83	Outside influence documentation
	enumeration	84	Effects of weather and natural causes documentation
	enumeration	89	Delay caused by external reasons on the next network documentation
	enumeration	90	Other external causes documentation
	enumeration	91	Dangerous incidents, accidents and hazards documentation
	enumeration	92	Track occupation caused by the lateness of the same train documentation
	enumeration	93	Track occupation caused by the lateness of another train documentation
			Turn round

	enumeration 94 documentation Connection
	enumeration 95 documentation Further investigation needed
annotation	documentation Identifies the reason for the train journey being modified
source	<pre><xs:element name="ModificationReason" type="DelayCode"> <xs:annotation> <xs:documentation>Identifiies the reason for the train journey being modified</xs:documentation> </xs:annotation> </xs:element></pre>

element **ModificationStatusIndicator**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer
properties	content simple
used by	element LocationModified
facets	Kind Value Annotation minInclusive 1 maxInclusive 99
annotation	documentation This elemnt shows if the location has been added or deleted in the modified train journey
source	<pre><xs:element name="ModificationStatusIndicator"> <xs:annotation> <xs:documentation>This elemnt shows if the location has been added or deleted in the modified train journey</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **Name**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple
used by	elements AdministrativeContactInformation Customer Customers RollingRoadUnit/RollingRoadUnitDetails/Haulier NetworkSpecificParameter

facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	<p>documentation</p> <p>Generic Name in Free Text</p>									
source	<pre><xs:element name="Name" type="FreeText"> <xs:annotation> <xs:documentation>Generic Name in Free Text</xs:documentation> </xs:annotation> </xs:element></pre>									

element **NetworkProjectedLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	NextLocation ProportionOfDistanceBetweenLocations DistancePrecision
used by	element GeoLocalisationOnNetwork
annotation	<p>documentation</p> <p>Projection of a geographical position on a network line.</p>
source	<pre><xs:element name="NetworkProjectedLocation"> <xs:annotation> <xs:documentation>Projection of a geographical position on a network line. </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NextLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>Next location forecasted to be encountered by the train. If this element isn't present, the GNSS position is considered to be within the "boundaries" of the location included in the LocationReport</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ProportionOfDistanceBetweenLocations" type="Percentage"> <xs:annotation> <xs:documentation>Percentage of the distance between the reporting location, and the next location, on a scale from 0 to 100. </xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:element name="DistancePrecision" type="xs:float" minOccurs="0"> <xs:annotation> <xs:documentation>Precision of the position along the track. Expressed in metres.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **NetworkProjectedLocation/NextLocation**


diagram	<p>The diagram shows a class NextLocation with a dashed border, indicating it is a complex content type. It is connected to a larger class LocationIdent (shaded yellow). LocationIdent contains four elements: CountryCodeISO (Identifies a County or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Next location forecasted to be encountered by the train. If this element isn't present, the GNSS position is considered to be within the "boundaries" of the location included in the LocationReport
source	<pre> <xs:element name="NextLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>Next location forecasted to be encountered by the train. If this element isn't present, the GNSS position is considered to be within the "boundaries" of the location included in the LocationReport</xs:documentation> </xs:annotation> </xs:element> </pre>

element **NetworkProjectedLocation/ProportionOfDistanceBetweenLocations**


diagram	<p>The diagram shows a class ProportionOfDistanceBetweenLocations (truncated) with a dashed border, indicating it is a simple content type. It is connected to a larger class Percentage.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Percentage
properties	content simple
facets	Kind Value Annotation minInclusive 0

	maxInclusive 100
annotation	documentation Percentage of the distance between the reporting location, and the next location, on a scale from 0 to 100.
source	<pre><xs:element name="ProportionOfDistanceBetweenLocations" type="Percentage"> <xs:annotation> <xs:documentation>Percentage of the distance between the reporting location, and the next location, on a scale from 0 to 100. </xs:documentation> </xs:annotation> </xs:element></pre>

element **NetworkProjectedLocation/DistancePrecision**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:float
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Precision of the position along the track. Expressed in metres.
source	<pre><xs:element name="DistancePrecision" type="xs:float" minOccurs="0"> <xs:annotation> <xs:documentation>Precision of the position along the track. Expressed in metres.</xs:documentation> </xs:annotation> </xs:element></pre>

element **NetworkSpecificParameter**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Name Value
used by	elements AffectedSection PathDetailsMessage PathRequestMessage PlannedJourneyLocation
annotation	documentation The usage of this element must be specified in national rules and has to be defined by each IM
source	<pre><xs:element name="NetworkSpecificParameter"> <xs:annotation> <xs:documentation>The usage of this element must be specified in national rules and has to be defined by each IM</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Name"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre><xs:element name="Value" type="FreeText"/> </xs:sequence> </xs:complexType> </xs:element></pre>
--	--


element **NetworkSpecificParameter/Value**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple
used by	elements Height Length Width
facets	Kind Value Annotation minLength 1 maxLength 255
source	<pre><xs:element name="Value" type="FreeText"/></pre>


element **NextIntermediateDestination**

diagram	<p>NextIntermediateDestination Identifies next stopping point on the route of a train</p> <p>IntermediateDestination A location on the route of a tr...</p> <p>DeliveryTimeAtInterchange The scheduled departure date and time or the scheduled handover date and time of wagons at an interchange point, where the responsibility of the wagons will ch...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	IntermediateDestination DeliveryTimeAtInterchange
used by	element WIMO Dataset/ConsignmentLevelData
annotation	documentation Identifies next stopping point on the route of a train
source	<pre><xs:element name="NextIntermediateDestination"> <xs:annotation> <xs:documentation>Identifies next stopping point on the route of a train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="IntermediateDestination"/> <xs:element ref="DeliveryTimeAtInterchange"/> </xs:sequence> </xs:complexType> </xs:element></pre>


element **NextResponsibleRU**

diagram	 The RU who is responsible for the train operation on the next journey section.												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	element WIMO Dataset/ConsignmentLevelData												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation The RU who is responsible for the train operation on the next journey section.												
source	<pre><xs:element name="NextResponsibleRU" type="CompanyCode"> <xs:annotation> <xs:documentation>The RU who is responsible for the train operation on the next journey section.</xs:documentation> </xs:annotation> </xs:element></pre>												

element **NHM_Code**

diagram	 NHM code of the go...									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	NHMCodeType									
properties	content simple									
used by	elements Goods GoodsInWagon/GoodsInContainer GoodsInWagon									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>6</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	6		pattern	\d*[1-9]\d*	
Kind	Value	Annotation								
length	6									
pattern	\d*[1-9]\d*									
annotation	documentation NHM code of the goods									
source	<pre><xs:element name="NHM_Code" type="NHMCodeType"> <xs:annotation> <xs:documentation>NHM code of the goods</xs:documentation> </xs:annotation> </xs:element></pre>									

element **Noise**

diagram	 Noise level at stand still in decibels
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer

properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Noise level at stand still in decibels									
source	<pre> <xs:element name="Noise"> <xs:annotation> <xs:documentation>Noise level at stand still in decibels</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **NoiseByPassLimit**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Noise limit on reference track									
source	<pre> <xs:element name="NoiseByPassLimit"> <xs:annotation> <xs:documentation>Noise limit on reference track</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Notes**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

properties	content complex
children	NoteLocationIdent Note
used by	element TrainRunningData
annotation	documentation Remarks to be transmitted to IM
source	<pre> <xs:element name="Notes"> <xs:annotation> <xs:documentation>Remarks to be transmitted to IM</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NoteLocationIdent" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Identification of location for which is note valid</xs:documentation> </xs:annotation> </xs:element> <xs:element name="Note" type="FreeText"/> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **Notes/NoteLocationIdent**

diagram	<p>The diagram shows a class NoteLocationIdent (dashed box) with the description "Identification of location for which is note valid". It is connected to a class LocationIdent (solid box) which contains four sub-elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	minOcc 0 maxOcc 1 content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Identification of location for which is note valid
source	<pre> <xs:element name="NoteLocationIdent" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Identification of location for which is note valid</xs:documentation> </xs:annotation> </xs:element> </pre>


element **Notes/Note**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
source	<code><xs:element name="Note" type="FreeText"/></code>									

element **NumberOfAxles**


diagram	 The sum of number of axles of all wagons and all traction units									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element TrainRunningTechData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0000</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0000		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0000									
maxInclusive	9999									
annotation	documentation The sum of number of axles of all wagons and all traction units									
source	<pre><xs:element name="NumberOfAxles"> <xs:annotation> <xs:documentation>The sum of number of axles of all wagons and all traction units</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0000"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **NumberOfBogies**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int
properties	content simple
used by	element RollingStockDataset/DesignDataSet

facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	9	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	9									
source	<pre><xs:element name="NumberOfBogies"> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **NumberOfVehicles**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element TrainRunningTechData									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0000</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0000		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0000									
maxInclusive	9999									
annotation	<p>documentation</p> <p>The sum of number of wagons and number of traction units</p>									
source	<pre><xs:element name="NumberOfVehicles"> <xs:annotation> <xs:documentation>The sum of number of wagons and number of traction units</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0000"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ObjectType**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple

used by	complexTypes CompositIdentifierOperationalType CompositIdentifierPlannedType																											
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{2}</td> <td></td> </tr> <tr> <td>enumeration</td> <td>TR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>RO</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PA</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PR</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2		pattern	[0-9A-Z]{2}		enumeration	TR		enumeration	RO		enumeration	PA		enumeration	CR		enumeration	PR	
Kind	Value	Annotation																										
minLength	2																											
maxLength	2																											
pattern	[0-9A-Z]{2}																											
enumeration	TR																											
enumeration	RO																											
enumeration	PA																											
enumeration	CR																											
enumeration	PR																											
annotation	<p>documentation</p> <p>Provides a possibility for differentiation between the objects: Train (TR), Route (RO), Path (PA), Case Reference (CR) and Path Request (PR)</p>																											
source	<pre><xs:element name="ObjectType"> <xs:annotation> <xs:documentation>Provides a possibility for differentiation between the objects: Train (TR), Route (RO), Path (PA), Case Reference (CR) and Path Request (PR)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:maxLength value="2"/> <xs:pattern value="[0-9A-Z]{2}"/> <xs:enumeration value="TR"/> <xs:enumeration value="RO"/> <xs:enumeration value="PA"/> <xs:enumeration value="CR"/> <xs:enumeration value="PR"/> </xs:restriction> </xs:simpleType> </xs:element></pre>																											


element **Offset**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:integer
properties	content simple
used by	element TimingAtLocation/Timing
source	<pre><xs:element name="Offset" type="xs:integer"/></pre>


element **OffsetToReference**

diagram	 <p>The OffsetToReference (OTR) is the shift of the days between Planned Calendar of the related object (route, path request or path) to the days in Reference Calendar. The shift is mentioned in days. OTR value is set to zero when there is no gap between Planned Calendar and Reference Calendar, OTR value is positive if Planned Calendar later than Reference Calendar and negative if Planned Calendar earlier than Reference Calendar.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:integer
properties	content simple
used by	element PlannedCalendar
annotation	documentation The OffsetToReference (OTR) is the shift of the days between Planned Calendar of the related object (route, path request or path) to the days in Reference Calendar. The shift is mentioned in days. OTR value is set to zero when there is no gap between Planned Calendar and Reference Calendar, OTR value is positive if Planned Calendar later than Reference Calendar and negative if Planned Calendar earlier than Reference Calendar.>
source	<pre><xs:element name="OffsetToReference" type="xs:integer"> <xs:annotation> <xs:documentation> The OffsetToReference (OTR) is the shift of the days between Planned Calendar of the related object (route, path request or path) to the days in Reference Calendar. The shift is mentioned in days. OTR value is set to zero when there is no gap between Planned Calendar and Reference Calendar, OTR value is positive if Planned Calendar later than Reference Calendar and negative if Planned Calendar earlier than Reference Calendar.></xs:documentation> </xs:annotation> </xs:element></pre>


element **OnDemandPath**

diagram	 <p>For the use of on demand or optional path (has to be either activated or deactivated depending to network rules)</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element PlannedJourneyLocation
annotation	documentation For the use of on demand or optional path (has to be either activated or deactivated depending to network rules)
source	<pre><xs:element name="OnDemandPath" type="xs:boolean"> <xs:annotation> <xs:documentation>For the use of on demand or optional path (has to be either activated or deactivated depending to network rules)</xs:documentation> </xs:annotation> </xs:element></pre>

element **OperationalTrainCouplingStrength**

diagram	 <p>OperationalTrainCouplingStrength expressed in kN. The operational strength of the train coupling is a crucial technical characteristic for the determination of a freight train's tonnage rating</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	9999									
annotation	documentation OperationalTrainCouplingStrength expressed in kN. The operational strength of the train coupling is a crucial technical characteristic for the determination of a freight train's tonnage rating									
source	<pre><xs:element name="OperationalTrainCouplingStrength"> <xs:annotation> <xs:documentation> OperationalTrainCouplingStrength expressed in kN. The operational strength of the train coupling is a crucial technical characteristic for the determination of a freight train's tonnage rating </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **OperationalTrainNumber**

diagram	 <p>Identifies the train for traffic management purposes by the Dispatcher, GSMR services,...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	String1-8									
properties	content simple									
used by	elements OperationalTrainNumberIdentifier PlannedJourneyLocation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>8</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	8	
Kind	Value	Annotation								
minLength	1									
maxLength	8									
annotation	documentation Identifies the train for traffic management purposes by the Dispatcher, GSMR services, etc.									
source	<pre><xs:element name="OperationalTrainNumber" type="String1-8"> <xs:annotation> <xs:documentation>Identifies the train for traffic management purposes by the Dispatcher, GSMR services, etc.</xs:documentation> </xs:annotation> </xs:element></pre>									

	<pre></xs:annotation> </xs:element></pre>
--	---

element **OperationalTrainNumberIdentifier**


diagram	<p>The diagram shows a box for OperationalTrainNumberIdentifier containing three sub-elements: OperationalTrainNumber, ScheduledTimeAtHandover, and ScheduledDateTimeAtTransfer. Each sub-element has a descriptive text box next to it:</p> <ul style="list-style-type: none"> OperationalTrainNumber: Identifies the train for traffic management purposes by the Dispatcher, GSMR services,... ScheduledTimeAtHandover: The referenced date and time of departure or entrance at the border between two different IMs ScheduledDateTimeAtTransfer: The referenced date and time of arrival or exit at the border between two different IMs
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	OperationalTrainNumber ScheduledTimeAtHandover ScheduledDateTimeAtTransfer
used by	elements AffectedLocation AffectedSection ChangeofTrackMessage ReferenceOTN TrainAtLocation TrainCompositionMessage TrainDelayCauseMessage TrainJourneyModificationMessage TrainReadyMessage TrainRunningForecastMessage TrainRunningInformationMessage TrainRunningInterruptionMessage
source	<pre><xs:element name="OperationalTrainNumberIdentifier"> <xs:complexType> <xs:sequence> <xs:element ref="OperationalTrainNumber"/> <xs:element ref="ScheduledTimeAtHandover" minOccurs="0"/> <xs:element ref="ScheduledDateTimeAtTransfer" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **OriginCountry**


diagram	<p>The diagram shows a box for OriginCountry with the text: "Code of origin country of the UTI."</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of CountryIdentISO												
properties	content simple												
used by	elements ITU Details Wagons/WagonDetails												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> <tr> <td>pattern</td> <td>[A-Z][A-Z]</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2		pattern	[A-Z][A-Z]	
Kind	Value	Annotation											
minLength	2												
maxLength	2												
pattern	[A-Z][A-Z]												
annotation	documentation Code of origin country of the UTI. documentation CODE: ISO-3166-2												
source	<pre><xs:element name="OriginCountry"> <xs:annotation></pre>												

	<pre> <xs:documentation>Code of origin country of the UTI.</xs:documentation> <xs:documentation>CODE: ISO-3166-2</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="CountryIdentISO"> <xs:pattern value="[A-Z][A-Z]"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **OverhaulValidityPeriod**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxExclusive</td> <td>20</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxExclusive	20	
Kind	Value	Annotation								
minInclusive	1									
maxExclusive	20									
annotation	documentation Validity period of last overhaul in years as marked on the wagon									
source	<pre> <xs:element name="OverhaulValidityPeriod"> <xs:annotation> <xs:documentation>Validity period of last overhaul in years as marked on the wagon</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxExclusive value="20"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ParkingBrakeForce**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:decimal						
properties	content simple						
used by	elements HandBrake WagonTechData						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>5</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	5	
Kind	Value	Annotation					
totalDigits	5						

	fractionDigits 1
annotation	documentation Indicates the parking brake force of the hand brake (kN). When the parking brake force is marked on the wagon the information must be provided in the RSRD message.
source	<pre> <xs:element name="ParkingBrakeForce"> <xs:annotation> <xs:documentation>Indicates the parking brake force of the hand brake (kN). When the parking brake force is marked on the wagon the information must be provided in the RSRD message.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="5"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **PassengerFlag**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element LocationPrimaryInformation
annotation	documentation Identifies that the Entity or Location is for Passenger Activity
source	<pre> <xs:element name="PassengerFlag" type="xs:boolean"> <xs:annotation> <xs:documentation>Identifies that the Entity or Location is for Passenger Activity</xs:documentation> </xs:annotation> </xs:element> </pre>

element **PathCanceledMessage**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader AdministrativeContactInformation Identifiers ReferenceTrainIDSubCalendar MessageStatus TypeOfRequest ProcessType TypeOfInformation CoordinatingIM LeadRU AffectedSection FreeTextField</p>
<p>annotation</p>	<p>documentation Path Canceled message according to Short Term Path Request specification (WG5)</p>
<p>source</p>	<pre><xs:element name="PathCanceledMessage"> <xs:annotation> <xs:documentation>Path Canceled message according to Short Term Path Request specification (WG5)</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="AdministrativeContactInformation"/> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/> <xs:element ref="MessageStatus"/> </xs:sequence> </xs:complexType> </xs:element></pre>

```

<xs:element ref="TypeOfRequest" minOccurs="0"/>
<xs:element ref="ProcessType" minOccurs="0"/>
<xs:element ref="TypeOfInformation" minOccurs="0"/>
<xs:element ref="CoordinatingIM" minOccurs="0"/>
<xs:element ref="LeadRU" minOccurs="0"/>
<xs:element ref="AffectedSection" maxOccurs="unbounded"/>
<xs:element ref="FreeTextField" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **PathConfirmedMessage**

<p>diagram</p>	<p>MessageHeader Used for all messa...</p> <p>AdministrativeContactInformation Used to define administrative contact informa...</p> <p>Identifiers AAAAAAAAAAAA</p> <p>ReferenceTrainIDSubCalendar ReferenceTrainIDSubCalendar contains all days of Reference Train (TRID) for days provided in PlannedCalendar. The days in PlannedCalendar may be fixed. Depending on value in element OfferTypeReference, in the following condition must always be true: ReferenceTrainIDSubCalendar = Off...</p> <p>MessageStat... Assigned by the Sender 1=creation, 2=modification, 3=deletion</p> <p>TypeOfRequest Enumeration for 3 different basic types of the processes in the planning: Study (1), Request (2), Modification (...)</p> <p>ProcessType Process type to further distinguish among type of requests.</p> <p>TypeOfInformation Enumeration indicating in which process step, process type in the planning does the message belong: path analysis pre-arranged/traditional path (1); other four offer: booked/delivered; utilization notifications; confirmation of...</p> <p>CoordinatingIM The coordinating (leading) IM coordinates the agreement process for the IMs. It is the primary point of contact for the RUs. Cancels critical stages in the international timetable process are initiated by the leading IM, such as transfer the path request to path administrator to involved IMs in order to prepare the offer with the ...</p> <p>LeadRU Lead Railway Undertak...</p> <p>AffectedSection 0..∞ Indicates for the recipient if not the entire path is affected, e.g. in case of a partial cancellation for the last part of the path.</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader AdministrativeContactInformation Identifiers ReferenceTrainIDSubCalendar MessageStatus TypeOfRequest ProcessType TypeOfInformation CoordinatingIM LeadRU AffectedSection</p>
<p>annotation</p>	<p>documentation This message is used by the RU to confirm the proposed path of the IM (PathDetailsMessage) in response to an RUs</p>

	Original Request
source	<pre> <xs:element name="PathConfirmedMessage"> <xs:annotation> <xs:documentation>This message is used by the RU to confirm the proposed path ofthe IM (PathDetailsMessage) in response to an RUs Original Request</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="AdministrativeContactInformation"/> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/> <xs:element ref="MessageStatus"/> <xs:element ref="TypeOfRequest" minOccurs="0"/> <xs:element ref="ProcessType" minOccurs="0"/> <xs:element ref="TypeOfInformation" minOccurs="0"/> <xs:element ref="CoordinatingIM" minOccurs="0"/> <xs:element ref="LeadRU" minOccurs="0"/> <xs:element ref="AffectedSection" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **PathDetailsMessage**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader AdministrativeContactInformation Identifiers ReferenceTrainIDSubCalendar MessageStatus TypeOfRUHarmonization TypeOfIMHarmonization CoordinatingIM LeadRU TypeOfRequest ProcessType TypeOfInformation PathInformation NetworkSpecificParameter FreeTextField</p>
<p>annotation</p>	<p>documentation This message is used by the IM to the RU confirming details of the path in response to an RU request</p>
<p>source</p>	<pre><xs:element name="PathDetailsMessage"> <xs:annotation> <xs:documentation>This message is used by the IM to the RU confirming details of the path in response to an RU request</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="AdministrativeContactInformation"/> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/></pre>

```

<xs:element ref="MessageStatus"/>
<xs:element ref="TypeOfRUHarmonization" minOccurs="0"/>
<xs:element ref="TypeOfIMHarmonization" minOccurs="0"/>
<xs:element ref="CoordinatingIM" minOccurs="0"/>
<xs:element ref="LeadRU" minOccurs="0"/>
<xs:element ref="TypeOfRequest">
  <xs:annotation>
    <xs:documentation>1    Path study
2    Path request
3    Path Modification
</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="ProcessType" minOccurs="0"/>
<xs:element ref="TypeOfInformation"/>
<xs:element ref="PathInformation"/>
<xs:element ref="NetworkSpecificParameter" minOccurs="0"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>A structured section for specific mandatory
attributes for that network. This has to be checked by the applications that
network section is contained in journey location only if journey location
belongs to PathInformation element
</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="FreeTextField" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **PathDetailsRefusedMessage**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader AdministrativeContactInformation Identifiers ReferenceTrainIDSubCalendar MessageStatus TypeOfRequest ProcessType TypeOfInformation CoordinatingIM LeadRU RevisedRequest AffectedSection FreeTextField</p>
<p>annotation</p>	<p>documentation This message is used by the RU to inform the IM that the PathDetails (with changed values to the request or to earlier booked path) are not acceptable</p>
<p>source</p>	<pre><xs:element name="PathDetailsRefusedMessage"> <xs:annotation> <xs:documentation>This message is used by the RU to inform the IM that the PathDetails (with changed values to the request or to earlier booked path) are not acceptable</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="AdministrativeContactInformation"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/> <xs:element ref="MessageStatus"/> <xs:element ref="TypeOfRequest" minOccurs="0"/> <xs:element ref="ProcessType" minOccurs="0"/> <xs:element ref="TypeOfInformation" minOccurs="0"/> <xs:element ref="CoordinatingIM" minOccurs="0"/> <xs:element ref="LeadRU" minOccurs="0"/> <xs:element ref="RevisedRequest" minOccurs="0"/> <xs:element ref="AffectedSection" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="FreeTextField" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **PathInformation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	PlannedJourneyLocation PlannedCalendar RequestedCalendar
used by	elements PathDetailsMessage PathRequestMessage
source	<pre> <xs:element name="PathInformation"> <xs:complexType> <xs:sequence> <xs:element ref="PlannedJourneyLocation" minOccurs="2" maxOccurs="unbounded"/> <xs:element ref="PlannedCalendar"/> <xs:element ref="RequestedCalendar" minOccurs="0"> <xs:annotation> <xs:documentation>subset of the requested calendar</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **PathNotAvailableMessage**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader AdministrativeContactInformation Identifiers ReferenceTrainIDSubCalendar MessageStatus TypeOfRequest ProcessType TypeOfInformation CoordinatingIM LeadRU AffectedSection InterruptionInformation FreeTextField</p>
<p>annotation</p>	<p>documentation Path Not Available message according to Short Term Path Request specification (WG5)</p>
<p>source</p>	<pre><xs:element name="PathNotAvailableMessage"> <xs:annotation> <xs:documentation>Path Not Available message according to Short Term Path Request specification (WG5) </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="AdministrativeContactInformation"/> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>


```

<xs:element ref="MessageStatus"/>
<xs:element ref="TypeOfRequest" minOccurs="0"/>
<xs:element ref="ProcessType" minOccurs="0"/>
<xs:element ref="TypeOfInformation" minOccurs="0"/>
<xs:element ref="CoordinatingIM" minOccurs="0"/>
<xs:element ref="LeadRU" minOccurs="0"/>
<xs:element ref="AffectedSection" maxOccurs="unbounded"/>
<xs:element ref="InterruptionInformation"/>
<xs:element ref="FreeTextField" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```


element **PathRequestMessage**

<p>diagram</p>	Detailed description of the diagram content
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader AdministrativeContactInformation Identifiers ReferenceTrainIDSubCalendar MessageStatus TypeOfRUHarmonization TypeOfIMHarmonization CoordinatingIM LeadRU TypeOfRequest ProcessType</p>


	TypeOfInformation TrainInformation PathInformation NetworkSpecificParameter FreeTextField
annotation	documentation This message serves to request a train path. The message is sent from the RU to each IM involved.
source	<pre> <xs:element name="PathRequestMessage"> <xs:annotation> <xs:documentation>This message serves to request a train path. The message is sent from the RU to each IM involved.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="AdministrativeContactInformation"/> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/> <xs:element ref="MessageStatus"/> <xs:element ref="TypeOfRUHarmonization" minOccurs="0"/> <xs:element ref="TypeOfIMHarmonization" minOccurs="0"/> <xs:element ref="CoordinatingIM" minOccurs="0"> <xs:annotation> <xs:documentation>Proposal from the RU, IM's will decide who will take the role.</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="LeadRU" minOccurs="0"/> <xs:element ref="TypeOfRequest"> <xs:annotation> <xs:documentation>1 Path study 2 Path request 3 Path Modification </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="ProcessType" minOccurs="0"/> <xs:element ref="TypeOfInformation"/> <xs:element ref="TrainInformation"> <xs:annotation> <xs:documentation>Train Information provided by the RUs as an overview for the whole train journey from origin to destination</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="PathInformation"> <xs:annotation> <xs:documentation>Information provided by the RU for a requested journey section or by the IM for an offered/booked of the Path section</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="NetworkSpecificParameter" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>A structured section for specific mandatory attributes for that network. This has to be checked by the applications that network section is contained in journey location only if journey location belongs to PathInformation element </xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

	<pre> </xs:element> <xs:element ref="FreeTextField" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **PermittedTolerance**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	99									
annotation	documentation Permitted tolerance after date of overhaul (in months)									
source	<pre> <xs:element name="PermittedTolerance"> <xs:annotation> <xs:documentation>Permitted tolerance after date of overhaul (in months)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **PhoneNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CommunicationRefID									
properties	content simple									
used by	element AdministrativeContactInformation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>70</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	70	
Kind	Value	Annotation								
minLength	1									
maxLength	70									
annotation	documentation Generic Phone number in Free text									
source	<pre> <xs:element name="PhoneNumber" type="CommunicationRefID"> <xs:annotation> </pre>									

	<pre><xs:documentation>Generic Phone number in Free text</xs:documentation> </xs:annotation> </xs:element></pre>
--	--

element PickupTimeAtLocation


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation The date and time of the release of a wagon at customer sidings
source	<pre><xs:element name="PickupTimeAtLocation" type="xs:dateTime"> <xs:annotation> <xs:documentation>The date and time of the release of a wagon at customer sidings</xs:documentation> </xs:annotation> </xs:element></pre>

element PlannedCalendar

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	BitmapDays ValidityPeriod OffsetToReference
used by	elements AffectedSection PathInformation TrainInformation
annotation	documentation This is the calendar item for path request/path details messages - used in planning phase
source	<pre><xs:element name="PlannedCalendar"> <xs:annotation> <xs:documentation>This is the calendar item for path request/path details messages - used in planning phase</xs:documentation> </xs:annotation> <xs:complexType></pre>

	<pre> <xs:sequence> <xs:element ref="BitmapDays" minOccurs="0"/> <xs:element ref="ValidityPeriod"/> <xs:element ref="OffsetToReference" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **PlannedDateNextOverhaul**

diagram	 <p>Date of planned next overhaul. It must be within the validity period of the last overhaul. The element serves as indication of the actually planned date of next overhaul by the wagon keeper/ECM. Minimum planned date next overhaul or overhaul validity period must be p...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
used by	element RollingStockDataset/DesignDataSet
annotation	documentation Date of planned next overhaul. It must be within the validity period of the last overhaul. The element serves as indication of the actually planned date of next overhaul by the wagon keeper/ECM. Minimum planned date next overhaul or overhaul validity period must be provided by the wagon keeper.
source	<pre> <xs:element name="PlannedDateNextOverhaul" type="xs:date"> <xs:annotation> <xs:documentation> Date of planned next overhaul. It must be within the validity period of the last overhaul. The element serves as indication of the actually planned date of next overhaul by the wagon keeper/ECM. Minimum planned date next overhaul or overhaul validity period must be provided by the wagon keeper. </xs:documentation> </xs:annotation> </xs:element> </pre>

element **PlannedJourneyLocation**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>extension of LocationIdent</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification TimingAtLocation FreeTextField ResponsibleApplicant ResponsibleRU ResponsibleIM PlannedTrainData StatusOfHarmonization TrainActivity OnDemandPath PreArrangedPath OperationalTrainNumber NetworkSpecificParameter JourneyLocationTypeCode</p>
<p>used by</p>	<p>elements PathInformation TrainInformation</p>
<p>annotation</p>	<p>documentation Any operation point along the train journey or path</p>
<p>source</p>	<pre><xs:element name="PlannedJourneyLocation"> <xs:annotation> <xs:documentation>Any operation point along the train journey or path</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent></pre>

```

<xs:extension base="LocationIdent">
  <xs:sequence minOccurs="1">
    <xs:element ref="TimingAtLocation" minOccurs="0"/>
    <xs:element ref="FreeTextField" minOccurs="0"
maxOccurs="unbounded"/>
    <xs:element ref="ResponsibleApplicant" minOccurs="0"/>
    <xs:element ref="ResponsibleRU" minOccurs="0"/>
    <xs:element ref="ResponsibleIM" minOccurs="0"/>
    <xs:element ref="PlannedTrainData" minOccurs="0"/>
    <xs:element name="StatusOfHarmonization" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Does not force harmonization, it just sets
an indication message: has the interchange/handover been harmonized or
not.</xs:documentation>
      </xs:annotation>
      <xs:complexType>
        <xs:sequence>
          <xs:element name="HandoverHarmonized" type="xs:boolean"
minOccurs="0">
            <xs:annotation>
              <xs:documentation>IM indicates that he has finished to
harmonized the handover point. Used for PathDetails message, should be
mandatory for applications.</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="InterchangeHarmonized" type="xs:boolean"
minOccurs="0">
            <xs:annotation>
              <xs:documentation>RU indicates that it has harmonized
the interchange point with its' partner. Used for PathRequest, should be
mandatory for applications</xs:documentation>
            </xs:annotation>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element ref="TrainActivity" minOccurs="0"
maxOccurs="unbounded"/>
    <xs:element ref="OnDemandPath" minOccurs="0"/>
    <xs:element ref="PreArrangedPath" minOccurs="0"/>
    <xs:element ref="OperationalTrainNumber" minOccurs="0"/>
    <xs:element ref="NetworkSpecificParameter" minOccurs="0"
maxOccurs="unbounded"/>
    <xs:element ref="JourneyLocationTypeCode" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
</xs:element>

```

element **PlannedJourneyLocation/StatusOfHarmonization**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 1 content complex</p>
<p>children</p>	<p>HandoverHarmonized InterchangeHarmonized</p>
<p>annotation</p>	<p>documentation Does not force harmonization, it just sets an indication message: has the interchange/handover been harmonized or not.</p>
<p>source</p>	<pre><xs:element name="StatusOfHarmonization" minOccurs="0"> <xs:annotation> <xs:documentation>Does not force harmonization, it just sets an indication message: has the interchange/handover been harmonized or not.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="HandoverHarmonized" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>IM indicates that he has finished to harmonized the handover point. Used for PathDetails message, should be mandatory for applications.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="InterchangeHarmonized" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>RU indicates that it has harmonized the interchange point with its' partner. Used for PathRequest, should be mandatory for applications</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

element **PlannedJourneyLocation/StatusOfHarmonization/HandoverHarmonized**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>xs:boolean</p>

properties	minOcc 0 maxOcc 1 content simple
annotation	documentation IM indicates that he has finished to harmonized the handover point. Used for PathDetails message, should be mandatory for applications.
source	<pre><xs:element name="HandoverHarmonized" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>IM indicates that he has finished to harmonized the handover point. Used for PathDetails message, should be mandatory for applications.</xs:documentation> </xs:annotation> </xs:element></pre>

element **PlannedJourneyLocation/StatusOfHarmonization/InterchangeHarmonized**

diagram	 <p>RU indicates that it has harmonized the interchange point with its' partner. Used for PathRequest, should be mandatory for applications</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation RU indicates that it has harmonized the interchange point with its' partner. Used for PathRequest, should be mandatory for applications
source	<pre><xs:element name="InterchangeHarmonized" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>RU indicates that it has harmonized the interchange point with its' partner. Used for PathRequest, should be mandatory for applications</xs:documentation> </xs:annotation> </xs:element></pre>

element **PlannedSpeed**

diagram	 <p>IM may inform the RA on the speed which was the basis for path construction</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Speed									
properties	content simple									
used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
annotation	documentation IM may inform the RA on the speed which was the basis for path construction									

source	<pre><xs:element name="PlannedSpeed" type="Speed"> <xs:annotation> <xs:documentation>IM may inform the RA on the speed which was the basis for path construction</xs:documentation> </xs:annotation> </xs:element></pre>
--------	--

element **PlannedTrainData**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TrainType TrafficType PushPullTrain TypeofService CommercialTrafficType PlannedTrainTechnicalData ExceptionalGaugingIdent DangerousGoodsIndication CombinedTrafficLoadProfile
used by	element PlannedJourneyLocation
annotation	documentation Train relevant data for a planning period
source	<pre><xs:element name="PlannedTrainData"> <xs:annotation></pre>

```

<xs:documentation>Train relevant data for a planning
period</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element ref="TrainType" minOccurs="0"/>
    <xs:element ref="TrafficType" minOccurs="0"/>
    <xs:element ref="PushPullTrain" minOccurs="0"/>
    <xs:element ref="TypeofService" minOccurs="0"/>
    <xs:element name="CommercialTrafficType"
type="tap:type7009BrandNameCodeList" minOccurs="0"/>
    <xs:element ref="PlannedTrainTechnicalData"/>
    <xs:element ref="ExceptionalGaugingIdent" minOccurs="0"
maxOccurs="unbounded"/>
    <xs:element ref="DangerousGoodsIndication" minOccurs="0"
maxOccurs="unbounded"/>
    <xs:element ref="CombinedTrafficLoadProfile" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **PlannedTrainData/CommercialTrafficType**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	type7009BrandNameCodeList		
properties	minOcc	0	
	maxOcc	1	
	content	simple	
facets	Kind	Value	Annotation
	maxLength	17	
	enumeration	46	documentation TAJ documentation TAJ documentation Day car train documentation 13 documentation 0
	enumeration	47	documentation TAC documentation TAC documentation Car sleeper train, motor rail (CST) documentation 14 documentation 0
	enumeration	48	documentation SAE documentation SAE documentation Unaccompanied car service, motor rail

		documentation 14
		documentation 0
enumeration	49	documentation EIC documentation EkspresIC documentation Fast and Comfortable Interregional trains documentation 10
		documentation 0
enumeration	50	documentation EC documentation EuroCity documentation EuroCity documentation 9
		documentation 0
enumeration	51	documentation ICE documentation ICE documentation ICE documentation 8
		documentation 0
enumeration	52	documentation AVE documentation AVE documentation AVE documentation 8
		documentation 0
enumeration	53	documentation EIL documentation EUROSTAR documentation Eurostar documentation 8
		documentation 0
enumeration	54	documentation
		documentation
		documentation Talgo documentation 9
		documentation

	enumeration	55	0 documentation OTU documentation Oresundstog documentation Oresundstog documentation 10 documentation 0
	enumeration	56	documentation TGV documentation TGV documentation TGV Bruxelles – Lille / Province documentation 8 documentation 0
	enumeration	58	documentation TRN documentation Intercités documentation Intercités documentation 9 documentation 0
	enumeration	59	documentation AE documentation ALLEGRO documentation Allegro documentation 8 documentation 0
	enumeration	60	documentation ECB documentation EuroCityBrenner documentation EuroCityBrenner documentation 9 documentation 0
	enumeration	62	documentation documentation documentation Suburban service documentation 12 documentation 0
	enumeration	63	documentation IC

		documentation Intercity documentation Intercity documentation 9 documentation 0 documentation
	enumeration 64	documentation
		documentation Hotel Train documentation 13 documentation 0 documentation
	enumeration 65	documentation
		documentation Ferry documentation hydrofoil documentation 33 documentation 0 documentation IC documentation Intercity documentation Inter City Lyn documentation 9 documentation 0 documentation
	enumeration 66	documentation
		documentation TRN documentation 10 documentation 0 documentation
	enumeration 68	documentation
		documentation International documentation 9 documentation 0 documentation
	enumeration 69	documentation
		documentation

			documentation Express
			documentation 10
			documentation 0
	enumeration	70	documentation EN
			documentation EuroNight
			documentation Euro Night
			documentation 13
			documentation 0
	enumeration	71	documentation HST
			documentation High-speed train
			documentation High-speed train
			documentation 8
			documentation 0
	enumeration	72	documentation TRN
			documentation TRAIN
			documentation Train SNCF
			documentation 9
			documentation 0
	enumeration	73	documentation TGV
			documentation TGV
			documentation TGV Sud-Est
			documentation 8
			documentation 0
	enumeration	74	documentation TGV
			documentation TGV
			documentation TGV Atlantique
			documentation 8
			documentation 0
	enumeration	75	documentation TGV
			documentation TGV
			documentation TGV Nord

		documentation 8
		documentation 0
	enumeration 76	documentation TGV documentation TGV documentation TGV Lyria documentation 8
		documentation 0
	enumeration 77	documentation TGV documentation TGV documentation TGV Duplex documentation 8
		documentation 0
	enumeration 79	documentation TGV documentation TGV documentation TGV Est documentation 8
		documentation 0
	enumeration 80	documentation TGV documentation TGV documentation TGV Interconnexion documentation 8
		documentation 0
	enumeration 82	documentation
		documentation THALYS documentation Thalys documentation 8
		documentation 0
	enumeration 83	documentation
		documentation Ferry documentation hovercraft documentation 33 documentation

	enumeration	84	0 documentation RE documentation regional train documentation Regional documentation 11 documentation
	enumeration	85	0 documentation WTE documentation Wilhelm Tell Express documentation Wilhelm Tell Express documentation 10 documentation
	enumeration	87	0 documentation documentation PENDOLINO documentation Pendolino documentation 8 documentation
	enumeration	88	0 documentation Suburban documentation 8 documentation
	enumeration	89	0 documentation ALV documentation Alvia documentation Alvia documentation 8 documentation
	enumeration	90	0 documentation AVN documentation Avant documentation Avant documentation 8 documentation
	enumeration	91	0 documentation TER documentation TRAIN documentation Regional TER

		documentation 11
		documentation 0
enumeration	92	documentation REG documentation NSB Regiontog documentation NSB Regiontog documentation 37
		documentation 0
enumeration	93	documentation FB documentation FRECCIABIANCA documentation FRECCIABIANCA documentation 8
		documentation 0
enumeration	94	documentation SC documentation SuperCity documentation Supercity documentation 9
		documentation 0
enumeration	95	documentation CNL documentation City Night Line (D) documentation DB Nachtzug documentation 13
		documentation 0
enumeration	96	documentation INI documentation InterCityNotte Italia documentation InterCityNotte documentation 13
		documentation 0
enumeration	97	documentation GB documentation ATOC MEMBER OPERATED SERVICE documentation ATOC MEMBER OPERATED SERVICE documentation 37
		documentation

	enumeration 98	0 documentation ESI documentation ES* Italia documentation Eurostar Italia documentation 8 documentation 0
	enumeration 99	documentation documentation documentation Funicular documentation 15 documentation 0
	enumeration 100	documentation documentation documentation Airport train documentation 12 documentation 0
	enumeration 101	documentation Night train documentation 13 documentation 0
	enumeration 102	documentation documentation documentation Touristic train documentation 9 documentation 0
	enumeration 107	documentation documentation documentation documentation Historical train, steam engine train documentation 16 documentation 0
	enumeration 108	documentation IRE documentation IRE

		documentation Interregio-Express documentation 10 documentation 0 documentation RB documentation RB documentation Regionalbahn documentation 11 documentation 0 documentation RE documentation RE documentation Regional-Express documentation 11 documentation 0 documentation RT documentation RT documentation RegioTram documentation 11 documentation 0 documentation
enumeration	109	
enumeration	110	
enumeration	111	
enumeration	112	
enumeration	113	documentation Shinkansen documentation 8 documentation 0 documentation THT documentation TrainHotel Talgo documentation Train hotel talgo documentation 13 documentation 0 documentation EUR documentation Euromed documentation Euromed documentation
enumeration	114	

		9	documentation
	enumeration	115	0 documentation ALR documentation Alaris documentation Alaris documentation 9 documentation 0
	enumeration	116	documentation ALT documentation Altaria documentation Altaria documentation 9 documentation 0
	enumeration	117	documentation ARC documentation Arco documentation intercity documentation 9 documentation 2
	enumeration	119	documentation documentation documentation S-Bahn documentation 12 documentation 0
	enumeration	121	documentation Night Train documentation Night Train documentation 13 documentation 0
	enumeration	122	documentation IR documentation Interregional documentation Interregional documentation 10 documentation 0
	enumeration	123	documentation IRN

		documentation Interregional Night Train documentation Interregional Night Train documentation 13 documentation 2 documentation NLT documentation TOLSTOI documentation Tolstoi documentation 13 documentation 0 documentation
enumeration	124	
enumeration	126	documentation
enumeration	128	documentation ARZ documentation 14 documentation 0 documentation AVE documentation RENFE SNCF EN COOPERATION documentation RENFE SNCF documentation 8 documentation 0 documentation TGV documentation RENFE SNCF EN COOPERATION documentation RENFE SNCF documentation 8 documentation 0 documentation BUS documentation IC Bus documentation Bus documentation 32 documentation 0 documentation BUS documentation IC Bus international documentation
enumeration	129	
enumeration	130	
enumeration	131	

		Bus documentation 32 documentation 0 documentation
enumeration	153	documentation special train documentation Sonderzug documentation 9 documentation 0 documentation
enumeration	154	documentation
enumeration	155	documentation InterCityRapid documentation 9 documentation 0 documentation
enumeration	157	documentation InterPici documentation 9 documentation 0 documentation
enumeration	158	documentation Fast train documentation 9 documentation 0 documentation
enumeration	159	documentation Euregio documentation 11 documentation 0 documentation
		documentation Bus documentation

	enumeration	160	<p>IC Ersatzbus documentation 32 documentation 0 documentation</p>
	enumeration	162	<p>documentation Bus documentation IP Ersatzbus documentation 32 documentation 0 documentation</p>
	enumeration	163	<p>documentation Bus documentation Replacement Bus documentation 32 documentation 0 documentation TGV documentation TGV documentation TGV Duplex Lyria documentation 8 documentation 0 documentation TGV documentation TGV INOUI documentation TGV Duplex France Allemagne documentation 8 documentation 2 documentation YHT documentation YHT documentation High speed train in Turkey documentation 8 documentation 0 documentation FA documentation FRECCIARGENTO documentation FRECCIARGENTO documentation 8</p>
	enumeration	166	<p>documentation TGV documentation TGV INOUI documentation TGV Duplex France Allemagne documentation 8 documentation 2 documentation YHT documentation YHT documentation High speed train in Turkey documentation 8 documentation 0 documentation FA documentation FRECCIARGENTO documentation FRECCIARGENTO documentation 8</p>
	enumeration	170	<p>documentation YHT documentation YHT documentation High speed train in Turkey documentation 8 documentation 0 documentation FA documentation FRECCIARGENTO documentation FRECCIARGENTO documentation 8</p>
	enumeration	171	<p>documentation FA documentation FRECCIARGENTO documentation FRECCIARGENTO documentation 8</p>

		documentation 0
enumeration	172	documentation FR documentation FRECCIAROSSA documentation FRECCIAROSSA documentation 8
enumeration	173	documentation 0 documentation AP documentation Albula Panoramawagen documentation Albula Panoramawagen documentation 10
enumeration	174	documentation 0 documentation BEX documentation Bernina Express documentation Bernina Express (Panorama Train) documentation 10
enumeration	175	documentation 0 documentation GEX documentation Glacier Express documentation Glacier Express (Panorama Train) documentation 10
enumeration	176	documentation 0 documentation GP documentation Golden Pass documentation Golden Pass (Panorama Train) documentation 10
enumeration	177	documentation 0 documentation BNI documentation Bernina Panorama documentation Bernina Panorama documentation 11
enumeration	178	documentation 0 documentation

		zb documentation zb Zentralbahn AG documentation Luzern-Interlaken Express (Panorama Train) documentation 10 documentation 0
enumeration	179	documentation BXB documentation Bernina Express Bus documentation Bernina Express (Panorama Bus) documentation 32 documentation 0
enumeration	200	documentation GGB documentation Gornergrat Bahn documentation Mountain train documentation 10 documentation 0
enumeration	202	documentation ICE documentation ICE-Allemagne France documentation ICE Allemagne-France documentation 8 documentation 0
enumeration	203	documentation documentation documentation ÖBB-NIGHTLINE documentation ÖBB Night Line documentation 13 documentation 0
enumeration	205	documentation ICP documentation Intercity Plus documentation Intercity Plus documentation 9 documentation 0
enumeration	206	documentation RID documentation Riviera Day

		documentation Riviera day documentation 9 documentation 0 documentation RIN documentation Riviera Night documentation Riviera night documentation 9 documentation 0
enumeration	207	documentation RIN documentation Riviera Night documentation Riviera night documentation 9 documentation 0
enumeration	209	documentation RJ documentation R A I L JET documentation Rail Jet documentation 9 documentation 0
enumeration	213	documentation AZ documentation DB Autozug documentation DB Autozug documentation 14 documentation 0
enumeration	214	documentation Berlin-Warszawa-Express documentation Berlin-Warszawa-Express documentation 8 documentation 0 documentation
enumeration	215	documentation Railpromo Austria Express/Treski documentation Austria Express/Treski documentation 13 documentation 0 documentation
enumeration	216	documentation PRECIOS MERCADO documentation Precios Mercado

		documentation 9
		documentation 0
	enumeration 219	documentation TGV
		documentation TGV
		documentation TGV
		documentation 8
		documentation 0
	enumeration 223	documentation FB
		documentation FB
		documentation FernBus
		documentation 32
		documentation 0
	enumeration 224	documentation ICB
		documentation Intercitybus
		documentation ÖBB-Intercitybus
		documentation 32
		documentation 0
	enumeration 225	documentation TLK
		documentation TLK train
		documentation Yours Rail Lines
		documentation 10
		documentation 0
	enumeration 226	documentation A
		documentation RailBus
		documentation RailBus
		documentation 32
		documentation 0
	enumeration 227	documentation BUS
		documentation Replacement bus for Regional Train
		documentation Replacement bus for Regional Train
		documentation 32
		documentation

	enumeration	228	0 documentation IR documentation InterREGIO train documentation InterREGIO train documentation 10 documentation 0
	enumeration	229	documentation IRB documentation Replacement bus for InterRegio train documentation Replacement bus for InterRegio train documentation 32 documentation 0
	enumeration	230	documentation MP documentation Fast International Train documentation Fast International Train documentation 10 documentation 0
	enumeration	231	documentation MR documentation musicREGIO train documentation musicREGIO train documentation 11 documentation 0
	enumeration	232	documentation Os documentation Stopping Train documentation Stopping Train documentation 11 documentation 0
	enumeration	233	documentation P documentation Fast Train documentation Fast Train documentation 10 documentation 0
	enumeration	234	documentation R

		documentation REGIO train documentation REGIO train documentation 11 documentation 0 documentation RE documentation REGIOekspres train documentation REGIOekspres train documentation 10 documentation 0
enumeration	235	
		documentation VR documentation viaREGIO train documentation viaREGIO train documentation 11 documentation 0
enumeration	236	
		documentation TK documentation TurKol documentation TurKol documentation 11 documentation 0
enumeration	237	
		documentation EIP documentation EIC Premium documentation High-speed train documentation 8 documentation 0
enumeration	238	
		documentation SKM documentation PKP SKM w Trojmiescie documentation PKP SKM w Trojmiescie documentation 12 documentation 0
enumeration	239	
		documentation SA documentation SAPSAN documentation
enumeration	240	

		High speed train documentation 8 documentation 0 documentation STR documentation STRIZH documentation Strizh night train documentation 13 documentation 0
enumeration	242	
		documentation STR documentation STRIZH documentation Strizh interregional documentation 8 documentation 0
enumeration	243	
		documentation NJ documentation NJ documentation NJ Night Jet documentation 13 documentation 0
enumeration	244	
		documentation CAR documentation AUTOCAR documentation French regional buses (not sold via Hermes) documentation 32 documentation 0
enumeration	245	
		documentation RJX documentation RJX documentation RJX railjet xpress documentation 8 documentation 0
enumeration	246	
		documentation CJX documentation CJX documentation CJX cityjet xpress documentation 10
enumeration	247	

		documentation 0
enumeration	248	documentation Night train BC documentation Night train BC documentation 13
enumeration	249	documentation 0 documentation TGV documentation TGV INOUI documentation TGV INOUI documentation 8
enumeration	250	documentation 0 documentation TGV documentation TGV INOUI documentation TGV INOUI DUPLEX (double decker TGV) documentation 8
enumeration	251	documentation 0 documentation ALI documentation Aare Linth documentation Aare Linth (Panorama Train) documentation 10
enumeration	252	documentation 0 documentation TGO documentation Treno Gottardo documentation Treno Gottardo (Panorama Train) documentation 10
enumeration	253	documentation 0 documentation VAE documentation Voralpen-Express documentation Voralpen-Express (Panorama Train) documentation 10
enumeration	254	documentation 0 documentation LK documentation

	<p>enumeration 255</p> <p>enumeration 256</p> <p>enumeration 257</p> <p>enumeration 258</p> <p>enumeration 259</p>	<p>FRECCIALINK documentation</p> <p>FRECCIALINK documentation</p> <p>32 documentation</p> <p>0 documentation</p> <p>FRN documentation</p> <p>FRECCIAROSSA NOTTE documentation</p> <p>FRECCIAROSSA NOTTE documentation</p> <p>13 documentation</p> <p>0 documentation</p> <p>ABS documentation</p> <p>ANEK – SUPERFAST JOINT VENTURE documentation</p> <p>Domestic routes Crete documentation</p> <p>33 documentation</p> <p>0 documentation</p> <p>ASF documentation</p> <p>ANEK – SUPERFAST JOINT VENTURE documentation</p> <p>International Lines Italy-Greece and V.V. documentation</p> <p>33 documentation</p> <p>0 documentation</p> <p>BSF documentation</p> <p>BLUE STAR FERRIES MARITIME SA CO JOINT VENTURE documentation</p> <p>Domestic routes Greece documentation</p> <p>33 documentation</p> <p>0 documentation</p> <p>HSW documentation</p> <p>BLUE STAR FERRIES MARITIME SA CO JOINT VENTURE documentation</p> <p>Domestic routes Greece documentation</p> <p>33 documentation</p> <p>0</p>
<p>source</p>	<pre><xs:element name="CommercialTrafficType" type="tap:type7009BrandNameCodeList" minOccurs="0"/></pre>	

element **PlannedTrainTechnicalData**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>TrainWeight TrainLength WeightOfSetOfCarriages LengthOfSetOfCarriages TractionDetails TrainMaxSpeed HighestPlannedSpeed PlannedSpeed Coasting MaxAxleWeight RouteClass BrakeType EmergencyBrakeOverride BrakingRatio MinBrakedWeightPercent BrakeWeight TrainCC System TrainRadioSystem TiltingFunction OperationalTrainCouplingStrength BogieWagonsOnly</p>
<p>used by</p>	<p>element PlannedTrainData</p>
<p>annotation</p>	<p>documentation Shows the relevant technical data for a running train</p>
<p>source</p>	<pre><xs:element name="PlannedTrainTechnicalData"> <xs:annotation> <xs:documentation>Shows the relevant technical data for a running train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TrainWeight"/> <xs:element ref="TrainLength"/></pre>

```

<xs:element ref="WeightOfSetOfCarriages" minOccurs="0"/>
<xs:element ref="LengthOfSetOfCarriages" minOccurs="0"/>
<xs:element ref="TractionDetails" maxOccurs="unbounded"/>
<xs:element ref="TrainMaxSpeed"/>
<xs:element ref="HighestPlannedSpeed" minOccurs="0"/>
<xs:element ref="PlannedSpeed" minOccurs="0"/>
<xs:element ref="Coasting" minOccurs="0"/>
<xs:element ref="MaxAxleWeight" minOccurs="0"/>
<xs:element ref="RouteClass" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Indication of the route class (based on CEN EN
15528: line categories for managing the interface between load limits of
vehicles on infrastructure).</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="BrakeType" minOccurs="0"/>
<xs:element ref="EmergencyBrakeOverride" minOccurs="0"/>
<xs:element ref="BrakingRatio" minOccurs="0"/>
<xs:element ref="MinBrakedWeightPercent" minOccurs="0"/>
<xs:element ref="BrakeWeight" minOccurs="0"/>
<xs:element ref="TrainCC_System" minOccurs="0" maxOccurs="unbounded"/>
<xs:element ref="TrainRadioSystem" minOccurs="0"/>
<xs:element ref="TiltingFunction" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Indicates if a train uses a tilting
system</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="OperationalTrainCouplingStrength" minOccurs="0"/>
<xs:element ref="BogieWagonsOnly" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **PlannedTransportIdentifiers**

diagram	<p>The diagram illustrates the structure of the PlannedTransportIdentifiers element. It is a complex content type derived from CompositIdentifierPlannedType. The components are:</p> <ul style="list-style-type: none"> ObjectType: Provides a possibility for differentiation between the objects: Train (TR), Route (RO), Path (PA), Case Reference (CR) and Path Request (PR) Compa...: Identifies a railway company (RU or IM) Core: It is the main part of identifier and is determined by the company that creates it. Variant: The variant shows a relationship between two identifiers referring to the same business case TimetableYear: Refers to the timetable period in which the business will be carried out StartDate: The start of the date/time in effect
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CompositIdentifierPlannedType
properties	content complex
children	ObjectType Company Core Variant TimetableYear StartDate
used by	elements ErrorMessage Identifiers
source	<pre><xs:element name="PlannedTransportIdentifiers" type="CompositIdentifierPlannedType"/></pre>

element **PostalCode**


diagram	<p>The diagram shows the PostalCode element as a simple content type, which is a restriction of xs:string. The description is: "The postal code for the postal address".</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>10</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	10	
Kind	Value	Annotation								
minLength	1									
maxLength	10									
annotation	documentation The postal code for the postal address									
source	<pre><xs:element name="PostalCode"> <xs:annotation> <xs:documentation>The postal code for the postal address</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>									

```


<xs:minLength value="1"/>
<xs:maxLength value="10"/>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **PreArrangedPath**


diagram	 <p>Path offered by the IMs with pre-defined frequencies, times of departures and destinations and routings suitable for freight transport services.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	element PlannedJourneyLocation									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>9</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	9	
Kind	Value	Annotation								
minLength	1									
maxLength	9									
annotation	documentation Path offered by the IMs with pre-defined frequencies, times of departures and destinations and routings suitable for freight transport services.									
source	<pre> <xs:element name="PreArrangedPath"> <xs:annotation> <xs:documentation>Path offered by the IMs with pre-defined frequencies, times of departures and destinations and routings suitable for freight transport services. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="9"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **PreviousConsignmentNumber**


diagram	 <p>This element shows the previous Reference number assigned to a consignment by ...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	ConsignmentIdent
properties	content complex
used by	element WIMO Dataset/ConsignmentLevelData
annotation	documentation This element shows the previous Reference number assigned to a consignment by a lead RU
source	<pre> <xs:element name="PreviousConsignmentNumber" type="ConsignmentIdent"> <xs:annotation> </pre>

	<pre><xs:documentation>This element shows the previous Reference number assigned to a consignment by a lead RU</xs:documentation> </xs:annotation> </xs:element></pre>
--	--

element **PreviousResponsibleRU**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	element WIMO Dataset/ConsignmentLevelData												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	<p>documentation</p> <p>This element identifies the RU, who was responsible for the train operation on the journey section before an interchange point</p>												
source	<pre><xs:element name="PreviousResponsibleRU" type="CompanyCode"> <xs:annotation> <xs:documentation>This element identifies the RU, who was responsible for the train operation on the journey section before an interchange point</xs:documentation> </xs:annotation> </xs:element></pre>												

element **PrimaryLocationName**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
used by	complexType LocationIdent									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	<p>documentation</p> <p>Location Name in an offication language of the Country using the ISO Unicode alphabet</p>									
source	<pre><xs:element name="PrimaryLocationName" type="FreeText"> <xs:annotation> <xs:documentation>Location Name in an offication language of the Country using the ISO Unicode alphabet</xs:documentation> </xs:annotation> </xs:element></pre>									

	<code></xs:element></code>
--	----------------------------------

element ProductionStation


diagram	<p>The diagram shows a ProductionStation element box containing two sub-elements: Location and RP_Code. The Location element is described as 'Identifies a Location using a LocationIdent'. The RP_Code element is described as 'Routing point code of the production station of the acceptance or delivery poi...'. A dashed line connects the ProductionStation box to the RP_Code box.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location RP Code
used by	elements ConsignmentOrderMessage/COMS/COM/AcceptancePoint ConsignmentOrderMessage/COMS/COM/DeliveryPoint
annotation	documentation Details of production station serving the point, this element is used if the productional station differs from the commercial station
source	<pre><xs:element name="ProductionStation"> <xs:annotation> <xs:documentation>Details of production station serving the point, this element is used if the productional station differs from the commercial station</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="RP_Code" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element PushPullTrain

diagram	<p>The diagram shows a PushPullTrain element box. Below it, text indicates: 'Indicates that the train can change direction without shunting. This flag can be used only with TractionMode 1X, 2X, 5X.'</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element PlannedTrainData
annotation	documentation Indicates that the train can change direction without shunting. This flag can be used only with TractionMode 1X, 2X, 5X.
source	<pre><xs:element name="PushPullTrain" type="xs:boolean"> <xs:annotation> <xs:documentation>Indicates that the train can change direction without shunting. This flag can be used only with TractionMode 1X, 2X, 5X.</xs:documentation></pre>

	<pre></xs:annotation> </xs:element></pre>
--	---

element **Quantity**

diagram	 <p>Amount of the loading tackles of the specified type.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
used by	elements ConsignmentOrderMessage/COMS/COM/AttachedDocuments LoadingTackles									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation Amount of the loading tackles of the specified type.									
source	<pre><xs:element name="Quantity"> <xs:annotation> <xs:documentation>Amount of the loading tackles of the specified type.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ReceiptConfirmationMessage**


<p>diagram</p>	<p>MessageHeader Used for all messa...</p> <p>Identifiers</p> <p>ReferenceTrainIDSubCalendar ReferenceTrainIDSubCalendar contains all days of Reference Train (TRIDv00) for days provided in PlannedCalendar. The days in PlannedCalendar may shifted depending on value in element OffsetToReference, ie the following condition must always be true : ReferenceTrainIDSubCalendar + Offs...</p> <p>TypeOfRequest Enumeration for 3 different basic types of the processes in the planning: Study (1), Request (2), Modification (...)</p> <p>TypeOfInformation Enumeration indicating to which process step / process type in the planning does the message belong: path study; pre-arranged/catalogue path; (draft) offer; final offer; booked; deleted; utilisation notification; confirmation of...</p> <p>AffectedSection 0..∞ Indication for the recipient if not the entire path is affected, e.g. in case of a partial cancelation for the last part of the path</p> <p>AffectedLocation Affected locati...</p> <p>Remarks Free Form ...</p> <p>InternalReferenceIdentifier The link to the IM System Refer...</p> <p>RelatedReference Identifies the message to which the actual message refers</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader Identifiers ReferenceTrainIDSubCalendar TypeOfRequest TypeOfInformation AffectedSection AffectedLocation Remarks InternalReferenceIdentifier RelatedReference</p>
<p>annotation</p>	<p>documentation This message is sent from the recipient of a message to the original sender of the message when the required response cannot be made available within 5 minutes as defined by the TAF TSI chapter 4.4. The identifiers in this message have to be same as those that have come from sender. The same applies to type-of-request and type-of-information.</p>
<p>source</p>	<pre><xs:element name="ReceiptConfirmationMessage"> <xs:annotation> <xs:documentation>This message is sent from the recipient of a message to the original sender of the message when the required response cannot be made available within 5 minutes as defined by the TAF TSI chapter 4.4. The identifiers in this message have to be same as those that have come from sender. The same applies to type-of-request and type-of-information.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:element ref="Identifiers" minOccurs="0"/> <xs:element ref="ReferenceTrainIDSubCalendar" minOccurs="0"/> <xs:element ref="TypeOfRequest" minOccurs="0"/> <xs:element ref="TypeOfInformation" minOccurs="0"/> <xs:element ref="AffectedSection" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="AffectedLocation" minOccurs="0"/> <xs:element ref="Remarks" minOccurs="0"/> <xs:element ref="InternalReferenceIdentifier" minOccurs="0"/> <xs:element ref="RelatedReference"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---


element Recipient

diagram						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3					
type	extension of CompanyCode					
properties	content complex					
used by	element MessageHeader					
facets	Kind	Value	Annotation			
	minLength	4				
	maxLength	4				
	pattern	[0-9A-Z]{4}				
attributes	Name	Type	Use	Default	Fixed	Annotation documentation
	CI_InstanceNumber	Numeric2-2				Number of a Common Interface Instance for the same Company
annotation	documentation Receiver of the message					
source	<pre> <xs:element name="Recipient"> <xs:annotation> <xs:documentation>Receiver of the message</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="CompanyCode"> <xs:attribute ref="CI_InstanceNumber"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element> </pre>					

element **ReferencedLocationDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements DelayEventReport InterruptionPoint TrainAtLocation TrainLocationReport
annotation	documentation Reference to original planned Date and Time agreed by all involved IMs and RUs.
source	<pre><xs:element name="ReferencedLocationDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Reference to original planned Date and Time agreed by all involved IMs and RUs. </xs:documentation> </xs:annotation> </xs:element></pre>

element **ReferenceNumbers**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MovementReferenceNumber ARC
used by	elements ITU Details Wagons/WagonDetails
annotation	documentation This element contains references according to NCTS or EMCS law. This element MUST NOT be empty!
source	<pre><xs:element name="ReferenceNumbers"> <xs:annotation> <xs:documentation>This element contains references according to NCTS or EMCS law. This element MUST NOT be empty!</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence maxOccurs="99"> <xs:element name="MovementReferenceNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Movement Reference Number according to NCTS</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MRN_Type"/> <xs:element name="MRN_Number"> <xs:annotation> <xs:documentation>Movement reference number. Data element in accordance with Regulation (EC) 1875/2006.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>


	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="21"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> <xs:element name="ARC" minOccurs="0"> <xs:annotation> <xs:documentation>Administrative Reference CodeEMCS (Excise Movement and Control System)</xs:documentation> <xs:documentation>CODE: EU (EC) No 684/2009</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="21"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **ReferenceNumbers/MovementReferenceNumber**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	MRN_Type MRN Number
annotation	documentation Movement Reference Number according to NCTS
source	<pre> <xs:element name="MovementReferenceNumber" minOccurs="0"> <xs:annotation> <xs:documentation>Movement Reference Number according to NCTS</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MRN_Type"/> <xs:element name="MRN_Number"> <xs:annotation> <xs:documentation>Movement reference number. Data element in accordance with Regulation (EC) 1875/2006.</xs:documentation> </xs:annotation> </pre>

	<pre> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="21"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **ReferenceNumbers/MovementReferenceNumber/MRN_Number**

diagram	 <p>MRN_Num...</p> <p>Movement reference number. Data element in accordance with Regulation (EC) 1875/2006.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>21</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	21	
Kind	Value	Annotation								
minLength	1									
maxLength	21									
annotation	<p>documentation</p> <p>Movement reference number. Data element in accordance with Regulation (EC) 1875/2006.</p>									
source	<pre> <xs:element name="MRN_Number"> <xs:annotation> <xs:documentation>Movement reference number. Data element in accordance with Regulation (EC) 1875/2006.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="21"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **ReferenceNumbers/ARC**

diagram	 <p>ARC</p> <p>Administrative Reference CodeEMCS (Excise Movement and Control Sy...</p>						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple
minOcc	0						
maxOcc	1						
content	simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>21</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	21	
Kind	Value	Annotation					
length	21						
annotation	<p>documentation</p> <p>Administrative Reference CodeEMCS (Excise Movement and Control System)</p>						

	documentation CODE: EU (EC) No 684/2009
source	<pre><xs:element name="ARC" minOccurs="0"> <xs:annotation> <xs:documentation>Administrative Reference CodeEMCS (Excise Movement and Control System)</xs:documentation> <xs:documentation>CODE: EU (EC) No 684/2009</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="21"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **ReferenceOTN**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	OperationalTrainNumberIdentifier
used by	elements ChangeofTrackMessage TrainAtLocation TrainCompositionMessage TrainDelayCauseMessage TrainJourneyModificationMessage TrainReadyMessage TrainRunningForecastMessage TrainRunningInformationMessage TrainRunningInterruptionMessage
source	<pre><xs:element name="ReferenceOTN"> <xs:complexType> <xs:sequence> <xs:element ref="OperationalTrainNumberIdentifier"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **ReferenceTrainIDSubCalendar**

diagram	<p>Structure BitmapDays must be provided if ValidityPeriod of associated calendar contains more than one day; it is optional otherwise.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	BitmapDays ValidityPeriod
used by	elements PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage ReceiptConfirmationMessage
annotation	documentation ReferenceTrainIDSubCalendar contains all days of Reference Train (TRIDv00) for days provided in PlannedCalendar. The days in PlannedCalendar may shifted depending on value in element OffsetToReference, ie the following condition must always be true : ReferenceTrainIDSubCalendar + OffsetToReference = PlannedCalendar"

source	<pre> <xs:element name="ReferenceTrainIDSubCalendar"> <xs:annotation> <xs:documentation>ReferenceTrainIDSubCalendar contains all days of Reference Train (TRIDv00) for days provided in PlannedCalendar. The days in PlannedCalendar may shifted depending on value in element OffsetToReference, ie the following condition must always be true : ReferenceTrainIDSubCalendar + OffsetToReference = PlannedCalendar"</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="BitmapDays" minOccurs="0"/> <xs:element ref="ValidityPeriod"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--------	--

element **RelatedIdentifier**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
used by	element RelatedReference									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
source	<pre><xs:element name="RelatedIdentifier" type="FreeText"/></pre>									

element **RelatedPlannedTransportIdentifiers**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>CompositIdentifierPlannedType</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>ObjectType Company Core Variant TimetableYear StartDate</p>
<p>used by</p>	<p>element Identifiers</p>
<p>source</p>	<pre><xs:element name="RelatedPlannedTransportIdentifiers" type="CompositIdentifierPlannedType"/></pre>

element **RelatedReference**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>RelatedType RelatedIdentifier RelatedSenderReference RelatedMessageDateTime</p>
<p>used by</p>	<p>elements ReceiptConfirmationMessage WagonDepartureNoticeMessage WagonDeviationMessage WagonETI ETA Message</p>
<p>annotation</p>	<p>documentation Identifies the message to which the actual message refers</p>
<p>source</p>	<pre><xs:element name="RelatedReference"> <xs:annotation> <xs:documentation>Identifies the message to which the actual message</pre>

	<pre> refers</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="RelatedType" type="MessageCode"/> <xs:element ref="RelatedIdentifier"/> <xs:element ref="RelatedSenderReference" minOccurs="0"/> <xs:element name="RelatedMessageDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date Time of related message. </xs:documentation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **RelatedReference/RelatedType**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	MessageCode									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	9999									
source	<code><xs:element name="RelatedType" type="MessageCode"/></code>									

element **RelatedReference/RelatedMessageDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation Date Time of related message.
source	<pre> <xs:element name="RelatedMessageDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Date Time of related message. </xs:documentation> </xs:annotation> </xs:element> </pre>

element **RelatedSenderReference**


diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple
used by	element RelatedReference
facets	Kind Value Annotation minLength 1 maxLength 255
annotation	documentation Sender reference given by the Sender
source	<pre><xs:element name="RelatedSenderReference" type="FreeText"> <xs:annotation> <xs:documentation>Sender reference given by the Sender</xs:documentation> </xs:annotation> </xs:element></pre>


element **RelatedTransportOperationalIdentifiers**

diagram	<p>The diagram illustrates the structure of the RelatedTransportOperationalIdentifiers element. It is composed of a CompositIdentifierOperationalType, which is a composite type containing several sub-elements: ObjectType (Provides a possibility for differentiation between the objects: Train (TR), Route (RO), Path (PA), Case Reference (CR) and Path Request (PR)), Compa... (Identifies a railway company (RU or IM)), Core (It is the main part of identifier and is determined by the company that creates it), Variant (The variant shows a relationship between two identifiers referring to the same business case), TimetableYear (Refers to the timetable period in which the business will be carried out), and StartDate (Is only used in the operational phase and refers to the date where the single train will start the train journey).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CompositIdentifierOperationalType
properties	content complex
children	ObjectType Company Core Variant TimetableYear StartDate
used by	element TrainOperationalIdentification
source	<pre><xs:element name="RelatedTransportOperationalIdentifiers" type="CompositIdentifierOperationalType"/></pre>


element Remarks

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	FreeText
properties	content simple
used by	elements DelayCauseTime InterruptionPoint ReceiptConfirmationMessage TrainJourneyModificationMessage
facets	Kind Value Annotation minLength 1 maxLength 255
annotation	documentation Free Form Text
source	<pre><xs:element name="Remarks" type="FreeText"> <xs:annotation> <xs:documentation>Free Form Text</xs:documentation> </xs:annotation> </xs:element></pre>

element RequestedCalendar

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	BitmapDays ValidityPeriod
used by	element PathInformation
source	<pre><xs:element name="RequestedCalendar"> <xs:complexType> <xs:sequence> <xs:element ref="BitmapDays" minOccurs="0"/> <xs:element ref="ValidityPeriod"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element RequestedPeriod

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

properties	content complex
children	StartDateTime EndDateTime
annotation	documentation Date/Time period of a request
source	<pre> <xs:element name="RequestedPeriod"> <xs:annotation> <xs:documentation>Date/Time period of a request</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="StartDateTime"/> <xs:element ref="EndDateTime"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element RequestedTimeframe

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	StartDateTime EndDateTime
annotation	documentation To specify a time period being requested
source	<pre> <xs:element name="RequestedTimeframe"> <xs:annotation> <xs:documentation>To specify a time period being requested</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="StartDateTime" minOccurs="0"/> <xs:element ref="EndDateTime" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **ResponsibilityActualSection**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	ResponsibleRU ResponsibleIM
used by	element JourneySection
annotation	documentation This element identifies the responsible RU or IM for the actual path section
source	<pre><xs:element name="ResponsibilityActualSection"> <xs:annotation> <xs:documentation>This element identifies the responsible RU or IM for the actual path section</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="ResponsibleRU"/> <xs:element ref="ResponsibleIM"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **ResponsibilityNextSection**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	ResponsibleRU ResponsibleIM
used by	element JourneySection

annotation	documentation This element identifies the responsible RU and IM for the following path section
source	<pre><xs:element name="ResponsibilityNextSection"> <xs:annotation> <xs:documentation>This element identifies the responsible RU and IM for the following path section</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="ResponsibleRU"/> <xs:element ref="ResponsibleIM"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **ResponsibleApplicant**


diagram	 <p>This element has to be used for the whole journey where the applicant has made the request</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of CompanyCode												
properties	content simple												
used by	element PlannedJourneyLocation												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation This element has to be used for the whole journey where the applicant has made the request												
source	<pre><xs:element name="ResponsibleApplicant"> <xs:annotation> <xs:documentation>This element has to be used for the whole journey where the applicant has made the request</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="CompanyCode"/> </xs:simpleType> </xs:element></pre>												

element **ResponsibleIM**

diagram	 <p>IM Responsible for Reporting. For Path Requests, this element has to be used - in the first journey location (origin of train) - in journey locations (could even be a network border without stopping of the train) in case where the IM on the oncoming section changes from the legal point of view. This means, the new IM has the legal responsibility for t...</p>
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	elements LocationPrimaryInformation PlannedJourneyLocation ResponsibilityActualSection ResponsibilityNextSection												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	<p>documentation</p> <p>IM Responsible for Reporting.</p> <p>For Path Requests, this element has to be used</p> <ul style="list-style-type: none"> - in the first journey location (origin of train) - in journey locations (could even be a network border without stopping of the train) in case where the IM on the oncoming section changes from the legal point of view. This means, the new IM has the legal responsibility for the oncoming section. 												
source	<pre><xs:element name="ResponsibleIM" type="CompanyCode"> <xs:annotation> <xs:documentation>IM Responsible for Reporting. For Path Requests, this element has to be used - in the first journey location (origin of train) - in journey locations (could even be a network border without stopping of the train) in case where the IM on the oncoming section legal changes from the legal point of view. This means, the new IM has the legal responsibility for the oncoming section. </xs:documentation> </xs:annotation> </xs:element></pre>												

element **ResponsibleRU**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	elements ExceptionPoint PlannedJourneyLocation ResponsibilityActualSection ResponsibilityNextSection TrainDelayCauseMessage TrainReadyMessage TrainRunningForecastMessage TrainRunningInformationMessage TrainRunningInterruptionMessage												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	<p>documentation</p> <p>RU Responsible for the physical operation of the train or wagon</p>												
source	<pre><xs:element name="ResponsibleRU" type="CompanyCode"> <xs:annotation> <xs:documentation>RU Responsible for the physical operation of the train or wagon</xs:documentation> </xs:annotation> </xs:element></pre>												

```
</xs:element>
```

element **RestrictionsDueToLoadOrDamage**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	RestrictionCodes		
properties	content	simple	
used by	element	WagonOperationalData	
facets	Kind	Value	Annotation
	enumeration	07	documentation F - Shunt only when hand brake operable with ground staff
	enumeration	08	documentation F - Tank wagon loaded with liquid
	enumeration	09	documentation F - Wagon loaded with people
	enumeration	11	documentation F - Wagon other than bogie wagon with wheelbase of more than 9 metres
	enumeration	12	documentation F - Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres
	enumeration	13	documentation F - Bogie wagon with distance between wheels of more than 17,50 metres
	enumeration	15	documentation F - Wagon not allowed over the hump
	enumeration	16	documentation F - Do not fly shunt or gravity shunt (3 red triangles)
	enumeration	18	documentation F - Must not use active braking equipment
	enumeration	25	documentation F - Gas carrying tank wagon with orange side stripe
	enumeration	30	documentation P (+F) - CCS fault (see CCS coding list)
	enumeration	31	documentation P (+F) - Braking system fault
	enumeration	32	documentation P (+F) - Wheelset, bogie fault
	enumeration	33	documentation P (+F) - Headlighting or back lighting fault
	enumeration	34	documentation P (+F) - Front glass broken
	enumeration	35	documentation P (+F) - Horn fault
	enumeration	36	documentation P (+F) - Radio fault
	enumeration	37	documentation P (+F) - Energy supply fault
	enumeration	38	documentation P (+F) - Traction or motor fault
	enumeration	39	documentation P - Access door fault
	enumeration	41	documentation F - Place this wagon at the front of the train
	enumeration	42	documentation

	<p>enumeration 50 F - Place this wagon at the rear of the train documentation</p> <p>enumeration 52 P (+F) - Speed restriction documentation</p> <p>enumeration 61 P (+F) - Diesel locomotive instead of electric locomotive documentation</p> <p>enumeration 62 F - Wagon forming part of a consignment of several wagons documentation</p> <p>enumeration 63 F - Wagon forming part of a group of wagons from which it must not be separated documentation</p> <p>enumeration 68 F (+P) - Special consignment or (for Passengers trains) loading/cinematic gauge larger than the planned one documentation</p> <p>enumeration 70 F - First or last wagon of a wagon group from which it must not be separated documentation</p> <p>enumeration 71 F - Shunt with care (1 red triangle) documentation</p> <p>enumeration 71 F - Shunt with special care (2 red triangle) documentation</p> <p>enumeration 90 P - Train planned with passengers operated without passengers documentation</p> <p>enumeration 91 P - Train planned without passengers operated with passengers documentation</p> <p>enumeration 92 P - Train planned with hauled rolling stock and operated without any coaches (light engine) documentation</p> <p>enumeration 94 F - Gas carrying wagon without orange side stripe documentation</p> <p>enumeration 99 P - Other documentation</p>
annotation	<p>documentation</p> <p>These are possible restrictions applicable in the originating country to shunting operations in stations and to main-line movements on account of the nature of the load. Coding in Restriction Codes (according to UIC Leaflet 920-13)</p>
source	<pre><xs:element name="RestrictionsDueToLoadOrDamage" type="RestrictionCodes"> <xs:annotation> <xs:documentation>These are possible restrictions applicable in the originating country to shunting operations in stations and to main-line movements on account of the nature of the load. Coding in Restriction Codes (according to UIC Leaflet 920-13) </xs:documentation> </xs:annotation> </xs:element></pre>

element **RevisedRequest**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element PathDetailsRefusedMessage
annotation	<p>documentation</p> <p>Indication for the IM whether wait because the RU will send a revised request soon or to make an alternative offer.</p>
source	<pre><xs:element name="RevisedRequest" type="xs:boolean"></pre>

	<pre> <xs:annotation> <xs:documentation>Indication for the IM whether wait because the RU will send a revised request soon or to make an alternative offer.</xs:documentation> </xs:annotation> </xs:element> </pre>
--	--

element **RID**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Law DangerousGoodsIndication TechnicalDescription ProperShippingName SpecialProvisionsRID AdditionalProvisionsRID ActionRequiredFromCarrier WeightNettoExplosiveMass ClassificationCode EmptyPackingCode
used by	element Goods
annotation	documentation The requirement (optional/mandatory) of the RID detail tags depend on the dangerous good and the regarding RID regulations. In contrast to the element "DangerousGoodsIndication" which only provides information to be provided

	to the IM according to chapter 1.4 RID, "RID" contains all information demanded in chapter 5.4 RID in order to provide all information used for RUs
source	<pre> <xs:element name="RID"> <xs:annotation> <xs:documentation>The requirement (optional/mandatory) of the RID detail tags depend on the dangerous good and the regarding RID regulations. In contrast to the element "DangerousGoodsIndication" which only provides information to be provided to the IM according to chapter 1.4 RID, "RID" contains all information demanded in chapter 5.4 RID in order to provide all information used for RUs</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="Law"> <xs:annotation> <xs:documentation>The law after which the RID data are declared.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:enumeration value="2013"/> <xs:enumeration value="2015"/> <xs:enumeration value="2017"/> <xs:enumeration value="2019"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="DangerousGoodsIndication"/> <xs:element name="TechnicalDescription" minOccurs="0"> <xs:annotation> <xs:documentation>The Technical Description is an approved chemical or biological name and has to be present if the dangerous good has assigned a special provision 274 according to RID chapter 3.2, table A, column 6.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ProperShippingName" minOccurs="0"> <xs:annotation> <xs:documentation>The official name of this dangerous good according to the RID chapter 3.2, table A, column 2 Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING"</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

<xs:element name="SpecialProvisionsRID" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Used for any global special provisions of
chapter 5.4, that are not treated by other elments in this
message</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="350"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="AdditionalProvisionsRID" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Used for any class related special provisions of
chapter 5.4, that are not treated by other elments in this
message</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="350"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ActionRequiredFromCarrier" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Special action required by the carrier according
to chapter 5.4.1.2.5.2 RID</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="350"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="WeightNettoExplosiveMass" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Special provision only necessary and allowed for
Class 1 (kg)- the total net mass of explosive substance (RID
5.4.1.2.1).</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:decimal">
      <xs:minInclusive value="0"/>
      <xs:fractionDigits value="1"/>
      <xs:totalDigits value="8"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ClassificationCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>The Classification Code of the dangerous good
according to the RID chapter 3.2, table A, column 3b. Mandatory for Class 1
- optional, but possibly for all the other classes.</xs:documentation>
    <xs:documentation>CODE: OTIF RID-Specification</xs:documentation>
  </xs:annotation>

```

```

</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="4">
      <xs:annotation>
        <xs:documentation>present only with class
1</xs:documentation>
      </xs:annotation>
    </xs:maxLength>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="EmptyPackingCode" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Code of empty packing as described in RID
5.4.1.1.6.2</xs:documentation>
    <xs:documentation>CODE: OTIF RID-Specification, element EMPTY has
been added as 'dummy' until the code list has been finished and approved.
</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="01">
        <xs:annotation>
          <xs:documentation>EMPTY PACKAGING</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="02">
        <xs:annotation>
          <xs:documentation>EMPTY CONTAINER</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="03">
        <xs:annotation>
          <xs:documentation>EMPTY IBC</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="04">
        <xs:annotation>
          <xs:documentation>EMPTY LARGE PACKAGING</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="05">
        <xs:annotation>
          <xs:documentation>EMPTY TANK-VEHICLE</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="06">
        <xs:annotation>
          <xs:documentation>EMPTY TANK-WAGON</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
      <xs:enumeration value="07">
        <xs:annotation>
          <xs:documentation>EMPTY DETACHABLE TANK</xs:documentation>
        </xs:annotation>
      </xs:enumeration>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

```


```

<xs:enumeration value="08">
  <xs:annotation>
    <xs:documentation>EMPTY DEMOUNTABLE TANK</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="09">
  <xs:annotation>
    <xs:documentation>EMPTY TANK-CONTAINER</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>EMPTY PORTABLE TANK</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>EMPTY BATTERY-VEHICLE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>EMPTY BATTERY-WAGON</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>EMPTY LARGE CONTAINER WITH MULTIPLE LINKED
ELEMENTS</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>EMPTY VEHICLE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>EMPTY WAGON</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>EMPTY RECEPTACLE le
1000L</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>EMPTY RECEPTACLE gt
1000L</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>EMPTY</xs:documentation>
  </xs:annotation>
</xs:enumeration>


```

	<pre> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element RID/Law


diagram																
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:int															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>2013</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2015</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2017</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2019</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	2013		enumeration	2015		enumeration	2017		enumeration	2019	
Kind	Value	Annotation														
enumeration	2013															
enumeration	2015															
enumeration	2017															
enumeration	2019															
annotation	documentation The law after which the RID data are declared.															
source	<pre> <xs:element name="Law"> <xs:annotation> <xs:documentation>The law after which the RID data are declared.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:enumeration value="2013"/> <xs:enumeration value="2015"/> <xs:enumeration value="2017"/> <xs:enumeration value="2019"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>															

element RID/TechnicalDescription

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	<table border="1"> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	minOcc	0	maxOcc	1	content	simple
minOcc	0						
maxOcc	1						
content	simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1	
Kind	Value	Annotation					
minLength	1						


	maxLength 350
annotation	documentation The Technical Description is an approved chemical or biological name and has to be present if the dangerous good has assigned a special provision 274 according to RID chapter 3.2, table A, column 6.
source	<pre><xs:element name="TechnicalDescription" minOccurs="0"> <xs:annotation> <xs:documentation>The Technical Description is an approved chemical or biological name and has to be present if the dangerous good has assigned a special provision 274 according to RID chapter 3.2, table A, column 6.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **RID/ProperShippingName**


diagram	 <p>The official name of this dangerous good according to the RID chapter 3.2, table A, column 2 Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE", "EMPTY RECEPTACLE &lt;=1000L, "EMPTY IBC" ...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>350</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	350	
Kind	Value	Annotation								
minLength	1									
maxLength	350									
annotation	documentation The official name of this dangerous good according to the RID chapter 3.2, table A, column 2 Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE", "EMPTY RECEPTACLE <=1000L, "EMPTY IBC" or "EMPTY LARGE PACKAGING"									
source	<pre><xs:element name="ProperShippingName" minOccurs="0"> <xs:annotation> <xs:documentation>The official name of this dangerous good according to the RID chapter 3.2, table A, column 2 Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE", "EMPTY RECEPTACLE &lt;=1000L, "EMPTY IBC" or "EMPTY LARGE PACKAGING"</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

	<code></xs:element></code>
--	----------------------------------

element RID/SpecialProvisionsRID

diagram	 <p>SpecialProvisionsRID Used for any global special provisions of chapter 5.4, that are not treated by other elements in this message</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 350
annotation	documentation Used for any global special provisions of chapter 5.4, that are not treated by other elements in this message
source	<pre><xs:element name="SpecialProvisionsRID" minOccurs="0"> <xs:annotation> <xs:documentation>Used for any global special provisions of chapter 5.4, that are not treated by other elements in this message</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element RID/AdditionalProvisionsRID

diagram	 <p>AdditionalProvisionsRID Used for any class related special provisions of chapter 5.4, that are not treated by other elements in this message</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 1 maxLength 350
annotation	documentation Used for any class related special provisions of chapter 5.4, that are not treated by other elements in this message
source	<pre><xs:element name="AdditionalProvisionsRID" minOccurs="0"> <xs:annotation> <xs:documentation>Used for any class related special provisions of chapter 5.4, that are not treated by other elements in this message</xs:documentation> </xs:annotation> </xs:element></pre>

	<pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **RID/ActionRequiredFromCarrier**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>350</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	350	
Kind	Value	Annotation								
minLength	1									
maxLength	350									
annotation	documentation Special action required by the carrier according to chapter 5.4.1.2.5.2 RID									
source	<pre> <xs:element name="ActionRequiredFromCarrier" minOccurs="0"> <xs:annotation> <xs:documentation>Special action required by the carrier according to chapter 5.4.1.2.5.2 RID</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="350"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **RID/WeightNettoExplosiveMass**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:decimal												
properties	minOcc 0 maxOcc 1 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>totalDigits</td> <td>8</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		totalDigits	8		fractionDigits	1	
Kind	Value	Annotation											
minInclusive	0												
totalDigits	8												
fractionDigits	1												


annotation	documentation Special provision only necessary and allowed for Class 1 (kg)- the total net mass of explosive substance (RID 5.4.1.2.1).
source	<pre><xs:element name="WeightNettoExplosiveMass" minOccurs="0"> <xs:annotation> <xs:documentation>Special provision only necessary and allowed for Class 1 (kg)- the total net mass of explosive substance (RID 5.4.1.2.1).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="0"/> <xs:fractionDigits value="1"/> <xs:totalDigits value="8"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **RID/ClassificationCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td>documentation present only with class 1</td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	4	documentation present only with class 1
Kind	Value	Annotation								
minLength	1									
maxLength	4	documentation present only with class 1								
annotation	documentation The Classification Code of the dangerous good according to the RID chapter 3.2, table A, column 3b. Mandatory for Class 1 - optional, but possibly for all the other classes. documentation CODE: OTIF RID-Specification									
source	<pre><xs:element name="ClassificationCode" minOccurs="0"> <xs:annotation> <xs:documentation>The Classification Code of the dangerous good according to the RID chapter 3.2, table A, column 3b. Mandatory for Class 1 - optional, but possibly for all the other classes.</xs:documentation> <xs:documentation>CODE: OTIF RID-Specification</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="4"> <xs:annotation> <xs:documentation>present only with class 1</xs:documentation> </xs:annotation> </xs:maxLength> </xs:restriction></pre>									

```
</xs:simpleType>
</xs:element>
```

element **RID/EmptyPackingCode**

diagram																																																										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																									
type	restriction of xs:string																																																									
properties	minOcc 0 maxOcc 1 content simple																																																									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>01</td><td>documentation EMPTY PACKAGING</td></tr> <tr><td>enumeration</td><td>02</td><td>documentation EMPTY CONTAINER</td></tr> <tr><td>enumeration</td><td>03</td><td>documentation EMPTY IBC</td></tr> <tr><td>enumeration</td><td>04</td><td>documentation EMPTY LARGE PACKAGING</td></tr> <tr><td>enumeration</td><td>05</td><td>documentation EMPTY TANK-VEHICLE</td></tr> <tr><td>enumeration</td><td>06</td><td>documentation EMPTY TANK-WAGON</td></tr> <tr><td>enumeration</td><td>07</td><td>documentation EMPTY DETACHABLE TANK</td></tr> <tr><td>enumeration</td><td>08</td><td>documentation EMPTY DEMOUNTABLE TANK</td></tr> <tr><td>enumeration</td><td>09</td><td>documentation EMPTY TANK-CONTAINER</td></tr> <tr><td>enumeration</td><td>10</td><td>documentation EMPTY PORTABLE TANK</td></tr> <tr><td>enumeration</td><td>11</td><td>documentation EMPTY BATTERY-VEHICLE</td></tr> <tr><td>enumeration</td><td>12</td><td>documentation EMPTY BATTERY-WAGON</td></tr> <tr><td>enumeration</td><td>13</td><td>documentation EMPTY LARGE CONTAINER WITH MULTIPLE LINKED ELEMENTS</td></tr> <tr><td>enumeration</td><td>14</td><td>documentation EMPTY VEHICLE</td></tr> <tr><td>enumeration</td><td>15</td><td>documentation EMPTY WAGON</td></tr> <tr><td>enumeration</td><td>16</td><td>documentation EMPTY RECEPTACLE le 1000L</td></tr> <tr><td>enumeration</td><td>17</td><td>documentation EMPTY RECEPTACLE gt 1000L</td></tr> <tr><td>enumeration</td><td>18</td><td>documentation EMPTY</td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	01	documentation EMPTY PACKAGING	enumeration	02	documentation EMPTY CONTAINER	enumeration	03	documentation EMPTY IBC	enumeration	04	documentation EMPTY LARGE PACKAGING	enumeration	05	documentation EMPTY TANK-VEHICLE	enumeration	06	documentation EMPTY TANK-WAGON	enumeration	07	documentation EMPTY DETACHABLE TANK	enumeration	08	documentation EMPTY DEMOUNTABLE TANK	enumeration	09	documentation EMPTY TANK-CONTAINER	enumeration	10	documentation EMPTY PORTABLE TANK	enumeration	11	documentation EMPTY BATTERY-VEHICLE	enumeration	12	documentation EMPTY BATTERY-WAGON	enumeration	13	documentation EMPTY LARGE CONTAINER WITH MULTIPLE LINKED ELEMENTS	enumeration	14	documentation EMPTY VEHICLE	enumeration	15	documentation EMPTY WAGON	enumeration	16	documentation EMPTY RECEPTACLE le 1000L	enumeration	17	documentation EMPTY RECEPTACLE gt 1000L	enumeration	18	documentation EMPTY
Kind	Value	Annotation																																																								
enumeration	01	documentation EMPTY PACKAGING																																																								
enumeration	02	documentation EMPTY CONTAINER																																																								
enumeration	03	documentation EMPTY IBC																																																								
enumeration	04	documentation EMPTY LARGE PACKAGING																																																								
enumeration	05	documentation EMPTY TANK-VEHICLE																																																								
enumeration	06	documentation EMPTY TANK-WAGON																																																								
enumeration	07	documentation EMPTY DETACHABLE TANK																																																								
enumeration	08	documentation EMPTY DEMOUNTABLE TANK																																																								
enumeration	09	documentation EMPTY TANK-CONTAINER																																																								
enumeration	10	documentation EMPTY PORTABLE TANK																																																								
enumeration	11	documentation EMPTY BATTERY-VEHICLE																																																								
enumeration	12	documentation EMPTY BATTERY-WAGON																																																								
enumeration	13	documentation EMPTY LARGE CONTAINER WITH MULTIPLE LINKED ELEMENTS																																																								
enumeration	14	documentation EMPTY VEHICLE																																																								
enumeration	15	documentation EMPTY WAGON																																																								
enumeration	16	documentation EMPTY RECEPTACLE le 1000L																																																								
enumeration	17	documentation EMPTY RECEPTACLE gt 1000L																																																								
enumeration	18	documentation EMPTY																																																								
annotation	documentation Code of empty packing as described in RID 5.4.1.1.6.2 documentation CODE: OTIF RID-Specification, element EMPTY has been added as 'dummy' until the code list has been finished and approved.																																																									
source	<pre><xs:element name="EmptyPackingCode" minOccurs="0"> <xs:annotation> <xs:documentation>Code of empty packing as described in RID 5.4.1.1.6.2</xs:documentation></pre>																																																									

```

    <xs:documentation>CODE: OTIF RID-Specification, element EMPTY has been
    added as 'dummy' until the code list has been finished and approved.
  </xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:enumeration value="01">
      <xs:annotation>
        <xs:documentation>EMPTY PACKAGING</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="02">
      <xs:annotation>
        <xs:documentation>EMPTY CONTAINER</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="03">
      <xs:annotation>
        <xs:documentation>EMPTY IBC</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="04">
      <xs:annotation>
        <xs:documentation>EMPTY LARGE PACKAGING</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="05">
      <xs:annotation>
        <xs:documentation>EMPTY TANK-VEHICLE</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="06">
      <xs:annotation>
        <xs:documentation>EMPTY TANK-WAGON</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="07">
      <xs:annotation>
        <xs:documentation>EMPTY DETACHABLE TANK</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="08">
      <xs:annotation>
        <xs:documentation>EMPTY DEMOUNTABLE TANK</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="09">
      <xs:annotation>
        <xs:documentation>EMPTY TANK-CONTAINER</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="10">
      <xs:annotation>
        <xs:documentation>EMPTY PORTABLE TANK</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="11">
      <xs:annotation>


```

```

<xs:documentation>EMPTY BATTERY-VEHICLE</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>EMPTY BATTERY-WAGON</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>EMPTY LARGE CONTAINER WITH MULTIPLE LINKED
ELEMENTS</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>EMPTY VEHICLE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>EMPTY WAGON</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>EMPTY RECEPTACLE le 1000L</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>EMPTY RECEPTACLE gt 1000L</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>EMPTY</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **RollingRoadUnit**



namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	RollingRoadUnitDetails Goods SummaryOFGoodsWithSameRID
used by	element Wagons
annotation	documentation Describes the type and content of a Rolling road unit
source	<pre> <xs:element name="RollingRoadUnit"> <xs:annotation> <xs:documentation>Describes the type and content of a Rolling road unit</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="RollingRoadUnitDetails"> <xs:annotation> <xs:documentation>Details for Rolling Road units on wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LoadingStatus"/> <xs:element name="RollingRoadUnitType" default="HGZ" minOccurs="0"> <xs:annotation> <xs:documentation>Type of Rolling Road unit on Wagon</xs:documentation> <xs:documentation>CODE:</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="3"/> <xs:enumeration value="HGZ"> <xs:annotation> <xs:documentation>articulated lorry</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="SAL"> <xs:annotation> <xs:documentation>semi-trailer</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MW"> <xs:annotation> <xs:documentation>motor vehicle</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ANH"> <xs:annotation> </pre>

```

        <xs:documentation>trailer</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
  </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Vehicles" minOccurs="0" maxOccurs="2">
  <xs:annotation>
    <xs:documentation>List of vehicles loaded (i.e. truck and
trailer).</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="NumberPlate">
        <xs:annotation>
          <xs:documentation>Number plate of the
vehicle.</xs:documentation>
          <xs:documentation>READ: <br/> -
Consignee</xs:documentation>
          <xs:documentation>WRITE: <br/> -
Consignor</xs:documentation>
          <xs:documentation>AMEND: <br/> - Contractual carrier
<br/> - Successive carrier<br/> (With the agreement of the
consignor)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="10"/>
            <xs:minLength value="1"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="CountryCodeISO"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TareWeightVehicle" type="WeightValueKilo">
  <xs:annotation>
    <xs:documentation>Total weight [kg] of vehicle (truck and
trailer).</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="Haulier" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Information concerning the
haulier.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="Name">
        <xs:annotation>
          <xs:documentation>Name of haulier.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element ref="CountryCodeISO"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```



```

<xs:element name="Attendants" minOccurs="0" maxOccurs="2">
  <xs:annotation>
    <xs:documentation>Attendants during the
transport.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="LastName">
        <xs:annotation>
          <xs:documentation>Last name of
attendant.</xs:documentation>
          <xs:documentation>READ: <br/> -
Consignee</xs:documentation>
          <xs:documentation>WRITE: <br/> -
Consignor</xs:documentation>
          <xs:documentation>AMEND: <br/> - Contractual carrier
<br/> - Successive carrier <br/> (With the agreement of the
consignor)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="25"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="FirstName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Optional first name of the
attendant.</xs:documentation>
          <xs:documentation>READ: <br/> -
Consignee</xs:documentation>
          <xs:documentation>WRITE: <br/> -
Consignor</xs:documentation>
          <xs:documentation>AMEND: <br/> - Contractual carrier
<br/> - Successive carrier <br/> (With the agreement of the
consignor)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="15"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="Goods" maxOccurs="99">
  <xs:annotation/>
</xs:element>
<xs:element ref="SummaryOfGoodsWithSameRID" minOccurs="0"
maxOccurs="25"/>
</xs:sequence>
</xs:complexType>

```

</xs:element>

element **RollingRoadUnit/RollingRoadUnitDetails**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>LoadingStatus RollingRoadUnitType Vehicles TareWeightVehicle Haulier Attendants</p>
<p>annotation</p>	<p>documentation Details for Rolling Road units on wagon</p>
<p>source</p>	<pre> <xs:element name="RollingRoadUnitDetails"> <xs:annotation> <xs:documentation>Details for Rolling Road units on wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LoadingStatus"/> <xs:element name="RollingRoadUnitType" default="HGZ" minOccurs="0"> <xs:annotation> <xs:documentation>Type of Rolling Road unit on Wagon</xs:documentation> <xs:documentation>CODE:</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="3"/> <xs:enumeration value="HGZ"> <xs:annotation> <xs:documentation>articulated lorry</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="Vehicles" minOccurs="0" maxOccurs="2"> <xs:annotation> <xs:documentation>List of vehicles loaded (i.e. truck and trailer).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TareWeightVehicle"> <xs:annotation> <xs:documentation>Total weight [kg] of vehicle (truck and trailer).</xs:documentation> </xs:annotation> </xs:element> <xs:element name="Haulier"> <xs:annotation> <xs:documentation>Information concerning the haulier.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="Attendants" minOccurs="0" maxOccurs="2"> <xs:annotation> <xs:documentation>Attendants during the transport.</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

</xs:enumeration>
<xs:enumeration value="SAL">
  <xs:annotation>
    <xs:documentation>semi-trailer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="MW">
  <xs:annotation>
    <xs:documentation>motor vehicle</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ANH">
  <xs:annotation>
    <xs:documentation>trailer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="Vehicles" minOccurs="0" maxOccurs="2">
  <xs:annotation>
    <xs:documentation>List of vehicles loaded (i.e. truck and
trailer).</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="NumberPlate">
        <xs:annotation>
          <xs:documentation>Number plate of the
vehicle.</xs:documentation>
          <xs:documentation>READ: <br/> - Consignee</xs:documentation>
          <xs:documentation>WRITE: <br/> -
Consignor</xs:documentation>
          <xs:documentation>AMEND: <br/> - Contractual carrier <br/> -
Successive carrier<br/> (With the agreement of the
consignor)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="10"/>
            <xs:minLength value="1"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="CountryCodeISO"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TareWeightVehicle" type="WeightValueKilo">
  <xs:annotation>
    <xs:documentation>Total weight [kg] of vehicle (truck and
trailer).</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="Haulier" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Information concerning the
haulier.</xs:documentation>

```


```

</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element ref="Name">
      <xs:annotation>
        <xs:documentation>Name of haulier.</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element ref="CountryCodeISO"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Attendants" minOccurs="0" maxOccurs="2">
  <xs:annotation>
    <xs:documentation>Attendants during the
transport.</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="LastName">
        <xs:annotation>
          <xs:documentation>Last name of attendant.</xs:documentation>
          <xs:documentation>READ: <br/> - Consignee</xs:documentation>
          <xs:documentation>WRITE: <br/> -
Consignor</xs:documentation>
          <xs:documentation>AMEND: <br/> - Contractual carrier <br/> -
Successive carrier <br/> (With the agreement of the
consignor)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="25"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="FirstName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Optional first name of the
attendant.</xs:documentation>
          <xs:documentation>READ: <br/> - Consignee</xs:documentation>
          <xs:documentation>WRITE: <br/> -
Consignor</xs:documentation>
          <xs:documentation>AMEND: <br/> - Contractual carrier <br/> -
Successive carrier <br/> (With the agreement of the
consignor)</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:minLength value="1"/>
            <xs:maxLength value="15"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:sequence>

```

	<pre></xs:complexType> </xs:element></pre>
--	--

element **RollingRoadUnit/RollingRoadUnitDetails/RollingRoadUnitType**

diagram																						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																					
type	restriction of xs:string																					
properties	minOcc 0 maxOcc 1 content simple default HGZ																					
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>3</td> <td></td> </tr> <tr> <td>enumeration</td> <td>HGZ</td> <td>documentation articulated lorry</td> </tr> <tr> <td>enumeration</td> <td>SAL</td> <td>documentation semi-trailer</td> </tr> <tr> <td>enumeration</td> <td>MW</td> <td>documentation motor vehicle</td> </tr> <tr> <td>enumeration</td> <td>ANH</td> <td>documentation trailer</td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	3		enumeration	HGZ	documentation articulated lorry	enumeration	SAL	documentation semi-trailer	enumeration	MW	documentation motor vehicle	enumeration	ANH	documentation trailer
Kind	Value	Annotation																				
minLength	1																					
maxLength	3																					
enumeration	HGZ	documentation articulated lorry																				
enumeration	SAL	documentation semi-trailer																				
enumeration	MW	documentation motor vehicle																				
enumeration	ANH	documentation trailer																				
annotation	documentation Type of Rolling Road unit on Wagon documentation CODE: documentation READ: - Consignee documentation WRITE: - Consignor documentation AMEND: - Contractual carrier - Successive carrier (With the agreement of the consignor)																					
source	<pre><xs:element name="RollingRoadUnitType" default="HGZ" minOccurs="0"> <xs:annotation> <xs:documentation>Type of Rolling Road unit on Wagon</xs:documentation> <xs:documentation>CODE:</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="3"/> <xs:enumeration value="HGZ"> <xs:annotation> <xs:documentation>articulated lorry</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="SAL"> <xs:annotation> <xs:documentation>semi-trailer</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element></pre>																					


	<pre> </xs:annotation> </xs:enumeration> <xs:enumeration value="MW"> <xs:annotation> <xs:documentation>motor vehicle</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ANH"> <xs:annotation> <xs:documentation>trailer</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **RollingRoadUnit/RollingRoadUnitDetails/Vehicles**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 2 content complex
children	NumberPlate CountryCodeISO
annotation	documentation List of vehicles loaded (i.e. truck and trailer).
source	<pre> <xs:element name="Vehicles" minOccurs="0" maxOccurs="2"> <xs:annotation> <xs:documentation>List of vehicles loaded (i.e. truck and trailer).</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NumberPlate"> <xs:annotation> <xs:documentation>Number plate of the vehicle.</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="10"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="CountryCodeISO"/> </xs:sequence> </pre>

	<pre></xs:complexType> </xs:element></pre>
--	--

element **RollingRoadUnit/RollingRoadUnitDetails/Vehicles/NumberPlate**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>10</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	10	
Kind	Value	Annotation								
minLength	1									
maxLength	10									
annotation	<p>documentation Number plate of the vehicle.</p> <p>documentation READ:
 - Consignee</p> <p>documentation WRITE:
 - Consignor</p> <p>documentation AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</p>									
source	<pre><xs:element name="NumberPlate"> <xs:annotation> <xs:documentation>Number plate of the vehicle.</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="10"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **RollingRoadUnit/RollingRoadUnitDetails/TareWeightVehicle**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	WeightValueKilo												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	<p>documentation Total weight [kg] of vehicle (truck and trailer).</p>												

source	<pre><xs:element name="TareWeightVehicle" type="WeightValueKilo"> <xs:annotation> <xs:documentation>Total weight [kg] of vehicle (truck and trailer).</xs:documentation> </xs:annotation> </xs:element></pre>
--------	---

element **RollingRoadUnit/RollingRoadUnitDetails/Haulier**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	Name CountryCodeISO
annotation	documentation Information concerning the haulier.
source	<pre><xs:element name="Haulier" minOccurs="0"> <xs:annotation> <xs:documentation>Information concerning the haulier.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Name"> <xs:annotation> <xs:documentation>Name of haulier.</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="CountryCodeISO"/> </xs:sequence> </xs:complexType> </xs:element></pre>


element **RollingRoadUnit/RollingRoadUnitDetails/Attendants**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 2 content complex
children	LastName FirstName
annotation	documentation Attendants during the transport.
source	<pre><xs:element name="Attendants" minOccurs="0" maxOccurs="2"></pre>


```


<xs:annotation>
  <xs:documentation>Attendants during the transport.</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="LastName">
      <xs:annotation>
        <xs:documentation>Last name of attendant.</xs:documentation>
        <xs:documentation>READ: <br/> - Consignee</xs:documentation>
        <xs:documentation>WRITE: <br/> - Consignor</xs:documentation>
        <xs:documentation>AMEND: <br/> - Contractual carrier <br/> -
        Successive carrier <br/> (With the agreement of the
        consignor)</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="25"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="FirstName" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Optional first name of the
        attendant.</xs:documentation>
        <xs:documentation>READ: <br/> - Consignee</xs:documentation>
        <xs:documentation>WRITE: <br/> - Consignor</xs:documentation>
        <xs:documentation>AMEND: <br/> - Contractual carrier <br/> -
        Successive carrier <br/> (With the agreement of the
        consignor)</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:minLength value="1"/>
          <xs:maxLength value="15"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
  
```

element **RollingRoadUnit/RollingRoadUnitDetails/Attendants/LastName**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>25</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	25	
Kind	Value	Annotation								
minLength	1									
maxLength	25									
annotation	documentation Last name of attendant.									

	<p>documentation READ:
 - Consignee documentation WRITE:
 - Consignor documentation AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</p>
source	<pre> <xs:element name="LastName"> <xs:annotation> <xs:documentation>Last name of attendant.</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="25"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **RollingRoadUnit/RollingRoadUnitDetails/Attendants/FirstName**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<p>minOcc 0 maxOcc 1 content simple</p>									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>15</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	15	
Kind	Value	Annotation								
minLength	1									
maxLength	15									
annotation	<p>documentation Optional first name of the attendant. documentation READ:
 - Consignee documentation WRITE:
 - Consignor documentation AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</p>									
source	<pre> <xs:element name="FirstName" minOccurs="0"> <xs:annotation> <xs:documentation>Optional first name of the attendant.</xs:documentation> <xs:documentation>READ:
 - Consignee</xs:documentation> <xs:documentation>WRITE:
 - Consignor</xs:documentation> <xs:documentation>AMEND:
 - Contractual carrier
 - Successive carrier
 (With the agreement of the consignor)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="15"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

```

</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **RollingStockDataset**

diagram	<pre> classDiagram class RollingStockDataset { AdministrativeDataSet DesignDataSet } </pre>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	AdministrativeDataSet DesignDataSet
used by	elements RollingStockDatasetMessage WIMO_Dataset
annotation	documentation Rolling Stock administrative and Technical Dataset
source	<pre> <xs:element name="RollingStockDataset"> <xs:annotation> <xs:documentation>Rolling Stock administrative and Technical Dataset</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="AdministrativeDataSet"> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:element name="PreviousWagonNumberFreight" type="WagonIdent" minOccurs="0"> <xs:annotation> <xs:documentation>For identification of a wagon after renumbering</xs:documentation> </xs:annotation> </xs:element> <xs:element name="RegistrationCountry" type="CountryIdentISO"> <xs:annotation> <xs:documentation>ISO country code of registration country</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="DatePutIntoService"> <xs:annotation> <xs:documentation>Date of first operation</xs:documentation> </xs:annotation> </xs:element> <xs:element name="AuthorisationValidUntil" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>End date for restricted authorisation (special case)</xs:documentation> </xs:annotation> </xs:element> <xs:element name="SuspensionOfAuthorisation" type="xs:boolean"> <xs:annotation> </pre>

```

        <xs:documentation>Information if authorisation has been
suspended by the authority</xs:documentation>
    </xs:annotation>
</xs:element>
    <xs:element name="DateSuspensionOfAuthorisation" type="xs:date"
minOccurs="0">
        <xs:annotation>
            <xs:documentation>Date of the suspension of authorisation;
must be provided in case of suspension</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="MultilateralAuthorisationCountries"
type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
            <xs:documentation> ISO country code of countries where the
wagon is authorised (applies only in case of limited interoperability);
first entry indicates the initial authorisation country</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ChannelTunnelPermitted" type="xs:boolean"
minOccurs="0">
        <xs:annotation>
            <xs:documentation>Indication if wagon is allowed to pass the
Channel Tunnel - if the transport is planned between UK and France and
should use Eurotunnel infrastructure.</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="QuieterRoutesExemptionCountry"
type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
            <xs:documentation>ISO code of country where the wagon has an
exemption in accordance with TSI Noise to run on quieter routes although it
is not TSI noise compliant</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element ref="KeeperShortNameVKM">
        <xs:annotation>
            <xs:documentation>Vehicle Keeper Marking of the wagon keeper
as listed in VKM register (http://www.era.europa.eu/Document-Register/Pages/list-VKM.aspx, column B - without special
characters)</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ECM">
        <xs:annotation>
            <xs:documentation> Full name of the assigned Entity in
Charge of Maintenance</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
            <xs:restriction base="xs:string">
                <xs:maxLength value="256"/>
            </xs:restriction>
        </xs:simpleType>
    </xs:element>
    <xs:element name="PlannedChangeOfECM" minOccurs="0">
        <xs:complexType>
            <xs:sequence>
                <xs:element name="CurrentECMAssignedUntil" type="xs:date">

```

```

        <xs:annotation>
          <xs:documentation> Date until the current Entity in
          Charge of Maintenance is assigned to the wagon</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="SubsequentECM">
        <xs:annotation>
          <xs:documentation> Full name of the following Entity
          in Charge of Maintenance</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="256"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ECMCertificate">
  <xs:annotation>
    <xs:documentation>ECM certificate
    information</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="EINNumber">
        <xs:annotation>
          <xs:documentation>ECM certificate reference number
          NOTE: this is a placeholder! CR 335 by ERA is containing this element and
          its full description and code lists.</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element ref="CountryCodeISO"/>
            <xs:element name="TypeDocumentEIN" type="Numeric2-
            2">
              <xs:annotation>
                <xs:documentation>Code List Candidate:
                31, 34</xs:documentation>
              </xs:annotation>
              </xs:element>
            <xs:element name="CounterAccreditedRecognizedBody"
            type="Numeric2-2"/>
            <xs:element name="EINYear" type="Numeric2-2"/>
            <xs:element name="EINCounter">
              <xs:simpleType>
                <xs:restriction base="xs:integer">
                  <xs:minInclusive value="0"/>
                  <xs:maxInclusive value="9999"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="ECMCertificateValidFrom" type="xs:date">
        <xs:annotation>

```

```

        <xs:documentation>Certificate valid from
date</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ECMCertificateValidTo" type="xs:date">
        <xs:annotation>
            <xs:documentation>Certificate valid to
date</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="CoversTankWagonsForDangerousGoods"
type="xs:boolean">
        <xs:annotation>
            <xs:documentation>Certificate covers tank wagons for
dangerous goods</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="CoversNonTankWagonsForDangerousGoods"
type="xs:boolean">
        <xs:annotation>
            <xs:documentation>Certificate covers other wagons
specialised in transport of dangerous goods</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ECMCertificateSuspended"
type="xs:boolean">
        <xs:annotation>
            <xs:documentation>Identification if certificate has
been suspended for any reason</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="DateECMCertificateSuspended"
type="xs:date" minOccurs="0">
        <xs:annotation>
            <xs:documentation>Date of the suspension of the ECM
certificate; must be provided in case of suspension</xs:documentation>
        </xs:annotation>
    </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="InteropCapability">
    <xs:annotation>
        <xs:documentation>Identification of the general
interoperability capability of the wagon
The following values/codes are proposed for the usage (defined in the
InteropCapabilityCode):

01 = National
02 = Bi-/Multilateral (with agreement or authorisation grid)

03 = RIV
05 = TEN

06 = TEN-GE

07 = TEN-CW
    
```

```

08 = TEN RIV</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="GCUWagon" type="xs:boolean">
  <xs:annotation>
    <xs:documentation>Indication if wagon is operated under the
GCU contract</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="DesignDataSet">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="LetterMarking">
        <xs:annotation>
          <xs:documentation>Complete wagon category letter code. The
Identification marking for freight rolling stock (wagon type) is defined in
UIC Leaflet 438-2</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="20"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="TankCode" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Tank code (applies only for tank wagons).
The codes are defined in the RID regulation, chapter 4.3.3 and
4.3.4.1.1</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="20"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="WagonNumberOfAxles"/>
      <xs:element name="WheelSetType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Type name of the wheel sets, and the name
of the type depends on the manufacturer.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="256"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element ref="WheelDiameter" minOccurs="0"/>
      <xs:element ref="WheelsetGauge" minOccurs="0"
maxOccurs="unbounded"/>
      <xs:element ref="WheelSetTransformationMethod" minOccurs="0"/>
      <xs:element ref="NumberOfBogies" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Number of bogies for a wagon (applies for

```

```

bogie wagons only)</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="BogiePitch" minOccurs="0"/>
<xs:element name="BogiePivotPitch" type="Numeric1-5"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Largest distance between two adjacent
bogie pitches in mm</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="InnerWheelbase" type="Numeric1-5">
  <xs:annotation>
    <xs:documentation>Maximum distance between two adjacent
axles in mm</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="CouplingType" minOccurs="0"/>
<xs:element name="BufferType" minOccurs="0">
  <xs:annotation>
    <xs:documentation> Classification of buffer. The following
values are mostly used in the sector.: A, AX, B, C, CX, L0 (130), L0 (150),
L2 (130), L2 (150), L4 (130), L4 (150)</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:maxLength value="256"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="NormalLoadingGauge" minOccurs="0"/>
<xs:element ref="MinCurveRadius">
  <xs:annotation>
    <xs:documentation> Minimum allowed curve radius due to
design characteristics, measured in meters</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="MinVerticalRadiusYardHump" minOccurs="0"/>
<xs:element ref="WagonWeightEmpty">
  <xs:annotation>
    <xs:documentation>Weight of the empty wagon (tara weight) in
kg</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="LengthOverBuffers"/>
<xs:element ref="MaxAxleWeight"/>
<xs:element name="LoadTable" minOccurs="0"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>Indicates the load tables marked on the
wagon.
When load tables are marked on the wagon the information must be provided in
the RSRD message.
Several load tables (international, product specific for LPG wagons and
additional/country specific) can be specified by providing the element
several times consecutively.
For special wagons with specific load tables (e.g. heavy haul wagons) no
load table need to be provided.

```


The complete load table must be provided including the empty load row (if existent).

```

</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="LoadTableProduct" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Product description, only applies
for product-specific load tables</xs:documentation>
        </xs:annotation>
        <xs:complexType>
          <xs:sequence>
            <xs:element name="ProductUNCode" type="Numeric4-4">
              <xs:annotation>
                <xs:documentation>UN code of product if product
specific load table</xs:documentation>
              </xs:annotation>
            </xs:element>
            <xs:element name="ProductRIDName">
              <xs:annotation>
                <xs:documentation> RID product name as written
on the folding panel</xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:string">
                  <xs:maxLength value="256"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="LoadTableCountry" type="CountryIdentISO"
minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>ISO country code of countries for
additional load tables</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="SpeedCategory" type="Numeric1-5"
maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Numeric speed in load table, without
speed empty in km/h</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element ref="LoadTableStars" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Number of load table stars.
Currently recognized values/codes:
1 = Authorised to run loaded in trains up to 100 km/h with a brake that does
not meet all the requirements for 100 km/h conditions
2 = Authorised to run loaded in trains up to 120 km/h with a brake that does
not meet all the requirements for 120 km/h conditions
3 = Authorised to run loaded in trains up to 120 km/h with a brake that does
not meet all the requirements for 120 km/h conditions. Wagon is fitted with
an automatic load-proportional braking system.
        </xs:documentation>
      </xs:documentation>
    </xs:documentation>
  </xs:documentation>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element name="RouteClassPayloads"
maxOccurs="unbounded">
        <xs:complexType>
          <xs:sequence>
            <xs:element ref="RouteClass"/>
            <xs:element name="MaxPayload" maxOccurs="unbounded">
              <xs:annotation>
                <xs:documentation>Maximum payload in tons of
line category; number of entries must fit to number of entries in
SpeedCategory</xs:documentation>
              </xs:annotation>
              <xs:simpleType>
                <xs:restriction base="xs:decimal">
                  <xs:totalDigits value="4"/>
                  <xs:fractionDigits value="1"/>
                </xs:restriction>
              </xs:simpleType>
            </xs:element>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element ref="MaxDesignSpeed"/>
<xs:element ref="AirBrake"/>
<xs:element ref="HandBrake">
  <xs:annotation>
    <xs:documentation>Characteristics of hand
brake</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="DerailmentDetectionDevice"
type="DerailmentDetectionDevice" minOccurs="0"/>
<xs:element name="BrakeBlock" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Characteristics of brake
blocks</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="BrakeBlockName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of the brake block type,
including the length in mm</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="256"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CompositeBrakeBlockRetrofitted"
type="xs:boolean" minOccurs="0">
        <xs:annotation>
          <xs:documentation> Indication if composite brake

```

```

blocks are retrofitted or originally equipped</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element name="CompositeBrakeBlockInstallationDate"
type="xs:date" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Date of composite brake block
installation, for originally equipped wagon = date put into
service</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
  <xs:element name="WagonTelematics" type="WagonTelematics"
minOccurs="0">
  <xs:annotation>
    <xs:documentation xml:lang="en">Information about telematics
devices mounted on the wagon.</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element ref="MaxLengthOfLoad" minOccurs="0">
  <xs:annotation>
    <xs:documentation> Maximum length of the load measured in mm
</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element ref="LoadArea" minOccurs="0"/>
  <xs:element name="HeightOfLoadingPlaneUnladen" type="Numeric1-5"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Height of the loading plane when wagon is
empty measured in mm</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element name="RemovableAccessories" minOccurs="0"
maxOccurs="unbounded">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="TypeOfRemovableAccessories">
        <xs:annotation>
          <xs:documentation>Specification of removable
accessory.
TypeOfRemovableAccessories code list is used. Values refer to UIC Leaflet
920-13:
01 = Removable stanchion
02 = Removable side flap of flat wagon
03 = Removable end flap of flat wagon
04 = Removable side rail
05 = Removable intermediate upright for securing the load
06 = Stanchion chain
07 = Removable handle and wheel for winch on car-carrying wagon
08 = Swivelling bolster (with stanchions)
09 = Coupling rod (rigid coupling)
10 = Ice bunker
11 = Ice bunker screen
12 = Ice bunker frame
13 = Trestle or bar with hooks for hanging meat

```

```

14 = Movable cross-member of wagon with low loading plane
15 = Removable support
16 = Mooring cross-member on wagon for special loads
17 = Movable floor panel on wagon for special loads
18 = Scotch
19 = Skid bar with or without shoes on car-carrying wagon
20 = Mooring strap on car-carrying wagon
21 = Beam for movable ramp on car-carrying wagon
22 = Spare heating half-coupling
23 = Fire extinguisher
24 = Wheel scotches (for cars) on car-carrying wagon
25 = Gangway loading ramp on car-carrying wagon
26 = Metal cradles for rolls of metal sheeting
27 = Panel for covering markings
28 = Loading frame for special types of goods
29 = Headstock for "rolling roads"
99 = Other wagon accessories
</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="NumberOfAccessorOfSpecType"
type="Numeric2-2">
    <xs:annotation>
      <xs:documentation>Number of specified accessory
equipped on the wagon</xs:documentation>
    </xs:annotation>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="LoadingCapacity" minOccurs="0"/>
<xs:element ref="MaxGrossWeight">
  <xs:annotation>
    <xs:documentation>Weight of max Gross Load Weight plus the
tare weight of the equipment in kg</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="VapourReturnSystem" type="xs:boolean"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Indication if tank wagon is equipped with
a vapour return system</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="FerryPermittedFlag" minOccurs="0">
  <xs:annotation>
    <xs:documentation> Indication if wagon is permitted to be
used on ferries</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="FerryRampAngle" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Maximum allowed angle of the ferry ramp
(in grades: °)</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:decimal">
      <xs:totalDigits value="3"/>

```

```

        <xs:fractionDigits value="2"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="TemperatureRange" minOccurs="0">
    <xs:complexType>
        <xs:sequence>
            <xs:annotation>
                <xs:documentation>Temperature Range</xs:documentation>
            </xs:annotation>
            <xs:element ref="MaxTemp"/>
            <xs:element ref="MinTemp"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element ref="TechnicalForwardingRestrictions" minOccurs="0"
maxOccurs="unbounded">
    <xs:annotation>
        <xs:documentation>Restrictions relevant to wagon operations
in train formation, yards or in trains due to design characteristics.
Type will be the RestrictionCode instead of ForwardingRestrictionType,
according to 920-13: annotation will carry the information that only
the technical parameters are allowed to be used here. Only the code numbers
should be in the annotation</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="DateLastOverhaul">
    <xs:annotation>
        <xs:documentation>Date of the last overhaul, if yet no
overhaul date of putting into service</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="OverhaulValidityPeriod"/>
<xs:element ref="PermittedTolerance"/>
<xs:element ref="PlannedDateNextOverhaul" minOccurs="0"/>
<xs:element name="DateOfNextTankInspection" type="xs:date"
minOccurs="0">
    <xs:annotation>
        <xs:documentation>Date of the next tank inspection, applies
only for tank wagons</xs:documentation>
    </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **RollingStockDataset/AdministrativeDataSet**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>WagonNumberFreight PreviousWagonNumberFreight RegistrationCountry DatePutIntoService AuthorisationValidUntil SuspensionOfAuthorisation DateSuspensionOfAuthorisation MultilateralAuthorisationCountries ChannelTunnelPermitted QuieterRoutesExemptionCountry KeeperShortNameVKM ECM PlannedChangeOfECM ECMCertificate InteropCapability GCUWagon</p>
<p>source</p>	<pre><xs:element name="AdministrativeDataSet"> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:element name="PreviousWagonNumberFreight" type="WagonIdent" minOccurs="0"> <xs:annotation> <xs:documentation>For identification of a wagon after renumbering</xs:documentation> </xs:annotation> </xs:element> <xs:element name="RegistrationCountry" type="CountryIdentISO"></pre>

```

        <xs:annotation>
          <xs:documentation>ISO country code of registration
country</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element ref="DatePutIntoService">
        <xs:annotation>
          <xs:documentation>Date of first operation</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="AuthorisationValidUntil" type="xs:date"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>End date for restricted authorisation (special
case)</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="SuspensionOfAuthorisation" type="xs:boolean">
        <xs:annotation>
          <xs:documentation>Information if authorisation has been suspended
by the authority</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="DateSuspensionOfAuthorisation" type="xs:date"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Date of the suspension of authorisation; must be
provided in case of suspension</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="MultilateralAuthorisationCountries"
type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation> ISO country code of countries where the wagon
is authorised (applies only in case of limited interoperability); first
entry indicates the initial authorisation country</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="ChannelTunnelPermitted" type="xs:boolean"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Indication if wagon is allowed to pass the
Channel Tunnel - if the transport is planned between UK and France and
should use Eurotunnel infrastructure.</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="QuieterRoutesExemptionCountry"
type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>ISO code of country where the wagon has an
exemption in accordance with TSI Noise to run on quieter routes although it
is not TSI noise compliant</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element ref="KeeperShortNameVKM">
        <xs:annotation>
          <xs:documentation>Vehicle Keeper Marking of the wagon keeper as
listed in VKM register (http://www.era.europa.eu/Document-

```

```

Register/Pages/list-VKM.aspx, column B - without special
characters)</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element name="ECM">
    <xs:annotation>
      <xs:documentation> Full name of the assigned Entity in Charge of
Maintenance</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:maxLength value="256"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:element>
  <xs:element name="PlannedChangeOfECM" minOccurs="0">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="CurrentECMAssignedUntil" type="xs:date">
          <xs:annotation>
            <xs:documentation> Date until the current Entity in Charge
of Maintenance is assigned to the wagon</xs:documentation>
          </xs:annotation>
        </xs:element>
        <xs:element name="SubsequentECM">
          <xs:annotation>
            <xs:documentation> Full name of the following Entity in
Charge of Maintenance</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:maxLength value="256"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="ECMCertificate">
    <xs:annotation>
      <xs:documentation>ECM certificate information</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="EINNumber">
          <xs:annotation>
            <xs:documentation>ECM certificate reference number
NOTE: this is a placeholder! CR 335 by ERA is containing this element and
its full description and code lists.</xs:documentation>
          </xs:annotation>
          <xs:complexType>
            <xs:sequence>
              <xs:element ref="CountryCodeISO"/>
              <xs:element name="TypeDocumentEIN" type="Numeric2-2">
                <xs:annotation>
                  <xs:documentation>Code List Candidate:
31, 34</xs:documentation>
                </xs:annotation>

```




```

        </xs:element>
        <xs:element name="CounterAccreditedRecognizedBody"
type="Numeric2-2"/>
        <xs:element name="EINYear" type="Numeric2-2"/>
        <xs:element name="EINCounter">
        <xs:simpleType>
        <xs:restriction base="xs:integer">
        <xs:minInclusive value="0"/>
        <xs:maxInclusive value="9999"/>
        </xs:restriction>
        </xs:simpleType>
        </xs:element>
        </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="ECMCertificateValidFrom" type="xs:date">
        <xs:annotation>
        <xs:documentation>Certificate valid from
date</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ECMCertificateValidTo" type="xs:date">
        <xs:annotation>
        <xs:documentation>Certificate valid to
date</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="CoversTankWagonsForDangerousGoods"
type="xs:boolean">
        <xs:annotation>
        <xs:documentation>Certificate covers tank wagons for
dangerous goods</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="CoversNonTankWagonsForDangerousGoods"
type="xs:boolean">
        <xs:annotation>
        <xs:documentation>Certificate covers other wagons
specialised in transport of dangerous goods</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ECMCertificateSuspended" type="xs:boolean">
        <xs:annotation>
        <xs:documentation>Identification if certificate has been
suspended for any reason</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="DateECMCertificateSuspended" type="xs:date"
minOccurs="0">
        <xs:annotation>
        <xs:documentation>Date of the suspension of the ECM
certificate; must be provided in case of suspension</xs:documentation>
        </xs:annotation>
    </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="InteropCapability">


```

	<pre> <xs:annotation> <xs:documentation>Identification of the general interoperability capability of the wagon The following values/codes are proposed for the usage (defined in the InteropCapabilityCode): 01 = National 02 = Bi-/Multilateral (with agreement or authorisation grid) 03 = RIV 05 = TEN 06 = TEN-GE 07 = TEN-CW 08 = TEN RIV</xs:documentation> </xs:annotation> </xs:element> <xs:element name="GCUWagon" type="xs:boolean"> <xs:annotation> <xs:documentation>Indication if wagon is operated under the GCU contract</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---


element **RollingStockDataset/AdministrativeDataSet/PreviousWagonNumberFreight**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	WagonIdent									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{12}</td> <td></td> </tr> </table>	Kind	Value	Annotation	maxLength	12		pattern	[0-9]{12}	
Kind	Value	Annotation								
maxLength	12									
pattern	[0-9]{12}									
annotation	documentation For identification of a wagon after renumbering									
source	<pre> <xs:element name="PreviousWagonNumberFreight" type="WagonIdent" minOccurs="0"> <xs:annotation> <xs:documentation>For identification of a wagon after renumbering</xs:documentation> </xs:annotation> </xs:element> </pre>									


element **RollingStockDataset/AdministrativeDataSet/RegistrationCountry**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CountryIdentISO									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2	
Kind	Value	Annotation								
minLength	2									
maxLength	2									
annotation	documentation ISO country code of registration country									
source	<pre><xs:element name="RegistrationCountry" type="CountryIdentISO"> <xs:annotation> <xs:documentation>ISO country code of registration country</xs:documentation> </xs:annotation> </xs:element></pre>									

element **RollingStockDataset/AdministrativeDataSet/AuthorisationValidUntil**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	xs:date						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple
minOcc	0						
maxOcc	1						
content	simple						
annotation	documentation End date for restricted authorisation (special case)						
source	<pre><xs:element name="AuthorisationValidUntil" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>End date for restricted authorisation (special case)</xs:documentation> </xs:annotation> </xs:element></pre>						

element **RollingStockDataset/AdministrativeDataSet/SuspensionOfAuthorisation**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
annotation	documentation Information if authorisation has been suspended by the authority
source	<pre><xs:element name="SuspensionOfAuthorisation" type="xs:boolean"></pre>

	<pre> <xs:annotation> <xs:documentation>Information if authorisation has been suspended by the authority</xs:documentation> </xs:annotation> </xs:element> </pre>
--	---


element **RollingStockDataset/AdministrativeDataSet/DateSuspensionOfAuthorisation**

diagram	 <p>Date of the suspension of authorisation; must be provided in case of suspension</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Date of the suspension of authorisation; must be provided in case of suspension
source	<pre> <xs:element name="DateSuspensionOfAuthorisation" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date of the suspension of authorisation; must be provided in case of suspension</xs:documentation> </xs:annotation> </xs:element> </pre>


element **RollingStockDataset/AdministrativeDataSet/MultilateralAuthorisationCountries**

diagram	 <p>ISO country code of countries where the wagon is authorised (applies only in case of limited interoperability); first entry indicates the initial authorisation country</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CountryIdentISO
properties	minOcc 0 maxOcc unbounded content simple
facets	Kind Value Annotation minLength 2 maxLength 2
annotation	documentation ISO country code of countries where the wagon is authorised (applies only in case of limited interoperability); first entry indicates the initial authorisation country
source	<pre> <xs:element name="MultilateralAuthorisationCountries" type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation> ISO country code of countries where the wagon is authorised (applies only in case of limited interoperability); first entry indicates the initial authorisation country</xs:documentation> </xs:annotation> </xs:element> </pre>


element **RollingStockDataset/AdministrativeDataSet/ChannelTunnelPermitted**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Indication if wagon is allowed to pass the Channel Tunnel - if the transport is planned between UK and France and should use Eurotunnel infrastructure.
source	<pre><xs:element name="ChannelTunnelPermitted" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>Indication if wagon is allowed to pass the Channel Tunnel - if the transport is planned between UK and France and should use Eurotunnel infrastructure.</xs:documentation> </xs:annotation> </xs:element></pre>


element **RollingStockDataset/AdministrativeDataSet/QuieterRoutesExemptionCountry**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CountryIdentISO
properties	minOcc 0 maxOcc unbounded content simple
facets	Kind Value Annotation minLength 2 maxLength 2
annotation	documentation ISO code of country where the wagon has an exemption in accordance with TSI Noise to run on quieter routes although it is not TSI noise compliant
source	<pre><xs:element name="QuieterRoutesExemptionCountry" type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>ISO code of country where the wagon has an exemption in accordance with TSI Noise to run on quieter routes although it is not TSI noise compliant</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/AdministrativeDataSet/ECM**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	content simple
facets	Kind Value Annotation maxLength 256
annotation	documentation Full name of the assigned Entity in Charge of Maintenance
source	<pre><xs:element name="ECM"> <xs:annotation> <xs:documentation> Full name of the assigned Entity in Charge of Maintenance</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **RollingStockDataset/AdministrativeDataSet/PlannedChangeOfECM**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	CurrentECMAssignedUntil SubsequentECM
source	<pre><xs:element name="PlannedChangeOfECM" minOccurs="0"> <xs:complexType> <xs:sequence> <xs:element name="CurrentECMAssignedUntil" type="xs:date"> <xs:annotation> <xs:documentation> Date until the current Entity in Charge of Maintenance is assigned to the wagon</xs:documentation> </xs:annotation> </xs:element> <xs:element name="SubsequentECM"> <xs:annotation> <xs:documentation> Full name of the following Entity in Charge of Maintenance</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>

	<pre> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **RollingStockDataset/AdministrativeDataSet/PlannedChangeOfECM/CurrentECMAssignedUntil**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
annotation	documentation Date until the current Entity in Charge of Maintenance is assigned to the wagon
source	<pre> <xs:element name="CurrentECMAssignedUntil" type="xs:date"> <xs:annotation> <xs:documentation> Date until the current Entity in Charge of Maintenance is assigned to the wagon</xs:documentation> </xs:annotation> </xs:element> </pre>

element **RollingStockDataset/AdministrativeDataSet/PlannedChangeOfECM/SubsequentECM**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	256	
Kind	Value	Annotation					
maxLength	256						
annotation	documentation Full name of the following Entity in Charge of Maintenance						
source	<pre> <xs:element name="SubsequentECM"> <xs:annotation> <xs:documentation> Full name of the following Entity in Charge of Maintenance</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>						

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>EINNumber ECMCertificateValidFrom ECMCertificateValidTo CoversTankWagonsForDangerousGoods CoversNonTankWagonsForDangerousGoods ECMCertificateSuspended DateECMCertificateSuspended</p>
<p>annotation</p>	<p>documentation ECM certificate information</p>
<p>source</p>	<pre> <xs:element name="ECMCertificate"> <xs:annotation> <xs:documentation>ECM certificate information</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="EINNumber"> <xs:annotation> <xs:documentation>ECM certificate reference number NOTE: this is a placeholder! CR 335 by ERA is containing this element and its full description and code lists.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="CountryCodeISO"/> <xs:element name="TypeDocumentEIN" type="Numeric2-2"> <xs:annotation> <xs:documentation>Code List Candidate: 31, 34</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CounterAccreditedRecognizedBody" type="Numeric2-2"/> <xs:element name="EINYear" type="Numeric2-2"/> <xs:element name="EINCounter"> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>


```

        <xs:maxInclusive value="9999"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ECMCertificateValidFrom" type="xs:date">
    <xs:annotation>
        <xs:documentation>Certificate valid from date</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="ECMCertificateValidTo" type="xs:date">
    <xs:annotation>
        <xs:documentation>Certificate valid to date</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="CoversTankWagonsForDangerousGoods"
type="xs:boolean">
    <xs:annotation>
        <xs:documentation>Certificate covers tank wagons for dangerous
goods</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="CoversNonTankWagonsForDangerousGoods"
type="xs:boolean">
    <xs:annotation>
        <xs:documentation>Certificate covers other wagons specialised in
transport of dangerous goods</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="ECMCertificateSuspended" type="xs:boolean">
    <xs:annotation>
        <xs:documentation>Identification if certificate has been suspended
for any reason</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="DateECMCertificateSuspended" type="xs:date"
minOccurs="0">
    <xs:annotation>
        <xs:documentation>Date of the suspension of the ECM certificate;
must be provided in case of suspension</xs:documentation>
    </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>CountryCodeISO TypeDocumentEIN CounterAcrcditedRecognizedBody EINYear EINCounter</p>
<p>annotation</p>	<p>documentation ECM certificate reference number NOTE: this is a placeholder! CR 335 by ERA is containing this element and its full description and code lists.</p>
<p>source</p>	<pre><xs:element name="EINNumber"> <xs:annotation> <xs:documentation>ECM certificate reference number NOTE: this is a placeholder! CR 335 by ERA is containing this element and its full description and code lists.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="CountryCodeISO"/> <xs:element name="TypeDocumentEIN" type="Numeric2-2"> <xs:annotation> <xs:documentation>Code List Candidate: 31, 34</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CounterAcrcditedRecognizedBody" type="Numeric2-2"/> <xs:element name="EINYear" type="Numeric2-2"/> <xs:element name="EINCounter"> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>


element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/TypeDocumentEIN**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>Numeric2-2</p>


properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
annotation	documentation Code List Candidate: 31, 34									
source	<pre><xs:element name="TypeDocumentEIN" type="Numeric2-2"> <xs:annotation> <xs:documentation>Code List Candidate: 31, 34</xs:documentation> </xs:annotation> </xs:element></pre>									

element


RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/CounterAccreditedRecognizedBody

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric2-2									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
source	<pre><xs:element name="CounterAccreditedRecognizedBody" type="Numeric2-2"/></pre>									

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/EINYear**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric2-2									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
source	<pre><xs:element name="EINYear" type="Numeric2-2"/></pre>									

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/EINCounter**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer

properties	content simple									
facets	<table border="1"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	9999									
source	<pre><xs:element name="EINCounter"> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/ECMCertificateValidFrom**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
annotation	documentation Certificate valid from date
source	<pre><xs:element name="ECMCertificateValidFrom" type="xs:date"> <xs:annotation> <xs:documentation>Certificate valid from date</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/ECMCertificateValidTo**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
annotation	documentation Certificate valid to date
source	<pre><xs:element name="ECMCertificateValidTo" type="xs:date"> <xs:annotation> <xs:documentation>Certificate valid to date</xs:documentation> </xs:annotation> </xs:element></pre>


element

RollingStockDataset/AdministrativeDataSet/ECMCertificate/CoversTankWagonsForDangerousGoods


diagram	 Certificate covers tank wagons for dangerous goods
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
annotation	documentation Certificate covers tank wagons for dangerous goods
source	<pre><xs:element name="CoversTankWagonsForDangerousGoods" type="xs:boolean"> <xs:annotation> <xs:documentation>Certificate covers tank wagons for dangerous goods</xs:documentation> </xs:annotation> </xs:element></pre>

element

RollingStockDataset/AdministrativeDataSet/ECMCertificate/CoversNonTankWagonsForDangerousGoods


diagram	 Certificate covers other wagons specialised in transport of dangerous goods
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
annotation	documentation Certificate covers other wagons specialised in transport of dangerous goods
source	<pre><xs:element name="CoversNonTankWagonsForDangerousGoods" type="xs:boolean"> <xs:annotation> <xs:documentation>Certificate covers other wagons specialised in transport of dangerous goods</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/AdministrativeDataSet/ECMCertificate/ECMCertificateSuspended**


diagram	 Identification if certificate has been suspended for any reason
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
annotation	documentation Identification if certificate has been suspended for any reason
source	<pre><xs:element name="ECMCertificateSuspended" type="xs:boolean"> <xs:annotation> <xs:documentation>Identification if certificate has been suspended for any reason</xs:documentation> </xs:annotation> </xs:element></pre>

```
</xs:annotation>
</xs:element>
```

element RollingStockDataset/AdministrativeDataSet/ECMCertificate/DateECMCertificateSuspended

diagram	 <p>Date of the suspension of the ECM certificate; must be provided in case of suspension</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Date of the suspension of the ECM certificate; must be provided in case of suspension
source	<pre><xs:element name="DateECMCertificateSuspended" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date of the suspension of the ECM certificate; must be provided in case of suspension</xs:documentation> </xs:annotation> </xs:element></pre>

element RollingStockDataset/AdministrativeDataSet/GCUWagon

diagram	 <p>Indication if wagon is operated under the GCU contract</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
annotation	documentation Indication if wagon is operated under the GCU contract
source	<pre><xs:element name="GCUWagon" type="xs:boolean"> <xs:annotation> <xs:documentation>Indication if wagon is operated under the GCU contract</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/DesignDataSet**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	LetterMarking TankCode WagonNumberOfAxles WheelSetType WheelDiameter WheelsetGauge WheelSetTransformationMethod NumberOfBogies BogiePitch BogiePivotPitch InnerWheelbase CouplingType BufferType NormalLoadingGauge MinCurveRadius MinVerticalRadiusYardHump WagonWeightEmpty LengthOverBuffers MaxAxleWeight LoadTable MaxDesignSpeed AirBrake HandBrake DerailmentDetectionDevice BrakeBlock WagonTelematics MaxLengthOfLoad LoadArea HeightOfLoadingPlaneUnladen RemovableAccessories LoadingCapacity MaxGrossWeight VapourReturnSystem FerryPermittedFlag FerryRampAngle TemperatureRange TechnicalForwardingRestrictions DateLastOverhaul OverhaulValidityPeriod PermittedTolerance PlannedDateNextOverhaul DateOfNextTankInspection
source	<pre> <xs:element name="DesignDataSet"> <xs:complexType> <xs:sequence> <xs:element name="LetterMarking"> <xs:annotation> <xs:documentation>Complete wagon category letter code. The Identification marking for freight rolling stock (wagon type) is defined in UIC Leaflet 438-2</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="20"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="TankCode" minOccurs="0"> <xs:annotation> <xs:documentation>Tank code (applies only for tank wagons). The codes are defined in the RID regulation, chapter 4.3.3 and 4.3.4.1.1</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="20"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="WagonNumberOfAxles"/> <xs:element name="WheelSetType" minOccurs="0"> <xs:annotation> <xs:documentation>Type name of the wheel sets, and the name of the type depends on the manufacturer.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="WheelDiameter" minOccurs="0"/> <xs:element ref="WheelsetGauge" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="WheelSetTransformationMethod" minOccurs="0"/> <xs:element ref="NumberOfBogies" minOccurs="0"> <xs:annotation> <xs:documentation>Number of bogies for a wagon (applies for bogie wagons only)</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```

</xs:annotation>
</xs:element>
<xs:element ref="BogiePitch" minOccurs="0"/>
<xs:element name="BogiePivotPitch" type="Numeric1-5" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Largest distance between two adjacent bogie
    pitches in mm</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="InnerWheelbase" type="Numeric1-5">
  <xs:annotation>
    <xs:documentation>Maximum distance between two adjacent axles in
    mm</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="CouplingType" minOccurs="0"/>
<xs:element name="BufferType" minOccurs="0">
  <xs:annotation>
    <xs:documentation> Classification of buffer. The following values
    are mostly used in the sector.: A, AX, B, C, CX, L0 (130), L0 (150), L2
    (130), L2 (150), L4 (130), L4 (150)</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:maxLength value="256"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="NormalLoadingGauge" minOccurs="0"/>
<xs:element ref="MinCurveRadius">
  <xs:annotation>
    <xs:documentation> Minimum allowed curve radius due to design
    characteristics, measured in meters</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="MinVerticalRadiusYardHump" minOccurs="0"/>
<xs:element ref="WagonWeightEmpty">
  <xs:annotation>
    <xs:documentation>Weight of the empty wagon (tara weight) in
    kg</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="LengthOverBuffers"/>
<xs:element ref="MaxAxleWeight"/>
<xs:element name="LoadTable" minOccurs="0" maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>Indicates the load tables marked on the wagon.
    When load tables are marked on the wagon the information must be provided in
    the RSRD message.
    Several load tables (international, product specific for LPG wagons and
    additional/country specific) can be specified by providing the element
    several times consecutively.
    For special wagons with specific load tables (e.g. heavy haul wagons) no
    load table need to be provided.
    The complete load table must be provided including the empty load row (if
    existent).</xs:documentation>
  </xs:annotation>
</xs:complexType>

```

```

<xs:sequence>
  <xs:element name="LoadTableProduct" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Product description, only applies for
product-specific load tables</xs:documentation>
    </xs:annotation>
    <xs:complexType>
      <xs:sequence>
        <xs:element name="ProductUNCode" type="Numeric4-4">
          <xs:annotation>
            <xs:documentation>UN code of product if product
specific load table</xs:documentation>
          </xs:annotation>
        </xs:element>
        <xs:element name="ProductRIDName">
          <xs:annotation>
            <xs:documentation> RID product name as written on the
folding panel</xs:documentation>
          </xs:annotation>
          <xs:simpleType>
            <xs:restriction base="xs:string">
              <xs:maxLength value="256"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="LoadTableCountry" type="CountryIdentISO"
minOccurs="0" maxOccurs="unbounded">
    <xs:annotation>
      <xs:documentation>ISO country code of countries for
additional load tables</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="SpeedCategory" type="Numeric1-5"
maxOccurs="unbounded">
    <xs:annotation>
      <xs:documentation>Numeric speed in load table, without speed
empty in km/h</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element ref="LoadTableStars" minOccurs="0">
    <xs:annotation>
      <xs:documentation>Number of load table stars. Currently
recognized values/codes:
1 = Authorised to run loaded in trains up to 100 km/h with a brake that does
not meet all the requirements for 100 km/h conditions
2 = Authorised to run loaded in trains up to 120 km/h with a brake that does
not meet all the requirements for 120 km/h conditions
3 = Authorised to run loaded in trains up to 120 km/h with a brake that does
not meet all the requirements for 120 km/h conditions. Wagon is fitted with
an automatic load-proportional braking system.
</xs:documentation>
    </xs:annotation>
  </xs:element>
  <xs:element name="RouteClassPayloads" maxOccurs="unbounded">
    <xs:complexType>

```

```

        <xs:sequence>
          <xs:element ref="RouteClass"/>
          <xs:element name="MaxPayload" maxOccurs="unbounded">
            <xs:annotation>
              <xs:documentation>Maximum payload in tons of line
category; number of entries must fit to number of entries in
SpeedCategory</xs:documentation>
            </xs:annotation>
            <xs:simpleType>
              <xs:restriction base="xs:decimal">
                <xs:totalDigits value="4"/>
                <xs:fractionDigits value="1"/>
              </xs:restriction>
            </xs:simpleType>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="MaxDesignSpeed"/>
<xs:element ref="AirBrake"/>
<xs:element ref="HandBrake">
  <xs:annotation>
    <xs:documentation>Characteristics of hand brake</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="DerailmentDetectionDevice"
type="DerailmentDetectionDevice" minOccurs="0"/>
<xs:element name="BrakeBlock" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Characteristics of brake
blocks</xs:documentation>
  </xs:annotation>
  <xs:complexType>
    <xs:sequence>
      <xs:element name="BrakeBlockName" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Name of the brake block type, including
the length in mm</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:maxLength value="256"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:element>
      <xs:element name="CompositeBrakeBlockRetrofitted"
type="xs:boolean" minOccurs="0">
        <xs:annotation>
          <xs:documentation> Indication if composite brake blocks are
retrofitted or originally equipped</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="CompositeBrakeBlockInstallationDate"
type="xs:date" minOccurs="0">
        <xs:annotation>

```

```

        <xs:documentation>Date of composite brake block
installation, for originally equipped wagon = date put into
service</xs:documentation>
    </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="WagonTelematics" type="WagonTelematics"
minOccurs="0">
    <xs:annotation>
        <xs:documentation xml:lang="en">Information about telematics
devices mounted on the wagon.</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="MaxLengthOfLoad" minOccurs="0">
    <xs:annotation>
        <xs:documentation> Maximum length of the load measured in mm
</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="LoadArea" minOccurs="0"/>
<xs:element name="HeightOfLoadingPlaneUnladen" type="Numeric1-5"
minOccurs="0">
    <xs:annotation>
        <xs:documentation>Height of the loading plane when wagon is empty
measured in mm</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element name="RemovableAccessories" minOccurs="0"
maxOccurs="unbounded">
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="TypeOfRemovableAccessories">
                <xs:annotation>
                    <xs:documentation>Specification of removable accessory.
TypeOfRemovableAccessories code list is used. Values refer to UIC Leaflet
920-13:
01 = Removable stanchion
02 = Removable side flap of flat wagon
03 = Removable end flap of flat wagon
04 = Removable side rail
05 = Removable intermediate upright for securing the load
06 = Stanchion chain
07 = Removable handle and wheel for winch on car-carrying wagon
08 = Swivelling bolster (with stanchions)
09 = Coupling rod (rigid coupling)
10 = Ice bunker
11 = Ice bunker screen
12 = Ice bunker frame
13 = Trestle or bar with hooks for hanging meat
14 = Movable cross-member of wagon with low loading plane
15 = Removable support
16 = Mooring cross-member on wagon for special loads
17 = Movable floor panel on wagon for special loads
18 = Scotch
19 = Skid bar with or without shoes on car-carrying wagon
20 = Mooring strap on car-carrying wagon

```

```


21 = Beam for movable ramp on car-carrying wagon
22 = Spare heating half-coupling
23 = Fire extinguisher
24 = Wheel scotches (for cars) on car-carrying wagon
25 = Gangway loading ramp on car-carrying wagon
26 = Metal cradles for rolls of metal sheeting
27 = Panel for covering markings
28 = Loading frame for special types of goods
29 = Headstock for "rolling roads"
99 = Other wagon accessories
</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element name="NumberOfAccessoriesOfSpecType" type="Numeric2-2">
    <xs:annotation>
      <xs:documentation>Number of specified accessory equipped on
the wagon</xs:documentation>
    </xs:annotation>
  </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="LoadingCapacity" minOccurs="0"/>
<xs:element ref="MaxGrossWeight">
  <xs:annotation>
    <xs:documentation>Weight of max Gross Load Weight plus the tare
weight of the equipment in kg</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="VapourReturnSystem" type="xs:boolean" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Indication if tank wagon is equipped with a
vapour return system</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="FerryPermittedFlag" minOccurs="0">
  <xs:annotation>
    <xs:documentation> Indication if wagon is permitted to be used on
ferries</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="FerryRampAngle" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Maximum allowed angle of the ferry ramp (in
grades: °)</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:decimal">
      <xs:totalDigits value="3"/>
      <xs:fractionDigits value="2"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="TemperatureRange" minOccurs="0">
  <xs:complexType>
    <xs:sequence>
      <xs:annotation>
        <xs:documentation>Temperature Range</xs:documentation>

```

```

        </xs:annotation>
        <xs:element ref="MaxTemp" />
        <xs:element ref="MinTemp" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="TechnicalForwardingRestrictions" minOccurs="0"
maxOccurs="unbounded">
    <xs:annotation>
        <xs:documentation>Restrictions relevant to wagon operations in
train formation, yards or in trains due to design characteristics.
Type will be the RestrictionCode instead of ForwardingRestrictionType,
according to 920-13: annotation will carry the information that only
the technical parameters are allowed to be used here. Only the code numbers
should be in the annotation</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="DateLastOverhaul">
    <xs:annotation>
        <xs:documentation>Date of the last overhaul, if yet no overhaul
date of putting into service</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="OverhaulValidityPeriod" />
<xs:element ref="PermittedTolerance" />
<xs:element ref="PlannedDateNextOverhaul" minOccurs="0" />
<xs:element name="DateOfNextTankInspection" type="xs:date"
minOccurs="0">
    <xs:annotation>
        <xs:documentation>Date of the next tank inspection, applies only
for tank wagons</xs:documentation>
    </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **RollingStockDataset/DesignDataSet/LetterMarking**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> </table>	Kind	Value	Annotation	maxLength	20	
Kind	Value	Annotation					
maxLength	20						
annotation	documentation Complete wagon category letter code. The Identification marking for freight rolling stock (wagon type) is defined in UIC Leaflet 438-2						
source	<pre> <xs:element name="LetterMarking"> <xs:annotation> <xs:documentation>Complete wagon category letter code. The </pre>						

	<p>Identification marking for freight rolling stock (wagon type) is defined in UIC Leaflet 438-2</xs:documentation></p> <pre> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="20"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **RollingStockDataset/DesignDataSet/TankCode**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation maxLength 20
annotation	documentation Tank code (applies only for tank wagons). The codes are defined in the RID regulation, chapter 4.3.3 and 4.3.4.1.1
source	<pre> <xs:element name="TankCode" minOccurs="0"> <xs:annotation> <xs:documentation>Tank code (applies only for tank wagons). The codes are defined in the RID regulation, chapter 4.3.3 and 4.3.4.1.1</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="20"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **RollingStockDataset/DesignDataSet/WheelSetType**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation maxLength 256
annotation	documentation Type name of the wheel sets, and the name of the type depends on the manufacturer.

source	<pre><xs:element name="WheelSetType" minOccurs="0"> <xs:annotation> <xs:documentation>Type name of the wheel sets, and the name of the type depends on the manufacturer.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element></pre>
--------	---

element **RollingStockDataset/DesignDataSet/BogiePivotPitch**


diagram	 <p>Largest distance between two adjacent bogie pitches ...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric1-5									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation Largest distance between two adjacent bogie pitches in mm									
source	<pre><xs:element name="BogiePivotPitch" type="Numeric1-5" minOccurs="0"> <xs:annotation> <xs:documentation>Largest distance between two adjacent bogie pitches in mm</xs:documentation> </xs:annotation> </xs:element></pre>									

element **RollingStockDataset/DesignDataSet/InnerWheelbase**

diagram	 <p>Maximum distance between two adjacent a...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric1-5									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation Maximum distance between two adjacent axles in mm									
source	<pre><xs:element name="InnerWheelbase" type="Numeric1-5"> <xs:annotation> <xs:documentation>Maximum distance between two adjacent axles in mm</xs:documentation></pre>									

	<pre></xs:annotation> </xs:element></pre>
--	---

element **RollingStockDataset/DesignDataSet/BufferType**

diagram	 <p>Classification of buffer. The following values are mostly used in the sector.: A, AX, B, C, CX, L0 (130), L0 (150), L2 (130), L2 (150), L4 (130), L4 (150)</p>						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	minOcc 0 maxOcc 1 content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	256	
Kind	Value	Annotation					
maxLength	256						
annotation	documentation Classification of buffer. The following values are mostly used in the sector.: A, AX, B, C, CX, L0 (130), L0 (150), L2 (130), L2 (150), L4 (130), L4 (150)						
source	<pre><xs:element name="BufferType" minOccurs="0"> <xs:annotation> <xs:documentation> Classification of buffer. The following values are mostly used in the sector.: A, AX, B, C, CX, L0 (130), L0 (150), L2 (130), L2 (150), L4 (130), L4 (150)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element></pre>						

element **RollingStockDataset/DesignDataSet/LoadTable**

<p>diagram</p>	<p>LoadTable (0, ∞) Indicates the load tables marked on the wagon. When load tables are marked on the wagon the information must be provided in the RSRD message. Several load tables (international, product specific for LPG wagons and additional/country specific) can be specified by providing the element several times consecutively. For special wagons with specific load tables (e.g. heavy haul wagons) no load table need to be provided. The complete load table must be provided including the e...</p> <p>LoadTableProduct (1, ∞) Product description, only applies for product-specific load tables</p> <p>LoadTableCountry (0, ∞) ISO country code of countries for additional load...</p> <p>SpeedCategory (1, ∞) Numeric speed in load table, without speed empty in k...</p> <p>LoadTableStars (1, ∞) Number of load table stars. Currently recognized values/codes: 1 = Authorised to run loaded in trains up to 100 km/h with a brake that does not meet all the requirements for 100 km/h conditions 2 = Authorised to run loaded in trains up to 120 km/h with a brake that does not meet all the requirements for 120 km/h conditions 3 = Authorised to run loaded in trains up to 120 km/h with a brake that does not meet all the requirements for 120 km/h conditions. Wagon is fitted with an automatic load-proportional braking sy...</p> <p>RouteClassPayloa... (1, ∞)</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc unbounded content complex</p>
<p>children</p>	<p>LoadTableProduct LoadTableCountry SpeedCategory LoadTableStars RouteClassPayloads</p>
<p>annotation</p>	<p>documentation Indicates the load tables marked on the wagon. When load tables are marked on the wagon the information must be provided in the RSRD message. Several load tables (international, product specific for LPG wagons and additional/country specific) can be specified by providing the element several times consecutively. For special wagons with specific load tables (e.g. heavy haul wagons) no load table need to be provided. The complete load table must be provided including the empty load row (if existent).</p>
<p>source</p>	<pre><xs:element name="LoadTable" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Indicates the load tables marked on the wagon. When load tables are marked on the wagon the information must be provided in the RSRD message. Several load tables (international, product specific for LPG wagons and additional/country specific) can be specified by providing the element several times consecutively. For special wagons with specific load tables (e.g. heavy haul wagons) no load table need to be provided. The complete load table must be provided including the empty load row (if existent).</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="LoadTableProduct" minOccurs="0"> <xs:annotation> <xs:documentation>Product description, only applies for product- specific load tables</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>


```

<xs:complexType>
  <xs:sequence>
    <xs:element name="ProductUNCode" type="Numeric4-4">
      <xs:annotation>
        <xs:documentation>UN code of product if product specific
load table</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="ProductRIDName">
      <xs:annotation>
        <xs:documentation> RID product name as written on the
folding panel</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:maxLength value="256"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="LoadTableCountry" type="CountryIdentISO"
minOccurs="0" maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>ISO country code of countries for additional
load tables</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="SpeedCategory" type="Numeric1-5"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>Numeric speed in load table, without speed empty
in km/h</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element ref="LoadTableStars" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Number of load table stars. Currently recognized
values/codes:
1 = Authorised to run loaded in trains up to 100 km/h with a brake that does
not meet all the requirements for 100 km/h conditions
2 = Authorised to run loaded in trains up to 120 km/h with a brake that does
not meet all the requirements for 120 km/h conditions
3 = Authorised to run loaded in trains up to 120 km/h with a brake that does
not meet all the requirements for 120 km/h conditions. Wagon is fitted with
an automatic load-proportional braking system.
</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="RouteClassPayloads" maxOccurs="unbounded">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="RouteClass"/>
      <xs:element name="MaxPayload" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Maximum payload in tons of line category;
number of entries must fit to number of entries in

```

	<pre> SpeedCategory</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="4"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **RollingStockDataSet/DesignDataSet/LoadTable/LoadTableProduct**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	ProductUNCode ProductRIDName
annotation	documentation Product description, only applies for product-specific load tables
source	<pre> <xs:element name="LoadTableProduct" minOccurs="0"> <xs:annotation> <xs:documentation>Product description, only applies for product-specific load tables</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="ProductUNCode" type="Numeric4-4"> <xs:annotation> <xs:documentation>UN code of product if product specific load table</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ProductRIDName"> <xs:annotation> <xs:documentation> RID product name as written on the folding panel</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </pre>

	<pre></xs:complexType> </xs:element></pre>
--	--

element **RollingStockDataset/DesignDataSet/LoadTable/LoadTableProduct/ProductUNCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric4-4									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0001		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0001									
maxInclusive	9999									
annotation	documentation UN code of product if product specific load table									
source	<pre><xs:element name="ProductUNCode" type="Numeric4-4"> <xs:annotation> <xs:documentation>UN code of product if product specific load table</xs:documentation> </xs:annotation> </xs:element></pre>									


element **RollingStockDataset/DesignDataSet/LoadTable/LoadTableProduct/ProductRIDName**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	256	
Kind	Value	Annotation					
maxLength	256						
annotation	documentation RID product name as written on the folding panel						
source	<pre><xs:element name="ProductRIDName"> <xs:annotation> <xs:documentation> RID product name as written on the folding panel</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element></pre>						


element **RollingStockDataset/DesignDataSet/LoadTable/LoadTableCountry**

diagram	 <p>ISO country code of countries for additional load...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	CountryIdentISO
properties	minOcc 0 maxOcc unbounded content simple
facets	Kind Value Annotation minLength 2 maxLength 2
annotation	documentation ISO country code of countries for additional load tables
source	<pre><xs:element name="LoadTableCountry" type="CountryIdentISO" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>ISO country code of countries for additional load tables</xs:documentation> </xs:annotation> </xs:element></pre>


element **RollingStockDataset/DesignDataSet/LoadTable/SpeedCategory**

diagram	 <p>Numeric speed in load table, without speed empty in k...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric1-5
properties	minOcc 1 maxOcc unbounded content simple
facets	Kind Value Annotation minInclusive 1 maxInclusive 99999
annotation	documentation Numeric speed in load table, without speed empty in km/h
source	<pre><xs:element name="SpeedCategory" type="Numeric1-5" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Numeric speed in load table, without speed empty in km/h</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/LoadTable/RouteClassPayloads**

<p>diagram</p>	 <p>RouteClass Indication of the route class (based on CEN EN 15528: line categories for managing the interface between load limits of vehicles on infrastructure). All the codes in this code list refer to CEN EN 15528: line categories for managing the interface between load limits of vehicles on infrastructure. CM2, CM3 and CM4 equal M2, M3 and M4 which might be used in some legacy sys...</p> <p>MaxPaylo... Maximum payload in tons of line category; number of entries must fit to number of entries in SpeedCategory</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 1 maxOcc unbounded content complex</p>
<p>children</p>	<p>RouteClass MaxPayload</p>
<p>source</p>	<pre><xs:element name="RouteClassPayloads" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element ref="RouteClass"/> <xs:element name="MaxPayload" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Maximum payload in tons of line category; number of entries must fit to number of entries in SpeedCategory</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="4"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/LoadTable/RouteClassPayloads/MaxPayload**

<p>diagram</p>	 <p>MaxPaylo... Maximum payload in tons of line category; number of entries must fit to number of entries in SpeedCategory</p>						
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>						
<p>type</p>	<p>restriction of xs:decimal</p>						
<p>properties</p>	<p>minOcc 1 maxOcc unbounded content simple</p>						
<p>facets</p>	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	4	
Kind	Value	Annotation					
totalDigits	4						

	fractionDigits 1
annotation	documentation Maximum payload in tonns of line category; number of entries must fit to number of entries in SpeedCategory
source	<pre><xs:element name="MaxPayload" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Maximum payload in tonns of line category; number of entries must fit to number of entries in SpeedCategory</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="4"/> <xs:fractionDigits value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/DerailmentDetectionDevice**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	DerailmentDetectionDevice
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation enumeration EDT 101 enumeration MDV 100 enumeration Non coded device
source	<pre><xs:element name="DerailmentDetectionDevice" type="DerailmentDetectionDevice" minOccurs="0"/></pre>

element **RollingStockDataset/DesignDataSet/BrakeBlock**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	BrakeBlockName CompositeBrakeBlockRetrofitted CompositeBrakeBlockInstallationDate
annotation	documentation Characteristics of brake blocks
source	<pre><xs:element name="BrakeBlock" minOccurs="0"> <xs:annotation></pre>

	<pre> <xs:documentation>Characteristics of brake blocks</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="BrakeBlockName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of the brake block type, including the length in mm</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="CompositeBrakeBlockRetrofitted" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation> Indication if composite brake blocks are retrofitted or originally equipped</xs:documentation> </xs:annotation> </xs:element> <xs:element name="CompositeBrakeBlockInstallationDate" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date of composite brake block installation, for originally equipped wagon = date put into service</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **RollingStockDataset/DesignDataSet/BrakeBlock/BrakeBlockName**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	minOcc 0 maxOcc 1 content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	256	
Kind	Value	Annotation					
maxLength	256						
annotation	documentation Name of the brake block type, including the length in mm						
source	<pre> <xs:element name="BrakeBlockName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of the brake block type, including the length in mm</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="256"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>						

```


</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **RollingStockDataset/DesignDataSet/BrakeBlock/CompositeBrakeBlockRetrofitted**

diagram	 <p>Indication if composite brake blocks are retrofitted or originally equipped</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Indication if composite brake blocks are retrofitted or originally equipped
source	<pre> <xs:element name="CompositeBrakeBlockRetrofitted" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation> Indication if composite brake blocks are retrofitted or originally equipped</xs:documentation> </xs:annotation> </xs:element> </pre>

element **RollingStockDataset/DesignDataSet/BrakeBlock/CompositeBrakeBlockInstallationDate**

diagram	 <p>Date of composite brake block installation, for originally equipped wagon = date put into service</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Date of composite brake block installation, for originally equipped wagon = date put into service
source	<pre> <xs:element name="CompositeBrakeBlockInstallationDate" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date of composite brake block installation, for originally equipped wagon = date put into service</xs:documentation> </xs:annotation> </xs:element> </pre>


element **RollingStockDataset/DesignDataSet/WagonTelematics**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	WagonTelematics
properties	minOcc 0 maxOcc 1 content complex
children	TelematicsOnBoard TelematicsDevice
annotation	documentation Information about telematics devices mounted on the wagon.
source	<pre><xs:element name="WagonTelematics" type="WagonTelematics" minOccurs="0"> <xs:annotation> <xs:documentation xml:lang="en">Information about telematics devices mounted on the wagon.</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/HeightOfLoadingPlaneUnladen**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric1-5
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minInclusive 1 maxInclusive 99999
annotation	documentation Height of the loading plane when wagon is empty measured in mm
source	<pre><xs:element name="HeightOfLoadingPlaneUnladen" type="Numeric1-5" minOccurs="0"> <xs:annotation> <xs:documentation>Height of the loading plane when wagon is empty measured in mm</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/RemovableAccessories**


<p>diagram</p>	 <p>TypeOfRemovableAccessories Specification of removable accessory. TypeOfRemovableAccessories code list is used. Values refer to UIC Leaflet 920-13: 01 = Removable stanchion 02 = Removable side flap of flat wagon 03 = Removable end flap of flat wagon 04 = Removable side rail 05 = Removable intermediate upright for securing the load 06 = Stanchion chain 07 = Removable handle and wheel for winch on car-carrying wagon 08 = Swivelling bolster (with stanchions) 09 = Coupling rod (rigid coupling) 10 = Ice bunker 11 = Ice bunker screen 12 = Ice bunker frame 13 = Trestle or bar with hooks for hanging meat 14 = Movable cross-member of wagon with low loading plane 15 = Removable support 16 = Mooring cross-member on wagon for special loads 17 = Movable floor panel on wagon for special loads 18 = Scotch 19 = Skid bar with or without shoes on car-carrying wagon 20 = Mooring strap on car-carrying wagon 21 = Beam for movable ramp on car-carrying wagon 22 = Spare heating half-coupling 23 = Fire extinguisher 24 = Wheel scotches (for cars) on car-carrying wagon 25 = Gangway loading ramp on car-carrying wagon 26 = Metal cradles for rolls of metal sheeting 27 = Panel for covering markings 28 = Loading frame for special types of goods 29 = Headstock for 'rolling road...</p> <p>NumberOfAccessorOfSpecType Number of specified accessory equipped on the wagon</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc unbounded content complex</p>
<p>children</p>	<p>TypeOfRemovableAccessories NumberOfAccessorOfSpecType</p>
<p>source</p>	<pre><xs:element name="RemovableAccessories" minOccurs="0" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element ref="TypeOfRemovableAccessories"> <xs:annotation> <xs:documentation>Specification of removable accessory. TypeOfRemovableAccessories code list is used. Values refer to UIC Leaflet 920-13: 01 = Removable stanchion 02 = Removable side flap of flat wagon 03 = Removable end flap of flat wagon 04 = Removable side rail 05 = Removable intermediate upright for securing the load 06 = Stanchion chain 07 = Removable handle and wheel for winch on car-carrying wagon 08 = Swivelling bolster (with stanchions) 09 = Coupling rod (rigid coupling) 10 = Ice bunker 11 = Ice bunker screen 12 = Ice bunker frame 13 = Trestle or bar with hooks for hanging meat 14 = Movable cross-member of wagon with low loading plane 15 = Removable support</pre>

	<p>16 = Mooring cross-member on wagon for special loads 17 = Movable floor panel on wagon for special loads 18 = Scotch 19 = Skid bar with or without shoes on car-carrying wagon 20 = Mooring strap on car-carrying wagon 21 = Beam for movable ramp on car-carrying wagon 22 = Spare heating half-coupling 23 = Fire extinguisher 24 = Wheel scotches (for cars) on car-carrying wagon 25 = Gangway loading ramp on car-carrying wagon 26 = Metal cradles for rolls of metal sheeting 27 = Panel for covering markings 28 = Loading frame for special types of goods 29 = Headstock for "rolling roads" 99 = Other wagon accessories</p> <pre> </xs:documentation> </xs:annotation> </xs:element> <xs:element name="NumberOfAccessorOfSpecType" type="Numeric2-2"> <xs:annotation> <xs:documentation>Number of specified accessory equipped on the wagon</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **RollingStockDataset/DesignDataSet/RemovableAccessories/NumberOfAccessorOfSpecType**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric2-2									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
annotation	<p>documentation Number of specified accessory equipped on the wagon</p>									
source	<pre> <xs:element name="NumberOfAccessorOfSpecType" type="Numeric2-2"> <xs:annotation> <xs:documentation>Number of specified accessory equipped on the wagon</xs:documentation> </xs:annotation> </xs:element> </pre>									

element **RollingStockDataset/DesignDataSet/VapourReturnSystem**

diagram	 <p>VapourReturnSystem Indication if tank wagon is equipped with a vapour return system</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Indication if tank wagon is equipped with a vapour return system
source	<pre><xs:element name="VapourReturnSystem" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>Indication if tank wagon is equipped with a vapour return system</xs:documentation> </xs:annotation> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/FerryRampAngle**

diagram	 <p>FerryRampAngle Maximum allowed angle of the ferry ramp (in grades...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:decimal
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation totalDigits 3 fractionDigits 2
annotation	documentation Maximum allowed angle of the ferry ramp (in grades: °)
source	<pre><xs:element name="FerryRampAngle" minOccurs="0"> <xs:annotation> <xs:documentation>Maximum allowed angle of the ferry ramp (in grades: °)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:totalDigits value="3"/> <xs:fractionDigits value="2"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **RollingStockDataset/DesignDataSet/TemperatureRange**

diagram	<p>The diagram shows a container element 'TemperatureRange' (indicated by a dashed border) containing a sequence of two child elements: 'MaxTemp' and 'MinTemp'. 'MaxTemp' is described as 'Maximum Temperature in °Celsius' and 'MinTemp' as 'Minimum temperature in ° Celsius'.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	MaxTemp MinTemp
source	<pre> <xs:element name="TemperatureRange" minOccurs="0"> <xs:complexType> <xs:sequence> <xs:annotation> <xs:documentation>Temperature Range</xs:documentation> </xs:annotation> <xs:element ref="MaxTemp"/> <xs:element ref="MinTemp"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **RollingStockDataset/DesignDataSet/DateOfNextTankInspection**

diagram	<p>The diagram shows the 'DateOfNextTankInspection' element (dashed border) with the documentation: 'Date of the next tank inspection, applies only for tank wagons'.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Date of the next tank inspection, applies only for tank wagons
source	<pre> <xs:element name="DateOfNextTankInspection" type="xs:date" minOccurs="0"> <xs:annotation> <xs:documentation>Date of the next tank inspection, applies only for tank wagons</xs:documentation> </xs:annotation> </xs:element> </pre>

element **RollingStockDatasetMessage**

diagram	<p>The diagram shows the 'RollingStockDatasetMessage' element (dashed border) containing three children: 'MessageHeader' (Used for all messa...), 'RollingStockDataset' (Rolling Stock administrative and Techn..., 0..∞), and 'RefusedWagonNumber' (0..∞).</p>
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader RollingStockDataset RefusedWagonNumbers
annotation	documentation Rolling Stock administrative and Technical Dataset
source	<pre> <xs:element name="RollingStockDatasetMessage"> <xs:annotation> <xs:documentation>Rolling Stock administrative and Technical Dataset</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="RollingStockDataset" minOccurs="0" maxOccurs="unbounded"/> <xs:element name="RefusedWagonNumbers" minOccurs="0" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:element ref="RefusalCode"/> <xs:element ref="KeeperShortNameVKM" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **RollingStockDatasetMessage/RefusedWagonNumbers**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc unbounded content complex
children	WagonNumberFreight RefusalCode KeeperShortNameVKM
source	<pre> <xs:element name="RefusedWagonNumbers" minOccurs="0" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:element ref="RefusalCode"/> <xs:element ref="KeeperShortNameVKM" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>


element **RollingStockDatasetQueryMessage**

diagram	<p>Rolling Stock administrative and Technical Dataset</p> <p>MessageHeader Used for all messa...</p> <p>WagonNumberFreig... 1..∞ Identifies uniquely the freight wagon by its number</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonNumberFreight
annotation	documentation Rolling Stock administrative and Technical Dataset
source	<pre><xs:element name="RollingStockDatasetQueryMessage"> <xs:annotation> <xs:documentation>Rolling Stock administrative and Technical Dataset</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonNumberFreight" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **RouteInformation**

diagram	<p>RouteInformation</p> <p>The route of the journey for a wagon / shipment or Intermodal unit assigned by the LRU</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation The route of the journey for a wagon / shipment or Intermodal unit assigned by the LRU									
source	<pre><xs:element name="RouteInformation" type="FreeText"> <xs:annotation> <xs:documentation>The route of the journey for a wagon / shipment or Intermodal unit assigned by the LRU</xs:documentation> </xs:annotation> </xs:element></pre>									

element **Routing**

<p>diagram</p>	 <p>Sequential information about the complete routing of the consignment, the LeadRu decides wether to provide this information or not</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>RouteSection</p>
<p>annotation</p>	<p>documentation Sequential information about the complete routing of the consignment, the LeadRu decides wether to provide this information or not</p>
<p>source</p>	<pre> <xs:element name="Routing"> <xs:annotation> <xs:documentation>Sequential information about the complete routing of the consignment, the LeadRu decides wether to provide this information or not</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="RouteSection" maxOccurs="30"> <xs:annotation> <xs:documentation>Route sequence</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="SequenceID" type="xs:int"> <xs:annotation> <xs:documentation>Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.</xs:documentation> </xs:annotation> </xs:element> <xs:sequence> <xs:element name="RouteCode"> <xs:annotation> <xs:documentation>Route code (International RouteCode)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="5"/> <xs:pattern value="\d*[1-9]\d*0"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="RouteText" minOccurs="0"> <xs:annotation> <xs:documentation>Description of the specific route section</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="80"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>


	<pre> </xs:simpleType> </xs:element> </xs:sequence> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **Routing/RouteSection**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 1 maxOcc 30 content complex
children	SequenceID RouteCode RouteText
annotation	documentation Route sequence
source	<pre> <xs:element name="RouteSection" maxOccurs="30"> <xs:annotation> <xs:documentation>Route sequence</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="SequenceID" type="xs:int"> <xs:annotation> <xs:documentation>Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.</xs:documentation> </xs:annotation> </xs:element> <xs:sequence> <xs:element name="RouteCode"> <xs:annotation> <xs:documentation>Route code (International RouteCode)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="5"/> <xs:pattern value="\d*[1-9]\d*0"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="RouteText" minOccurs="0"> </pre>

	<pre> <xs:annotation> <xs:documentation>Description of the specific route section</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="80"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **Routing/RouteSection/SequenceID**


diagram	 <p>Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:int
properties	content simple
annotation	documentation Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.
source	<pre> <xs:element name="SequenceID" type="xs:int"> <xs:annotation> <xs:documentation>Position of the route section in transport chain. Used to determine the exact way of the transport for customs purposes.</xs:documentation> </xs:annotation> </xs:element> </pre>

element **Routing/RouteSection/RouteCode**


diagram	 <p>Route code (International RouteCode)</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>5</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*0</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	5		pattern	\d*[1-9]\d*0	
Kind	Value	Annotation								
length	5									
pattern	\d*[1-9]\d*0									
annotation	documentation Route code (International RouteCode)									
source	<pre> <xs:element name="RouteCode"> <xs:annotation> </pre>									

	<pre> <xs:documentation>Route code (International RouteCode)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="5"/> <xs:pattern value="\d*[1-9]\d*0"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **Routing/RouteSection/RouteText**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>80</td> <td></td> </tr> </table>	Kind	Value	Annotation	minLength	1		maxLength	80	
Kind	Value	Annotation								
minLength	1									
maxLength	80									
annotation	documentation Description of the specific route section									
source	<pre> <xs:element name="RouteText" minOccurs="0"> <xs:annotation> <xs:documentation>Description of the specific route section</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="80"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **RP_Code**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
used by	elements ConsignmentOrderMessage/COMS/COM/AcceptancePoint ConsignmentOrderMessage/COMS/COM/DeliveryPoint ProductionStation						
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>length</td> <td>5</td> <td></td> </tr> </table>	Kind	Value	Annotation	length	5	
Kind	Value	Annotation					
length	5						

annotation	documentation Routing point code of the production station of the acceptance or delivery point.
source	<pre> <xs:element name="RP_Code"> <xs:annotation> <xs:documentation>Routing point code of the production station of the acceptance or delivery point. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="5"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **RU_Partner**


diagram	 RU_Partner Railway Undertaka...												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	elements ConsignmentOrderMessage/COMS/COM/CustomsProcedures SpecialTreatments												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Railway Undertaking												
source	<pre> <xs:element name="RU_Partner" type="CompanyCode"> <xs:annotation> <xs:documentation>Railway Undertaking</xs:documentation> </xs:annotation> </xs:element> </pre>												

element **ScheduledDateTimeAtTransfer**


diagram	 ScheduledDateTimeAtTransfer The referenced date and time of arrival or exit at the border between two different IMs
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element OperationalTrainNumberIdentifier
annotation	documentation The referenced date and time of arrival or exit at the border between two different IMs
source	<pre> <xs:element name="ScheduledDateTimeAtTransfer" type="xs:dateTime"> <xs:annotation> <xs:documentation>The referenced date and time of arrival or exit at the </pre>

	<pre>border between two different IMs</xs:documentation> </xs:annotation> </xs:element></pre>
--	---

element **ScheduledTimeAtHandover**

diagram	 <p>The referenced date and time of departure or entrance at the border between two different IMs</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element OperationalTrainNumberIdentifier
annotation	documentation The referenced date and time of departure or entrance at the border between two different IMs
source	<pre><xs:element name="ScheduledTimeAtHandover" type="xs:dateTime"> <xs:annotation> <xs:documentation>The referenced date and time of departure or entrance at the border between two different IMs</xs:documentation> </xs:annotation> </xs:element></pre>

element **ScheduledTimeAtLocation**

diagram	 <p>Scheduled Date and Time at a location related to the status of the train or wagon at the given loca...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element ExceptionPoint
annotation	documentation Scheduled Date and Time at a location related to the status of the train or wagon at the given location
source	<pre><xs:element name="ScheduledTimeAtLocation" type="xs:dateTime"> <xs:annotation> <xs:documentation>Scheduled Date and Time at a location related to the status of the train or wagon at the given location</xs:documentation> </xs:annotation> </xs:element></pre>

element **Seals**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>NumberOfSeals SealsDescription</p>
<p>used by</p>	<p>elements ITU Details Wagons/WagonDetails</p>
<p>annotation</p>	<p>documentation Describes the seals used for the consignment</p>
<p>source</p>	<pre> <xs:element name="Seals"> <xs:annotation> <xs:documentation>Describes the seals used for the consignment</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="NumberOfSeals"> <xs:annotation> <xs:documentation>Number of the seals attached by the original consignor.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:totalDigits value="2"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="SealsDescription" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>Additional information of the original consignor regarding the attached seals.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="10"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **Seals/NumberOfSeals**

<p>diagram</p>	
----------------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>totalDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		totalDigits	2	
Kind	Value	Annotation								
minInclusive	0									
totalDigits	2									
annotation	documentation Number of the seals attached by the original consignor.									
source	<pre><xs:element name="NumberOfSeals"> <xs:annotation> <xs:documentation>Number of the seals attached by the original consignor.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:totalDigits value="2"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Seals/SealsDescription**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>10</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	10	content	simple			
minOcc	0									
maxOcc	10									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>10</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	10	
Kind	Value	Annotation								
minLength	1									
maxLength	10									
annotation	documentation Additional information of the original consignor regarding the attached seals.									
source	<pre><xs:element name="SealsDescription" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>Additional information of the original consignor regarding the attached seals.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="10"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Sender**

diagram						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3					
type	extension of CompanyCode					
properties	content complex					
used by	element MessageHeader					
facets	Kind	Value	Annotation			
	minLength	4				
	maxLength	4				
	pattern	[0-9A-Z]{4}				
attributes	Name	Type	Use	Default	Fixed	Annotation
	CI_InstanceNumber	Numeric2-2				documentation Number of a Common Interface Instance for the same Company
annotation	documentation The sender of the message					
source	<pre><xs:element name="Sender"> <xs:annotation> <xs:documentation>The sender of the message</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="CompanyCode"> <xs:attribute ref="CI_InstanceNumber"/> </xs:extension> </xs:simpleContent> </xs:complexType> </xs:element></pre>					

element **SenderReference**

diagram						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3					
type	FreeText					
properties	content simple					
used by	element MessageHeader					
facets	Kind	Value	Annotation			
	minLength	1				
	maxLength	255				
annotation	documentation reference used by the sender (e.g. FTP file name)					


source	<pre><xs:element name="SenderReference" type="FreeText"> <xs:annotation> <xs:documentation>reference used by the sender (e.g. FTP file name)</xs:documentation> </xs:annotation> </xs:element></pre>
--------	--

element Ship


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	VesselIndication HarbourName ShipOwner
used by	elements ITU Details Wagons/WagonDetails
annotation	documentation Additional information for transports, which shall be handed over to a ship
source	<pre><xs:element name="Ship"> <xs:annotation> <xs:documentation>Additional information for transports, which shall be handed over to a ship</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="VesselIndication"/> <xs:element name="HarbourName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of harbour, where the transport will be handed over to a ship.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ShipOwner" minOccurs="0"> <xs:annotation> <xs:documentation>Name of ship owner.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **Ship/HarbourName**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Name of harbour, where the transport will be handed over to a ship.									
source	<pre> <xs:element name="HarbourName" minOccurs="0"> <xs:annotation> <xs:documentation>Name of harbour, where the transport will be handed over to a ship.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="35"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Ship/ShipOwner**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>35</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	35	
Kind	Value	Annotation								
minLength	1									
maxLength	35									
annotation	documentation Name of ship owner.									
source	<pre> <xs:element name="ShipOwner" minOccurs="0"> <xs:annotation> <xs:documentation>Name of ship owner.</xs:documentation> </xs:annotation> </pre>									

```
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="35"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
```

element **SpecialTreatments**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>RU_Partner SpecialTreatmentCode SpecialTreatmentInformation Location</p>
<p>used by</p>	<p>elements ConsignmentOrderMessage/COMS/COM WIMO Dataset/ConsignmentLevelData</p>
<p>annotation</p>	<p>documentation Special treatment</p>
<p>source</p>	<pre><xs:element name="SpecialTreatments"> <xs:annotation> <xs:documentation>Special treatment</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="RU_Partner" minOccurs="0"> <xs:annotation> <xs:documentation>Railway Undertaking dedicated to fulfill the special treatment</xs:documentation> </xs:annotation> </xs:element> <xs:element name="SpecialTreatmentCode"> <xs:annotation> <xs:documentation>Special Treatment code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="2"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="SpecialTreatmentInformation" minOccurs="0"> <xs:annotation> <xs:documentation>Additional Text for codes with free text</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="40"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="Location" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **SpecialTreatments/SpecialTreatmentCode**


diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	2	
Kind	Value	Annotation					
length	2						
annotation	documentation Special Treatment code						
source	<pre> <xs:element name="SpecialTreatmentCode"> <xs:annotation> <xs:documentation>Special Treatment code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="2"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>						

element **SpecialTreatments/SpecialTreatmentInformation**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>40</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	40	
Kind	Value	Annotation								
minLength	1									
maxLength	40									
annotation	documentation Additional Text for codes with free text									
source	<pre> <xs:element name="SpecialTreatmentInformation" minOccurs="0"> <xs:annotation> <xs:documentation>Additional Text for codes with free </pre>									

	<pre> text</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="40"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **SRID**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	content simple						
used by	element GeographicCoordinates						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[0-9]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	pattern	[0-9]{4}	
Kind	Value	Annotation					
pattern	[0-9]{4}						
annotation	documentation ID of coordinates system used (EPSG code)						
source	<pre> <xs:element name="SRID"> <xs:annotation> <xs:documentation>ID of coordinates system used (EPSG code)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:pattern value="[0-9]{4}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>						

element **StartDate**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:date
properties	content simple
used by	complexTypees CompositIdentifierOperationalType CompositIdentifierPlannedType
annotation	documentation The start of the date/time in effect
source	<pre> <xs:element name="StartDate" type="xs:date"> <xs:annotation> <xs:documentation>The start of the date/time in effect</xs:documentation> </pre>

	<pre></xs:annotation> </xs:element></pre>
--	---

element StartDateTime

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	elements RequestedPeriod RequestedTimeframe ValidityPeriod
annotation	documentation The start of the date/time in effect
source	<pre><xs:element name="StartDateTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>The start of the date/time in effect</xs:documentation> </xs:annotation> </xs:element></pre>

element StartLocation

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Starting point of section or segment
source	<pre><xs:element name="StartLocation" type="LocationIdent"> <xs:annotation> <xs:documentation>Starting point of section or segment</xs:documentation> </xs:annotation> </xs:element></pre>

element **Station**

diagram	<p>The diagram shows a class Station (with a small square icon) connected to a class LocationIdent (with a dashed box around it). Station is an extension of LocationIdent. LocationIdent has four child elements: CountryCodeISO (Identifies a Country or State by code (ISO 316...)), LocationPrimaryCode, PrimaryLocationName (Location Name in an offication language of the Country using the ISO Unicode alph...), and LocationSubsidiaryIdentification (Code, Name and allocation company of Subsidiary Location).</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
used by	elements ConsignmentOrderMessage/COMS/COM/AcceptancePoint ConsignmentOrderMessage/COMS/COM/DeliveryPoint
annotation	documentation Details of station serving the point
source	<pre> <xs:element name="Station"> <xs:annotation> <xs:documentation>Details of station serving the point</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"/> </xs:complexContent> </xs:complexType> </xs:element> </pre>

element **StatusOfDocument**

diagram	<p>The diagram shows an enumerated type StatusOfDocument (with a small square icon). It is described as an enumerated value for the status of the attached document. It has two values: 1 (not electronical attached) and 2 (embedded in ECTD, EC...).</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:token									
properties	content simple									
used by	element ConsignmentOrderMessage/COMS/COM/AttachedDocuments									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>2</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	2		enumeration	1	
Kind	Value	Annotation								
enumeration	2									
enumeration	1									
annotation	documentation									

	<p>Enumerated value for the status of the attached document</p> <p>1 = not electronical attached</p> <p>2 embedded in ECTD, ECN or PCN</p>
source	<pre> <xs:element name="StatusOfDocument"> <xs:annotation> <xs:documentation> Enumerated value for the status of the attached document 1 = not electronical attached 2 embedded in ECTD, ECN or PCN </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="2"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **SummaryOfGoodsWithSameRID**

diagram	<p>The diagram shows a central box labeled 'SummaryOfGoodsWithSameRID' with a dashed border and a small icon. To its right, four smaller boxes are arranged vertically, each representing a child element: 'UN_Number', 'PackingGroup', 'DangerousGoodsWeight', and 'DangerousGoodsVolume'. Dashed lines connect the central box to each of these child boxes, indicating their relationship. Each child box has a small icon and a title. Below each child box is a brief description of its content.</p> <p>UN_Number The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC...</p> <p>PackingGro... The Packing Group according to the RID chapter 3.2, table A, column 4. Possible values are "I", "II" or "III", otherwise the Packing Group have to be omitted. Mandatory, if it's foreseen in column 4, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC...</p> <p>DangerousGoodsWeig... The weight of the dangerous goods in Kilogr...</p> <p>DangerousGoodsVolu... The volume of the dangerous goods in cubic ...</p> <p>This element is only in use if the consignment includes more than one good with the same UN-Number in , packing group and probershipping name in the wagon. The added amount of the dangerous goods are to be stored here</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	UN Number PackingGroup DangerousGoodsWeight DangerousGoodsVolume
used by	elements ITU RollingRoadUnit Wagons
annotation	documentation This element is only in use if the consignment includes more than one good with the same UN-Number in , packing group and probershipping name in the wagon. The added amount of the dangerous goods are to be stored here
source	<pre> <xs:element name="SummaryOfGoodsWithSameRID"> <xs:annotation> <xs:documentation>This element is only in use if the consignment </pre>

```

includes more than one good with the same UN-Number in , packing group and
probershipping name in the wagon. The added amount of the dangerous goods
are to be stored here</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element ref="UN_Number" minOccurs="0"/>
    <xs:element ref="PackingGroup" minOccurs="0"/>
    <xs:element ref="DangerousGoodsWeight" minOccurs="0">
      <xs:annotation>
        <xs:documentation>The weight of the dangerous goods in
Kilograms</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element ref="DangerousGoodsVolume" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:element>

```

element **TechnicalForwardingRestrictions**

diagram

TechnicalForwardingRestrictions

This element is designed to identify any special aspects or restrictions which might be relevant to wagon handling operations in train formation yards or in trains because of technical feature of the wagon or its load-
All codes of Transport restrictions for Freight Traffic (cf. UIC 920-13) and Passengers Traffic are in the same list which is contained in the code list RestrictionCodes.

In this element we use only those codes that have "T - Technical" characteristics and "F - Freight" as the type. The codes below are sorted out from the RestrictionCodes. Only these codes should be used in this element.

F =
Freight

P = Passenger
T = Technical
D = Damage
L = Load

Code	F or P	Description
		T
D	L	
07	F	Shunt only when hand brake operable with ground staff
		x
11	F	Wagon other than bogie wagon with wheelbase of more than 9 metres
		x
12	F	Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres
13	F	Bogie wagon with distance between wheels of more than 17,50 metres
		x
15	F	Wagon not allowed over the hump
		x
16	F	Do not fly shunt or gravity shunt (3 red triangles)
		...


namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	RestrictionCodes		
properties	content	simple	
used by	element	RollingStockDataset/DesignDataSet	
facets	Kind	Value	Annotation
	enumeration	07	documentation F - Shunt only when hand brake operable with ground staff
	enumeration	08	documentation F - Tank wagon loaded with liquid
	enumeration	09	documentation F - Wagon loaded with people
	enumeration	11	documentation F - Wagon other than bogie wagon with wheelbase of more than 9 metres
	enumeration	12	documentation F - Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres
	enumeration	13	documentation F - Bogie wagon with distance between wheels of more than 17,50 metres
	enumeration	15	documentation F - Wagon not allowed over the hump
	enumeration	16	documentation F - Do not fly shunt or gravity shunt (3 red triangles)
	enumeration	18	documentation F - Must not use active braking equipment
	enumeration	25	documentation F - Gas carrying tank wagon with orange side stripe
	enumeration	30	documentation P (+F) - CCS fault (see CCS coding list)
	enumeration	31	documentation P (+F) - Braking system fault
	enumeration	32	documentation P (+F) - Wheelset, bogie fault
	enumeration	33	documentation P (+F) - Headlighting or back lighting fault
	enumeration	34	documentation P (+F) - Front glass broken
	enumeration	35	documentation P (+F) - Horn fault
	enumeration	36	documentation P (+F) - Radio fault
	enumeration	37	documentation P (+F) - Energy supply fault
	enumeration	38	documentation P (+F) - Traction or motor fault
	enumeration	39	documentation P - Access door fault
	enumeration	41	documentation F - Place this wagon at the front of the train
	enumeration	42	documentation F - Place this wagon at the rear of the train
	enumeration	50	documentation P (+F) - Speed restriction
	enumeration	52	documentation P (+F) - Diesel locomotive instead of electric locomotive
	enumeration	61	documentation F - Wagon forming part of a consignment of several wagons
	enumeration	62	documentation F - Wagon forming part of a group of wagons from which it must not be separated
	enumeration	63	documentation F (+P) - Special consignment or (for Passengers trains) loading/cinematic gauge larger

	enumeration 68	than the planned one documentation F - First or last wagon of a wagon group from which it must not be separated																																																												
	enumeration 70	documentation F - Shunt with care (1 red triangle)																																																												
	enumeration 71	documentation F - Shunt with special care (2 red triangle)																																																												
	enumeration 90	documentation P - Train planned with passengers operated without passengers																																																												
	enumeration 91	documentation P - Train planned without passengers operated with passengers																																																												
	enumeration 92	documentation P - Train planned with hauled rolling stock and operated without any coaches (light engine)																																																												
	enumeration 94	documentation F - Gas carrying wagon without orange side stripe																																																												
	enumeration 99	documentation P - Other																																																												
annotation	documentation	<p>This element is designed to identify any special aspects or restrictions which might be relevant to wagon handling operations in train formation yards or in trains because of technical feature of the wagon or its load- All codes of Transport restrictions for Freight Traffic (cf. UIC 920-13) and Passengers Traffic are in the same list which is contained in the code list RestrictionCodes. In this element we use only those codes that have "T - Technical" characteristics and "F - Freight" as the type. The codes below are sorted out from the RestrictionCodes. Only these codes should be used in this element.</p> <p style="text-align: right;">F = Freight</p> <p>P = Passenger T = Technical D = Damage L = Load</p> <table border="1"> <thead> <tr> <th>Code</th> <th>F or P</th> <th>Description</th> <th>T</th> <th>D</th> <th>L</th> </tr> </thead> <tbody> <tr> <td>07</td> <td>F</td> <td>Shunt only when hand brake operable with ground staff</td> <td></td> <td></td> <td></td> </tr> <tr> <td>11</td> <td>F</td> <td>Wagon other than bogie wagon with wheelbase of more than 9 metres</td> <td></td> <td></td> <td>x</td> </tr> <tr> <td>12</td> <td>F</td> <td>Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres</td> <td></td> <td></td> <td>x</td> </tr> <tr> <td>13</td> <td>F</td> <td>Bogie wagon with distance between wheels of more than 17,50 metres</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>F</td> <td>Wagon not allowed over the hump</td> <td></td> <td></td> <td></td> </tr> <tr> <td>16</td> <td>F</td> <td>Do not fly shunt or gravity shunt (3 red triangles)</td> <td></td> <td>x</td> <td>x</td> </tr> <tr> <td>18</td> <td>F</td> <td>Must not use active braking equipment</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td>F</td> <td>Gas carrying tank wagon with orange side stripe</td> <td></td> <td></td> <td></td> </tr> <tr> <td>41</td> <td>F</td> <td>Place this wagon at the front of the train</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Code	F or P	Description	T	D	L	07	F	Shunt only when hand brake operable with ground staff				11	F	Wagon other than bogie wagon with wheelbase of more than 9 metres			x	12	F	Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres			x	13	F	Bogie wagon with distance between wheels of more than 17,50 metres				15	F	Wagon not allowed over the hump				16	F	Do not fly shunt or gravity shunt (3 red triangles)		x	x	18	F	Must not use active braking equipment				25	F	Gas carrying tank wagon with orange side stripe				41	F	Place this wagon at the front of the train			
Code	F or P	Description	T	D	L																																																									
07	F	Shunt only when hand brake operable with ground staff																																																												
11	F	Wagon other than bogie wagon with wheelbase of more than 9 metres			x																																																									
12	F	Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres			x																																																									
13	F	Bogie wagon with distance between wheels of more than 17,50 metres																																																												
15	F	Wagon not allowed over the hump																																																												
16	F	Do not fly shunt or gravity shunt (3 red triangles)		x	x																																																									
18	F	Must not use active braking equipment																																																												
25	F	Gas carrying tank wagon with orange side stripe																																																												
41	F	Place this wagon at the front of the train																																																												

	<table border="0"> <tr> <td>42</td> <td>x F</td> <td>x</td> <td>x</td> <td>Place this wagon at the rear of the train</td> </tr> <tr> <td>63</td> <td>x F (+P)</td> <td>x</td> <td>x</td> <td>Special consignment or (for Passengers trains) loading/cinematic gauge larger than the planned one</td> </tr> <tr> <td>70</td> <td>F</td> <td></td> <td></td> <td>Shunt with care (1 red triangle)</td> </tr> <tr> <td>71</td> <td>F</td> <td></td> <td>x x x</td> <td>Shunt with special care (2 red triangle)</td> </tr> <tr> <td>94</td> <td>x F</td> <td>x</td> <td>x</td> <td>Gas carrying wagon without orange side stripe</td> </tr> </table> <p style="text-align: right;">x</p>	42	x F	x	x	Place this wagon at the rear of the train	63	x F (+P)	x	x	Special consignment or (for Passengers trains) loading/cinematic gauge larger than the planned one	70	F			Shunt with care (1 red triangle)	71	F		x x x	Shunt with special care (2 red triangle)	94	x F	x	x	Gas carrying wagon without orange side stripe
42	x F	x	x	Place this wagon at the rear of the train																						
63	x F (+P)	x	x	Special consignment or (for Passengers trains) loading/cinematic gauge larger than the planned one																						
70	F			Shunt with care (1 red triangle)																						
71	F		x x x	Shunt with special care (2 red triangle)																						
94	x F	x	x	Gas carrying wagon without orange side stripe																						
<p>source</p>	<pre><xs:element name="TechnicalForwardingRestrictions" type="RestrictionCodes"> <xs:annotation> <xs:documentation>This element is designed to identify any special aspects or restrictions which might be relevant to wagon handling operations in train formation yards or in trains because of technical feature of the wagon or its load- All codes of Transport restrictions for Freight Traffic (cf. UIC 920- 13) and Passengers Traffic are in the same list which is contained in the code list RestrictionCodes. In this element we use only those codes that have "T - Technical" characteristics and "F - Freight" as the type. The codes below are sorted out from the RestrictionCodes. Only these codes should be used in this element. F = Freight P = Passenger T = Technical D = Damage L = Load Code F or P Description T D L 07 F Shunt only when hand brake operable with ground staff x x 11 F Wagon other than bogie wagon with wheelbase of more than 9 metres x 12 F Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres x 13 F Bogie wagon with distance between wheels of more than 17,50 metres x 15 F Wagon not allowed over the hump</pre>																									


16	F	<p style="text-align: center;">x x x</p> Do not fly shunt or gravity shunt (3 red triangles)
18	F	<p style="text-align: center;">x x x</p> Must not use active braking equipment
25	F	<p style="text-align: center;">x</p> Gas carrying tank wagon with orange side stripe
41	F	<p style="text-align: center;">x</p> Place this wagon at the front of the train
42	F	<p style="text-align: center;">x x x</p> Place this wagon at the rear of the train
63	F (+P)	<p style="text-align: center;">x x x</p> Special consignment or (for Passengers trains) loading/cinematic gauge larger than the planned one
70	F	<p style="text-align: center;">x x</p> Shunt with care (1 red triangle)
71	F	<p style="text-align: center;">x x x</p> Shunt with special care (2 red triangle)
94	F	<p style="text-align: center;">x x x</p> Gas carrying wagon without orange side stripe
		<p style="text-align: center;">x</p> </xs:documentation> </xs:annotation> </xs:element>

element TiltingFunction


diagram	 <p>Indicates if a rolling stock is fitted with a tilting system</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
used by	element PlannedTrainTechnicalData
annotation	documentation Indicates if a rolling stock is fitted with a tilting system
source	<xs:element name="TiltingFunction" type="xs:boolean"> <xs:annotation> <xs:documentation>Indicates if a rolling stock is fitted with a tilting

	<pre>system</xs:documentation> </xs:annotation> </xs:element></pre>
--	---

element **TimetableYear**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	complexTypees CompositIdentifierOperationalType CompositIdentifierPlannedType									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>2012</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>2097</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	2012		maxInclusive	2097	
Kind	Value	Annotation								
minInclusive	2012									
maxInclusive	2097									
annotation	documentation Refers to the timetable period in which the business will be carried out									
source	<pre><xs:element name="TimetableYear"> <xs:annotation> <xs:documentation>Refers to the timetable period in which the business will be carried out</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="2012"/> <xs:maxInclusive value="2097"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **TimingAtLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Timing DwellTime
used by	elements AssociatedAttachedTimingAtLocation PlannedJourneyLocation

annotation	<p>documentation</p> <p>Timing at an operation point</p> <p>It has an attribute TimerQualifierCode with the following values:</p> <p>PLA = Public Location Arrival ELA = Earliest Location Arrival ALA = Actual Location Arival LLA = Latest Location Arrival PLD = Public Location Departure ELD = Earliest Location Departure ALD = Actual Location Departure LLD = Latest Location Departure ERT = Earliest Run Through ART = Actual Run Through LRT = Latest Run Through</p>
source	<pre> <xs:element name="TimingAtLocation"> <xs:annotation> <xs:documentation>Timing at an operation point It has an attribute TimerQualifierCode with the following values: PLA = Public Location Arrival ELA = Earliest Location Arrival ALA = Actual Location Arival LLA = Latest Location Arrival PLD = Public Location Departure ELD = Earliest Location Departure ALD = Actual Location Departure LLD = Latest Location Departure ERT = Earliest Run Through ART = Actual Run Through LRT = Latest Run Through </xs:documentation> </xs:annotation> </xs:complexType> <xs:sequence> <xs:element name="Timing" minOccurs="0" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element name="Time"> <xs:annotation> <xs:documentation>hh:mm:ss</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:time"/> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element ref="Offset"> <xs:annotation> <xs:documentation>in days</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> </xs:sequence> <xs:attribute ref="TimingQualifierCode"/> </xs:complexType> </xs:element> <xs:element ref="DwellTime" minOccurs="0"/> </pre>

	<pre> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **TimingAtLocation/Timing**


diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
properties	minOcc 0 maxOcc unbounded content complex												
children	Time Offset BookedLocationDateTime												
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>TimingQualifierCode</td> <td>derived by: xs:token</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	TimingQualifierCode	derived by: xs:token				
Name	Type	Use	Default	Fixed	Annotation								
TimingQualifierCode	derived by: xs:token												
source	<pre> <xs:element name="Timing" minOccurs="0" maxOccurs="unbounded"> <xs:complexType> <xs:sequence> <xs:element name="Time"> <xs:annotation> <xs:documentation>hh:mm:ss</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:time"/> </xs:simpleContent> </xs:complexType> </xs:element> <xs:element ref="Offset"> <xs:annotation> <xs:documentation>in days</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="BookedLocationDateTime" minOccurs="0"/> </xs:sequence> <xs:attribute ref="TimingQualifierCode"/> </xs:complexType> </xs:element> </pre>												

element **TimingAtLocation/Timing/Time**


diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of xs:time
properties	content complex
annotation	documentation hh:mm:ss
source	<pre><xs:element name="Time"> <xs:annotation> <xs:documentation>hh:mm:ss</xs:documentation> </xs:annotation> <xs:complexType> <xs:simpleContent> <xs:extension base="xs:time"/> </xs:simpleContent> </xs:complexType> </xs:element></pre>

element **TotalLoadWeight**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	WeightValueKilo												
properties	content simple												
used by	element WagonOperationalData												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation The total weight of the transportation unit on the freight wagon. This is the booked or actual weight of goods including packing and carrier's equipment												
source	<pre><xs:element name="TotalLoadWeight" type="WeightValueKilo"> <xs:annotation> <xs:documentation>The total weight of the transportation unit on the freight wagon. This is the booked or actual weight of goods including packing and carrier's equipment</xs:documentation> </xs:annotation> </xs:element></pre>												

element **TotalWeight**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	WeightValueKilo


properties	content simple												
used by	elements Wagons/WagonDetails WagonInformation												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation Total weight of the loaded wagon [kg].												
source	<pre><xs:element name="TotalWeight" type="WeightValueKilo"> <xs:annotation> <xs:documentation>Total weight of the loaded wagon [kg]. </xs:documentation> </xs:annotation> </xs:element></pre>												

element **TractionDetails**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	LocoTypeNumber TypeOfUsedHybridPowerunit TractionMode TractionWeight Length
used by	element PlannedTrainTechnicalData
annotation	documentation Defines the design series, mode of deployment and technical specifications associated with the traction of a train.
source	<pre><xs:element name="TractionDetails"> <xs:annotation> <xs:documentation>Defines the design series, mode of deployment and technical specifications associated with the traction of a train.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LocoTypeNumber"/> <xs:element ref="TypeOfUsedHybridPowerunit" minOccurs="0"> <xs:annotation> <xs:documentation>Indication of type of power unit of a hybrid</pre>


	<pre> loco which is used; it has be filled only mandatory in case of hybrid locomotive</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TractionMode" minOccurs="0"> <xs:annotation> <xs:documentation>Identifies the mode of deployment of a traction unit within a train</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TractionWeight" minOccurs="0"> <xs:annotation> <xs:documentation>Check with group to see if it is for sum or individual - check TAP</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="Length" minOccurs="0"> <xs:annotation> <xs:documentation>Length in milimetres - Used for TAP</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **TractionPositionInTrain**

diagram	 <p>Identifies position of intermediate traction unit(s) in the train indicating after which wagon (specified by order number) the unit is placed.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element TrainCompositionJourneySection/LocIdent									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
annotation	documentation Identifies position of intermediate traction unit(s) in the train indicating after which wagon (specified by order number) the unit is placed.									
source	<pre> <xs:element name="TractionPositionInTrain"> <xs:annotation> <xs:documentation>Identifies position of intermediate traction unit(s) in the train indicating after which wagon (specified by order number) the unit is placed.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="01"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

	<pre></xs:simpleType> </xs:element></pre>
--	---

element **TractionWeight**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	WeightValueTonne									
properties	content simple									
used by	element TractionDetails									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation The weight of the traction unit									
source	<pre><xs:element name="TractionWeight" type="WeightValueTonne"> <xs:annotation> <xs:documentation>The weight of the traction unit</xs:documentation> </xs:annotation> </xs:element></pre>									


element **TrafficType**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	element PlannedTrainData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	2	
Kind	Value	Annotation								
minLength	1									
maxLength	2									
annotation	documentation information about the type of traffic (combined, rolling highway, etc). It is added here as a placeholder for coded values (e.g. from Merits)									
source	<pre><xs:element name="TrafficType"> <xs:annotation> <xs:documentation>information about the type of traffic (combined, rolling highway, etc). It is added here as a placeholder for coded values (e.g. from Merits)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="2"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

	<pre></xs:restriction> </xs:simpleType> </xs:element></pre>
--	---

element **TrainActivity**

diagram



namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	TrainActivityType
properties	content complex
children	TrainActivityType AssociatedAttachedTrainID AssociatedAttachedOTN AssociatedAttachedTrainServiceNumber AssociatedAttachedTimingAtLocation FreeTextField
used by	elements TrainRunningData/Activities PlannedJourneyLocation
annotation	documentation Since the activities can be related to attaching / detaching of wagons and/or cars to different trains, the reference to other trains should be possible to be indicated.
source	<pre><xs:element name="TrainActivity" type="TrainActivityType"> <xs:annotation> <xs:documentation>Since the activities can be related to attaching / detaching of wagons and/or cars to different trains, the reference to other trains should be possible to be indicated.</xs:documentation> </xs:annotation> </xs:element></pre>

element **TrainActivityType**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																																																																																																																										
type	restriction of xs:string																																																																																																																																																										
properties	content simple																																																																																																																																																										
used by	complexType	TrainActivityType																																																																																																																																																									
facets	Kind	Value	Annotation																																																																																																																																																								
	minLength	4																																																																																																																																																									
	maxLength	4																																																																																																																																																									
annotation	<p>documentation</p> <p>Indicates certain treatments or operations required for a train. If national codes are used, the first 2 position will be the ISO country code, followed by 00-99.</p> <table border="0"> <tr> <td>0001</td> <td>Commercial stop</td> <td>RU</td> <td>Board/disembark passenger train, load/unload freight train</td> </tr> <tr> <td>0002</td> <td>Operational stop</td> <td>IM</td> <td>Stops needed by the IM (e.g. overpassing by another train)</td> </tr> <tr> <td>0003</td> <td>Service stop</td> <td>RU/IM</td> <td>Stops which are used for non-commercial activities (e.g. boarding of staff)</td> </tr> <tr> <td>0004</td> <td>System stop</td> <td>RU/IM</td> <td>allowing the RU to change a system (e.g. signalling system, safety system)</td> </tr> <tr> <td>0005</td> <td>Reversing stop</td> <td>RU/IM</td> <td>stop to enable train unit to run in the opposite direction (without change of engine)</td> </tr> <tr> <td>0006</td> <td>Stops for reversing move or driver change ends</td> <td>RU</td> <td>stop to enable train unit to run in the opposite direction (with using another engine at the other end of the train and change of driver)</td> </tr> <tr> <td>0007</td> <td>Stops for locomotive to run round train</td> <td>RU</td> <td>stop to enable train unit to run in the opposite direction (with using the same engine at the other end of the train)</td> </tr> <tr> <td>0008</td> <td>Technical check/inspection coaches/wagons</td> <td>RU/IM</td> <td>e.g. at origin or intermediate station: brake test, checking load</td> </tr> <tr> <td>0009</td> <td>Change gauge</td> <td>RU/IM</td> <td>continuation on a network with a different gauge with change of bogies or adaptation of the axles (F->E, SVE->FI)</td> </tr> <tr> <td>0010</td> <td>attach engine/unit</td> <td>RU</td> <td>Unit not previously in service</td> </tr> <tr> <td>0011</td> <td>detach engine/unit</td> <td>RU</td> <td>Unit no longer in service</td> </tr> <tr> <td>0012</td> <td>change engine</td> <td>RU</td> <td></td> </tr> <tr> <td>0013</td> <td>attach coach/wagon</td> <td>RU</td> <td></td> </tr> <tr> <td>0014</td> <td>detach coach/wagon</td> <td>RU</td> <td></td> </tr> <tr> <td>0015</td> <td>attach and detach coach/wagon</td> <td>RU</td> <td></td> </tr> <tr> <td>0016</td> <td>attach train</td> <td></td> <td>Operational Train (in service)</td> </tr> <tr> <td>0017</td> <td>split train</td> <td></td> <td>Operational Train (in service)</td> </tr> <tr> <td>0018</td> <td>Parking of vehicle</td> <td>RU</td> <td>e.g. need to park the train/composition midway for several hours</td> </tr> <tr> <td>0019</td> <td>Mail/parcel services</td> <td>RU</td> <td></td> </tr> <tr> <td>0020</td> <td>shunting</td> <td>RU</td> <td>actual activity of shunting</td> </tr> <tr> <td>0021</td> <td>shunting service</td> <td>RU</td> <td>Request for shunting service (if offered by the IM or a third party)</td> </tr> <tr> <td>0022</td> <td>Terminal service (terminal in the meaning of final destination)</td> <td>RU</td> <td>Request for services at the end of a train run (if offered by the IM or a third party)</td> </tr> <tr> <td>0023</td> <td>Loco driver change</td> <td>RU</td> <td></td> </tr> <tr> <td>0024</td> <td>Loco driver break</td> <td>RU</td> <td>legal issue, e.g. to respect working law</td> </tr> <tr> <td>0025</td> <td>Crew change</td> <td>RU</td> <td>different to loco driver change as for the change of the crew a platform will be needed</td> </tr> <tr> <td>0026</td> <td>Custom and passport facilities</td> <td>RU</td> <td></td> </tr> <tr> <td>0027</td> <td>Other stop reason (miscellaneous)</td> <td>RU/IM</td> <td></td> </tr> <tr> <td>0028</td> <td>Boarding only</td> <td>RU</td> <td></td> </tr> <tr> <td>0029</td> <td>Disembarking only</td> <td>RU</td> <td></td> </tr> <tr> <td>0030</td> <td>Stop on request</td> <td>RU</td> <td></td> </tr> <tr> <td>0031</td> <td>Departure equals to arrival time</td> <td>RU</td> <td>If in some stations only arrival times are published, this activity code may used to indicate that the train cannot continue before the published arrival time in case of an early arrival.</td> </tr> <tr> <td>0032</td> <td>Departure after disembarking</td> <td>RU</td> <td>mainly used at the end of train run, train may continue as soon as all passengers have disembarked</td> </tr> <tr> <td>0033</td> <td>No waiting for connection</td> <td>RU</td> <td></td> </tr> <tr> <td>0034</td> <td>Watering</td> <td>RU</td> <td>Indicates the IM that a track with water access will be needed.</td> </tr> <tr> <td>0035</td> <td>Heating</td> <td>RU</td> <td>Indicates the IM that a track with heating equipment will be needed.</td> </tr> <tr> <td>0036</td> <td>Cleaning / disinfecting</td> <td>RU</td> <td></td> </tr> <tr> <td>0037</td> <td>Treatment on plants and live animals</td> <td>RU</td> <td>Watering, Foddering, Milking, Spraying, Closing ventilation flaps, Opening ventilation flaps</td> </tr> <tr> <td>0038</td> <td>Treatment of perishable goods</td> <td>RU</td> <td>Checking the temperature, Re-icing, Heating, Checking</td> </tr> </table>			0001	Commercial stop	RU	Board/disembark passenger train, load/unload freight train	0002	Operational stop	IM	Stops needed by the IM (e.g. overpassing by another train)	0003	Service stop	RU/IM	Stops which are used for non-commercial activities (e.g. boarding of staff)	0004	System stop	RU/IM	allowing the RU to change a system (e.g. signalling system, safety system)	0005	Reversing stop	RU/IM	stop to enable train unit to run in the opposite direction (without change of engine)	0006	Stops for reversing move or driver change ends	RU	stop to enable train unit to run in the opposite direction (with using another engine at the other end of the train and change of driver)	0007	Stops for locomotive to run round train	RU	stop to enable train unit to run in the opposite direction (with using the same engine at the other end of the train)	0008	Technical check/inspection coaches/wagons	RU/IM	e.g. at origin or intermediate station: brake test, checking load	0009	Change gauge	RU/IM	continuation on a network with a different gauge with change of bogies or adaptation of the axles (F->E, SVE->FI)	0010	attach engine/unit	RU	Unit not previously in service	0011	detach engine/unit	RU	Unit no longer in service	0012	change engine	RU		0013	attach coach/wagon	RU		0014	detach coach/wagon	RU		0015	attach and detach coach/wagon	RU		0016	attach train		Operational Train (in service)	0017	split train		Operational Train (in service)	0018	Parking of vehicle	RU	e.g. need to park the train/composition midway for several hours	0019	Mail/parcel services	RU		0020	shunting	RU	actual activity of shunting	0021	shunting service	RU	Request for shunting service (if offered by the IM or a third party)	0022	Terminal service (terminal in the meaning of final destination)	RU	Request for services at the end of a train run (if offered by the IM or a third party)	0023	Loco driver change	RU		0024	Loco driver break	RU	legal issue, e.g. to respect working law	0025	Crew change	RU	different to loco driver change as for the change of the crew a platform will be needed	0026	Custom and passport facilities	RU		0027	Other stop reason (miscellaneous)	RU/IM		0028	Boarding only	RU		0029	Disembarking only	RU		0030	Stop on request	RU		0031	Departure equals to arrival time	RU	If in some stations only arrival times are published, this activity code may used to indicate that the train cannot continue before the published arrival time in case of an early arrival.	0032	Departure after disembarking	RU	mainly used at the end of train run, train may continue as soon as all passengers have disembarked	0033	No waiting for connection	RU		0034	Watering	RU	Indicates the IM that a track with water access will be needed.	0035	Heating	RU	Indicates the IM that a track with heating equipment will be needed.	0036	Cleaning / disinfecting	RU		0037	Treatment on plants and live animals	RU	Watering, Foddering, Milking, Spraying, Closing ventilation flaps, Opening ventilation flaps	0038	Treatment of perishable goods	RU	Checking the temperature, Re-icing, Heating, Checking
0001	Commercial stop	RU	Board/disembark passenger train, load/unload freight train																																																																																																																																																								
0002	Operational stop	IM	Stops needed by the IM (e.g. overpassing by another train)																																																																																																																																																								
0003	Service stop	RU/IM	Stops which are used for non-commercial activities (e.g. boarding of staff)																																																																																																																																																								
0004	System stop	RU/IM	allowing the RU to change a system (e.g. signalling system, safety system)																																																																																																																																																								
0005	Reversing stop	RU/IM	stop to enable train unit to run in the opposite direction (without change of engine)																																																																																																																																																								
0006	Stops for reversing move or driver change ends	RU	stop to enable train unit to run in the opposite direction (with using another engine at the other end of the train and change of driver)																																																																																																																																																								
0007	Stops for locomotive to run round train	RU	stop to enable train unit to run in the opposite direction (with using the same engine at the other end of the train)																																																																																																																																																								
0008	Technical check/inspection coaches/wagons	RU/IM	e.g. at origin or intermediate station: brake test, checking load																																																																																																																																																								
0009	Change gauge	RU/IM	continuation on a network with a different gauge with change of bogies or adaptation of the axles (F->E, SVE->FI)																																																																																																																																																								
0010	attach engine/unit	RU	Unit not previously in service																																																																																																																																																								
0011	detach engine/unit	RU	Unit no longer in service																																																																																																																																																								
0012	change engine	RU																																																																																																																																																									
0013	attach coach/wagon	RU																																																																																																																																																									
0014	detach coach/wagon	RU																																																																																																																																																									
0015	attach and detach coach/wagon	RU																																																																																																																																																									
0016	attach train		Operational Train (in service)																																																																																																																																																								
0017	split train		Operational Train (in service)																																																																																																																																																								
0018	Parking of vehicle	RU	e.g. need to park the train/composition midway for several hours																																																																																																																																																								
0019	Mail/parcel services	RU																																																																																																																																																									
0020	shunting	RU	actual activity of shunting																																																																																																																																																								
0021	shunting service	RU	Request for shunting service (if offered by the IM or a third party)																																																																																																																																																								
0022	Terminal service (terminal in the meaning of final destination)	RU	Request for services at the end of a train run (if offered by the IM or a third party)																																																																																																																																																								
0023	Loco driver change	RU																																																																																																																																																									
0024	Loco driver break	RU	legal issue, e.g. to respect working law																																																																																																																																																								
0025	Crew change	RU	different to loco driver change as for the change of the crew a platform will be needed																																																																																																																																																								
0026	Custom and passport facilities	RU																																																																																																																																																									
0027	Other stop reason (miscellaneous)	RU/IM																																																																																																																																																									
0028	Boarding only	RU																																																																																																																																																									
0029	Disembarking only	RU																																																																																																																																																									
0030	Stop on request	RU																																																																																																																																																									
0031	Departure equals to arrival time	RU	If in some stations only arrival times are published, this activity code may used to indicate that the train cannot continue before the published arrival time in case of an early arrival.																																																																																																																																																								
0032	Departure after disembarking	RU	mainly used at the end of train run, train may continue as soon as all passengers have disembarked																																																																																																																																																								
0033	No waiting for connection	RU																																																																																																																																																									
0034	Watering	RU	Indicates the IM that a track with water access will be needed.																																																																																																																																																								
0035	Heating	RU	Indicates the IM that a track with heating equipment will be needed.																																																																																																																																																								
0036	Cleaning / disinfecting	RU																																																																																																																																																									
0037	Treatment on plants and live animals	RU	Watering, Foddering, Milking, Spraying, Closing ventilation flaps, Opening ventilation flaps																																																																																																																																																								
0038	Treatment of perishable goods	RU	Checking the temperature, Re-icing, Heating, Checking																																																																																																																																																								

	<p>the proper functioning of the mechanical refrigeration equipment, Refuelling machinery, Switching machinery on or off</p> <p>0039 Administrative operations RU Weighing, Re-forwarding, Submission to phytosanitary inspections</p> <p>0040 Run Through (Passing Time) IM</p> <p>0041 Photo run-by / Photo-stop</p> <p>0042 Train Waiting Waiting according to local rules</p> <p>0043 Train running with another train RU Where trains have been attached at a previous location on the schedule</p> <p>0044 Connecting service to other train RU Association where there is a need to define a relationship between a train and its next service. The same vehicle is used for the next train service. Also called "train-set turnover"</p> <p>0045 Connecting service from other train RU Association where there is a need to define a relationship between a train and its previous service. The same vehicle is reused from the previous train service.</p> <p>0046 Connecting service to other train.</p> <p>0047 Connecting service from other train</p> <p>0048 Linkage of OTNs belonging to the same transport if no TrainID is present</p> <p>National / company codes: Examples: Numbers 00 to 99 may be used by an IM for Network national purposes, just adding ISO country code</p> <p>CZ01 Stops from new stop opening day</p> <p>UK55 Stop shorter than 1/2 min</p> <p>IT72 Train report stop cancelled</p>
source	<pre><xs:element name="TrainActivityType"> <xs:annotation> <xs:documentation>Indicates certain treatments or operations required for a train. If national codes are used, the first 2 position will be the ISO country code, followed by 00-99. 0001 Commercial stop RU Board/disembark passenger train, load/unload freight train 0002 Operational stop IM Stops needed by the IM (e.g. overpassing by another train) 0003 Service stop RU/IM Stops which are used for non-commercial activities (e.g. boarding of staff) 0004 System stop RU/IM allowing the RU to change a system (e.g. signalling system, safety system) 0005 Reversing stop RU/IM stop to enable train unit to run in the opposite direction (without change of engine) 0006 Stops for reversing move or driver change ends RU stop to enable train unit to run in the opposite direction (with using another engine at the other end of the train and change of driver) 0007 Stops for locomotive to run round trainRU stop to enable train unit to run in the opposite direction (with using the same engine at the other end of the train) 0008 Technical check/inspection coaches/wagons RU/IM e.g. at origin or intermediate station: brake test, checking load 0009 Change gauge RU/IM continuation on a network with a different gauge with change of bogies or adaptation of the axles (F->E, SVE->FI) 0010 attach engine/unit RU Unit not previously in service 0011 detach engine/unit RU Unit no longer in service 0012 change engineRU 0013 attach coach/wagon RU 0014 detach coach/wagon RU 0015 attach and detach coach/wagon RU 0016 attach train Operational Train (in service) 0017 split train Operational Train (in service)</pre>

0018 Parking of vehicle RU e.g. need to park the train/composition midway for several hours

0019 Mail/parcel services RU

0020 shunting RU actual activity of shunting

0021 shunting service RU Request for shunting service (if offered by the IM or a third party)

0022 Terminal service (terminal in the meaning of final destination) RU Request for services at the end of a train run (if offered by the IM or a third party)

0023 Loco driver change RU

0024 Loco driver break RU legal issue, e.g. to respect working law

0025 Crew change RU different to loco driver change as for the change of the crew a platform will be needed

0026 Custom and passport facilities RU

0027 Other stop reason (miscellaneous) RU/IM

0028 Boarding onlyRU

0029 Disembarking only RU

0030 Stop on request RU

0031 Departure equals to arrival time RU If in some stations only arrival times are published, this activity code may used to indicate that the train cannot continue before the published arrival time in case of an early arrival.

0032 Departure after disembarking RU mainly used at the end of train run, train may continue as soon as all passengers have disembarked

0033 No waiting for connection RU

0034 Watering RU Indicates the IM that a track with water access will be needed.

0035 Heating Indicates the IM that a track with heating equipment will be needed.

0036 Cleaning / disinfecting RU

0037 Treatment on plants and live animals RU Watering, Foddering, Milking, Spraying, Closing ventilation flaps, Opening ventilation flaps

0038 Treatment of perishable goods RU Checking the temperature, Re-icing, Heating, Checking the proper functioning of the mechanical refrigeration equipment, Refuelling machinery, Switching machinery on or off

0039 Administrative operations RU Weighing, Re-forwarding, Submission to phytosanitary inspections

0040 Run Through (Passing Time)IM

0041 Photo run-by / Photo-stop

0042 Train Waiting Waiting according to local rules

0043 Train running with another train RU Where trains have been attached at a previous location on the schedule

0044 Connecting service to other train RU Association where there is a need to define a relationship between a train and its next service. The same vehicle is used for the next train service. Also called "train-set turnover"

0045 Connecting service from other train RU Association where there is a need to define a relationship between a train and its previous service. The same vehicle is reused from the previous train service.

0046 Connecting service to other train.

0047 Connecting service from other train

0048 Linkage of OTNs belonging to the same transport if no TrainID is present

National / company codes:

Examples: Numbers 00 to 99 may be used by an IM for Network national purposes, just adding ISO country code

	<p>CZ01 Stops from new stop opening day UK55 Stop shorter than 1/2 min IT72 Train report stop cancelled</p> <pre> </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="4"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--


element **TrainAtLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TrainLocationStatus OperationalTrainNumberIdentifier ReferenceOTN TrainOperationalIdentification BookedLocationDateTime ReferencedLocationDateTime LocationDateTime TrainDelay
used by	element TrainForecastAtReportingLocationMessage
annotation	documentation Specifies information about a train at a specific location
source	<pre> <xs:element name="TrainAtLocation"> <xs:annotation> <xs:documentation>Specifies information about a train at a specific location</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TrainLocationStatus"/> <xs:element ref="OperationalTrainNumberIdentifier"/> <xs:element ref="ReferenceOTN" minOccurs="0"/> <xs:element ref="TrainOperationalIdentification" minOccurs="0"/> </pre>

```

<xs:element ref="BookedLocationDateTime"/>
<xs:element ref="ReferencedLocationDateTime" minOccurs="0"/>
<xs:element ref="LocationDateTime"/>
<xs:element ref="TrainDelay"/>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **TrainCC_System**

diagram	 <p>Identifies the command control system of the train in coded values.</p>																																																																																													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																																																													
type	TrainCC_SystemCode																																																																																													
properties	content simple																																																																																													
used by	elements PlannedTrainTechnicalData TrainRunningTechData																																																																																													
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>01</td><td></td></tr> <tr><td>enumeration</td><td>02</td><td></td></tr> <tr><td>enumeration</td><td>03</td><td></td></tr> <tr><td>enumeration</td><td>04</td><td></td></tr> <tr><td>enumeration</td><td>05</td><td></td></tr> <tr><td>enumeration</td><td>06</td><td></td></tr> <tr><td>enumeration</td><td>07</td><td></td></tr> <tr><td>enumeration</td><td>08</td><td></td></tr> <tr><td>enumeration</td><td>09</td><td></td></tr> <tr><td>enumeration</td><td>10</td><td></td></tr> <tr><td>enumeration</td><td>11</td><td></td></tr> <tr><td>enumeration</td><td>12</td><td></td></tr> <tr><td>enumeration</td><td>13</td><td></td></tr> <tr><td>enumeration</td><td>14</td><td></td></tr> <tr><td>enumeration</td><td>15</td><td></td></tr> <tr><td>enumeration</td><td>16</td><td></td></tr> <tr><td>enumeration</td><td>17</td><td></td></tr> <tr><td>enumeration</td><td>18</td><td></td></tr> <tr><td>enumeration</td><td>19</td><td></td></tr> <tr><td>enumeration</td><td>20</td><td></td></tr> <tr><td>enumeration</td><td>21</td><td></td></tr> <tr><td>enumeration</td><td>22</td><td></td></tr> <tr><td>enumeration</td><td>23</td><td></td></tr> <tr><td>enumeration</td><td>24</td><td></td></tr> <tr><td>enumeration</td><td>25</td><td></td></tr> <tr><td>enumeration</td><td>26</td><td></td></tr> <tr><td>enumeration</td><td>27</td><td></td></tr> <tr><td>enumeration</td><td>28</td><td></td></tr> <tr><td>enumeration</td><td>29</td><td></td></tr> <tr><td>enumeration</td><td>30</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	01		enumeration	02		enumeration	03		enumeration	04		enumeration	05		enumeration	06		enumeration	07		enumeration	08		enumeration	09		enumeration	10		enumeration	11		enumeration	12		enumeration	13		enumeration	14		enumeration	15		enumeration	16		enumeration	17		enumeration	18		enumeration	19		enumeration	20		enumeration	21		enumeration	22		enumeration	23		enumeration	24		enumeration	25		enumeration	26		enumeration	27		enumeration	28		enumeration	29		enumeration	30	
Kind	Value	Annotation																																																																																												
enumeration	01																																																																																													
enumeration	02																																																																																													
enumeration	03																																																																																													
enumeration	04																																																																																													
enumeration	05																																																																																													
enumeration	06																																																																																													
enumeration	07																																																																																													
enumeration	08																																																																																													
enumeration	09																																																																																													
enumeration	10																																																																																													
enumeration	11																																																																																													
enumeration	12																																																																																													
enumeration	13																																																																																													
enumeration	14																																																																																													
enumeration	15																																																																																													
enumeration	16																																																																																													
enumeration	17																																																																																													
enumeration	18																																																																																													
enumeration	19																																																																																													
enumeration	20																																																																																													
enumeration	21																																																																																													
enumeration	22																																																																																													
enumeration	23																																																																																													
enumeration	24																																																																																													
enumeration	25																																																																																													
enumeration	26																																																																																													
enumeration	27																																																																																													
enumeration	28																																																																																													
enumeration	29																																																																																													
enumeration	30																																																																																													

	<p>enumeration 31</p> <p>enumeration 32</p> <p>enumeration 33</p> <p>enumeration 34</p> <p>enumeration 35</p> <p>enumeration 36</p> <p>enumeration 37</p> <p>enumeration 38</p> <p>enumeration 39</p> <p>enumeration 40</p> <p>enumeration 41</p> <p>enumeration 42</p> <p>enumeration 43</p> <p>enumeration 44</p> <p>enumeration 45</p> <p>enumeration 46</p> <p>enumeration 47</p> <p>enumeration 48</p> <p>enumeration 49</p> <p>enumeration 50</p> <p>enumeration 51</p> <p>enumeration 52</p> <p>enumeration 53</p> <p>enumeration 54</p>
annotation	<p>documentation</p> <p>Identifies the command control system of the train in coded values.</p>
source	<pre><xs:element name="TrainCC_System" type="TrainCC_SystemCode"> <xs:annotation> <xs:documentation>Identifies the command control system of the train in coded values.</xs:documentation> </xs:annotation> </xs:element></pre>


element **TrainCompositionJourneySection**

<p>diagram</p>	<pre> classDiagram class JourneySection { Defines the data provided by the IM for a journey s... } class TrainRunningData { Train relevant data for a running train } class LocoIdent { Defines the actual Type, the number and the mode of deployment of a traction unit of the freight train } class LivestockOrPeopleIndicator { Indicates that livestock and people (other than train crew) will be carried. Coding: if live animals or people are transported = 1, in opposite case = 0. If code = 1, then at the wagon level for at least one wagon Info-Goods Shape, Type and Danger has to include the code '98' or Restrictions due to Load or Damage has to inclu... } class WagonData { Wagon relevant data for the wagons within a running tr... } class TrainCompositionJourneySection { Defines the make up of a train for each section of its journey } JourneySection "0..1" -- "0..1" TrainCompositionJourneySection TrainRunningData "0..1" -- "0..1" TrainCompositionJourneySection WagonData "0..∞" -- "0..∞" TrainCompositionJourneySection LocoIdent "0..∞" -- "0..∞" TrainCompositionJourneySection LivestockOrPeopleIndicator "0..∞" -- "0..∞" TrainCompositionJourneySection </pre>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>JourneySection TrainRunningData LocoIdent LivestockOrPeopleIndicator WagonData</p>
<p>used by</p>	<p>element TrainCompositionMessage</p>
<p>annotation</p>	<p>documentation Defines the make up of a train for each section of its journey</p>
<p>source</p>	<pre> <xs:element name="TrainCompositionJourneySection"> <xs:annotation> <xs:documentation>Defines the make up of a train for each section of its journey</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="JourneySection"/> <xs:element ref="TrainRunningData"/> <xs:element name="LocoIdent" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Defines the actual Type, the number and the mode of deployment of a traction unit of the freight train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TractionType"/> <xs:element ref="TypeOfUsedHybridPowerunit" minOccurs="0"/> <xs:element ref="LocoTypeNumber" minOccurs="0"/> <xs:element ref="LocoNumber" minOccurs="0"/> <xs:element ref="TractionMode" minOccurs="0"/> <xs:element name="DriverIndication" minOccurs="0"> <xs:annotation> <xs:documentation>0 - no driver present in Loco, 1 - driver(s) is /are) present in Loco</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> </pre>

```

        <xs:enumeration value="0"/>
        <xs:enumeration value="1"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element ref="TractionPositionInTrain" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="LivestockOrPeopleIndicator" minOccurs="0"
maxOccurs="1"/>
<xs:element ref="WagonData" minOccurs="0" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **TrainCompositionJourneySection/Locident**



properties	minOcc 0 maxOcc unbounded content complex
children	TractionType TypeOfUsedHybridPowerunit LocoTypeNumber LocoNumber TractionMode DriverIndication TractionPositionInTrain
annotation	documentation Defines the actual Type, the number and the mode of deployment of a traction unit of the freight train
source	<pre> <xs:element name="LocoIdent" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Defines the actual Type, the number and the mode of deployment of a traction unit of the freight train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TractionType"/> <xs:element ref="TypeOfUsedHybridPowerunit" minOccurs="0"/> <xs:element ref="LocoTypeNumber" minOccurs="0"/> <xs:element ref="LocoNumber" minOccurs="0"/> <xs:element ref="TractionMode" minOccurs="0"/> <xs:element name="DriverIndication" minOccurs="0"> <xs:annotation> <xs:documentation>0 - no driver present in Loco, 1 - driver(s) is /are) present in Loco</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="TractionPositionInTrain" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **TrainCompositionJourneySection/LocIdent/DriverIndication**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0		enumeration	1	
Kind	Value	Annotation								
enumeration	0									
enumeration	1									
annotation	documentation 0 - no driver present in Loco, 1 - driver(s) is /are) present in Loco									
source	<pre> <xs:element name="DriverIndication" minOccurs="0"> <xs:annotation> <xs:documentation>0 - no driver present in Loco, 1 - driver(s) is /are) </pre>									


	<pre> present in Loco</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **TrainCompositionMessage**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader MessageStatus TransportOperationalIdentifiers OperationalTrainNumberIdentifier ReferenceOTN TransferPoint TransfereeIM TrainCompositionJourneySection
annotation	documentation This message is sent from an RU to an IM defining the composition of the proposed train.
source	<pre> <xs:element name="TrainCompositionMessage"> <xs:annotation> <xs:documentation>This message is sent from an RU to an IM defining the composition of the proposed train.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"/> <xs:element ref="TransportOperationalIdentifiers" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="OperationalTrainNumberIdentifier"/> <xs:element ref="ReferenceOTN" minOccurs="0"/> <xs:element ref="TransferPoint" minOccurs="0"/> <xs:element ref="TransfereeIM" minOccurs="0"/> <xs:element ref="TrainCompositionJourneySection" maxOccurs="99"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

	<pre></xs:complexType> </xs:element></pre>
--	--

element TrainContactDetails

diagram	 <p>Contact to driver of leading traction unit. This contact can be mobile phone number, GSM-R call number or e.g. details for an analogue radio call.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CommunicationRefID									
properties	content simple									
used by	element TrainReadyMessage									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>70</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	70	
Kind	Value	Annotation								
minLength	1									
maxLength	70									
annotation	documentation Contact to driver of leading traction unit. This contact can be mobile phone number, GSM-R call number or e.g. details for an analogue radio call.									
source	<pre><xs:element name="TrainContactDetails" type="CommunicationRefID"> <xs:annotation> <xs:documentation>Contact to driver of leading traction unit. This contact can be mobile phone number, GSM-R call number or e.g. details for an analogue radio call.</xs:documentation> </xs:annotation> </xs:element></pre>									

element TrainDelay

diagram	 <p>Identifies the Delta delay time of a train against the booked schedule as well as against the referenced time</p> <p>Identifies the Delta delay time against the booked schedule in minutes</p> <p>Delay compared to the referenced Date/...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	AgainstBooked AgainstReferenced
used by	elements TrainAtLocation TrainLocationReport TrainReadyMessage/TrainReadyStatus TrainReadyStatus
annotation	documentation Identifies the Delta delay time of a train against the booked schedule as well as against the referenced time
source	<pre><xs:element name="TrainDelay"> <xs:annotation> <xs:documentation>Identifies the Delta delay time of a train against the booked schedule as well as against the referenced time </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="AgainstBooked" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:element ref="AgainstReferenced" minOccurs="0"> <xs:annotation> <xs:documentation>Delay compared to the referenced Date/Time</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **TrainDelayCauseMessage**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader MessageStatus TrainOperationalIdentification OperationalTrainNumberIdentifier ReferenceOTN ResponsibleRU DelayEventReport TransferPoint TransfereeIM
annotation	documentation This message is issued to make known the cause for additional delay during the Train's Journey (Changed name of the message from Reason to Cause) Description changed
source	<pre> <xs:element name="TrainDelayCauseMessage"> <xs:annotation> <xs:documentation>This message is issued to make known the cause for additional delay during the Train's Journey (Changed name of the message from Reason to Cause) Description changed </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"/> <xs:element ref="TrainOperationalIdentification" minOccurs="0"/> <xs:element ref="OperationalTrainNumberIdentifier"/> <xs:element ref="ReferenceOTN" minOccurs="0"/> <xs:element ref="ResponsibleRU" minOccurs="0"/> </pre>

	<pre> <xs:element ref="DelayEventReport"/> <xs:element ref="TransferPoint" minOccurs="0"/> <xs:element ref="TransfereeIM" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---


element **TrainForecastAtReportingLocationMessage**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader MessageStatus Location TrainAtLocation
annotation	documentation This message is issued following receipt of an enquiry about train forecasts at a particular reporting location. It gives a report of the forecasted time for all trains of the enquirer at a specified location.
source	<pre> <xs:element name="TrainForecastAtReportingLocationMessage"> <xs:annotation> <xs:documentation>This message is issued following receipt of an enquiry about train forecasts at a particular reporting location. It gives a report of the forecasted time for all trains of the enquirer at a specified location. </xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"/> <xs:element ref="Location"/> <xs:element ref="TrainAtLocation"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **TrainID**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>CompositIdentifierOperationalType</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>ObjectType Company Core Variant TimetableYear StartDate</p>
<p>used by</p>	<p>elements ArrivalInterchangeReport DepartureInterchangeReport</p>
<p>source</p>	<p><code><xs:element name="TrainID" type="CompositIdentifierOperationalType"/></code></p>

element **TrainInformation**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>PlannedJourneyLocation PlannedCalendar PathPlanningReferenceLocation</p>
<p>used by</p>	<p>element PathRequestMessage</p>

annotation	<p>documentation Train information provided by the RUs as an overview for the entire train journey from origin to destination</p>
source	<pre> <xs:element name="TrainInformation"> <xs:annotation> <xs:documentation>Train information provided by the RUs as an overview for the entire train journey from origin to destination</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="PlannedJourneyLocation" minOccurs="2" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>Any operation point along a train journey</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="PlannedCalendar"> <xs:annotation> <xs:documentation>This is the master calendar for Path Request. Contains BitmapDays as well as DayOfStart element. one of them has to be always present. Applications have to provide the data accordingly. </xs:documentation> </xs:annotation> </xs:element> <xs:element name="PathPlanningReferenceLocation"> <xs:annotation> <xs:documentation>It has to be indicated whether the path planning (direction of construction) is carried out at the traindeparturepoint (origin), intermediate or traindestinationpoint. The operation point referenced here MUST have a calendar/dayOfDeparture entry - applications have to check this.</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"/> </xs:complexContent> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **TrainInformation/PathPlanningReferenceLocation**




namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation It has to be indicated whether the path planning (direction of construction) is carried out at the traindeparturepoint (origin), intermediate or traindestinationpoint. The operation point referenced here MUST have a calendar/dayOfDeparture entry - applications have to check this.
source	<pre><xs:element name="PathPlanningReferenceLocation"> <xs:annotation> <xs:documentation>It has to be indicated whether the path planning (direction of construction) is carried out at the traindeparturepoint (origin), intermediate or traindestinationpoint. The operation point referenced here MUST have a calendar/dayOfDeparture entry - applications have to check this.</xs:documentation> </xs:annotation> <xs:complexType> <xs:complexContent> <xs:extension base="LocationIdent"/> </xs:complexContent> </xs:complexType> </xs:element></pre>


element **TrainJourneyModification**

diagram	<p>The diagram shows a class TrainJourneyModification with a description: "This element shows which locations are changed during the running of a train". It contains two sub-elements: TrainJourneyModificationIndicator (description: "This indicates what has changed in the train running e.g. rerouting, cancellation e...") and LocationModified (description: "This element shows the Location that has been changed for the train r..."). The cardinality for LocationModified is 1..∞.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TrainJourneyModificationIndicator LocationModified
used by	element TrainJourneyModificationMessage
annotation	documentation This element shows which locations are changed during the running of a train
source	<pre><xs:element name="TrainJourneyModification"> <xs:annotation> <xs:documentation>This element shows which locations are changed during the running of a train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TrainJourneyModificationIndicator"/> <xs:element ref="LocationModified" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **TrainJourneyModificationIndicator**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element TrainJourneyModification									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99									
annotation	documentation This indicates what has changed in the train running e.g. rerouting, cancellation etc..									
source	<pre> <xs:element name="TrainJourneyModificationIndicator"> <xs:annotation> <xs:documentation>This indicates what has changed in the train running e.g. rerouting, cancellation etc..</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **TrainJourneyModificationMessage**


<p>diagram</p> 	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader MessageStatus TrainOperationalIdentification OperationalTrainNumberIdentifier ReferenceOTN TrainJourneyModification ModificationReason TrainJourneyModificationTime Remarks TransferPoint InternalReferencIdentifier TransfereelM</p>
<p>annotation</p>	<p>documentation This message is issued to show, in real time, that the train is rerouted-cancelled-stopping pattern is changed</p>
<p>source</p>	<pre><xs:element name="TrainJourneyModificationMessage"> <xs:annotation> <xs:documentation> This message is issued to show, in real time, that the train is rerouted-cancelled-stopping pattern is changed</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"> <xs:annotation> <xs:documentation>Assigned by the Sender 1=Creation, 2=Modification, 3=deletion </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TrainOperationalIdentification" minOccurs="0"/> <xs:element ref="OperationalTrainNumberIdentifier"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:element ref="ReferenceOTN" minOccurs="0"/> <xs:element ref="TrainJourneyModification" maxOccurs="unbounded"/> <xs:element ref="ModificationReason" minOccurs="0"/> <xs:element ref="TrainJourneyModificationTime" minOccurs="0"/> <xs:element ref="Remarks" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="TransferPoint" minOccurs="0"> <xs:annotation> <xs:documentation>Transfer point or station of destination in the considered network where the Reference Train Numbers refers to </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="InternalReferenceIdentifier" minOccurs="0"/> <xs:element ref="TransfereeIM" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **TrainJourneyModificationTime**

diagram	 <p>Indicates the time time when the modification was made to the train journey</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element TrainJourneyModificationMessage
annotation	documentation Indicates the time time when the modification was made to the train journey
source	<pre> <xs:element name="TrainJourneyModificationTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>Indicates the time time when the modification was made to the train journey</xs:documentation> </xs:annotation> </xs:element> </pre>

element **TrainJourneyStartTime**

diagram	 <p>The precise time at which the train should present itself on the network</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
annotation	documentation The precise time at which the train should present itself on the network
source	<pre> <xs:element name="TrainJourneyStartTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>The precise time at which the train should present itself on the network</xs:documentation> </xs:annotation> </xs:element> </pre>

	<pre></xs:annotation> </xs:element></pre>
--	---

element **TrainLength**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric4-4									
properties	content simple									
used by	elements PlannedTrainTechnicalData TrainRunningTechData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0001		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0001									
maxInclusive	9999									
annotation	documentation The calculated Length of a train (sum of all length over buffer of the wagons and traction units). Expressed in Metres									
source	<pre><xs:element name="TrainLength" type="Numeric4-4"> <xs:annotation> <xs:documentation>The calculated Length of a train (sum of all length over buffer of the wagons and traction units). Expressed in Metres</xs:documentation> </xs:annotation> </xs:element></pre>									

element **TrainLocationReport**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3


properties	content complex
children	Location LocationDateTime TrainLocationStatus BookedLocationDateTime ReferencedLocationDateTime TrainDelay GeoLocalisationOnNetwork
used by	elements TrainRunningForecastMessage TrainRunningInformationMessage
annotation	documentation Specifies the relevant running data of a train related to a specific location
source	<pre> <xs:element name="TrainLocationReport"> <xs:annotation> <xs:documentation>Specifies the relevant running data of a train related to a specific location</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="LocationDateTime"/> <xs:element ref="TrainLocationStatus"/> <xs:element ref="BookedLocationDateTime" minOccurs="0"> <xs:annotation> <xs:documentation>Scheduled Date and Time of a train at a specified location as defined in the path contract</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="ReferencedLocationDateTime" minOccurs="0"/> <xs:element ref="TrainDelay" minOccurs="0"/> <xs:element ref="GeoLocalisationOnNetwork" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **TrainLocationStatus**


diagram																									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																								
type	RunningStatus																								
properties	content simple																								
used by	elements ChangeofTrackMessage DelayEventReport LocationModified TrainAtLocation TrainLocationReport																								
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>00</td> <td>documentation Not specified</td> </tr> <tr> <td>enumeration</td> <td>01</td> <td>documentation Arrival at destination</td> </tr> <tr> <td>enumeration</td> <td>02</td> <td>documentation Departure at origin</td> </tr> <tr> <td>enumeration</td> <td>03</td> <td>documentation Intermediate arrival</td> </tr> <tr> <td>enumeration</td> <td>04</td> <td>documentation Intermediate departure</td> </tr> <tr> <td>enumeration</td> <td>05</td> <td>documentation Pass through</td> </tr> <tr> <td>enumeration</td> <td>06</td> <td>documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	00	documentation Not specified	enumeration	01	documentation Arrival at destination	enumeration	02	documentation Departure at origin	enumeration	03	documentation Intermediate arrival	enumeration	04	documentation Intermediate departure	enumeration	05	documentation Pass through	enumeration	06	documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)
Kind	Value	Annotation																							
enumeration	00	documentation Not specified																							
enumeration	01	documentation Arrival at destination																							
enumeration	02	documentation Departure at origin																							
enumeration	03	documentation Intermediate arrival																							
enumeration	04	documentation Intermediate departure																							
enumeration	05	documentation Pass through																							
enumeration	06	documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)																							

	enumeration 07	
	enumeration 08	
	enumeration 09	
	enumeration 10	documentation Not specified for wagon
	enumeration 11	documentation Wagon arrival at its destination by train
	enumeration 12	documentation Wagon departure from its station of origin by train
	enumeration 13	documentation Wagon arrival at reporting point by train
	enumeration 14	documentation Wagon departure from reporting point by train
	enumeration 15	documentation Wagon run-through at reporting point by train
	enumeration 16	documentation Wagon parked at reporting point
	enumeration 17	documentation Wagon shunted at reporting point
	enumeration 18	documentation Wagon arrived at reporting point
	enumeration 19	documentation Wagon departure from reporting point
annotation	documentation	Identifies the status of a train related to the actual time at a reporting point
source	<pre><xs:element name="TrainLocationStatus" type="RunningStatus"> <xs:annotation> <xs:documentation>Identifies the status of a train related to the actual time at a reporting point</xs:documentation> </xs:annotation> </xs:element></pre>	


element **TrainMaxSpeed**

diagram		
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3	
type	Speed	
properties	content simple	
used by	elements PlannedTrainTechnicalData TrainRunningTechData	
facets	Kind	Value Annotation
	minInclusive	001
	maxInclusive	999
annotation	documentation	The max. possible speed of a train in km/h
source	<pre><xs:element name="TrainMaxSpeed" type="Speed"> <xs:annotation> <xs:documentation>The max. possible speed of a train in km/h</xs:documentation> </xs:annotation> </xs:element></pre>	

element **TrainNotAtInterruptionPoint**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	1	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	1									
annotation	<p>documentation</p> <p>It is already known that train running might be interrupted in interruption point although the train has not arrived to interruption point yet</p>									
source	<pre><xs:element name="TrainNotAtInterruptionPoint"> <xs:annotation> <xs:documentation>It is already known that train running might be interrupted in interruption point although the train has not arrived to interruption point yet</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									


element **TrainOperationalIdentification**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TransportOperationalIdentifiers RelatedTransportOperationalIdentifiers
used by	<p>elements</p> <p>ChangeofTrackMessage TrainAtLocation TrainDelayCauseMessage TrainJourneyModificationMessage TrainRunningForecastMessage TrainRunningInformationMessage TrainRunningInterruptionMessage</p>
source	<pre><xs:element name="TrainOperationalIdentification"> <xs:complexType> <xs:sequence> <xs:element ref="TransportOperationalIdentifiers" maxOccurs="unbounded"> <xs:annotation> <xs:documentation>according to the new identifier structure, ObjectType has to be used to differ between train and path</pre>

```

id</xs:documentation>
  </xs:annotation>
</xs:element>
  <xs:element ref="RelatedTransportOperationalIdentifiers" minOccurs="0"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation>according to the new identifier structure,
ObjectType has to be used to differ between train and path
id</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **TrainReadyMessage**

<p>diagram</p> 	<p>The diagram shows the structure of the TrainReadyMessage element. It is a complex type containing several other elements:</p> <ul style="list-style-type: none"> MessageHeader: Used for all messages. MessageStat...: Assigned by the Sender. Extension: 1, modification: 2, deletion: 3. TransportOperationalIdentifiers: 0..* OperationalTrainNumberIdentifier ReferenceOTN Responsible...: RU Responsible for the physical operation of the train or wagon. TrainContactDetails: Contact to driver of leading traction unit. This contact can be mobile phone number, GSM-R call number or e.g. details for an analogue radio call. TrainLocation: Handover, Interchange, Handling and flagging point if needed, track could be identify directly via substation code. TrainReadyStatus TransferPoint: Transfer point or station of destination in the considered network where the Reference Train Numbers... TransfereedM: Next ... TrainStartTime: The Date and Time at which the train actually started the journey. TrainReadyTime: It indicates date/time when the train will be ready for departure. If contact will define if this element can be used. Only to be used if this time is in future (sent in advance). Purpose of this element is to short the tra...
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>

children	<p>MessageHeader MessageStatus TransportOperationalIdentifiers OperationalTrainNumberIdentifier ReferenceOTN ResponsibleRU TrainContactDetails TrainLocation TrainReadyStatus TransferPoint TransfereeIM TrainStartTime TrainReadyTime</p>
annotation	<p>documentation This message is sent from an RU to an IM indicating that the train is ready for access to the network.</p>
source	<pre> <xs:element name="TrainReadyMessage"> <xs:annotation> <xs:documentation>This message is sent from an RU to an IM indicating that the train is ready for access to the network.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="MessageStatus"/> <xs:element ref="TransportOperationalIdentifiers" minOccurs="0" maxOccurs="unbounded"/> <xs:element ref="OperationalTrainNumberIdentifier"/> <xs:element ref="ReferenceOTN" minOccurs="0"/> <xs:element ref="ResponsibleRU" minOccurs="0"/> <xs:element ref="TrainContactDetails" minOccurs="0"/> <xs:element name="TrainLocation" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Handover, Interchange, Handling and Reporting point: if needed, track could be identify directly via subsidiar code </xs:documentation> </xs:annotation> </xs:element> <xs:element name="TrainReadyStatus" minOccurs="0"> <xs:complexType> <xs:sequence> <xs:element name="TrainReady"> <xs:annotation> <xs:documentation>0=Not Ready 1=Ready</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="TrainDelay" minOccurs="0"/> <xs:element name="TrainNotReadyDescription" type="FreeText" minOccurs="0"> <xs:annotation> <xs:documentation>Description of the reason why the train is not ready.</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="DelayCause" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> <xs:element ref="TransferPoint" minOccurs="0"> <xs:annotation> <xs:documentation>Transfer point or station of destination in the considered network where the Reference Train Numbers refers to </pre>

	<pre> </xs:documentation> </xs:annotation> </xs:element> <xs:element ref="TransfereeIM" minOccurs="0"/> <xs:element ref="TrainStartTime" minOccurs="0"/> <xs:element name="TrainReadyTime" type="xs:dateTime" minOccurs="0"> <xs:annotation> <xs:documentation>It indicates date/time when the train will be ready for departure. IM contract will define if this element can be used. Only to be used if this time is in future (sent in advance). Purpose of this element is to short the train stay. </xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **TrainReadyMessage/TrainLocation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	minOcc 0 maxOcc 1 content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
annotation	documentation Handover, Interchange, Handling and Reporting point: if needed, track could be identify directly via subsidiar code
source	<pre> <xs:element name="TrainLocation" type="LocationIdent" minOccurs="0"> <xs:annotation> <xs:documentation>Handover, Interchange, Handling and Reporting point: if needed, track could be identify directly via subsidiar code </xs:documentation> </xs:annotation> </xs:element> </pre>

element **TrainReadyMessage/TrainReadyStatus**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc 1 content complex</p>
<p>children</p>	<p>TrainReady TrainDelay TrainNotReadyDescription DelayCause</p>
<p>source</p>	<pre><xs:element name="TrainReadyStatus" minOccurs="0"> <xs:complexType> <xs:sequence> <xs:element name="TrainReady"> <xs:annotation> <xs:documentation>0=Not Ready 1=Re...</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="TrainDelay" minOccurs="0"/> <xs:element name="TrainNotReadyDescription" type="FreeText" minOccurs="0"> <xs:annotation> <xs:documentation>Description of the reason why the train is not ready.</xs:documentation> </xs:annotation> </xs:element> <xs:element ref="DelayCause" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **TrainReadyMessage/TrainReadyStatus/TrainReady**


<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>restriction of xs:integer</p>
<p>properties</p>	<p>content simple</p>

facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0		enumeration	1	
Kind	Value	Annotation								
enumeration	0									
enumeration	1									
annotation	documentation 0=Not Ready 1=Ready									
source	<pre><xs:element name="TrainReady"> <xs:annotation> <xs:documentation>0=Not Ready 1=Ready</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **TrainReadyMessage/TrainReadyStatus/TrainNotReadyDescription**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Description of the reason why the train is not ready.									
source	<pre><xs:element name="TrainNotReadyDescription" type="FreeText" minOccurs="0"> <xs:annotation> <xs:documentation>Description of the reason why the train is not ready.</xs:documentation> </xs:annotation> </xs:element></pre>									

element **TrainReadyMessage/TrainReadyTime**

diagram							
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	xs:dateTime						
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple
minOcc	0						
maxOcc	1						
content	simple						

annotation	documentation It indicates date/time when the train will be ready for departure. IM contract will define if this element can be used. Only to be used if this time is in future (sent in advance). Purpose of this element is to short the train stay.
source	<pre><xs:element name="TrainReadyTime" type="xs:dateTime" minOccurs="0"> <xs:annotation> <xs:documentation>It indicates date/time when the train will be ready for departure. IM contract will define if this element can be used. Only to be used if this time is in future (sent in advance). Purpose of this element is to short the train stay. </xs:documentation> </xs:annotation> </xs:element></pre>

element **TrainReadyStatus**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TrainReady TrainDelay DelayCause
source	<pre><xs:element name="TrainReadyStatus"> <xs:complexType> <xs:sequence> <xs:element name="TrainReady"> <xs:annotation> <xs:documentation>0=Not Ready 1=Ready</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="TrainDelay" minOccurs="0"/> <xs:element ref="DelayCause" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **TrainReadyStatus/TrainReady**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3

type	restriction of xs:integer									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0		enumeration	1	
Kind	Value	Annotation								
enumeration	0									
enumeration	1									
annotation	documentation 0=Not Ready 1=Ready									
source	<pre><xs:element name="TrainReady"> <xs:annotation> <xs:documentation>0=Not Ready 1=Ready</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **TrainRunningData**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TrainRunningTechData ExceptionalGaugingInd DangerousGoodsIndicator Activities Notes
used by	element TrainCompositionJourneySection
annotation	documentation Train relevant data for a running train
source	<pre><xs:element name="TrainRunningData"> <xs:annotation> <xs:documentation>Train relevant data for a running train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TrainRunningTechData"/> <xs:element ref="ExceptionalGaugingInd" minOccurs="0"/></pre>

	<pre> <xs:element ref="DangerousGoodsIndicator" minOccurs="0"/> <xs:element name="Activities" minOccurs="0" maxOccurs="99"> <xs:complexType> <xs:sequence> <xs:element ref="TrainActivity"/> <xs:element name="ActivityLocationIdent" type="LocationIdent"/> </xs:sequence> </xs:complexType> </xs:element> <xs:element ref="Notes" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **TrainRunningData/Activities**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 99 content complex
children	TrainActivity ActivityLocationIdent
source	<pre> <xs:element name="Activities" minOccurs="0" maxOccurs="99"> <xs:complexType> <xs:sequence> <xs:element ref="TrainActivity"/> <xs:element name="ActivityLocationIdent" type="LocationIdent"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **TrainRunningData/Activities/ActivityLocationIdent**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent

properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
source	<code><xs:element name="ActivityLocationIdent" type="LocationIdent"/></code>

element **TrainRunningForecastMessage**

diagram	<p>This message is issued from the IM to the neighbouring IM upon departure from or movement past agreed points or prior to reaching the first reporting point if, owing to a delay, the train has not reached the bilaterally agreed initial running time. This message is also issued from the IM to the RU when, at the next stopping or handling station, out-of-schedule running is anticipated that exceeds the threshold agreed with the RU responsible for the train. This message is also issued in any cases for handover points, interchange points, for the destination point and for each other reporting point predefined by contract</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader MessageStatus TrainOperationalIdentification OperationalTrainNumberIdentifier ReferenceOTN ResponsibleRU TrainLocationReport TransferPoint TransfereeIM
annotation	documentation This message is issued from the IM to the neighbouring IM upon departure from or movement past agreed points or prior to reaching the first reporting point if, owing to a delay, the train has not reached the bilaterally agreed station, out-of-schedule running is anticipated that exceeds the threshold agreed with the RU responsible for the train. This message is also issued in any cases for handover points, interchange points, for the destination point and for each other reporting point predefined by contract
source	<pre> <xs:element name="TrainRunningForecastMessage"> <xs:annotation> <xs:documentation>This message is issued from the IM to the neighbouring IM upon departure from or movement past agreed points or prior to reaching the first reporting point if, owing to a delay, the train has not reached the bilaterally agreed initial running time. This message is also issued from the IM to the RU when, at the next stopping or handling station, out- of-schedule running is anticipated that exceeds the threshold agreed with the RU responsible for the train. This message is also issued in any cases for handover points, interchange points, for the destination point and for each other reporting point predefined by contract</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> </pre>

```

<xs:element ref="MessageHeader"/>
<xs:element ref="MessageStatus"/>
<xs:element ref="TrainOperationalIdentification" minOccurs="0"/>
<xs:element ref="OperationalTrainNumberIdentifier"/>
<xs:element ref="ReferenceOTN" minOccurs="0"/>
<xs:element ref="ResponsibleRU" minOccurs="0"/>
<xs:element ref="TrainLocationReport" maxOccurs="unbounded"/>
<xs:element ref="TransferPoint" minOccurs="0"/>
<xs:element ref="TransfereeIM" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>
    
```

element **TrainRunningInformationMessage**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader MessageStatus TrainOperationalIdentification OperationalTrainNumberIdentifier ReferenceOTN ResponsibleRU TrainLocationReport TransferPoint TransfereeIM</p>
<p>annotation</p>	<p>documentation This message is issued upon 1) Arrival, departure or run-through in agreed reporting points and/or 2) Attainment of the agreed initial running time and/or 3) A new divergence between nominal and actual being achieved in excess of the agreed threshold value 4) as a response to the EnquiryTrainsAtReportingLocationMessage. There will only be one train reported per message and will include one response per train at a location.</p>
<p>source</p>	<pre> <xs:element name="TrainRunningInformationMessage"> <xs:annotation> <xs:documentation>This message is issued upon 1) Arrival, departure or run-through in agreed reporting points and/or 2) Attainment of the agreed initial running time and/or 3) A new divergence between nominal and actual being achieved in excess of the agreed threshold value 4) as a response to the EnquiryTrainsAtReportingLocationMessage. There will only be one train reported per message and will include one response per train at a location.</xs:documentation> </xs:annotation> </pre>

```

<xs:complexType>
  <xs:sequence>
    <xs:element ref="MessageHeader"/>
    <xs:element ref="MessageStatus">
      <xs:annotation>
        <xs:documentation>Assigned by the Sender 1=Creation,
2=Modification, 3=deletion </xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element ref="TrainOperationalIdentification" minOccurs="0"/>
    <xs:element ref="OperationalTrainNumberIdentifier"/>
    <xs:element ref="ReferenceOTN" minOccurs="0"/>
    <xs:element ref="ResponsibleRU" minOccurs="0"/>
    <xs:element ref="TrainLocationReport"/>
    <xs:element ref="TransferPoint" minOccurs="0"/>
    <xs:element ref="TransfereeIM" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
  
```

element **TrainRunningInterruptionMessage**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader MessageStatus TrainOperationalIdentification OperationalTrainNumberIdentifier ReferenceOTN ResponsibleRU InterruptionPoint TrainRunningInterruptionStatus TransferPoint TransfereeIM</p>
<p>annotation</p>	<p>documentation This message is used to inform about the trains which has been already interrupted. Message is sent only for those trains, directly interrupted by the disruption.</p>
<p>source</p>	<pre> <xs:element name="TrainRunningInterruptionMessage"> <xs:annotation> <xs:documentation>This message is used to inform about the trains which </pre>


```
has been already interrupted. Message is sent only for those trains,
directly interrupted by the disruption. </xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element ref="MessageHeader"/>
    <xs:element ref="MessageStatus"/>
    <xs:element ref="TrainOperationalIdentification" minOccurs="0"/>
    <xs:element ref="OperationalTrainNumberIdentifier"/>
    <xs:element ref="ReferenceOTN" minOccurs="0"/>
    <xs:element ref="ResponsibleRU" minOccurs="0"/>
    <xs:element ref="InterruptionPoint"/>
    <xs:element ref="TrainRunningInterruptionStatus" minOccurs="0"/>
    <xs:element ref="TransferPoint" minOccurs="0"/>
    <xs:element ref="TransfereeIM" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
</xs:element>
```


element **TrainRunningTechData**


<p>diagram</p>	<p>TrainType Element TrainType defines the main purpose of the train in a fundamental way. These purposes are: Transport of passengers Transport of freightgoods Transport of passengers and freightgoods Train only for sum of traction units/locomotives Train of the EM in case of emergency The element is not repeatable, and it does not support any overloading meaning.</p> <p>TrainWeight The sum of all weights of wagons and traction...</p> <p>TrainLength The calculated length of a train (sum of all length over surface of the wagons and traction units). Expressed in Metres.</p> <p>TrainCC_System 0..9 Identifies the command control system of the train in coded values.</p> <p>TrainRadioSystem 0..9 The on board radio system of the train in coded format.</p> <p>TrainMaxSpeed The max. possible speed of a train in km/h.</p> <p>MaxAxleWeight Indicates the maximum design axle weight (kg).</p> <p>BrakeType Type of braking system.</p> <p>BrakeWeight Shows the brake mass of the wagon according to the type of the braking system in Tonnes.</p> <p>NumberOfVehicles The sum of number of wagons and number of traction units.</p> <p>NumberOfAxes The sum of number of axes of all wagons and all traction units.</p> <p>TrainRunningTechData Shows the relevant technical data for a running train.</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>TrainType TrainWeight TrainLength TrainCC_System TrainRadioSystem TrainMaxSpeed MaxAxleWeight BrakeType BrakeWeight NumberOfVehicles NumberOfAxes</p>
<p>used by</p>	<p>element TrainRunningData</p>
<p>annotation</p>	<p>documentation Shows the relevant technical data for a running train</p>
<p>source</p>	<pre><xs:element name="TrainRunningTechData"> <xs:annotation> <xs:documentation>Shows the relevant technical data for a running train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="TrainType"/> <xs:element ref="TrainWeight"/> <xs:element ref="TrainLength"/> <xs:element ref="TrainCC_System" minOccurs="0" maxOccurs="9"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<pre> <xs:element ref="TrainRadioSystem" minOccurs="0" maxOccurs="9"/> <xs:element ref="TrainMaxSpeed" minOccurs="0"/> <xs:element ref="MaxAxleWeight" minOccurs="0"/> <xs:element ref="BrakeType" minOccurs="0"/> <xs:element ref="BrakeWeight" minOccurs="0"/> <xs:element ref="NumberOfVehicles" minOccurs="0"/> <xs:element ref="NumberOfAxles" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **TrainStartTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
used by	element TrainReadyMessage
annotation	documentation The Date and Time at which the train actually started the journey
source	<pre> <xs:element name="TrainStartTime" type="xs:dateTime"> <xs:annotation> <xs:documentation>The Date and Time at which the train actually started the journey</xs:documentation> </xs:annotation> </xs:element> </pre>

element **TrainWeight**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of WeightValueTonne									
properties	content simple									
used by	elements PlannedTrainTechnicalData TrainRunningTechData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation The sum of all weights of wagons and traction units									
source	<pre> <xs:element name="TrainWeight"> <xs:annotation> <xs:documentation>The sum of all weights of wagons and traction units</xs:documentation> </xs:annotation> <xs:simpleType> </pre>									

	<pre> <xs:restriction base="WeightValueTonne"> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **TransfereelM**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	CompanyCode												
properties	content simple												
used by	elements ChangeofTrackMessage TrainCompositionMessage TrainDelayCauseMessage TrainJourneyModificationMessage TrainReadyMessage TrainRunningForecastMessage TrainRunningInformationMessage TrainRunningInterruptionMessage												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Next IM												
source	<pre> <xs:element name="TransfereelM" type="CompanyCode"> <xs:annotation> <xs:documentation>Next IM</xs:documentation> </xs:annotation> </xs:element> </pre>												

element **TransferPoint**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	LocationIdent
properties	content complex
children	CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification
used by	elements ChangeofTrackMessage TrainCompositionMessage TrainDelayCauseMessage TrainJourneyModificationMessage TrainReadyMessage TrainRunningForecastMessage TrainRunningInformationMessage TrainRunningInterruptionMessage
annotation	documentation Transfer point or station of destination in the considered network

source	<pre><xs:element name="TransferPoint" type="LocationIdent"> <xs:annotation> <xs:documentation>Transfer point or station of destination in the considered network</xs:documentation> </xs:annotation> </xs:element></pre>
--------	--

element **TransportInstruction**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	FreeText									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Special instructions regarding the transportation of the wagon or shipment in free text									
source	<pre><xs:element name="TransportInstruction" type="FreeText"> <xs:annotation> <xs:documentation>Special instructions regarding the transportation of the wagon or shipment in free text</xs:documentation> </xs:annotation> </xs:element></pre>									

element **TransportOperationalIdentifiers**


diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of CompositIdentifierOperationalType
properties	content complex
children	ObjectType Company Core Variant TimetableYear StartDate
used by	elements ErrorMessage TrainCompositionMessage TrainOperationalIdentification TrainReadyMessage
source	<pre><xs:element name="TransportOperationalIdentifiers"> <xs:complexType> <xs:complexContent> <xs:extension base="CompositIdentifierOperationalType"/> </xs:complexContent> </xs:complexType> </xs:element></pre>

element **TypeOfIMHarmonization**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	TypeOfIMHarmonizationCode
properties	content simple
used by	elements PathDetailsMessage PathRequestMessage
facets	Kind Value Annotation enumeration Full enumeration Part
annotation	documentation Enumeration of Type of IM harmonization: Full, Part
source	<pre><xs:element name="TypeOfIMHarmonization" type="TypeOfIMHarmonizationCode"> <xs:annotation> <xs:documentation>Enumeration of Type of IM harmonization: Full, Part </xs:documentation> </xs:annotation> </xs:element></pre>


element **TypeOfInformation**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	TypeOfInformationCode
properties	content simple
used by	elements PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage ReceiptConfirmationMessage

facets	Kind	Value	Annotation
	minInclusive	0	
	maxInclusive	99	
	enumeration	1	documentation harmonisation - in process
	enumeration	2	documentation harmonisation - accepted
	enumeration	3	documentation harmonisation - rejected
	enumeration	4	documentation Request ready
	enumeration	5	documentation path study request
	enumeration	6	documentation pre-arranged path/reserve capacity
	enumeration	7	documentation create offer
	enumeration	8	documentation coordination update
	enumeration	9	documentation draft offer
	enumeration	10	documentation draft alternative offer
	enumeration	11	documentation observation - in process
	enumeration	12	documentation observation - complete
	enumeration	13	documentation preparation of final offer - in process
	enumeration	14	documentation preparation of final offer - accepted
	enumeration	15	documentation preparation of final offer - rejected
	enumeration	16	documentation final offer
	enumeration	17	documentation final offer - accepted
	enumeration	18	documentation alternative offer accepted
	enumeration	19	documentation pre-accepted offer
	enumeration	20	documentation Final Offer rejected
	enumeration	21	documentation no alternative available
	enumeration	22	documentation booked
	enumeration	23	documentation preparation of draft alternative offer is in progress
	enumeration	24	documentation alternative offer triggered by IM
	enumeration	25	documentation offer/final offer rejected (without revision)
	enumeration	26	documentation alternative offer rejected (without revision)
	enumeration	27	documentation offer/final offer rejected (revision required)
	enumeration	28	documentation alternative offer rejected (revision required)
	enumeration	29	documentation withdrawal
	enumeration	30	documentation Create Dossier

	enumeration 31	documentation Close Dossier
	enumeration 32	documentation Path canceled full
	enumeration 33	documentation Path canceled partial
	enumeration 40	documentation Fully Assembled Path (FAP, constructed path)
	enumeration 42	documentation Preparation of draft offer – accepted
	enumeration 43	documentation Preparation of draft offer – rejected
	enumeration 44	documentation Draft offer rejected
	enumeration 45	documentation Draft no alternative available
	enumeration 50	documentation activate path (utilisation notification)
	enumeration 51	documentation deactivate path (utilisation notification)
	enumeration 52	documentation confirmation of utilisation notification
	enumeration 53	documentation Path and train cancelled
	enumeration 65	documentation Preparation of alternative offer in progress due to route update (used in PathNotAvailableMessage)
	enumeration 66	documentation Booked after route update (used in PathDetailsMessage)
annotation		documentation Enumeration indicating to which process step / process type in the planning does the message belong: path study; pre-arranged/catalogue path; (draft) offer; final offer; booked; deleted; utilisation notification; confirmation of utilisation confirmation
source		<code><xs:element name="TypeOfInformation" type="TypeOfInformationCode"> <xs:annotation> <xs:documentation> Enumeration indicating to which process step / process type in the planning does the message belong: path study; pre-arranged/catalogue path; (draft) offer; final offer; booked; deleted; utilisation notification; confirmation of utilisation confirmation</xs:documentation> </xs:annotation> </xs:element></code>

element **TypeOfRequest**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	TypeOfRequestCode		
properties	content	simple	
used by	elements	PathCanceledMessage PathConfirmedMessage PathDetailsMessage PathDetailsRefusedMessage PathNotAvailableMessage PathRequestMessage ReceiptConfirmationMessage	
facets	Kind	Value	Annotation
	minInclusive	1	
	enumeration	1	documentation

	<p>enumeration 2 Study documentation Request</p> <p>enumeration 3 documentation Modification</p>
annotation	<p>documentation Enumeration for 3 different basic types of the processes in the planning: Study (1), Request (2), Modification (3)</p>
source	<pre><xs:element name="TypeOfRequest" type="TypeOfRequestCode"> <xs:annotation> <xs:documentation> Enumeration for 3 different basic types of the processes in the planning: Study (1), Request (2), Modification (3) </xs:documentation> </xs:annotation> </xs:element></pre>

element **TypeOfRUHarmonization**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	TypeOfRUHarmonizationCode												
properties	content simple												
used by	elements PathDetailsMessage PathRequestMessage												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Full</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Part</td> <td></td> </tr> <tr> <td>enumeration</td> <td>None</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	Full		enumeration	Part		enumeration	None	
Kind	Value	Annotation											
enumeration	Full												
enumeration	Part												
enumeration	None												
annotation	<p>documentation Type of RU harmonization: Full, Part, None.</p>												
source	<pre><xs:element name="TypeOfRUHarmonization" type="TypeOfRUHarmonizationCode"> <xs:annotation> <xs:documentation>Type of RU harmonization: Full, Part, None.</xs:documentation> </xs:annotation> </xs:element></pre>												

element **TypeofService**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	SpecialServiceDescriptionCode FacilityTypeDescriptionCode CharacteristicDescriptionCode
used by	element PlannedTrainData

annotation	documentation Information about the services available on a train. Used for publication towards the passenger
source	<pre> <xs:element name="TypeofService"> <xs:annotation> <xs:documentation>Information about the services available on a train. Used for publication towards the passenger</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="SpecialServiceDescriptionCode" type="tap:type7161CodeList" minOccurs="0" maxOccurs="unbounded"/> <xs:element name="FacilityTypeDescriptionCode" type="tap:type9039CodeList" minOccurs="0" maxOccurs="unbounded"/> <xs:element name="CharacteristicDescriptionCode" type="tap:type7037CodeList" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **TypeofService/SpecialServiceDescriptionCode**

diagram																						
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																					
type	type7161CodeList																					
properties	minOcc 0 maxOcc unbounded content simple																					
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> <td></td> </tr> <tr> <td>enumeration</td> <td>00</td> <td>documentation Alternative service documentation The journey planner algorithm should look for an alternative Service documentation 0</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation Additional loading documentation Additional loading of vehicles on a train of accompanied motorcars documentation 0</td> </tr> <tr> <td>enumeration</td> <td>4</td> <td>documentation Additional unloading documentation Additional unloading of vehicles from a train of accompanied motorcars documentation 0</td> </tr> <tr> <td>enumeration</td> <td>5</td> <td>documentation Breakfast documentation Breakfast documentation 0</td> </tr> <tr> <td>enumeration</td> <td>6</td> <td>documentation Dinner documentation</td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	3		enumeration	00	documentation Alternative service documentation The journey planner algorithm should look for an alternative Service documentation 0	enumeration	3	documentation Additional loading documentation Additional loading of vehicles on a train of accompanied motorcars documentation 0	enumeration	4	documentation Additional unloading documentation Additional unloading of vehicles from a train of accompanied motorcars documentation 0	enumeration	5	documentation Breakfast documentation Breakfast documentation 0	enumeration	6	documentation Dinner documentation
Kind	Value	Annotation																				
maxLength	3																					
enumeration	00	documentation Alternative service documentation The journey planner algorithm should look for an alternative Service documentation 0																				
enumeration	3	documentation Additional loading documentation Additional loading of vehicles on a train of accompanied motorcars documentation 0																				
enumeration	4	documentation Additional unloading documentation Additional unloading of vehicles from a train of accompanied motorcars documentation 0																				
enumeration	5	documentation Breakfast documentation Breakfast documentation 0																				
enumeration	6	documentation Dinner documentation																				


		Dinner documentation 0
enumeration	7	documentation Loading documentation Loading of vehicles on a train of accompanied motorcars documentation 0
enumeration	8	documentation Lunch documentation Lunch documentation 0
enumeration	9	documentation Unloading documentation Unloading of vehicles from a train of accompanied motorcars documentation 0
enumeration	11	documentation Child documentation Services for children documentation 0
enumeration	21	documentation Cold buffet documentation Cold buffet service documentation 0
enumeration	22	documentation Restaurant in 1st class only documentation Restaurant service in 1st class only documentation 0
enumeration	23	documentation Hot buffet documentation Hot buffet service documentation 0
enumeration	24	documentation Meal included for 1st class passengers documentation Meal service included for 1st class passengers documentation 0
enumeration	25	documentation Trolley documentation Trolley service (beverage and food cart) documentation 0
enumeration	26	documentation Snack documentation Snack documentation 0

enumeration	27	documentation Disabled documentation Services for disabled persons documentation 0
enumeration	28	documentation Movies documentation Movies documentation 0
enumeration	29	documentation Business documentation Services for business people documentation 0
enumeration	30	documentation Nursery documentation Nursery service documentation 0
enumeration	31	documentation Buffet documentation Buffet documentation 0
enumeration	32	documentation Special services for military documentation Special services for army families documentation 0
enumeration	33	documentation Boarding possible 2 hours before departure documentation Boarding is possible 2 hours before departure documentation 0
enumeration	34	documentation Alighting possible until 2 hours after arrival documentation Alighting is possible up to 2 hours after arrival documentation 0
enumeration	35	documentation Boarding possible 30 minutes before departure documentation Boarding is possible 30 minutes before departure documentation 0
enumeration	36	documentation Alighting possible until 30 minutes after arrival documentation Alighting is possible up to 30 minutes after arrival documentation 0
enumeration	37	documentation Postal services documentation

		Postal services available documentation 0
enumeration	38	documentation Meal at the seat documentation Meal is provided at the seat documentation 0
enumeration	39	documentation Self service documentation Self service meals documentation 0
enumeration	40	documentation Overnight stay documentation Overnight stay possible on board documentation 0
enumeration	41	documentation Luggage transport documentation Luggage transport offered documentation 0
enumeration	42	documentation Luggage transport excluded documentation Luggage transport is not offered documentation 0
enumeration	43	documentation Music documentation Music documentation 0
enumeration	44	documentation Check-in documentation Time at which the traveller checks in documentation 0
enumeration	45	documentation Check-out documentation Time at which the traveller checks out documentation 0
enumeration	46	documentation Free WiFi on board documentation Free WiFi service on board available documentation 0
enumeration	47	documentation WiFi on board documentation WiFi service on board available documentation 0

	enumeration 48 documentation Warning! Service may be affected by strike action documentation Warning! Service may be affected by strike action documentation 0
source	<xs:element name="SpecialServiceDescriptionCode" type="tap:type7161CodeList" minOccurs="0" maxOccurs="unbounded"/>

element **TypeofService/FacilityTypeDescriptionCode**

diagram																									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																								
type	type9039CodeList																								
properties	minOcc 0 maxOcc unbounded content simple																								
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation First-class sleepers documentation First-class sleepers documentation 0</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation Standard class sleepers documentation Standard class (second class) sleepers documentation 0</td> </tr> <tr> <td>enumeration</td> <td>4</td> <td>documentation First-class seats documentation First-class seats documentation 0</td> </tr> <tr> <td>enumeration</td> <td>5</td> <td>documentation Second-class seats documentation Second-class seats documentation Also: standard, etc. documentation 0</td> </tr> <tr> <td>enumeration</td> <td>6</td> <td>documentation First-class couchettes documentation First-class couchettes documentation 0</td> </tr> <tr> <td>enumeration</td> <td>7</td> <td>documentation Second-class couchettes documentation Second-class couchettes documentation 0</td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	3		enumeration	2	documentation First-class sleepers documentation First-class sleepers documentation 0	enumeration	3	documentation Standard class sleepers documentation Standard class (second class) sleepers documentation 0	enumeration	4	documentation First-class seats documentation First-class seats documentation 0	enumeration	5	documentation Second-class seats documentation Second-class seats documentation Also: standard, etc. documentation 0	enumeration	6	documentation First-class couchettes documentation First-class couchettes documentation 0	enumeration	7	documentation Second-class couchettes documentation Second-class couchettes documentation 0
Kind	Value	Annotation																							
maxLength	3																								
enumeration	2	documentation First-class sleepers documentation First-class sleepers documentation 0																							
enumeration	3	documentation Standard class sleepers documentation Standard class (second class) sleepers documentation 0																							
enumeration	4	documentation First-class seats documentation First-class seats documentation 0																							
enumeration	5	documentation Second-class seats documentation Second-class seats documentation Also: standard, etc. documentation 0																							
enumeration	6	documentation First-class couchettes documentation First-class couchettes documentation 0																							
enumeration	7	documentation Second-class couchettes documentation Second-class couchettes documentation 0																							

enumeration	8	documentation Sleeperette documentation Sleeperette or reclining seat documentation 0
enumeration	9	documentation Restaurant documentation Restaurant facility documentation 0
enumeration	11	documentation First-class sleeper, single documentation First-class sleeper, single documentation 0
enumeration	12	documentation First-class sleeper, special documentation First-class sleeper, special documentation 0
enumeration	13	documentation First-class sleeper, double documentation First-class sleeper, double documentation 0
enumeration	14	documentation Vehicle transport documentation Facilities for vehicle transport etc. Not bicycles. documentation Cars, boats, trailers, motorbikes, documentation 0
enumeration	15	documentation Second-class sleeper, T2 documentation Second-class sleeper, T2 (two-bed compartment) documentation 0
enumeration	16	documentation Second-class sleeper, T3 documentation Second-class sleeper, T3 (three-bed compartment) documentation 0
enumeration	17	documentation Second-class sleeper T4 documentation Second-class sleeper, T4 (four-bed compartment) documentation 0
enumeration	18	documentation First-class sleeper, single, shower documentation First-class sleeper, single with shower documentation 0
enumeration	19	documentation

		First-class sleeper, double, shower documentation
		First-class sleeper, double with shower documentation
enumeration	20	0 documentation
		Non-smoker service documentation
		The travel service is non-smoking documentation
enumeration	21	0 documentation
		Heavily disabled documentation
		Facilities for heavily disabled persons available documentation
enumeration	24	0 documentation
		Baby room documentation
		Baby care facilities available documentation
enumeration	26	0 documentation
		Bicycle transport documentation
		Facility for bicycle transport available documentation
enumeration	28	0 documentation
		Wheelchair access documentation
		Access for wheelchairs possible documentation
enumeration	33	0 documentation
		Video coach documentation
		Video coach available documentation
enumeration	34	0 documentation
		Mini-bar documentation
		Mini-bar available documentation
enumeration	36	0 documentation
		Panorama coach documentation
		Panorama coach available documentation
enumeration	44	0 documentation
		Telephone documentation
		Telephone service is available documentation
enumeration	45	0 documentation
		Power supply documentation
		Service provides power supply sockets

		documentation 0
enumeration	46	documentation Pullmann coach documentation Pullman car seats documentation 0
enumeration	47	documentation Bar documentation A bar is available documentation 0
enumeration	48	documentation Family compartment documentation Family compartment(s) available documentation 0
enumeration	50	documentation Buffet machine documentation Buffet machine available documentation 0
enumeration	54	documentation Premium class documentation A class with comfort level higher than first class Business, etc documentation Includes Comfort, Club, Pullman, documentation 0
enumeration	55	documentation Preferente documentation Spanish first class on long distance trains documentation RENFE documentation 0
enumeration	56	documentation Turista documentation Spanish second class on long distance trains documentation RENFE documentation 0
enumeration	57	documentation First-class sleeper, single, shower, WC documentation First-class sleeper, single with shower and WC documentation RENFE documentation 0
enumeration	58	documentation First-class sleeper, double shower, WC documentation First-class sleeper, double with shower and WC documentation

		<p>RENFE</p> <p>documentation</p> <p>0</p>
enumeration	59	<p>documentation</p> <p>Second class sleeper, T3, shower, WC</p> <p>documentation</p> <p>Second class sleeper, T3, shower, WC</p> <p>documentation</p> <p>0</p>
enumeration	60	<p>documentation</p> <p>Second class sleeper double</p> <p>documentation</p> <p>Second class sleeper for two</p> <p>documentation</p> <p>0</p>
enumeration	61	<p>documentation</p> <p>Second class sleeper double shower/toilets</p> <p>documentation</p> <p>Second class sleeper for two with shower and toilets</p> <p>documentation</p> <p>0</p>
enumeration	62	<p>documentation</p> <p>Second-class, couchette, two-bed, C2</p> <p>documentation</p> <p>Second class compartment with 2 couchettes</p> <p>documentation</p> <p>0</p>
enumeration	63	<p>documentation</p> <p>Second-class, couchette, four-bed, C4</p> <p>documentation</p> <p>Second class compartment with 4 couchettes</p> <p>documentation</p> <p>0</p>
enumeration	64	<p>documentation</p> <p>Second-class, couchette, six-bed, C6</p> <p>documentation</p> <p>Second class compartment with 6 couchettes</p> <p>documentation</p> <p>0</p>
enumeration	65	<p>documentation</p> <p>Second class couchette wheelchair</p> <p>documentation</p> <p>Second class couchette with wheelchair space</p> <p>documentation</p> <p>0</p>
enumeration	66	<p>documentation</p> <p>Executive class</p> <p>documentation</p> <p>A class with comfort level higher than first class</p> <p>documentation</p> <p>Trenitalia</p> <p>documentation</p> <p>0</p>
enumeration	67	<p>documentation</p> <p>Business class</p> <p>documentation</p> <p>First class</p> <p>documentation</p> <p>Trenitalia</p> <p>documentation</p> <p>0</p>
enumeration	68	<p>documentation</p> <p>Premium class</p>

		documentation A second class with comfort level higher than normal second class documentation Trenitalia documentation 0
enumeration	69	documentation Standard class documentation Trenitalia's normal second class documentation Trenitalia documentation 0
enumeration	70	documentation Unified class documentation For services with no class differentiation. A service with only one class documentation UIC documentation 0
enumeration	71	documentation Medical-grade masks documentation Medical-grade masks must be worn documentation 0
enumeration	72	documentation Mask obligation according to legal regulation documentation Mask obligation according to legal regulation documentation 0
enumeration	101	documentation Metro connection documentation Metro, subway, underground connection documentation Only used in TSDUPD documentation 0
enumeration	102	documentation Taxi connection documentation Taxi connection documentation Only used in TSDUPD documentation 0
enumeration	103	documentation Bus connection documentation Bus connections available documentation Used only in TSDUPD documentation 0
enumeration	104	documentation Tram connection documentation Tram connections available documentation

	<p>Used only in TSDUPD documentation 0</p> <p>enumeration 105 documentation 2nd Class couchette five beds C5 documentation 2nd Class couchette five beds C5 documentation DB Nachtzug documentation 0</p> <p>enumeration 106 documentation Vaccinated, tested, recovered rule applied documentation Vaccinated, tested, recovered rule applied documentation Vaccinated, tested, recovered rule applies on trains, valid proof must be presented documentation 0</p> <p>enumeration 107 documentation Dedicated toilet and place for wheelchair documentation Dedicated toilet and place for wheelchair documentation Dedicated toilet together with dedicated space for wheelchair documentation 0</p>
source	<pre><xs:element name="FacilityTypeDescriptionCode" type="tap:type9039CodeList" minOccurs="0" maxOccurs="unbounded"/></pre>


element **TypeofService/CharacteristicDescriptionCode**

diagram																
namespace	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>															
type	<p>type7037CodeList</p>															
properties	<p>minOcc 0 maxOcc unbounded content simple</p>															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>17</td> <td></td> </tr> <tr> <td>enumeration</td> <td>6</td> <td>documentation First class documentation First class accommodation documentation 0</td> </tr> <tr> <td>enumeration</td> <td>7</td> <td>documentation Second class documentation Second class accommodation documentation 0</td> </tr> <tr> <td>enumeration</td> <td>11</td> <td>documentation Reservation possible documentation Reservation is possible documentation</td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	17		enumeration	6	documentation First class documentation First class accommodation documentation 0	enumeration	7	documentation Second class documentation Second class accommodation documentation 0	enumeration	11	documentation Reservation possible documentation Reservation is possible documentation
Kind	Value	Annotation														
maxLength	17															
enumeration	6	documentation First class documentation First class accommodation documentation 0														
enumeration	7	documentation Second class documentation Second class accommodation documentation 0														
enumeration	11	documentation Reservation possible documentation Reservation is possible documentation														

	enumeration	12	0 documentation With supplement documentation A supplement is charged documentation
	enumeration	13	0 documentation Reservation compulsory documentation Reservation is compulsory documentation
	enumeration	14	0 documentation Reservation advised documentation Reservation is recommended documentation
	enumeration	15	0 documentation Reservation compulsory for parties documentation Reservation is compulsory for parties documentation
	enumeration	16	0 documentation Reservation compulsory in first-class documentation Reservation is compulsory in first-class documentation
	enumeration	17	0 documentation Group booking restricted documentation Booking by groups restricted documentation
	enumeration	18	0 documentation Groups not allowed documentation Groups of travellers are not allowed documentation
	enumeration	19	0 documentation No reservation documentation Reservation is not possible documentation
	enumeration	20	0 documentation Reservation in first class only documentation Reservation is only possible in first documentation
	enumeration	21	0 documentation Reservation compulsory from origin station documentation Reservation compulsory from origin station documentation
	enumeration	22	0 documentation Reservation allowed for certain classes/products

	documentation Reservation possible for some booking classes/products documentation 0 documentation Reservation in second class only documentation Reservation is only possible in second class. documentation 0
enumeration 23	documentation Not available documentation The product is not available documentation 0
enumeration 24	documentation Non-bookable documentation The product is not bookable documentation 0
enumeration 25	documentation Bookable through an international reservation system documentation Bookable through an international reservation system documentation 0
enumeration 26	documentation Bookable through a national reservation system documentation Bookable through a national reservation system documentation 0
enumeration 27	documentation Bookable manually on the RU selling point documentation Bookable manually on the RU selling point documentation 0
enumeration 28	documentation 0
source	<code><xs:element name="CharacteristicDescriptionCode" type="tap:type7037CodeList" minOccurs="0" maxOccurs="unbounded"/></code>

element **UltimateDestinationCountry**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	CountryIdentISO									
properties	content simple									
used by	element ITU Details									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2	
Kind	Value	Annotation								
minLength	2									
maxLength	2									
annotation	documentation Country of Ultimate Destination									

source	<pre><xs:element name="UltimateDestinationCountry" type="CountryIdentISO"> <xs:annotation> <xs:documentation>Country of Ultimate Destination</xs:documentation> </xs:annotation> </xs:element></pre>
--------	--

element **UN_Number**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
used by	element SummaryOfGoodsWithSameRID									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	4		pattern	\d*[1-9]\d*	
Kind	Value	Annotation								
length	4									
pattern	\d*[1-9]\d*									
annotation	<p>documentation</p> <p>The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING" .</p>									
source	<pre><xs:element name="UN_Number"> <xs:annotation> <xs:documentation>The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING" .</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="4"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **ValidityPeriod**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex

children	StartDateTime EndDateTime
used by	elements LocationPrimaryInformation LocationSubsidiaryInformation PlannedCalendar ReferenceTrainIDSubCalendar RequestedCalendar
source	<pre><xs:element name="ValidityPeriod"> <xs:complexType> <xs:sequence> <xs:element ref="StartDateTime"/> <xs:element ref="EndDateTime" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element Value

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:decimal												
properties	content simple												
used by	elements Height Length Width												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999999999</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	9999999999		fractionDigits	1	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	9999999999												
fractionDigits	1												
source	<pre><xs:element name="Value"> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="0"/> <xs:fractionDigits value="1"/> <xs:maxInclusive value="9999999999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>												

element Variant

diagram	 <p>The variant shows a relationship between two identifiers referring to the same business case</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:string												
properties	content simple												
used by	complexTypees CompositIdentifierOperationalType CompositIdentifierPlannedType												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>2</td> <td></td> </tr> <tr> <td>maxLength</td> <td>2</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{2}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	2		maxLength	2		pattern	[0-9A-Z]{2}	
Kind	Value	Annotation											
minLength	2												
maxLength	2												
pattern	[0-9A-Z]{2}												

annotation	documentation The variant shows a relationship between two identifiers referring to the same business case
source	<pre> <xs:element name="Variant"> <xs:annotation> <xs:documentation>The variant shows a relationship between two identifiers referring to the same business case</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:maxLength value="2"/> <xs:pattern value="[0-9A-Z]{2}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **VesselIndication**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	VesselName ClosingTime
used by	elements WIMO Dataset/EventLevelData Ship
annotation	documentation This element identifies to which extent the transportation unit is used
source	<pre> <xs:element name="VesselIndication"> <xs:annotation> <xs:documentation>This element identifies to which extent the transportation unit is used</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="VesselName"/> <xs:element ref="ClosingTime" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **VesselName**

diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Name
properties	content simple
used by	element VesselIndication
facets	Kind Value Annotation maxLength 254
annotation	documentation This element identifies the vessel by name according the Lloyd register, if the shipment has to change the transportation mode from rail to sea
source	<pre><xs:element name="VesselName" type="Name"> <xs:annotation> <xs:documentation>This element identifies the vessel by name according the Lloyd register, if the shipment has to change the transportation mode from rail to sea</xs:documentation> </xs:annotation> </xs:element></pre>

element Volume

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	VolumeValue
properties	content simple
annotation	documentation Identifies the volume of a shipment, expressed in cubic metres
source	<pre><xs:element name="Volume" type="VolumeValue"> <xs:annotation> <xs:documentation>Identifies the volume of a shipment, expressed in cubic metres</xs:documentation> </xs:annotation> </xs:element></pre>

element WagonArrivalNoticeMessage

diagram	
---------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonInformation ArrivalAtDestination
annotation	documentation This message is used by the last RU/Service Provider in the transport chain to inform the Lead RU that the wagon has arrived at its yard.
source	<pre> <xs:element name="WagonArrivalNoticeMessage"> <xs:annotation> <xs:documentation>This message is used by the last RU/Service Provider in the transport chain to inform the Lead RU that the wagon has arrived at its yard.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonInformation"/> <xs:element ref="ArrivalAtDestination"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonAtDeparture**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location DepartureTimeAtLocation
used by	element WagonDepartureNoticeMessage
annotation	documentation Departure point of a wagon with location and departure time
source	<pre> <xs:element name="WagonAtDeparture"> <xs:annotation> <xs:documentation>Departure point of a wagon with location and departure time</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="DepartureTimeAtLocation"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonData**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>WagonNumberFreight WagonTrainPosition WagonOperationalData WagonTechData</p>
<p>used by</p>	<p>element TrainCompositionJourneySection</p>
<p>annotation</p>	<p>documentation Wagon relevant data for the wagons within a running train</p>
<p>source</p>	<pre><xs:element name="WagonData"> <xs:annotation> <xs:documentation>Wagon relevant data for the wagons within a running train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:element ref="WagonTrainPosition"/> <xs:element ref="WagonOperationalData"/> <xs:element ref="WagonTechData"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **WagonDeliveryNoticeMessage**

<p>diagram</p>	
----------------	--

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonInformation DeliveryAtDestination Customers
annotation	documentation This message is used by the last RU/Service Provider in the transport chain to inform the Lead RU that the wagon has been placed at the consignee's siding.
source	<pre><xs:element name="WagonDeliveryNoticeMessage"> <xs:annotation> <xs:documentation>This message is used by the last RU/Service Provider in the transport chain to inform the Lead RU that the wagon has been placed at the consignee's siding.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonInformation"/> <xs:element ref="DeliveryAtDestination"/> <xs:element ref="Customers" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **WagonDepartureNoticeMessage**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader RelatedReference WagonInformation Customers WagonAtDeparture
annotation	documentation This message is used by the RU in charge to inform the LRU that the wagon has been picked-up (pulled) and has reached the RU's Yard of Departure. This message is the response to the WagonReleaseNoticeMessage.
source	<pre><xs:element name="WagonDepartureNoticeMessage"> <xs:annotation> <xs:documentation>This message is used by the RU in charge to inform the LRU that the wagon has been picked-up (pulled) and has reached the RU's Yard of Departure. This message is the response to the WagonReleaseNoticeMessage.</xs:documentation></pre>

	<pre> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="RelatedReference" minOccurs="0"/> <xs:element ref="WagonInformation"/> <xs:element ref="Customers" minOccurs="0"/> <xs:element ref="WagonAtDeparture"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **WagonDeviationMessage**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader RelatedReference WagonNumberFreight ActualETI WagonExceptionReport
annotation	documentation This message is issued following receipt of an enquiry about the wagon deviation. It delivers a report of all deviations of a specified wagon at all reporting points.
source	<pre> <xs:element name="WagonDeviationMessage"> <xs:annotation> <xs:documentation>This message is issued following receipt of an enquiry about the wagon deviation. It delivers a report of all deviations of a specified wagon at all reporting points.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="RelatedReference"/> <xs:element ref="WagonNumberFreight"/> <xs:element ref="ActualETI"/> <xs:element ref="WagonExceptionReport"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonETI_ETA_Message**

<p>diagram</p>	<p>MessageHeader Used for all messa...</p> <p>RelatedReference Identifies the message to which the actual message refers</p> <p>WagonInformati... This element shows the unique wagon number together with the transportation units, loaded on the wagon, the used capacity and the weight of the complete load of the ...</p> <p>ArrivalInterchangeReport The arrival or interchange station where ETI end</p> <p>DepartureInterchangeReport Departure or interchange station ETI Origin</p> <p>WagonETI_ETA_Messa... This message is sent by the RU to the next RU in the transport chain to give him the calculation of its ETI. The last RU sends this message with ETA to the Lead RU, which may inform its customer. Following the handover information from the IM, the RU sends with this message also the updated ETI to the next RU and ...</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader RelatedReference WagonInformation ArrivalInterchangeReport DepartureInterchangeReport</p>
<p>annotation</p>	<p>documentation This message is sent by the RU to the next RU in the transport chain to give him the calculation of its ETI. The last RU sends this message with ETA to the Lead RU, which may inform its customer. Following the handover information from the IM, the RU sends with this message also the updated ETI to the next RU and the last RU sends the updated ETA to the LRU.</p>
<p>source</p>	<pre><xs:element name="WagonETI_ETA_Message"> <xs:annotation> <xs:documentation>This message is sent by the RU to the next RU in the transport chain to give him the calculation of its ETI. The last RU sends this message with ETA to the Lead RU, which may inform its customer. Following the handover information from the IM, the RU sends with this message also the updated ETI to the next RU and the last RU sends the updated ETA to the LRU.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="RelatedReference"/> <xs:element ref="WagonInformation"/> <xs:element ref="ArrivalInterchangeReport"/> <xs:element ref="DepartureInterchangeReport" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **WagonEventInformation**

<p>diagram</p>	<p>WagonEventInformati... This is a WIMO element that is derived from the Wagon Release Notice and Event Me...</p> <p>WagonEve...</p> <p>EventDateTime</p> <p>Location Identifies a Location using a LocationIdent</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>

properties	content complex
children	WagonEvent EventDateTime Location
used by	element WIMO Dataset/EventLevelData
annotation	documentation This is a WIMO element that is derived from the Wagon Release Notice and Event Messages
source	<pre> <xs:element name="WagonEventInformation"> <xs:annotation> <xs:documentation>This is a WIMO element that is derived from the Wagon Release Notice and Event Messages</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="WagonEvent"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="Release"/> <xs:enumeration value="Arrival"/> <xs:enumeration value="Departure"/> <xs:enumeration value="Exception"/> <xs:enumeration value="Delivery"/> <xs:enumeration value="InterchangeDelivery"/> <xs:enumeration value="InterchangeReceipt"/> <xs:enumeration value="YardDeparture"/> <xs:enumeration value="YardArrival"/> <xs:enumeration value="DeliveryConfirmation"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="EventDateTime" type="xs:dateTime"/> <xs:element ref="Location"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonEventInformation/WagonEvent**

diagram																															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																														
type	restriction of xs:token																														
properties	content simple																														
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Release</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Arrival</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Departure</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Exception</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Delivery</td> <td></td> </tr> <tr> <td>enumeration</td> <td>InterchangeDelivery</td> <td></td> </tr> <tr> <td>enumeration</td> <td>InterchangeReceipt</td> <td></td> </tr> <tr> <td>enumeration</td> <td>YardDeparture</td> <td></td> </tr> <tr> <td>enumeration</td> <td>YardArrival</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	Release		enumeration	Arrival		enumeration	Departure		enumeration	Exception		enumeration	Delivery		enumeration	InterchangeDelivery		enumeration	InterchangeReceipt		enumeration	YardDeparture		enumeration	YardArrival	
Kind	Value	Annotation																													
enumeration	Release																														
enumeration	Arrival																														
enumeration	Departure																														
enumeration	Exception																														
enumeration	Delivery																														
enumeration	InterchangeDelivery																														
enumeration	InterchangeReceipt																														
enumeration	YardDeparture																														
enumeration	YardArrival																														

	enumeration DeliveryConfirmation
source	<pre><xs:element name="WagonEvent"> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="Release"/> <xs:enumeration value="Arrival"/> <xs:enumeration value="Departure"/> <xs:enumeration value="Exception"/> <xs:enumeration value="Delivery"/> <xs:enumeration value="InterchangeDelivery"/> <xs:enumeration value="InterchangeReceipt"/> <xs:enumeration value="YardDeparture"/> <xs:enumeration value="YardArrival"/> <xs:enumeration value="DeliveryConfirmation"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **WagonEventInformation/EventDateTime**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:dateTime
properties	content simple
source	<pre><xs:element name="EventDateTime" type="xs:dateTime"/></pre>

element **WagonExceptionMessage**

diagram	<p>The diagram shows the structure of the WagonExceptionMessage element. It consists of a MessageHeader (Used for all messa...), a WagonInformati... (This element shows the unique wagon number together with the transportation units, loaded on the wagon, the used capacity and the weight of the complete load of the ...), a WagonExceptionRep... (Specifies the exceptions of a wagon related to a specific location), and a DangerousGoodsIndicati... (Identifies dangerous go...). The WagonExceptionMessage is described as: "This message is used by the RU/Service Provider to inform the Lead RU about deviations e.g. bad order, hold".</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonInformation WagonExceptionReport DangerousGoodsIndication
annotation	documentation This message is used by the RU/Service Provider to inform the Lead RU about deviations e.g. bad order, hold
source	<pre><xs:element name="WagonExceptionMessage"> <xs:annotation> <xs:documentation>This message is used by the RU/Service Provider to</pre>

	<pre> inform the Lead RU about deviations e.g. bad order, hold</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonInformation"/> <xs:element ref="WagonExceptionReport"/> <xs:element ref="DangerousGoodsIndication" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **WagonExceptionReasonMessage**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonInformation WagonExceptionReport DangerousGoodsIndication
annotation	documentation This message is used by the Lead RU to inform the other RU/Service providers about deviations and to request a new ETI/ETA.
source	<pre> <xs:element name="WagonExceptionReasonMessage"> <xs:annotation> <xs:documentation>This message is used by the Lead RU to inform the other RU/Service providers about deviations and to request a new ETI/ETA.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonInformation"/> <xs:element ref="WagonExceptionReport"/> <xs:element ref="DangerousGoodsIndication" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonExceptionReport**


diagram	<p>WagonExceptionRep... Specifies the exceptions of a wagon related to a specific location</p> <p>ExceptionPoi... Describes the interruption points with location and the time of the interruption</p> <p>ExceptionReas... Identifies the reason of an unexpected interruption for a wagon during the transportation. In addition it allows to put in a more detailed description</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	ExceptionPoint ExceptionReason
used by	elements WagonDeviationMessage WagonExceptionMessage WagonExceptionReasonMessage
annotation	documentation Specifies the exceptions of a wagon related to a specific location
source	<pre> <xs:element name="WagonExceptionReport"> <xs:annotation> <xs:documentation>Specifies the exceptions of a wagon related to a specific location</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="ExceptionPoint"/> <xs:element ref="ExceptionReason" minOccurs="0" maxOccurs="unbounded"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonInformation**


diagram	<p>WagonInformati... This element shows the unique wagon number together with the transportation units, loaded on the wagon, the used capacity and the weight of the complete load of the ...</p> <p>WagonNumberFreig... Identifies uniquely the freight wagon by its number</p> <p>LoadingStat... Loading status of the equipment. 0=Empty, 1=Loaded</p> <p>TotalWeight... Total weight of the loaded wagon [kg].</p> <p>GoodsInWag... Go...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	WagonNumberFreight LoadingStatus TotalWeight GoodsInWagon
used by	elements WIMO Dataset/ConsignmentLevelData WagonArrivalNoticeMessage WagonDeliveryNoticeMessage WagonDepartureNoticeMessage WagonETI ETA Message WagonExceptionMessage WagonExceptionReasonMessage WagonReleaseNoticeMessage
annotation	documentation This element shows the unique wagon number together with the transportation units, loaded on the wagon, the used capacity and the weight of the complete load of the wagon

source	<pre> <xs:element name="WagonInformation"> <xs:annotation> <xs:documentation>This element shows the unique wagon number together with the transportation units, loaded on the wagon, the used capacity and the weight of the complete load of the wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:element ref="LoadingStatus"/> <xs:element ref="TotalWeight" minOccurs="0"/> <xs:element ref="GoodsInWagon" minOccurs="0" maxOccurs="99"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--------	---

element **WagonLength**


diagram	 <small>Length over buffers in c...</small>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
used by	element Wagons/WagonDetails/WagonTypeDetails									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999999									
annotation	documentation Length over buffers in cms									
source	<pre> <xs:element name="WagonLength"> <xs:annotation> <xs:documentation>Length over buffers in cms</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **WagonLocationStatus**

diagram	 <small>identifies the status of a wagon, related to the actual time at a reporting ...</small>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	RunningStatus
properties	content simple


used by	element ExceptionPoint																																																															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>00</td> <td>documentation Not specified</td> </tr> <tr> <td>enumeration</td> <td>01</td> <td>documentation Arrival at destination</td> </tr> <tr> <td>enumeration</td> <td>02</td> <td>documentation Departure at origin</td> </tr> <tr> <td>enumeration</td> <td>03</td> <td>documentation Intermediate arrival</td> </tr> <tr> <td>enumeration</td> <td>04</td> <td>documentation Intermediate departure</td> </tr> <tr> <td>enumeration</td> <td>05</td> <td>documentation Pass through</td> </tr> <tr> <td>enumeration</td> <td>06</td> <td>documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)</td> </tr> <tr> <td>enumeration</td> <td>07</td> <td></td> </tr> <tr> <td>enumeration</td> <td>08</td> <td></td> </tr> <tr> <td>enumeration</td> <td>09</td> <td></td> </tr> <tr> <td>enumeration</td> <td>10</td> <td>documentation Not specified for wagon</td> </tr> <tr> <td>enumeration</td> <td>11</td> <td>documentation Wagon arrival at its destination by train</td> </tr> <tr> <td>enumeration</td> <td>12</td> <td>documentation Wagon departure from its station of origin by train</td> </tr> <tr> <td>enumeration</td> <td>13</td> <td>documentation Wagon arrival at reporting point by train</td> </tr> <tr> <td>enumeration</td> <td>14</td> <td>documentation Wagon departure from reporting point by train</td> </tr> <tr> <td>enumeration</td> <td>15</td> <td>documentation Wagon run-through at reporting point by train</td> </tr> <tr> <td>enumeration</td> <td>16</td> <td>documentation Wagon parked at reporting point</td> </tr> <tr> <td>enumeration</td> <td>17</td> <td>documentation Wagon shunted at reporting point</td> </tr> <tr> <td>enumeration</td> <td>18</td> <td>documentation Wagon arrived at reporting point</td> </tr> <tr> <td>enumeration</td> <td>19</td> <td>documentation Wagon departure from reporting point</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	00	documentation Not specified	enumeration	01	documentation Arrival at destination	enumeration	02	documentation Departure at origin	enumeration	03	documentation Intermediate arrival	enumeration	04	documentation Intermediate departure	enumeration	05	documentation Pass through	enumeration	06	documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)	enumeration	07		enumeration	08		enumeration	09		enumeration	10	documentation Not specified for wagon	enumeration	11	documentation Wagon arrival at its destination by train	enumeration	12	documentation Wagon departure from its station of origin by train	enumeration	13	documentation Wagon arrival at reporting point by train	enumeration	14	documentation Wagon departure from reporting point by train	enumeration	15	documentation Wagon run-through at reporting point by train	enumeration	16	documentation Wagon parked at reporting point	enumeration	17	documentation Wagon shunted at reporting point	enumeration	18	documentation Wagon arrived at reporting point	enumeration	19	documentation Wagon departure from reporting point
Kind	Value	Annotation																																																														
enumeration	00	documentation Not specified																																																														
enumeration	01	documentation Arrival at destination																																																														
enumeration	02	documentation Departure at origin																																																														
enumeration	03	documentation Intermediate arrival																																																														
enumeration	04	documentation Intermediate departure																																																														
enumeration	05	documentation Pass through																																																														
enumeration	06	documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)																																																														
enumeration	07																																																															
enumeration	08																																																															
enumeration	09																																																															
enumeration	10	documentation Not specified for wagon																																																														
enumeration	11	documentation Wagon arrival at its destination by train																																																														
enumeration	12	documentation Wagon departure from its station of origin by train																																																														
enumeration	13	documentation Wagon arrival at reporting point by train																																																														
enumeration	14	documentation Wagon departure from reporting point by train																																																														
enumeration	15	documentation Wagon run-through at reporting point by train																																																														
enumeration	16	documentation Wagon parked at reporting point																																																														
enumeration	17	documentation Wagon shunted at reporting point																																																														
enumeration	18	documentation Wagon arrived at reporting point																																																														
enumeration	19	documentation Wagon departure from reporting point																																																														
annotation	documentation identifies the status of a wagon, related to the actual time at a reporting point																																																															
source	<pre><xs:element name="WagonLocationStatus" type="RunningStatus"> <xs:annotation> <xs:documentation>identifies the status of a wagon, related to the actual time at a reporting point</xs:documentation> </xs:annotation> </xs:element></pre>																																																															

element **WagonMaxSpeed**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int

properties	content simple									
used by	element WagonOperationalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
annotation	documentation Maximum allowed speed of the wagon according to the load and entry in the Rolling Stock Databases. In kmh									
source	<pre><xs:element name="WagonMaxSpeed"> <xs:annotation> <xs:documentation>Maximum allowed speed of the wagon according to the load and entry in the Rolling Stock Databases. In kmh</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="001"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **WagonNumberFreight**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	WagonIdent									
properties	content simple									
used by	elements RollingStockDataset/AdministrativeDataSet AlertMessage RollingStockDatasetMessage/RefusedWagonNumbers RollingStockDatasetQueryMessage WagonData WagonDeviationMessage WagonInformation Wagons WagonYardArrivalMessage WagonYardDepartureMessage									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{12}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	12		pattern	[0-9]{12}	
Kind	Value	Annotation								
maxLength	12									
pattern	[0-9]{12}									
annotation	documentation Identifies uniquely the freight wagon by its number									
source	<pre><xs:element name="WagonNumberFreight" type="WagonIdent"> <xs:annotation> <xs:documentation>Identifies uniquely the freight wagon by its number</xs:documentation> </xs:annotation> </xs:element></pre>									

element **WagonNumberOfAxes**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:int

properties	content simple									
used by	elements RollingStockDataset/DesignDataSet WagonTechData Wagons/WagonDetails/WagonTypeDetails									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>2</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	2		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	2									
maxInclusive	99									
annotation	documentation Number of Axels for a wagon									
source	<pre><xs:element name="WagonNumberOfAxles"> <xs:annotation> <xs:documentation>Number of Axels for a wagon</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="2"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **WagonOperationalData**



namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	BrakeType BrakeWeight WagonMaxSpeed ExceptionalGaugingProfile ExceptionalGaugingIdent DangerousGoodsDetails InfoOnGoodsShapeTypeDanger RestrictionsDueToLoadOrDamage TotalLoadWeight
used by	element WagonData
annotation	documentation Actual wagon parameters, dependent on load or damage. This group and its elements are optional (contract defines what IM requires). But if there is dangerous goods in the train, then this group is mandatory.
source	<pre> <xs:element name="WagonOperationalData"> <xs:annotation> <xs:documentation>Actual wagon parameters, dependent on load or damage. This group and its elements are optional (contract defines what IM requires). But if there is dangerous goods in the train, then this group is mandatory.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="BrakeType" minOccurs="0"/> <xs:element ref="BrakeWeight" minOccurs="0"/> <xs:element ref="WagonMaxSpeed" minOccurs="0"/> <xs:element ref="ExceptionalGaugingProfile" minOccurs="0"/> <xs:element ref="ExceptionalGaugingIdent" minOccurs="0"/> <xs:element name="DangerousGoodsDetails" minOccurs="0" maxOccurs="99"> <xs:complexType> <xs:sequence> <xs:element ref="DangerousGoodsIndication" minOccurs="0"/> <xs:element name="WeightOfDangerousGoods" minOccurs="0"> <xs:annotation> <xs:documentation>Requested by RID specification, weight in kilograms</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999999"/> <xs:totalDigits value="6"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> <xs:element ref="InfoOnGoodsShapeTypeDanger" minOccurs="0" maxOccurs="9"/> <xs:element ref="RestrictionsDueToLoadOrDamage" minOccurs="0" maxOccurs="9"/> <xs:element ref="TotalLoadWeight" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonOperationalData/DangerousGoodsDetails**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 99 content complex
children	DangerousGoodsIndication WeightOfDangerousGoods
source	<pre><xs:element name="DangerousGoodsDetails" minOccurs="0" maxOccurs="99"> <xs:complexType> <xs:sequence> <xs:element ref="DangerousGoodsIndication" minOccurs="0"/> <xs:element name="WeightOfDangerousGoods" minOccurs="0"> <xs:annotation> <xs:documentation>Requested by RID specification, weight in kilograms</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999999"/> <xs:totalDigits value="6"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element></pre>

element **WagonOperationalData/DangerousGoodsDetails/WeightOfDangerousGoods**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:decimal												
properties	minOcc 0 maxOcc 1 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>totalDigits</td> <td>6</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		totalDigits	6	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
totalDigits	6												
annotation	documentation Requested by RID specification, weight in kilograms												
source	<pre><xs:element name="WeightOfDangerousGoods" minOccurs="0"> <xs:annotation> <xs:documentation>Requested by RID specification, weight in kilograms</xs:documentation> </xs:annotation></pre>												

	<pre> <xs:simpleType> <xs:restriction base="xs:decimal"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999999"/> <xs:totalDigits value="6"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **WagonPickupAtOrigin**

diagram	<p>The diagram shows a class WagonPickupAtOrigin with a description: "Place and Date and Time of when the wagon is ready to be taken over by the RU/Service Provider at the customer sidings". It contains two sub-elements: Location (described as "Identifies a Location using a LocationIdent") and DepartureTimeAtLocation (described as "the scheduled departure date and time at a defined location").</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location DepartureTimeAtLocation
used by	element WagonReleaseNoticeMessage
annotation	documentation Place and Date and Time of when the wagon is ready to be taken over by the RU/Service Provider at the customer sidings
source	<pre> <xs:element name="WagonPickupAtOrigin"> <xs:annotation> <xs:documentation>Place and Date and Time of when the wagon is ready to be taken over by the RU/Service Provider at the customer sidings</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="DepartureTimeAtLocation"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WagonReleaseNoticeMessage**

<p>diagram</p>	<p>WagonReleaseNoticeMessa... This message is used by the Lead RU for the case that the LRU is not the first RU in the Transport chain. It is to inform the RU in charge that the wagon is ready to be pulled.</p> <p>MessageHeader Used for all messa...</p> <p>WagonInformati... This element shows the unique wagon number together with the transportation units, loaded on the wagon, the used capacity and the weight of the complete load of the ...</p> <p>Customers Information about the consignor, consignee and freight payers.</p> <p>WagonPickupAtOrig... Place and Date and Time of when the wagon is ready to be taken over by the RU/Service Provider at the c...</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>MessageHeader WagonInformation Customers WagonPickupAtOrigin</p>
<p>annotation</p>	<p>documentation This message is used by the Lead RU for the case that the LRU is not the first RU in the Transport chain. It is to inform the RU in charge that the wagon is ready to be pulled.</p>
<p>source</p>	<pre><xs:element name="WagonReleaseNoticeMessage"> <xs:annotation> <xs:documentation>This message is used by the Lead RU for the case that the LRU is not the first RU in the Transport chain. It is to inform the RU in charge that the wagon is ready to be pulled.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonInformation"/> <xs:element ref="Customers" minOccurs="0"/> <xs:element ref="WagonPickupAtOrigin"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **Wagons**

<p>diagram</p>	<p>WagonNumberFreight Identifies uniquely the freight wagon by its number</p> <p>WagonDetails Details for the specific wa...</p> <p>SummaryOfGoodsWithSameRID 0..25 This element is only in use if the consignment includes more than one good with the same UN-Number in , packing group and propershipping name in the wagon. The added amount of the dangerous goods are to be stored here</p> <p>LoadingTackles 0..99 Describes the loading tackles used inside the wagon</p> <p>Goods 1..99 Describes the goods inside the means of transport</p> <p>ITU 1..25 Describes the type and content of an IntermodalTransport...</p> <p>RollingRoadUnit 1..5 Describes the type and content of a Rolling road ...</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>WagonNumberFreight WagonDetails SummaryOfGoodsWithSameRID LoadingTackles Goods ITU RollingRoadUnit</p>
<p>used by</p>	<p>element ConsignmentOrderMessage/COMS/COM</p>
<p>annotation</p>	<p>documentation Content of the wagon</p>
<p>source</p>	<pre><xs:element name="Wagons"> <xs:annotation> <xs:documentation>Content of the wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="WagonNumberFreight"/> <xs:sequence> <xs:element name="WagonDetails"> <xs:annotation> <xs:documentation>Details for the specific wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LoadingStatus"/> <xs:element name="WagonInfo" minOccurs="0"> <xs:annotation> <xs:documentation>Additional information, concerning the goods of the whole wagon. </xs:documentation> </xs:annotation> <xs:simpleType></pre>

```

        <xs:restriction base="xs:string">
            <xs:maxLength value="500"/>
            <xs:minLength value="1"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element name="WagonTypeDetails" minOccurs="0">
    <xs:annotation>
        <xs:documentation>These elements are only needed, if the
wagon has to be treated as CUV (empty wagon).</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="WagonWeightEmpty"/>
            <xs:element ref="WagonNumberOfAxles"/>
            <xs:element ref="WagonLength"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element ref="TotalWeight" minOccurs="0"/>
<xs:element name="LoadLimit" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Load limit from table of load limits in
[t].</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:decimal">
            <xs:minInclusive value="0"/>
            <xs:totalDigits value="4"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element ref="Seals" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Describes the seals used for the
consignment</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="Ship" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Additional information for transports,
which shall be handed over to a ship.</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="DeliveryReference" minOccurs="0"/>
<xs:element ref="OriginCountry" minOccurs="0"/>
<xs:element name="ExceptionalConsignment" minOccurs="0"
maxOccurs="10">
    <xs:annotation>
        <xs:documentation>Exceptional
Consignment</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="IM_Partner"/>
            <xs:element name="PermissionNumber">
                <xs:annotation>
                    <xs:documentation>Reference/permission number of the

```

```

exceptional consignment.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1"/>
      <xs:maxLength value="24"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ShuntingModalLabel" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Shunting modal label according to
chapter 5.3.4 RID</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:token">
      <xs:enumeration value="13"/>
      <xs:enumeration value="15"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="ReferenceNumbers" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element ref="SummaryOFGoodsWithSameRID" minOccurs="0"
maxOccurs="25"/>
  <xs:choice>
    <xs:sequence>
      <xs:element ref="LoadingTackles" minOccurs="0" maxOccurs="99"/>
      <xs:element ref="Goods" maxOccurs="99"/>
    </xs:sequence>
    <xs:element ref="ITU" maxOccurs="25"/>
    <xs:element ref="RollingRoadUnit" maxOccurs="5"/>
  </xs:choice>
</xs:sequence>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **Wagons/WagonDetails**

<p>diagram</p>	<p>LoadingStat... Loading status of the equipment. 0=Empty, 1=Loaded</p> <p>WagonIn... Additional information, concerning the goods of the whole wagon.</p> <p>WagonTypeDeta... These elements are only needed, if the wagon has to be treated as CUV (empty wagon).</p> <p>TotalWeight Total weight of the loaded wagon [kg].</p> <p>LoadLimit Load limit from table of load limits in [t].</p> <p>Seals Describes the seals used for the consignment</p> <p>Ship Additional information for transports, which shall be handed over to a ship.</p> <p>DeliveryReference</p> <p>OriginCountry Code of origin country of the UTI.</p> <p>ExceptionalConsignme... 0..10 Exceptional Consignm...</p> <p>ShuntingModallA... Shunting modal label according to chapter 5.3.4 RID</p> <p>ReferenceNumbers This element contains references according to NCTS or EMCS law. This element MUST NOT be e...</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>LoadingStatus WagonInfo WagonTypeDetails TotalWeight LoadLimit Seals Ship DeliveryReference OriginCountry ExceptionalConsignment ShuntingModalLabel ReferenceNumbers</p>
<p>annotation</p>	<p>documentation Details for the specific wagon</p>
<p>source</p>	<pre><xs:element name="WagonDetails"> <xs:annotation> <xs:documentation>Details for the specific wagon</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LoadingStatus"/> <xs:element name="WagonInfo" minOccurs="0"> <xs:annotation> <xs:documentation>Additional information, concerning the goods of the whole wagon. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>


```

        <xs:maxLength value="500"/>
        <xs:minLength value="1"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="WagonTypeDetails" minOccurs="0">
    <xs:annotation>
        <xs:documentation>These elements are only needed, if the wagon has
to be treated as CUV (empty wagon).</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="WagonWeightEmpty"/>
            <xs:element ref="WagonNumberOfAxles"/>
            <xs:element ref="WagonLength"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element ref="TotalWeight" minOccurs="0"/>
<xs:element name="LoadLimit" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Load limit from table of load limits in
[t].</xs:documentation>
    </xs:annotation>
    <xs:simpleType>
        <xs:restriction base="xs:decimal">
            <xs:minInclusive value="0"/>
            <xs:totalDigits value="4"/>
        </xs:restriction>
    </xs:simpleType>
</xs:element>
<xs:element ref="Seals" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Describes the seals used for the
consignment</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="Ship" minOccurs="0">
    <xs:annotation>
        <xs:documentation>Additional information for transports, which
shall be handed over to a ship.</xs:documentation>
    </xs:annotation>
</xs:element>
<xs:element ref="DeliveryReference" minOccurs="0"/>
<xs:element ref="OriginCountry" minOccurs="0"/>
<xs:element name="ExceptionalConsignment" minOccurs="0"
maxOccurs="10">
    <xs:annotation>
        <xs:documentation>Exceptional Consignment</xs:documentation>
    </xs:annotation>
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="IM_Partner"/>
            <xs:element name="PermissionNumber">
                <xs:annotation>
                    <xs:documentation>Reference/permission number of the
exceptional consignment.</xs:documentation>
                </xs:annotation>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>


```

	<pre> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> <xs:element name="ShuntingModalLabel" minOccurs="0"> <xs:annotation> <xs:documentation>Shunting modal label according to chapter 5.3.4 RID</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="13"/> <xs:enumeration value="15"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element ref="ReferenceNumbers" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **Wagons/WagonDetails/WagonInfo**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>500</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	500	
Kind	Value	Annotation								
minLength	1									
maxLength	500									
annotation	documentation Additional information, concerning the goods of the whole wagon.									
source	<pre> <xs:element name="WagonInfo" minOccurs="0"> <xs:annotation> <xs:documentation>Additional information, concerning the goods of the whole wagon. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="500"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Wagons/WagonDetails/WagonTypeDetails**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 1 content complex
children	WagonWeightEmpty WagonNumberOfAxles WagonLength
annotation	documentation These elements are only needed, if the wagon has to be treated as CUV (empty wagon).
source	<pre> <xs:element name="WagonTypeDetails" minOccurs="0"> <xs:annotation> <xs:documentation>These elements are only needed, if the wagon has to be treated as CUV (empty wagon).</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="WagonWeightEmpty"/> <xs:element ref="WagonNumberOfAxles"/> <xs:element ref="WagonLength"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **Wagons/WagonDetails/LoadLimit**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:decimal									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>totalDigits</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		totalDigits	4	
Kind	Value	Annotation								
minInclusive	0									
totalDigits	4									
annotation	documentation Load limit from table of load limits in [t].									
source	<pre> <xs:element name="LoadLimit" minOccurs="0"> <xs:annotation> <xs:documentation>Load limit from table of load limits in [t].</xs:documentation> </xs:annotation> <xs:simpleType> </pre>									

```

<xs:restriction base="xs:decimal">
  <xs:minInclusive value="0"/>
  <xs:totalDigits value="4"/>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **Wagons/WagonDetails/ExceptionalConsignment**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	minOcc 0 maxOcc 10 content complex
children	IM Partner PermissionNumber
annotation	documentation Exceptional Consignment
source	<pre> <xs:element name="ExceptionalConsignment" minOccurs="0" maxOccurs="10"> <xs:annotation> <xs:documentation>Exceptional Consignment</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="IM_Partner"/> <xs:element name="PermissionNumber"> <xs:annotation> <xs:documentation>Reference/permission number of the exceptional consignment.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **Wagons/WagonDetails/ExceptionalConsignment/PermissionNumber**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string

properties	content simple									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>24</td> <td></td> </tr> </table>	Kind	Value	Annotation	minLength	1		maxLength	24	
Kind	Value	Annotation								
minLength	1									
maxLength	24									
annotation	documentation Reference/permission number of the exceptional consignment.									
source	<pre><xs:element name="PermissionNumber"> <xs:annotation> <xs:documentation>Reference/permission number of the exceptional consignment.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="24"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **Wagons/WagonDetails/ShuntingModalLabel**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:token									
properties	<table border="0"> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>enumeration</td> <td>13</td> <td></td> </tr> <tr> <td>enumeration</td> <td>15</td> <td></td> </tr> </table>	Kind	Value	Annotation	enumeration	13		enumeration	15	
Kind	Value	Annotation								
enumeration	13									
enumeration	15									
annotation	documentation Shunting modal label according to chapter 5.3.4 RID									
source	<pre><xs:element name="ShuntingModalLabel" minOccurs="0"> <xs:annotation> <xs:documentation>Shunting modal label according to chapter 5.3.4 RID</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="13"/> <xs:enumeration value="15"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **WagonTechData**


<p>diagram</p>	<p>LengthOverBuffers Length over buffers is expressed in cm.</p> <p>WagonNumberOfAxles Number of Axels for a wa...</p> <p>AirBrakeType Classification of air bra...</p> <p>BrakingPowerVariationDevice Coding in 404-2, chapter ...</p> <p>AirBrakeSpecialCharacteristic Coding in 404-2, chapter ...</p> <p>HandBrakeType Classification of hand br...</p> <p>HandBrakeBrakedWeight Coding in 404-2, chapter ...</p> <p>ParkingBrakeForce Indicates the parking brake force of the hand brake (kN). When the parking brake force is marked on the wagon the information must be provided in the RSRD message.</p> <p>NormalLoadingGauge All codes are defined in the UTC leaflet 505-1 and 503, as well as in the EN 15273-2:2013. For details please refer to EN 15273-2:2013 (Railway applications - Gauges - Part 2: Rolling stock gauge). For the existing gauges in the list, th...</p> <p>CouplingType Classification of coupl...</p> <p>WagonWeightEmpty The weight of an empty wagon according to the entry in the rolling stock d...</p> <p>TechnicalRestrictions 0..6</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>LengthOverBuffers WagonNumberOfAxles AirBrakeType BrakingPowerVariationDevice AirBrakeSpecialCharacteristic HandBrakeType HandBrakeBrakedWeight ParkingBrakeForce NormalLoadingGauge CouplingType WagonWeightEmpty TechnicalRestrictions</p>
<p>used by</p>	<p>element WagonData</p>
<p>annotation</p>	<p>documentation This element shows the wagon relevant technical data for the wagons within a running train</p>
<p>source</p>	<pre><xs:element name="WagonTechData"> <xs:annotation> <xs:documentation>This element shows the wagon relevant technical data for the wagons within a running train</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="LengthOverBuffers"/> <xs:element ref="WagonNumberOfAxles"/> <xs:element ref="AirBrakeType" minOccurs="0"/> <xs:element ref="BrakingPowerVariationDevice" minOccurs="0"/></pre>

```

<xs:element name="AirBrakeSpecialCharacteristic" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Coding in 404-2, chapter 1.8</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:integer">
      <xs:minInclusive value="0"/>
      <xs:maxInclusive value="9"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="HandBrakeType" minOccurs="0"/>
<xs:element name="HandBrakeBrakedWeight" minOccurs="0">
  <xs:annotation>
    <xs:documentation>Coding in 404-2, chapter 1.7 </xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:integer">
      <xs:minInclusive value="000"/>
      <xs:maxInclusive value="999"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="ParkingBrakeForce" minOccurs="0"/>
<xs:element ref="NormalLoadingGauge" minOccurs="0"/>
<xs:element ref="CouplingType" minOccurs="0"/>
<xs:element ref="WagonWeightEmpty"/>
<xs:element name="TechnicalRestrictions" type="Numeric2-2"
minOccurs="0" maxOccurs="6"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

element **WagonTechData/AirBrakeSpecialCharacteristic**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minInclusive 0 maxInclusive 9
annotation	documentation Coding in 404-2, chapter 1.8
source	<pre> <xs:element name="AirBrakeSpecialCharacteristic" minOccurs="0"> <xs:annotation> <xs:documentation>Coding in 404-2, chapter 1.8</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> </pre>

```


<xs:maxInclusive value="9"/>
</xs:restriction>
</xs:simpleType>
</xs:element>

```


element **WagonTechData/HandBrakeBrakedWeight**

diagram	 HandBrakeBrakedWeight Coding in 404-2, chapter ...
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:integer
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minInclusive 000 maxInclusive 999
annotation	documentation Coding in 404-2, chapter 1.7
source	<pre> <xs:element name="HandBrakeBrakedWeight" minOccurs="0"> <xs:annotation> <xs:documentation>Coding in 404-2, chapter 1.7 </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="000"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>


element **WagonTechData/TechnicalRestrictions**

diagram	 TechnicalRestrictions 0..6
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric2-2
properties	minOcc 0 maxOcc 6 content simple
facets	Kind Value Annotation minInclusive 01 maxInclusive 99
source	<pre> <xs:element name="TechnicalRestrictions" type="Numeric2-2" minOccurs="0" maxOccurs="6"/> </pre>

element **WagonTrainPosition**

diagram	 <p>Identifies the position of a wagon within a train. Sequential number starting with the first wagon at the front of train as N°1.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	content simple									
used by	element WagonData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999									
annotation	documentation Identifies the position of a wagon within a train. Sequential number starting with the first wagon at the front of train as N°1.									
source	<pre><xs:element name="WagonTrainPosition"> <xs:annotation> <xs:documentation>Identifies the position of a wagon within a train. Sequential number starting with the first wagon at the front of train as N°1.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									

element **WagonWeightEmpty**

diagram	 <p>The weight of an empty wagon according to the entry in the rolling stock d...</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	WeightValueKilo												
properties	content simple												
used by	elements RollingStockDataset/DesignDataSet WagonTechData Wagons/WagonDetails/WagonTypeDetails												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation The weight of an empty wagon according to the entry in the rolling stock database												
source	<pre><xs:element name="WagonWeightEmpty" type="WeightValueKilo"> <xs:annotation> <xs:documentation>The weight of an empty wagon according to the entry in the rolling stock database</xs:documentation> </xs:annotation></pre>												

	<code></xs:element></code>
--	----------------------------------

element WagonYardArrivalMessage


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonNumberFreight YardArrival
annotation	documentation This message is used by the RU to inform the LRU that the wagon has arrived at its yard.
source	<pre> <xs:element name="WagonYardArrivalMessage"> <xs:annotation> <xs:documentation>This message is used by the RU to inform the LRU that the wagon has arrived at its yard.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonNumberFreight"/> <xs:element ref="YardArrival"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element WagonYardDepartureMessage


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	MessageHeader WagonNumberFreight YardDeparture
annotation	documentation This message is used by the RU/Service Provider to inform the Lead RU that the wagon has left the yard.
source	<pre> <xs:element name="WagonYardDepartureMessage"> <xs:annotation> <xs:documentation>This message is used by the RU/Service Provider to </pre>

	<pre> inform the Lead RU that the wagon has left the yard.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="MessageHeader"/> <xs:element ref="WagonNumberFreight"/> <xs:element ref="YardDeparture"/> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **WeightOfSetOfCarriages**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	WeightValueTonne									
properties	content simple									
used by	element PlannedTrainTechnicalData									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation The calculated maximum weight of all carriages without the traction									
source	<pre> <xs:element name="WeightOfSetOfCarriages" type="WeightValueTonne"> <xs:annotation> <xs:documentation>The calculated maximum weight of all carriages without the traction</xs:documentation> </xs:annotation> </xs:element> </pre>									

element **WheelDiameter**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	9999									
annotation	documentation Diameter of wheels measured in mm. Reference wheel diameter at maximum.									

source	<pre> <xs:element name="WheelDiameter"> <xs:annotation> <xs:documentation>Diameter of wheels measured in mm. Reference wheel diameter at maximum. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--------	--

element **WheelsetGauge**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
used by	element RollingStockDataset/DesignDataSet									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	9999									
annotation	documentation Track Gauge measured in mm; multi-entry for wagons with changeable wheel set gauge									
source	<pre> <xs:element name="WheelsetGauge"> <xs:annotation> <xs:documentation>Track Gauge measured in mm; multi-entry for wagons with changeable wheel set gauge </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **Width**

diagram	
---------	---

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Value Measure
used by	element Dimensions complexType DimensionValue
annotation	documentation Width of ITU
source	<pre> <xs:element name="Width"> <xs:annotation> <xs:documentation>Width of ITU</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Value"/> <xs:element ref="Measure"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **WIMO_Dataset**

diagram	<pre> classDiagram class WIMO_Dataset { ConsignmentLevelData EventLevelData RollingStockDataset } </pre>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	ConsignmentLevelData EventLevelData RollingStockDataset
annotation	documentation Comment describing your root element
source	<pre> <xs:element name="WIMO_Dataset"> <xs:annotation> <xs:documentation>Comment describing your root element</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="ConsignmentLevelData"> <xs:complexType> <xs:sequence> <xs:element ref="Customer" maxOccurs="2"/> <xs:element ref="ConsignmentNumber"/> <xs:element ref="Goods"/> <xs:element ref="AgreedTimeOfDelivery"/> <xs:element ref="Destination"/> <xs:element ref="WagonInformation"/> <xs:element ref="ContractNumber" minOccurs="0"/> <xs:element ref="DangerousGoodsIndication" minOccurs="0"/> <xs:element ref="SpecialTreatments" minOccurs="0"/> <xs:element name="PreviousWagonNumber" type="WagonIdent" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>

```
<xs:element ref="PreviousConsignmentNumber" minOccurs="0"/>
<xs:sequence minOccurs="0">
  <xs:element ref="NextIntermediateDestination"/>
  <xs:element ref="PreviousResponsibleRU"/>
  <xs:element ref="NextResponsibleRU"/>
</xs:sequence>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="EventLevelData">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="WagonEventInformation"/>
      <xs:element ref="VesselIndication" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element ref="RollingStockDataset"/>
</xs:sequence>
</xs:complexType>
</xs:element>
```

element **WIMO_Dataset/ConsignmentLevelData**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>content complex</p>
<p>children</p>	<p>Customer ConsignmentNumber Goods AgreedTimeOfDelivery Destination WagonInformation ContractNumber DangerousGoodsIndication SpecialTreatments PreviousWagonNumber PreviousConsignmentNumber NextIntermediateDestination PreviousResponsibleRU NextResponsibleRU</p>
<p>source</p>	<pre><xs:element name="ConsignmentLevelData"> <xs:complexType> <xs:sequence> <xs:element ref="Customer" maxOccurs="2"/> <xs:element ref="ConsignmentNumber"/> <xs:element ref="Goods"/> <xs:element ref="AgreedTimeOfDelivery"/> <xs:element ref="Destination"/> <xs:element ref="WagonInformation"/> <xs:element ref="ContractNumber" minOccurs="0"/> <xs:element ref="DangerousGoodsIndication" minOccurs="0"/> <xs:element ref="SpecialTreatments" minOccurs="0"/> <xs:element name="PreviousWagonNumber" type="WagonIdent"</pre>

	<pre> minOccurs="0"/> <xs:element ref="PreviousConsignmentNumber" minOccurs="0"/> <xs:sequence minOccurs="0"> <xs:element ref="NextIntermediateDestination"/> <xs:element ref="PreviousResponsibleRU"/> <xs:element ref="NextResponsibleRU"/> </xs:sequence> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **WIMO_Dataset/ConsignmentLevelData/PreviousWagonNumber**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	WagonIdent									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{12}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	12		pattern	[0-9]{12}	
Kind	Value	Annotation								
maxLength	12									
pattern	[0-9]{12}									
source	<pre><xs:element name="PreviousWagonNumber" type="WagonIdent" minOccurs="0"/></pre>									

element **WIMO_Dataset/EventLevelData**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	WagonEventInformation VesselIndication
source	<pre> <xs:element name="EventLevelData"> <xs:complexType> <xs:sequence> <xs:element ref="WagonEventInformation"/> <xs:element ref="VesselIndication" minOccurs="0"/> </xs:sequence> </xs:complexType> </xs:element> </pre>

element **YardArrival**

diagram	<p>The arrival point of a wagon and the Date and Time when the wagon is taken over by the RU/Service P...</p> <p>Identifies a Location using a LocationId</p> <p>The actual arrival date and time at the defined location</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location ArrivalTimeAtLocationActual
used by	element WagonYardArrivalMessage
annotation	documentation The arrival point of a wagon and the Date and Time when the wagon is taken over by the RU/Service Provider
source	<pre><xs:element name="YardArrival"> <xs:annotation> <xs:documentation>The arrival point of a wagon and the Date and Time when the wagon is taken over by the RU/Service Provider</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="ArrivalTimeAtLocationActual"/> </xs:sequence> </xs:complexType> </xs:element></pre>

element **YardDeparture**

diagram	<p>The departure point of a wagon and the Date and Time when the wagon is taken over by the RU/Service Provider</p> <p>Identifies a Location using a LocationId</p> <p>the scheduled departure date and time at a defined location</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	Location DepartureTimeAtLocation
used by	element WagonYardDepartureMessage
annotation	documentation The departure point of a wagon and the Date and Time when the wagon is taken over by the RU/Service Provider
source	<pre><xs:element name="YardDeparture"> <xs:annotation> <xs:documentation>The departure point of a wagon and the Date and Time when the wagon is taken over by the RU/Service Provider</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element ref="Location"/> <xs:element ref="DepartureTimeAtLocation"/> </xs:sequence> </xs:complexType> </xs:element></pre>

	<code></xs:element></code>
--	----------------------------------

complexType **CargoCodeType**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	extension of FreeText									
properties	base FreeText									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	documentation Identification of the Cargo and the nomenclature used									
source	<pre> <xs:complexType name="CargoCodeType"> <xs:annotation> <xs:documentation>Identification of the Cargo and the nomenclature used</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="FreeText"/> </xs:simpleContent> </xs:complexType> </pre>									

complexType **CompositIdentifierOperationalType**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
children	ObjectType Company Core Variant TimetableYear StartDate
used by	elements RelatedTransportOperationalIdentifiers TrainID TransportOperationalIdentifiers


annotation	documentation Used for unique identification of the objects handled in the messages such as train, path, path request or case reference.
source	<pre><xs:complexType name="CompositIdentifierOperationalType"> <xs:annotation> <xs:documentation>Used for unique identification of the objects handled in the messages such as train, path, path request or case reference.</xs:documentation> </xs:annotation> <xs:sequence> <xs:element ref="ObjectType"/> <xs:element ref="Company"/> <xs:element ref="Core"/> <xs:element ref="Variant"/> <xs:element ref="TimetableYear"/> <xs:element ref="StartDate"> <xs:annotation> <xs:documentation>Is only used in the operational phase and refers to the date where the single train will start the train journey</xs:documentation> </xs:annotation> </xs:element> </xs:sequence> </xs:complexType></pre>

complexType **CompositIdentifierPlannedType**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
children	ObjectType Company Core Variant TimetableYear StartDate
used by	elements AssociatedAttachedTrainID PlannedTransportIdentifiers RelatedPlannedTransportIdentifiers
annotation	documentation Used for unique identification of the objects handled in the messages such as train, path, path request or case reference.
source	<pre><xs:complexType name="CompositIdentifierPlannedType"> <xs:annotation></pre>

	<pre> <xs:documentation>Used for unique identification of the objects handled in the messages such as train, path, path request or case reference.</xs:documentation> </xs:annotation> <xs:sequence> <xs:element ref="ObjectType"/> <xs:element ref="Company"/> <xs:element ref="Core"/> <xs:element ref="Variant"/> <xs:element ref="TimetableYear"/> <xs:element ref="StartDate" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>
--	--

complexType **ConsignmentIdent**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	extension of xs:string
properties	base xs:string
used by	elements ConsignmentNumber PreviousConsignmentNumber
annotation	documentation Identifies a waybill by its number and type
source	<pre> <xs:complexType name="ConsignmentIdent"> <xs:annotation> <xs:documentation>Identifies a waybill by its number and type</xs:documentation> </xs:annotation> <xs:simpleContent> <xs:extension base="xs:string"/> </xs:simpleContent> </xs:complexType> </pre>

complexType **CustomerCode**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
children	CountryCodeISO PrimaryCode AdditionalCode
used by	element Customer
annotation	documentation Identifies the railway customer
source	<pre> <xs:complexType name="CustomerCode"> <xs:annotation> <xs:documentation>Identifies the railway customer</xs:documentation> </pre>

	<pre> </xs:annotation> <xs:sequence> <xs:element ref="CountryCodeISO"/> <xs:element name="PrimaryCode" type="String1-14"/> <xs:element name="AdditionalCode" type="String1-7" minOccurs="0"/> </xs:sequence> </xs:complexType> </pre>
--	---


element **CustomerCode/PrimaryCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	String1-14									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>14</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	14	
Kind	Value	Annotation								
minLength	1									
maxLength	14									
source	<pre><xs:element name="PrimaryCode" type="String1-14"/></pre>									

element **CustomerCode/AdditionalCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	String1-7									
properties	<table border="1"> <tbody> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </tbody> </table>	minOcc	0	maxOcc	1	content	simple			
minOcc	0									
maxOcc	1									
content	simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>7</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	7	
Kind	Value	Annotation								
minLength	1									
maxLength	7									
source	<pre><xs:element name="AdditionalCode" type="String1-7" minOccurs="0"/></pre>									

complexType **DanGoodsType**

<p>diagram</p> 	<p>HazardIdentificationNumber</p> <p>UN Numb...</p> <p>The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1, Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC...</p> <p>DangerLabel</p> <p>0.5</p> <p>All Danger Label of this dangerous good according to the RID chapter 3.2, table A, column 5, excepting the shunting labels Model 13 and 15 (CODE: OTIF RID-Specification).</p> <p>RID_Class</p> <p>The Class of the dangerous good according to the RID chapter 3.2, table A, column 3a.</p> <p>PackingGro...</p> <p>The Packing Group according to the RID chapter 3.2, table A, column 4, Possible values are "I", "II" or "III", otherwise the Packing Group have to be omitted. Mandatory, if it's foreseen in column 4, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC...</p> <p>DangerousGoodsWeig...</p> <p>The weight of the dangerous goods in Kilogr...</p> <p>DangerousGoodsVolu...</p> <p>The volume of the dangerous goods in cubic ...</p> <p>LimitedQuantityIndicator</p> <p>Indicator for labelled dangerous goods in limited quantity according to chapter 3.4 RID</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>children</p>	<p>HazardIdentificationNumber UN_Number DangerLabel RID_Class PackingGroup DangerousGoodsWeight DangerousGoodsVolume LimitedQuantityIndicator</p>
<p>used by</p>	<p>element DangerousGoodsIndication</p>
<p>annotation</p>	<p>documentation This element indicates the type of a dangerous load</p>
<p>source</p>	<pre><xs:complexType name="DanGoodsType"> <xs:annotation> <xs:documentation>This element indicates the type of a dangerous load</xs:documentation> </xs:annotation> <xs:sequence> <xs:element name="HazardIdentificationNumber" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element></pre>


```

<xs:element name="UN_Number" minOccurs="0">
  <xs:annotation>
    <xs:documentation>The UNNumber of the dangerous good according to
the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a
declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY
RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING"
.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:length value="4"/>
      <xs:pattern value="\d*[1-9]\d*" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="DangerLabel" minOccurs="0" maxOccurs="5" />
<xs:element name="RID_Class" minOccurs="0">
  <xs:annotation>
    <xs:documentation>The Class of the dangerous good according to the
RID chapter 3.2, table A, column 3a.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:minLength value="1" />
      <xs:maxLength value="4" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element ref="PackingGroup" minOccurs="0" />
<xs:element ref="DangerousGoodsWeight" minOccurs="0">
  <xs:annotation>
    <xs:documentation>The weight of the dangerous goods in
Kilograms</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="DangerousGoodsVolume" type="VolumeValue"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>The volume of the dangerous goods in cubic
meters</xs:documentation>
  </xs:annotation>
</xs:element>
<xs:element name="LimitedQuantityIndicator" type="xs:boolean"
minOccurs="0">
  <xs:annotation>
    <xs:documentation>Indicator for labelled dangerous goods in limited
quantity according to chapter 3.-4 RID</xs:documentation>
  </xs:annotation>
</xs:element>
</xs:sequence>
</xs:complexType>

```


element **DanGoodsType/HazardIdentificationNumber**

diagram




namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation minLength 2 maxLength 4
source	<pre><xs:element name="HazardIdentificationNumber" minOccurs="0"> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **DanGoodsType/UN_Number**


diagram	 <p>The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC..."</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
used by	element SummaryOfGoodsWithSameRID
facets	Kind Value Annotation length 4 pattern \d*[1-9]\d*
annotation	documentation The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE <=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING".
source	<pre><xs:element name="UN_Number" minOccurs="0"> <xs:annotation> <xs:documentation>The UNNumber of the dangerous good according to the RID chapter 3.2, table A, column 1. Mandatory, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING" .</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:length value="4"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType></pre>

	<code></xs:element></code>
--	----------------------------------


element **DanGoodsType/RID_Class**

diagram	 <p>The Class of the dangerous good according to the RID chapter 3.2, table A, column 3a.</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	minOcc 0 maxOcc 1 content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	4	
Kind	Value	Annotation								
minLength	1									
maxLength	4									
annotation	documentation The Class of the dangerous good according to the RID chapter 3.2, table A, column 3a.									
source	<pre><xs:element name="RID_Class" minOccurs="0"> <xs:annotation> <xs:documentation>The Class of the dangerous good according to the RID chapter 3.2, table A, column 3a.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType> </xs:element></pre>									


element **DanGoodsType/DangerousGoodsVolume**

diagram	 <p>The volume of the dangerous goods in cubic ...</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	VolumeValue
properties	minOcc 0 maxOcc 1 content simple
used by	element SummaryOfGoodsWithSameRID
annotation	documentation The volume of the dangerous goods in cubic meters
source	<pre><xs:element name="DangerousGoodsVolume" type="VolumeValue" minOccurs="0"> <xs:annotation> <xs:documentation>The volume of the dangerous goods in cubic meters</xs:documentation> </xs:annotation> </xs:element></pre>

element **DanGoodsType/LimitedQuantityIndicator**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Indicator for labelled dangerous goods in limited quantity according to chapter 3.-4 RID
source	<pre><xs:element name="LimitedQuantityIndicator" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation>Indicator for labelled dangerous goods in limited quantity according to chapter 3.-4 RID</xs:documentation> </xs:annotation> </xs:element></pre>

complexType **DimensionValue**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
children	Length Height Width
annotation	documentation Measurement Values of Length, Height and Width
source	<pre><xs:complexType name="DimensionValue"> <xs:annotation> <xs:documentation>Measurement Values of Length, Height and Width</xs:documentation> </xs:annotation> <xs:sequence> <xs:element ref="Length"/> <xs:element ref="Height"/> <xs:element ref="Width"/> </xs:sequence> </xs:complexType></pre>

complexType **LocationIdent**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>children</p>	<p>CountryCodeISO LocationPrimaryCode PrimaryLocationName LocationSubsidiaryIdentification</p>
<p>used by</p>	<p>elements</p> <p>TrainRunningData/Activities/ActivityLocationIdent ArrivalTrackAtLocation DelayLocation DepartureJourneyTrack DepartureTrackAtLocation Destination ConsignmentOrderMessage/COMS/COM/RU Declarations/DifferentAcceptance/DifferentAcceptancePoint ConsignmentOrderMessage/COMS/COM/ChargingSections/End EndLocation AffectedSection/EndOfSection IntermediateDestination JourneySectionDestination JourneySectionOrigin Location LocationActualTrack LocationPlannedTrack NetworkProjectedLocation/NextLocation Notes/NoteLocationIdent ConsignmentOrderMessage/COMS/COM/PrepaymentInstructions/PaidUpTo TrainInformation/PathPlanningReferenceLocation PlannedJourneyLocation ConsignmentOrderMessage/COMS/COM/Carriers/SectionFrom ConsignmentOrderMessage/COMS/COM/Carriers/SectionTo ConsignmentOrderMessage/COMS/COM/ChargingSections/Start StartLocation AffectedSection/StartOfSection Station TrainReadyMessage/TrainLocation TransferPoint</p>
<p>annotation</p>	<p>documentation</p> <p>Indication of the Railway or Customer Location</p>
<p>source</p>	<pre><xs:complexType name="LocationIdent"> <xs:annotation> <xs:documentation>Indication of the Railway or Customer Location</xs:documentation> </xs:annotation> <xs:sequence> <xs:element ref="CountryCodeISO"/> <xs:element ref="LocationPrimaryCode"/> <xs:element ref="PrimaryLocationName" minOccurs="0"/> <xs:element ref="LocationSubsidiaryIdentification" minOccurs="0"/> </xs:sequence> </xs:complexType></pre>

complexType **TrainActivityType**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
children	TrainActivityType AssociatedAttachedTrainID AssociatedAttachedOTN AssociatedAttachedTrainServiceNumber AssociatedAttachedTimingAtLocation FreeTextField
used by	element TrainActivity
source	<pre><xs:complexType name="TrainActivityType"> <xs:sequence> <xs:element ref="TrainActivityType"/> <xs:element ref="AssociatedAttachedTrainID" minOccurs="0"/> <xs:element ref="AssociatedAttachedOTN" minOccurs="0"/> <xs:element ref="AssociatedAttachedTrainServiceNumber" minOccurs="0"/> <xs:element ref="AssociatedAttachedTimingAtLocation" minOccurs="0"/> <xs:element ref="FreeTextField" minOccurs="0"/> </xs:sequence> </xs:complexType></pre>

complexType **WagonTelematics**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
children	TelematicsOnBoard TelematicsDevice
used by	element RollingStockDataset/DesignDataSet/WagonTelematics
source	<pre><xs:complexType name="WagonTelematics"> <xs:sequence> <xs:element name="TelematicsOnBoard" type="xs:boolean"> <xs:annotation> <xs:documentation xml:lang="en">Indication if wagon is equipped with a telematics device.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="TelematicsDevice" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation xml:lang="en">Detailed information about a specific telematics device.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DeviceType"> <xs:annotation> <xs:documentation xml:lang="en">Specification of type of telematics device.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Telematics Unit"/> <xs:enumeration value="Sensor"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </xs:sequence> </xs:complexType></pre>

```


</xs:simpleType>
</xs:element>
<xs:element name="ComponentMounted" minOccurs="0">
  <xs:annotation>
    <xs:documentation xml:lang="en">Indication of the component to
    which the telematics unit is attached.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="Superstructure"/>
      <xs:enumeration value="Tank"/>
      <xs:enumeration value="End wall"/>
      <xs:enumeration value="Side wall"/>
      <xs:enumeration value="Marking plate"/>
      <xs:enumeration value="Frame"/>
      <xs:enumeration value="Headstock"/>
      <xs:enumeration value="Saddle plate"/>
      <xs:enumeration value="Longitudinal beam"/>
      <xs:enumeration value="Latitudinal beam"/>
      <xs:enumeration value="Hitch"/>
      <xs:enumeration value="Bogie"/>
      <xs:enumeration value="Axle"/>
      <xs:enumeration value="Axle box"/>
      <xs:enumeration value="Lift off protection"/>
      <xs:enumeration value="Brake system"/>
      <xs:enumeration value="Brake blocks"/>
      <xs:enumeration value="Air pipes"/>
      <xs:enumeration value="Brake valves"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="MountedPosition" minOccurs="0"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation xml:lang="en">Indication of where the
    telematics unit is located on the component.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="Side"/>
      <xs:enumeration value="Top"/>
      <xs:enumeration value="Bottom"/>
      <xs:enumeration value="Inside"/>
      <xs:enumeration value="Left"/>
      <xs:enumeration value="Right"/>
      <xs:enumeration value="Center"/>
      <xs:enumeration value="Below isolation"/>
      <xs:enumeration value="Hand brake end"/>
      <xs:enumeration value="Non brake end"/>
      <xs:enumeration value="1"/>
      <xs:enumeration value="2"/>
      <xs:enumeration value="3"/>
      <xs:enumeration value="4"/>
      <xs:enumeration value="5"/>
      <xs:enumeration value="6"/>
      <xs:enumeration value="7"/>
      <xs:enumeration value="8"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

```

```

        </xs:simpleType>
    </xs:element>
    <xs:element name="ManufacturerName" minOccurs="0">
        <xs:annotation>
            <xs:documentation xml:lang="en">Name of the manufacturer of
the telematics device.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
            <xs:restriction base="xs:string">
                <xs:maxLength value="255"/>
            </xs:restriction>
        </xs:simpleType>
    </xs:element>
    <xs:element name="ATEXCertified" type="xs:boolean" minOccurs="0">
        <xs:annotation>
            <xs:documentation xml:lang="en">Indication if the telematics
device is ATEX certified.</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="ATEXLevel" minOccurs="0" maxOccurs="2">
        <xs:annotation>
            <xs:documentation xml:lang="en">Indication of ATEX level (gas
and dust if applicable) based on ATEX/IECEX standard; e.g.: II 2G Ex ib IIB
T4 Gb or II 2D Ex ib IIIC T135°C Db.</xs:documentation>
        </xs:annotation>
        <xs:simpleType>
            <xs:restriction base="xs:string">
                <xs:maxLength value="50"/>
            </xs:restriction>
        </xs:simpleType>
    </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
</xs:complexType>
    
```

element **WagonTelematics/TelematicsOnBoard**

diagram	 <p>Indication if wagon is equipped with a telematics device.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean
properties	content simple
annotation	documentation Indication if wagon is equipped with a telematics device.
source	<pre> <xs:element name="TelematicsOnBoard" type="xs:boolean"> <xs:annotation> <xs:documentation xml:lang="en">Indication if wagon is equipped with a telematics device.</xs:documentation> </xs:annotation> </xs:element> </pre>

element **WagonTelematics/TelematicsDevice**

<p>diagram</p>	<p>TelematicsDevice 0..∞ Detailed information about a specific telematics device.</p> <p>DeviceType 1 Specification of type of telematics device.</p> <p>ComponentMounted 1 Indication of the component to which the telematics unit is attached.</p> <p>MountedPosition 0..∞ Indication of where the telematics unit is located on the component.</p> <p>ManufacturerName 1 Name of the manufacturer of the telematics device.</p> <p>ATEXCertified 1 Indication if the telematics device is ATEX certified.</p> <p>ATEXLevel 0..2 Indication of ATEX level (gas and dust if applicable) based on ATEX/IECEX standard; e.g.: II 2G Ex ib IIB T4 Gb or II 2D Ex ib I...</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>properties</p>	<p>minOcc 0 maxOcc unbounded content complex</p>
<p>children</p>	<p>DeviceType ComponentMounted MountedPosition ManufacturerName ATEXCertified ATEXLevel</p>
<p>annotation</p>	<p>documentation Detailed information about a specific telematics device.</p>
<p>source</p>	<pre><xs:element name="TelematicsDevice" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation xml:lang="en">Detailed information about a specific telematics device.</xs:documentation> </xs:annotation> <xs:complexType> <xs:sequence> <xs:element name="DeviceType"> <xs:annotation> <xs:documentation xml:lang="en">Specification of type of telematics device.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Telematics Unit"/> <xs:enumeration value="Sensor"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ComponentMounted" minOccurs="0"> <xs:annotation> <xs:documentation xml:lang="en">Indication of the component to which the telematics unit is attached.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"></pre>


```

<xs:enumeration value="Superstructure"/>
<xs:enumeration value="Tank"/>
<xs:enumeration value="End wall"/>
<xs:enumeration value="Side wall"/>
<xs:enumeration value="Marking plate"/>
<xs:enumeration value="Frame"/>
<xs:enumeration value="Headstock"/>
<xs:enumeration value="Saddle plate"/>
<xs:enumeration value="Longitudinal beam"/>
<xs:enumeration value="Latitudinal beam"/>
<xs:enumeration value="Hitch"/>
<xs:enumeration value="Bogie"/>
<xs:enumeration value="Axle"/>
<xs:enumeration value="Axle box"/>
<xs:enumeration value="Lift off protection"/>
<xs:enumeration value="Brake system"/>
<xs:enumeration value="Brake blocks"/>
<xs:enumeration value="Air pipes"/>
<xs:enumeration value="Brake valves"/>
</xs:restriction>
</xs:simpleType>
</xs:element>
<xs:element name="MountedPosition" minOccurs="0"
maxOccurs="unbounded">
  <xs:annotation>
    <xs:documentation xml:lang="en">Indication of where the telematics
unit is located on the component.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="Side"/>
      <xs:enumeration value="Top"/>
      <xs:enumeration value="Bottom"/>
      <xs:enumeration value="Inside"/>
      <xs:enumeration value="Left"/>
      <xs:enumeration value="Right"/>
      <xs:enumeration value="Center"/>
      <xs:enumeration value="Below isolation"/>
      <xs:enumeration value="Hand brake end"/>
      <xs:enumeration value="Non brake end"/>
      <xs:enumeration value="1"/>
      <xs:enumeration value="2"/>
      <xs:enumeration value="3"/>
      <xs:enumeration value="4"/>
      <xs:enumeration value="5"/>
      <xs:enumeration value="6"/>
      <xs:enumeration value="7"/>
      <xs:enumeration value="8"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
<xs:element name="ManufacturerName" minOccurs="0">
  <xs:annotation>
    <xs:documentation xml:lang="en">Name of the manufacturer of the
telematics device.</xs:documentation>
  </xs:annotation>
  <xs:simpleType>
    <xs:restriction base="xs:string">


```


	<pre> <xs:maxLength value="255"/> </xs:restriction> </xs:simpleType> </xs:element> <xs:element name="ATEXCertified" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation xml:lang="en">Indication if the telematics device is ATEX certified.</xs:documentation> </xs:annotation> </xs:element> <xs:element name="ATEXLevel" minOccurs="0" maxOccurs="2"> <xs:annotation> <xs:documentation xml:lang="en">Indication of ATEX level (gas and dust if applicable) based on ATEX/IECEX standard; e.g.: II 2G Ex ib IIB T4 Gb or II 2D Ex ib IIIC T135°C Db.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="50"/> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--

element **WagonTelematics/TelematicsDevice/DeviceType**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	content simple									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>enumeration</td> <td>Telematics Unit</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Sensor</td> <td></td> </tr> </table>	Kind	Value	Annotation	enumeration	Telematics Unit		enumeration	Sensor	
Kind	Value	Annotation								
enumeration	Telematics Unit									
enumeration	Sensor									
annotation	documentation Specification of type of telematics device.									
source	<pre> <xs:element name="DeviceType"> <xs:annotation> <xs:documentation xml:lang="en">Specification of type of telematics device.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Telematics Unit"/> <xs:enumeration value="Sensor"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									


element **WagonTelematics/TelematicsDevice/ComponentMounted**

diagram																																																													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																												
type	restriction of xs:string																																																												
properties	minOcc 0 maxOcc 1 content simple																																																												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>Superstructure</td><td></td></tr> <tr><td>enumeration</td><td>Tank</td><td></td></tr> <tr><td>enumeration</td><td>End wall</td><td></td></tr> <tr><td>enumeration</td><td>Side wall</td><td></td></tr> <tr><td>enumeration</td><td>Marking plate</td><td></td></tr> <tr><td>enumeration</td><td>Frame</td><td></td></tr> <tr><td>enumeration</td><td>Headstock</td><td></td></tr> <tr><td>enumeration</td><td>Saddle plate</td><td></td></tr> <tr><td>enumeration</td><td>Longitudinal beam</td><td></td></tr> <tr><td>enumeration</td><td>Latitudinal beam</td><td></td></tr> <tr><td>enumeration</td><td>Hitch</td><td></td></tr> <tr><td>enumeration</td><td>Bogie</td><td></td></tr> <tr><td>enumeration</td><td>Axle</td><td></td></tr> <tr><td>enumeration</td><td>Axle box</td><td></td></tr> <tr><td>enumeration</td><td>Lift off protection</td><td></td></tr> <tr><td>enumeration</td><td>Brake system</td><td></td></tr> <tr><td>enumeration</td><td>Brake blocks</td><td></td></tr> <tr><td>enumeration</td><td>Air pipes</td><td></td></tr> <tr><td>enumeration</td><td>Brake valves</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	Superstructure		enumeration	Tank		enumeration	End wall		enumeration	Side wall		enumeration	Marking plate		enumeration	Frame		enumeration	Headstock		enumeration	Saddle plate		enumeration	Longitudinal beam		enumeration	Latitudinal beam		enumeration	Hitch		enumeration	Bogie		enumeration	Axle		enumeration	Axle box		enumeration	Lift off protection		enumeration	Brake system		enumeration	Brake blocks		enumeration	Air pipes		enumeration	Brake valves	
Kind	Value	Annotation																																																											
enumeration	Superstructure																																																												
enumeration	Tank																																																												
enumeration	End wall																																																												
enumeration	Side wall																																																												
enumeration	Marking plate																																																												
enumeration	Frame																																																												
enumeration	Headstock																																																												
enumeration	Saddle plate																																																												
enumeration	Longitudinal beam																																																												
enumeration	Latitudinal beam																																																												
enumeration	Hitch																																																												
enumeration	Bogie																																																												
enumeration	Axle																																																												
enumeration	Axle box																																																												
enumeration	Lift off protection																																																												
enumeration	Brake system																																																												
enumeration	Brake blocks																																																												
enumeration	Air pipes																																																												
enumeration	Brake valves																																																												
annotation	documentation Indication of the component to which the telematics unit is attached.																																																												
source	<pre> <xs:element name="ComponentMounted" minOccurs="0"> <xs:annotation> <xs:documentation xml:lang="en">Indication of the component to which the telematics unit is attached.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Superstructure"/> <xs:enumeration value="Tank"/> <xs:enumeration value="End wall"/> <xs:enumeration value="Side wall"/> <xs:enumeration value="Marking plate"/> <xs:enumeration value="Frame"/> <xs:enumeration value="Headstock"/> <xs:enumeration value="Saddle plate"/> <xs:enumeration value="Longitudinal beam"/> <xs:enumeration value="Latitudinal beam"/> <xs:enumeration value="Hitch"/> <xs:enumeration value="Bogie"/> <xs:enumeration value="Axle"/> <xs:enumeration value="Axle box"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>																																																												

```


<xs:enumeration value="Lift off protection"/>
<xs:enumeration value="Brake system"/>
<xs:enumeration value="Brake blocks"/>
<xs:enumeration value="Air pipes"/>
<xs:enumeration value="Brake valves"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **WagonTelematics/TelematicsDevice/MountedPosition**


diagram																																																										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																									
type	restriction of xs:string																																																									
properties	minOcc 0 maxOcc unbounded content simple																																																									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>Side</td><td></td></tr> <tr><td>enumeration</td><td>Top</td><td></td></tr> <tr><td>enumeration</td><td>Bottom</td><td></td></tr> <tr><td>enumeration</td><td>Inside</td><td></td></tr> <tr><td>enumeration</td><td>Left</td><td></td></tr> <tr><td>enumeration</td><td>Right</td><td></td></tr> <tr><td>enumeration</td><td>Center</td><td></td></tr> <tr><td>enumeration</td><td>Below isolation</td><td></td></tr> <tr><td>enumeration</td><td>Hand brake end</td><td></td></tr> <tr><td>enumeration</td><td>Non brake end</td><td></td></tr> <tr><td>enumeration</td><td>1</td><td></td></tr> <tr><td>enumeration</td><td>2</td><td></td></tr> <tr><td>enumeration</td><td>3</td><td></td></tr> <tr><td>enumeration</td><td>4</td><td></td></tr> <tr><td>enumeration</td><td>5</td><td></td></tr> <tr><td>enumeration</td><td>6</td><td></td></tr> <tr><td>enumeration</td><td>7</td><td></td></tr> <tr><td>enumeration</td><td>8</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	Side		enumeration	Top		enumeration	Bottom		enumeration	Inside		enumeration	Left		enumeration	Right		enumeration	Center		enumeration	Below isolation		enumeration	Hand brake end		enumeration	Non brake end		enumeration	1		enumeration	2		enumeration	3		enumeration	4		enumeration	5		enumeration	6		enumeration	7		enumeration	8	
Kind	Value	Annotation																																																								
enumeration	Side																																																									
enumeration	Top																																																									
enumeration	Bottom																																																									
enumeration	Inside																																																									
enumeration	Left																																																									
enumeration	Right																																																									
enumeration	Center																																																									
enumeration	Below isolation																																																									
enumeration	Hand brake end																																																									
enumeration	Non brake end																																																									
enumeration	1																																																									
enumeration	2																																																									
enumeration	3																																																									
enumeration	4																																																									
enumeration	5																																																									
enumeration	6																																																									
enumeration	7																																																									
enumeration	8																																																									
annotation	documentation Indication of where the telematics unit is located on the component.																																																									
source	<pre> <xs:element name="MountedPosition" minOccurs="0" maxOccurs="unbounded"> <xs:annotation> <xs:documentation xml:lang="en">Indication of where the telematics unit is located on the component.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:enumeration value="Side"/> <xs:enumeration value="Top"/> <xs:enumeration value="Bottom"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>																																																									

	<pre> <xs:enumeration value="Inside"/> <xs:enumeration value="Left"/> <xs:enumeration value="Right"/> <xs:enumeration value="Center"/> <xs:enumeration value="Below isolation"/> <xs:enumeration value="Hand brake end"/> <xs:enumeration value="Non brake end"/> <xs:enumeration value="1"/> <xs:enumeration value="2"/> <xs:enumeration value="3"/> <xs:enumeration value="4"/> <xs:enumeration value="5"/> <xs:enumeration value="6"/> <xs:enumeration value="7"/> <xs:enumeration value="8"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **WagonTelematics/TelematicsDevice/ManufacturerName**


diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation maxLength 255
annotation	documentation Name of the manufacturer of the telematics device.
source	<pre> <xs:element name="ManufacturerName" minOccurs="0"> <xs:annotation> <xs:documentation xml:lang="en">Name of the manufacturer of the telematics device.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="255"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **WagonTelematics/TelematicsDevice/ATEXCertified**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:boolean

properties	minOcc 0 maxOcc 1 content simple
annotation	documentation Indication if the telematics device is ATEX certified.
source	<pre><xs:element name="ATEXCertified" type="xs:boolean" minOccurs="0"> <xs:annotation> <xs:documentation xml:lang="en">Indication if the telematics device is ATEX certified.</xs:documentation> </xs:annotation> </xs:element></pre>

element **WagonTelematics/TelematicsDevice/ATEXLevel**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 2 content simple
facets	Kind Value Annotation maxLength 50
annotation	documentation Indication of ATEX level (gas and dust if applicable) based on ATEX/IECEX standard; e.g.: II 2G Ex ib IIB T4 Gb or II 2D Ex ib IIIC T135°C Db.
source	<pre><xs:element name="ATEXLevel" minOccurs="0" maxOccurs="2"> <xs:annotation> <xs:documentation xml:lang="en">Indication of ATEX level (gas and dust if applicable) based on ATEX/IECEX standard; e.g.: II 2G Ex ib IIB T4 Gb or II 2D Ex ib IIIC T135°C Db.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:maxLength value="50"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

simpleType **CommunicationRefID**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	base xs:string
used by	elements Customers/Contacts/Email eMail Customers/Contacts/FaxNumber FaxNumber Customers/Contacts/PhoneNumber PhoneNumber TrainContactDetails
facets	Kind Value Annotation minLength 1 maxLength 70

annotation	documentation Identifier for communications contact reference (i.e. fax number, phone number, e-mail, URL)
source	<pre><xs:simpleType name="CommunicationRefID"> <xs:annotation> <xs:documentation>Identifier for communications contact reference (i.e. fax number, phone number, e-mail, URL)</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:maxLength value="70"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType></pre>

simpleType **CompanyCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of String4-4												
properties	base String4-4												
used by	<p>elements</p> <ul style="list-style-type: none"> AllocationCompany ConsignmentOrderMessage/COMS/COM/AcceptancePoint/CarrierCode ConsignmentOrderMessage/COMS/COM/CommercialSpecifications/CarrierCode ConsignmentOrderMessage/COMS/COM/Carriers/CarrierCode ConsignmentOrderMessage/COMS/COM/LeadCarrier/CarrierCode Company CoordinatingIM ConsignmentOrderMessage/COMS/COM/RU_Declarations/RU_Declaration/DeclaringRU IM Partner ImpactedRU ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicingCarrierCode LeadRU NextResponsibleRU PreviousResponsibleRU ConsignmentOrderMessage/COMS/COM/CustomsData/PrincipalRU ConsignmentOrderMessage/COMS/COM_Header/ReceivingRU Recipient ResponsibleApplicant ConsignmentOrderMessage/COMS/COM/Carriers/ResponsibleCarrierCode ResponsibleIM ResponsibleRU RU Partner ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicedSection/SectionCarrierCode Sender ConsignmentOrderMessage/COMS/COM_Header/SendingRU TransfereeIM 												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9A-Z]{4}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4		pattern	[0-9A-Z]{4}	
Kind	Value	Annotation											
minLength	4												
maxLength	4												
pattern	[0-9A-Z]{4}												
annotation	documentation Identifies the RU, IM or other company involved in the Rail Transport Chain												
source	<pre><xs:simpleType name="CompanyCode"> <xs:annotation> <xs:documentation>Identifies the RU, IM or other company involved in the Rail Transport Chain</xs:documentation> </xs:annotation> <xs:restriction base="String4-4"> <xs:pattern value="[0-9A-Z]{4}"/> </xs:restriction> </xs:simpleType></pre>												

simpleType **CountryIdentISO**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
-----------	---

type	restriction of xs:string
properties	base xs:string
used by	element Customers/Country s ConsignmentOrderMessage/COMS/COM/SectionalInvoicing/Section/InvoicedSection/CountryCode ConsignmentOrderMessage/COMS/COM/Carriers/CountryCode ConsignmentOrderMessage/COMS/COM/LeadCarrier/CountryCode CountryCodeISO ITU_Details/DepartureCountry RollingStockDataset/DesignDataSet/LoadTable/LoadTableCountry RollingStockDataset/AdministrativeDataSet/MultilateralAuthorisationCountries OriginCountry RollingStockDataset/AdministrativeDataSet/QuieterRoutesExemptionCountry RollingStockDataset/AdministrativeDataSet/RegistrationCountry UltimateDestinationCountry
facets	Kind Value Annotation minLength 2 maxLength 2
annotation	documentation ISO 3166-1 alpha code (2 positions)
source	<pre> <xs:simpleType name="CountryIdentISO"> <xs:annotation> <xs:documentation>ISO 3166-1 alpha code (2 positions)</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="2"/> <xs:maxLength value="2"/> </xs:restriction> </xs:simpleType> </pre>

simpleType **CurrencyCode_Type**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	base xs:string
used by	elements ConsignmentOrderMessage/COMS/COM/DeclarationOfValue/CurrencyCode ConsignmentOrderMessage/COMS/COM/InterestInDelivery/CurrencyCode ConsignmentOrderMessage/COMS/COM/CashOnDelivery/CurrencyCode ConsignmentOrderMessage/COMS/COM/ChargingSections/CurrencyCode
facets	Kind Value Annotation pattern [A-Z][A-Z][A-Z]
annotation	documentation CODE: ISO Currency code (ISO-4217)
source	<pre> <xs:simpleType name="CurrencyCode_Type"> <xs:annotation> <xs:documentation>CODE: ISO Currency code (ISO-4217)</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="[A-Z][A-Z][A-Z]"/> </xs:restriction> </xs:simpleType> </pre>

simpleType **DeltaTime**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string

properties	base xs:string
used by	elements AgainstBooked AgainstReferenced
facets	Kind Value Annotation length 5
annotation	documentation Time difference delay (+) or ahead of schedule (-) this shall be 1character + 4 Numeric
source	<pre><xs:simpleType name="DeltaTime"> <xs:annotation> <xs:documentation>Time difference delay (+) or ahead of schedule (-) this shall be 1character + 4 Numeric</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:length value="5"/> </xs:restriction> </xs:simpleType></pre>

simpleType **DerailmentDetectionDevice**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	base xs:string
used by	element RollingStockDataset/DesignDataSet/DerailmentDetectionDevice
facets	Kind Value Annotation enumeration EDT 101 enumeration MDV 100 enumeration Non coded device
annotation	documentation Identification of derailment detection device equipped on the wagon. Element is mandatory if wagon is equipped with such device. The following values are defined: EDT 101 MDV 100 Non coded device
source	<pre><xs:simpleType name="DerailmentDetectionDevice"> <xs:annotation> <xs:documentation>Identification of derailment detection device equipped on the wagon. Element is mandatory if wagon is equipped with such device. The following values are defined: EDT 101 MDV 100 Non coded device </xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="EDT 101"/> <xs:enumeration value="MDV 100"/> <xs:enumeration value="Non coded device"/> </xs:restriction> </xs:simpleType></pre>

simpleType EquipmentNumberType

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	elements GoodsInWagon/ContainerNumber ITU Details/Number									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>13</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	13	
Kind	Value	Annotation								
minLength	1									
maxLength	13									
annotation	documentation Number of ITU									
source	<pre><xs:simpleType name="EquipmentNumberType"> <xs:annotation> <xs:documentation>Number of ITU</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="13"/> </xs:restriction> </xs:simpleType></pre>									

simpleType EquipmentTypeType

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:token												
properties	base xs:token												
used by	element ITU Type												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>cn</td> <td>documentation Container</td> </tr> <tr> <td>enumeration</td> <td>sw</td> <td>documentation swap body</td> </tr> <tr> <td>enumeration</td> <td>te</td> <td>documentation Trailer (RollingRoad)</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	cn	documentation Container	enumeration	sw	documentation swap body	enumeration	te	documentation Trailer (RollingRoad)
Kind	Value	Annotation											
enumeration	cn	documentation Container											
enumeration	sw	documentation swap body											
enumeration	te	documentation Trailer (RollingRoad)											
annotation	documentation Type of equipment												
source	<pre><xs:simpleType name="EquipmentTypeType"> <xs:annotation> <xs:documentation>Type of equipment</xs:documentation> </xs:annotation> <xs:restriction base="xs:token"> <xs:enumeration value="cn"> <xs:annotation> <xs:documentation>Container</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="sw"> <xs:annotation> <xs:documentation>swap body</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="te"> <xs:annotation></pre>												

	<pre> <xs:documentation>Trailer (RollingRoad)</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>
--	---

simpleType **ForwardingRestrictionType**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																									
type	restriction of xs:token																																																									
properties	base xs:token																																																									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>07</td><td></td></tr> <tr><td>enumeration</td><td>08</td><td></td></tr> <tr><td>enumeration</td><td>09</td><td></td></tr> <tr><td>enumeration</td><td>11</td><td></td></tr> <tr><td>enumeration</td><td>12</td><td></td></tr> <tr><td>enumeration</td><td>13</td><td></td></tr> <tr><td>enumeration</td><td>15</td><td></td></tr> <tr><td>enumeration</td><td>16</td><td></td></tr> <tr><td>enumeration</td><td>41</td><td></td></tr> <tr><td>enumeration</td><td>42</td><td></td></tr> <tr><td>enumeration</td><td>61</td><td></td></tr> <tr><td>enumeration</td><td>62</td><td></td></tr> <tr><td>enumeration</td><td>63</td><td></td></tr> <tr><td>enumeration</td><td>70</td><td></td></tr> <tr><td>enumeration</td><td>71</td><td></td></tr> <tr><td>enumeration</td><td>92</td><td></td></tr> <tr><td>enumeration</td><td>94</td><td></td></tr> <tr><td>enumeration</td><td></td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	07		enumeration	08		enumeration	09		enumeration	11		enumeration	12		enumeration	13		enumeration	15		enumeration	16		enumeration	41		enumeration	42		enumeration	61		enumeration	62		enumeration	63		enumeration	70		enumeration	71		enumeration	92		enumeration	94		enumeration		
Kind	Value	Annotation																																																								
enumeration	07																																																									
enumeration	08																																																									
enumeration	09																																																									
enumeration	11																																																									
enumeration	12																																																									
enumeration	13																																																									
enumeration	15																																																									
enumeration	16																																																									
enumeration	41																																																									
enumeration	42																																																									
enumeration	61																																																									
enumeration	62																																																									
enumeration	63																																																									
enumeration	70																																																									
enumeration	71																																																									
enumeration	92																																																									
enumeration	94																																																									
enumeration																																																										
annotation	documentation Code List Candidate: This code is designed to identify any special aspects or restrictions which might be relevant to wagon handling operations in train formation yards or in trains because of technical feature of the wagon or its load																																																									
source	<pre> <xs:simpleType name="ForwardingRestrictionType"> <xs:annotation> <xs:documentation>Code List Candidate: This code is designed to identify any special aspects or restrictions which might be relevant to wagon handling operations in train formation yards or in trains because of technical feature of the wagon or its load</xs:documentation> </xs:annotation> <xs:restriction base="xs:token"> <xs:enumeration value="07"/> <xs:enumeration value="08"/> <xs:enumeration value="09"/> <xs:enumeration value="11"/> <xs:enumeration value="12"/> <xs:enumeration value="13"/> <xs:enumeration value="15"/> <xs:enumeration value="16"/> <xs:enumeration value="41"/> <xs:enumeration value="42"/> </xs:restriction> </xs:simpleType> </pre>																																																									

	<pre> <xs:enumeration value="61"/> <xs:enumeration value="62"/> <xs:enumeration value="63"/> <xs:enumeration value="70"/> <xs:enumeration value="71"/> <xs:enumeration value="92"/> <xs:enumeration value="94"/> <xs:enumeration value=""/> </xs:restriction> </xs:simpleType> </pre>
--	---

simpleType **FreeText**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	<p>elements AdditionalInstruction Address Comments ContractNumberMovement InterruptionPoint/DetailedDescriptionOfLocation FreeTextField GoodsDescription HandlingInstruction InternalReferencelIdentifier InterruptionDescription LocationSubsidiaryName MessageIdentifier ErrorMessage/ErrorCauseReference/MessageSenderReference Name Notes/Note PrimaryLocationName RelatedIdentifier RelatedSenderReference Remarks RouteInformation SenderReference TrainReadyMessage/TrainReadyStatus/TrainNotReadyDescription TransportInstruction NetworkSpecificParameter/Value</p> <p>complexType CargoCodeType</p>									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>255</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	255	
Kind	Value	Annotation								
minLength	1									
maxLength	255									
annotation	<p>documentation</p> <p>Clear Text in ISO Unicode character set</p>									
source	<pre> <xs:simpleType name="FreeText"> <xs:annotation> <xs:documentation>Clear Text in ISO Unicode character set</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:maxLength value="255"/> <xs:minLength value="1"/> </xs:restriction> </xs:simpleType> </pre>									

simpleType **LoadUnitNumberType**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>11</td> <td></td> </tr> <tr> <td>pattern</td> <td>[A-Za-z0-9]{11}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	11		pattern	[A-Za-z0-9]{11}	
Kind	Value	Annotation								
length	11									
pattern	[A-Za-z0-9]{11}									
annotation	<p>documentation</p> <p>Clear Text in ISO Unicode character set</p>									
source	<pre> <xs:simpleType name="LoadUnitNumberType"> </pre>									

	<pre> <xs:annotation> <xs:documentation>Clear Text in ISO Unicode character set</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:length value="11"/> <xs:pattern value="[A-Za-z0-9]{11}"/> </xs:restriction> </xs:simpleType> </pre>
--	---

simpleType **Money_Type**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:decimal									
properties	base xs:decimal									
used by	elements <ul style="list-style-type: none"> ConsignmentOrderMessage/COMS/COM/DeclarationOfValue/Amount ConsignmentOrderMessage/COMS/COM/InterestInDelivery/Amount ConsignmentOrderMessage/COMS/COM/CashOnDelivery/Amount ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/FreightCharges/Prepaid ConsignmentOrderMessage/COMS/COM/ChargingSections/AdditionalCharges/Prepaid ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/FreightCharges/Transferred ConsignmentOrderMessage/COMS/COM/ChargingSections/AdditionalCharges/Transferred 									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>18</td> <td></td> </tr> <tr> <td>fractionDigits</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	18		fractionDigits	2	
Kind	Value	Annotation								
totalDigits	18									
fractionDigits	2									
annotation	documentation Type for all payments									
source	<pre> <xs:simpleType name="Money_Type"> <xs:annotation> <xs:documentation>Type for all payments</xs:documentation> </xs:annotation> <xs:restriction base="xs:decimal"> <xs:totalDigits value="18"/> <xs:fractionDigits value="2"/> </xs:restriction> </xs:simpleType> </pre>									

simpleType **Name**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3						
type	restriction of xs:string						
properties	base xs:string						
used by	element VesselName						
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>254</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	254	
Kind	Value	Annotation					
maxLength	254						
annotation	documentation Name in Free Text						
source	<pre> <xs:simpleType name="Name"> <xs:annotation> <xs:documentation>Name in Free Text</xs:documentation> </xs:annotation> </pre>						

	<pre><xs:restriction base="xs:string"> <xs:maxLength value="254"/> </xs:restriction> </xs:simpleType></pre>
--	---

simpleType **NHMCodeType**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	elements NHM Code ConsignmentOrderMessage/COMS/COM/ChargingSections/Tariff/NHMCode Goods/PreviousLoadedGood									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>6</td> <td></td> </tr> <tr> <td>pattern</td> <td>\d*[1-9]\d*</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	length	6		pattern	\d*[1-9]\d*	
Kind	Value	Annotation								
length	6									
pattern	\d*[1-9]\d*									
annotation	documentation NHM Code									
source	<pre><xs:simpleType name="NHMCodeType"> <xs:annotation> <xs:documentation>NHM Code</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:length value="6"/> <xs:pattern value="\d*[1-9]\d*" /> </xs:restriction> </xs:simpleType></pre>									

simpleType **Numeric1-5**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:positiveInteger									
properties	base xs:positiveInteger									
used by	elements RollingStockDataset/DesignDataSet/BogiePivotPitch RollingStockDataset/DesignDataSet/HeightOfLoadingPlaneUnladen RollingStockDataset/DesignDataSet/InnerWheelbase LocationPrimaryCode RollingStockDataset/DesignDataSet/LoadTable/SpeedCategory									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
source	<pre><xs:simpleType name="Numeric1-5"> <xs:restriction base="xs:positiveInteger"> <xs:minInclusive value="1"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType></pre>									

simpleType **Numeric1-6**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
-----------	---

type	restriction of xs:int									
properties	base xs:int									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	999999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	999999									
source	<pre><xs:simpleType name="Numeric1-6"> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> <xs:maxInclusive value="999999"/> </xs:restriction> </xs:simpleType></pre>									

simpleType **Numeric2-2**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	base xs:integer									
used by	<table border="1"> <thead> <tr> <th>elements</th> <th>attribute</th> </tr> </thead> <tbody> <tr> <td> RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/CounterAccreditedRecognizedBody RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/EINYear MessageRoutingID RollingStockDataset/DesignDataSet/RemovableAccessories/NumberOfAccessorOfSpecType AirBrake/NumberOfBrakes WagonTechData/TechnicalRestrictions RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/TypeDocumentEIN </td> <td> CI InstanceNumber </td> </tr> </tbody> </table>	elements	attribute	RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/CounterAccreditedRecognizedBody RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/EINYear MessageRoutingID RollingStockDataset/DesignDataSet/RemovableAccessories/NumberOfAccessorOfSpecType AirBrake/NumberOfBrakes WagonTechData/TechnicalRestrictions RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/TypeDocumentEIN	CI InstanceNumber					
elements	attribute									
RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/CounterAccreditedRecognizedBody RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/EINYear MessageRoutingID RollingStockDataset/DesignDataSet/RemovableAccessories/NumberOfAccessorOfSpecType AirBrake/NumberOfBrakes WagonTechData/TechnicalRestrictions RollingStockDataset/AdministrativeDataSet/ECMCertificate/EINNumber/TypeDocumentEIN	CI InstanceNumber									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
source	<pre><xs:simpleType name="Numeric2-2"> <xs:restriction base="xs:integer"> <xs:minInclusive value="01"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType></pre>									

simpleType **Numeric3-3**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	base xs:integer									
used by	<table border="1"> <thead> <tr> <th>elements</th> <th>simpleType</th> </tr> </thead> <tbody> <tr> <td> AirBrake/LoadChangeDevice/AirBrakedMassLoaded AirBrake/LoadChangeDevice/ChangeOverWeight </td> <td> Speed </td> </tr> </tbody> </table>	elements	simpleType	AirBrake/LoadChangeDevice/AirBrakedMassLoaded AirBrake/LoadChangeDevice/ChangeOverWeight	Speed					
elements	simpleType									
AirBrake/LoadChangeDevice/AirBrakedMassLoaded AirBrake/LoadChangeDevice/ChangeOverWeight	Speed									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
source	<pre><xs:simpleType name="Numeric3-3"> <xs:restriction base="xs:integer"> <xs:minInclusive value="001"/> </xs:restriction> </xs:simpleType></pre>									

```
<xs:maxInclusive value="999"/>
</xs:restriction>
</xs:simpleType>
```

simpleType Numeric4-4

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	base xs:integer									
used by	elements LengthOfSetOfCarriages RollingStockDataset/DesignDataSet/LoadTable/LoadTableProduct/ProductUNCode TrainLength									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0001		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	0001									
maxInclusive	9999									
source	<pre><xs:simpleType name="Numeric4-4"> <xs:restriction base="xs:integer"> <xs:minInclusive value="0001"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType></pre>									

simpleType Percentage

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:float									
properties	base xs:float									
used by	element NetworkProjectedLocation/ProportionOfDistanceBetweenLocations									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>100</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	100	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	100									
annotation	documentation decimal value between 0 and 100									
source	<pre><xs:simpleType name="Percentage"> <xs:annotation> <xs:documentation>decimal value between 0 and 100</xs:documentation> </xs:annotation> <xs:restriction base="xs:float"> <xs:minInclusive value="0"/> <xs:maxInclusive value="100"/> </xs:restriction> </xs:simpleType></pre>									

simpleType Speed

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	Numeric3-3
properties	base Numeric3-3

used by	elements GNSS DynamicPosition/CurrentSpeed HighestPlannedSpeed PlannedSpeed TrainMaxSpeed									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>001</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	001		maxInclusive	999	
Kind	Value	Annotation								
minInclusive	001									
maxInclusive	999									
annotation	documentation Shown in Km/h									
source	<pre><xs:simpleType name="Speed"> <xs:annotation> <xs:documentation>Shown in Km/h</xs:documentation> </xs:annotation> <xs:restriction base="Numeric3-3"/> </xs:simpleType></pre>									

simpleType **String1-10**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	element LocationSubsidiaryCode									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>10</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	10	
Kind	Value	Annotation								
minLength	1									
maxLength	10									
source	<pre><xs:simpleType name="String1-10"> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="10" fixed="false"/> </xs:restriction> </xs:simpleType></pre>									

simpleType **String1-14**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	element CustomerCode/PrimaryCode									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>14</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	14	
Kind	Value	Annotation								
minLength	1									
maxLength	14									
source	<pre><xs:simpleType name="String1-14"> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="14"/> </xs:restriction> </xs:simpleType></pre>									

simpleType String1-5

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	element DelayMinutes									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>5</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	5	
Kind	Value	Annotation								
minLength	1									
maxLength	5									
source	<pre><xs:simpleType name="String1-5"> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType></pre>									

simpleType String1-7

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	element CustomerCode/AdditionalCode									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>7</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	7	
Kind	Value	Annotation								
minLength	1									
maxLength	7									
source	<pre><xs:simpleType name="String1-7"> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="7"/> </xs:restriction> </xs:simpleType></pre>									

simpleType String1-8

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	elements AssociatedAttachedOTN AssociatedAttachedTrainServiceNumber OperationalTrainNumber									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>8</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	8	
Kind	Value	Annotation								
minLength	1									
maxLength	8									
source	<pre><xs:simpleType name="String1-8"> <xs:restriction base="xs:string"> <xs:minLength value="1"/> <xs:maxLength value="8"/> </xs:restriction> </xs:simpleType></pre>									

simpleType String4-4

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	simpleType CompanyCode									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>4</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	4		maxLength	4	
Kind	Value	Annotation								
minLength	4									
maxLength	4									
source	<pre><xs:simpleType name="String4-4"> <xs:restriction base="xs:string"> <xs:minLength value="4"/> <xs:maxLength value="4"/> </xs:restriction> </xs:simpleType></pre>									

simpleType String5-5

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>5</td> <td></td> </tr> <tr> <td>maxLength</td> <td>5</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	5		maxLength	5	
Kind	Value	Annotation								
minLength	5									
maxLength	5									
source	<pre><xs:simpleType name="String5-5"> <xs:restriction base="xs:string"> <xs:minLength value="5"/> <xs:maxLength value="5"/> </xs:restriction> </xs:simpleType></pre>									

simpleType String5-8

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>5</td> <td></td> </tr> <tr> <td>maxLength</td> <td>8</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minLength	5		maxLength	8	
Kind	Value	Annotation								
minLength	5									
maxLength	8									
source	<pre><xs:simpleType name="String5-8"> <xs:restriction base="xs:string"> <xs:minLength value="5"/> <xs:maxLength value="8"/> </xs:restriction> </xs:simpleType></pre>									

simpleType Time

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:time
properties	base xs:time
annotation	documentation Time expressed in HH:MM:SS
source	<pre><xs:simpleType name="Time"> <xs:annotation> <xs:documentation>Time expressed in HH:MM:SS</xs:documentation> </xs:annotation> <xs:restriction base="xs:time"/> </xs:simpleType></pre>

simpleType VolumeValue

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	xs:float
properties	base xs:float
used by	elements DangerousGoodsVolume DanGoodsType/DangerousGoodsVolume Volume
annotation	documentation Volume value of the load units by cbm
source	<pre><xs:simpleType name="VolumeValue"> <xs:annotation> <xs:documentation>Volume value of the load units by cbm</xs:documentation> </xs:annotation> <xs:restriction base="xs:float"/> </xs:simpleType></pre>

simpleType WagonIdent

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
used by	elements WIMO Dataset/ConsignmentLevelData/PreviousWagonNumber RollingStockDataset/AdministrativeDataSet/PreviousWagonNumberFreight WagonNumberFreight ConsignmentOrderMessage/COMS/COM/WagonPreviousNumberFreight									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>pattern</td> <td>[0-9]{12}</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	maxLength	12		pattern	[0-9]{12}	
Kind	Value	Annotation								
maxLength	12									
pattern	[0-9]{12}									
annotation	documentation Identification code of a freight wagon based on the TSI OPE and CEN Recommendations and CIS wagons coded according to OSJD-UIC leaflet 402, which allows the conversion from 8 digits to 12 digits and viceversa.									
source	<pre><xs:simpleType name="WagonIdent"> <xs:annotation> <xs:documentation>Identification code of a freight wagon based on the TSI OPE and CEN Recommendations and CIS wagons coded according to OSJD-UIC leaflet 402, which allows the conversion from 8 digits to 12 digits and</pre>									

	<pre> viceversa.</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:maxLength value="12"/> <xs:pattern value="[0-9]{12}"/> </xs:restriction> </xs:simpleType> </pre>
--	---

simpleType **WeightValueKilo**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:integer												
properties	base xs:integer												
used by	elements DangerousGoodsWeight GrossWeight MaxGrossWeight ITU_Details/TareWeight RollingRoadUnit/RollingRoadUnitDetails/TareWeightVehicle TotalLoadWeight TotalWeight LoadingTackles/TotalWeightLoadingTackles WagonWeightEmpty												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>999999</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>collapse</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	999999		whiteSpace	collapse	
Kind	Value	Annotation											
minInclusive	0												
maxInclusive	999999												
whiteSpace	collapse												
annotation	documentation In Kilograms												
source	<pre> <xs:simpleType name="WeightValueKilo"> <xs:annotation> <xs:documentation>In Kilograms</xs:documentation> </xs:annotation> <xs:restriction base="xs:integer"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999999"/> <xs:whiteSpace value="collapse"/> </xs:restriction> </xs:simpleType> </pre>												

simpleType **WeightValueTonne**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:int									
properties	base xs:int									
used by	elements TractionWeight TrainWeight WeightOfSetOfCarriages									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	99999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	99999									
annotation	documentation In Tonnes									
source	<pre> <xs:simpleType name="WeightValueTonne"> <xs:annotation> <xs:documentation>In Tonnes</xs:documentation> </xs:annotation> <xs:restriction base="xs:int"> <xs:minInclusive value="1"/> </xs:restriction> </xs:simpleType> </pre>									

```
<xs:maxInclusive value="99999"/>
</xs:restriction>
</xs:simpleType>
```

attribute **CI_InstanceNumber**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	Numeric2-2									
used by	elements Recipient Sender									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>01</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	01		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	01									
maxInclusive	99									
annotation	documentation Number of a Common Interface Instance for the same Company									
source	<pre><xs:attribute name="CI_InstanceNumber" type="Numeric2-2"> <xs:annotation> <xs:documentation>Number of a Common Interface Instance for the same Company</xs:documentation> </xs:annotation> </xs:attribute></pre>									

3. Schema taf_cat_codelists.xsd

schema location: [taf_cat_codelists.xsd](#)
 attributeFormDefault: **unqualified**
 elementFormDefault: **qualified**
 targetNamespace: <http://www.era.europa.eu/schemes/TAFTSI/3.3>

Elements

[AirBrakeType](#)
[BrakeSpecialCharacteristics](#)
[BrakeType](#)
[BrakingPowerVariationDevice](#)
[CodeOfCause](#)
[CombinedTrafficLoadProfile](#)
[CommercialSpecificationCode](#)
[ConsignmentOrderType](#)
[ConsignorDeclarationCode](#)
[CouplingType](#)
[CustomerType](#)
[DangerLabel](#)
[EmptyPackingCode](#)
[HandBrakeType](#)
[ILU_TypeDetail](#)
[IncotermCode](#)
[InfoOnGoodsShapeTypeDanger](#)

Simple types


[ConsignmentTypeCode](#)
[DelayCode](#)
[InfoIndex](#)
[MessageCode](#)
[RestrictionCodes](#)
[RunningStatus](#)
[TrainCC_SystemCode](#)
[TypeOfIMHarmonizationCode](#)
[TypeOfInformationCode](#)
[TypeOfRequestCode](#)
[TypeOfRUHarmonizationCode](#)
[UnitType](#)

Attributes

[LocationSubsidiaryTypeCode](#)
[TimingQualifierCode](#)

- [InteropCapability](#)
- [JourneyLocationTypeCode](#)
- [LivestockOrPeopleIndicator](#)
- [LoadTableStars](#)
- [MessageStatus](#)
- [MRN Type](#)
- [NormalLoadingGauge](#)
- [PackingGroup](#)
- [PrepaidCodeCarrier](#)
- [PrepaidCodeCustomer](#)
- [ProcessType](#)
- [ReasonOfReference](#)
- [RefusalCode](#)
- [RollingRoadUnitType](#)
- [RouteClass](#)
- [RU DeclarationCode](#)
- [TractionMode](#)
- [TractionType](#)
- [TrainRadioSystem](#)
- [TrainRunningInterruptionStatus](#)
- [TrainType](#)
- [TypeOfRemovableAccessories](#)
- [TypeOfUsedHybridPowerunit](#)
- [WheelSetTransformationMethod](#)

element **AirBrakeType**


diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content simple		
facets	Kind	Value	Annotation
	enumeration	0	documentation Through pipe
	enumeration	1	documentation G system only
	enumeration	2	documentation P system only
	enumeration	3	documentation G/P combined system
	enumeration	8	documentation No air brake or brake pipe
	enumeration	9	documentation Non coded system
annotation	documentation Classification of air brake.		
source	<pre><xs:element name="AirBrakeType"> <xs:annotation></pre>		

```

<xs:documentation>Classification of air brake.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:token">
    <xs:enumeration value="0">
      <xs:annotation>
        <xs:documentation>Through pipe</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="1">
      <xs:annotation>
        <xs:documentation>G system only</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="2">
      <xs:annotation>
        <xs:documentation>P system only</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="3">
      <xs:annotation>
        <xs:documentation>G/P combined system</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="8">
      <xs:annotation>
        <xs:documentation>No air brake or brake pipe</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="9">
      <xs:annotation>
        <xs:documentation>Non coded system</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
  </xs:restriction>
</xs:simpleType>
</xs:element>

```

element **BrakeSpecialCharacteristics**


diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	0	documentation Cast Iron Brake Blocks
	enumeration	1	documentation Disc Brake
	enumeration	2	documentation K-Brake Blocks
	enumeration	3	documentation

	<p>enumeration 4 Cast Iron Brake Blocks, single release brake documentation</p> <p>enumeration 5 Composite Brake Blocks, single release brake documentation</p> <p>enumeration 6 L-Brake Blocks documentation</p> <p>enumeration 9 LL-Brake Blocks documentation</p> <p>Unknown or non-coded information</p>
<p>annotation</p>	<p>documentation</p> <p>General brake characteristics. The values refer to UIC leaflet 920-13.</p>
<p>source</p>	<pre> <xs:element name="BrakeSpecialCharacteristics"> <xs:annotation> <xs:documentation> General brake characteristics. The values refer to UIC leaflet 920-13. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>Cast Iron Brake Blocks</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Disc Brake</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>K-Brake Blocks</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Cast Iron Brake Blocks, single release brake</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Composite Brake Blocks, single release brake</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>L-Brake Blocks</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="6"> <xs:annotation> <xs:documentation>LL-Brake Blocks</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>


```

<xs:enumeration value="9">
  <xs:annotation>
    <xs:documentation>Unknown or non-coded
information</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **BrakeType**

diagram																																																	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																
type	restriction of xs:token																																																
properties	content simple																																																
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td>documentation G: "Goods" for freight services with slow application and release times</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation P: "Passenger" for passenger and freight services with quick application and release times.</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation X: an indication that brake system of the freight wagon out of order (actually / current). Additionally, X cannot be used in Planning.</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation R: a subdivision brake position of brake mode "P", for rapid (express) services with high brake performances</td> </tr> <tr> <td>enumeration</td> <td>4</td> <td>documentation G+E: brake position G with additional brake=electro-dynamic brake</td> </tr> <tr> <td>enumeration</td> <td>5</td> <td>documentation G+H: brake position G with additional brake=hydro-dynamic brake</td> </tr> <tr> <td>enumeration</td> <td>6</td> <td>documentation P+E: brake position P with additional brake=electro-dynamic brake</td> </tr> <tr> <td>enumeration</td> <td>7</td> <td>documentation P+H: brake position P with additional brake=hydro-dynamic brake</td> </tr> <tr> <td>enumeration</td> <td>8</td> <td>documentation P+Mg: brake position P with additional brake=magnetic track brake</td> </tr> <tr> <td>enumeration</td> <td>9</td> <td>documentation R+E: brake position R with additional brake=electro-dynamic brake</td> </tr> <tr> <td>enumeration</td> <td>10</td> <td>documentation R+H: brake position R with additional brake=hydro-dynamic brake</td> </tr> <tr> <td>enumeration</td> <td>11</td> <td>documentation R+Mg: brake position R with additional brake=magnetic track brake</td> </tr> <tr> <td>enumeration</td> <td>12</td> <td>documentation R+WB: brake position R with additional brake=eddy current brake (German: Wirbelstrombremse)</td> </tr> <tr> <td>enumeration</td> <td>13</td> <td>documentation R+E+Mg: brake position R with additional brake=electro-dynamic brake and magnetic track brake</td> </tr> <tr> <td>enumeration</td> <td>14</td> <td>documentation R+E+WB: brake position R with additional brake=electro-dynamic brake and eddy current brake</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0	documentation G: "Goods" for freight services with slow application and release times	enumeration	1	documentation P: "Passenger" for passenger and freight services with quick application and release times.	enumeration	2	documentation X: an indication that brake system of the freight wagon out of order (actually / current). Additionally, X cannot be used in Planning.	enumeration	3	documentation R: a subdivision brake position of brake mode "P", for rapid (express) services with high brake performances	enumeration	4	documentation G+E: brake position G with additional brake=electro-dynamic brake	enumeration	5	documentation G+H: brake position G with additional brake=hydro-dynamic brake	enumeration	6	documentation P+E: brake position P with additional brake=electro-dynamic brake	enumeration	7	documentation P+H: brake position P with additional brake=hydro-dynamic brake	enumeration	8	documentation P+Mg: brake position P with additional brake=magnetic track brake	enumeration	9	documentation R+E: brake position R with additional brake=electro-dynamic brake	enumeration	10	documentation R+H: brake position R with additional brake=hydro-dynamic brake	enumeration	11	documentation R+Mg: brake position R with additional brake=magnetic track brake	enumeration	12	documentation R+WB: brake position R with additional brake=eddy current brake (German: Wirbelstrombremse)	enumeration	13	documentation R+E+Mg: brake position R with additional brake=electro-dynamic brake and magnetic track brake	enumeration	14	documentation R+E+WB: brake position R with additional brake=electro-dynamic brake and eddy current brake
Kind	Value	Annotation																																															
enumeration	0	documentation G: "Goods" for freight services with slow application and release times																																															
enumeration	1	documentation P: "Passenger" for passenger and freight services with quick application and release times.																																															
enumeration	2	documentation X: an indication that brake system of the freight wagon out of order (actually / current). Additionally, X cannot be used in Planning.																																															
enumeration	3	documentation R: a subdivision brake position of brake mode "P", for rapid (express) services with high brake performances																																															
enumeration	4	documentation G+E: brake position G with additional brake=electro-dynamic brake																																															
enumeration	5	documentation G+H: brake position G with additional brake=hydro-dynamic brake																																															
enumeration	6	documentation P+E: brake position P with additional brake=electro-dynamic brake																																															
enumeration	7	documentation P+H: brake position P with additional brake=hydro-dynamic brake																																															
enumeration	8	documentation P+Mg: brake position P with additional brake=magnetic track brake																																															
enumeration	9	documentation R+E: brake position R with additional brake=electro-dynamic brake																																															
enumeration	10	documentation R+H: brake position R with additional brake=hydro-dynamic brake																																															
enumeration	11	documentation R+Mg: brake position R with additional brake=magnetic track brake																																															
enumeration	12	documentation R+WB: brake position R with additional brake=eddy current brake (German: Wirbelstrombremse)																																															
enumeration	13	documentation R+E+Mg: brake position R with additional brake=electro-dynamic brake and magnetic track brake																																															
enumeration	14	documentation R+E+WB: brake position R with additional brake=electro-dynamic brake and eddy current brake																																															
annotation	documentation Type of braking system.																																																
source	<xs:element name="BrakeType">																																																

```


<xs:annotation>
  <xs:documentation>Type of braking system.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:token">
    <xs:enumeration value="0">
      <xs:annotation>
        <xs:documentation>G: "Goods" for freight services with slow
application and release times</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="1">
      <xs:annotation>
        <xs:documentation>P: "Passenger" for passenger and freight
services with quick application and release times.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="2">
      <xs:annotation>
        <xs:documentation>X: an indication that brake system of the
freight wagon out of order (actually / current). Additionally, X cannot be
used in Planning.</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="3">
      <xs:annotation>
        <xs:documentation>R: a subdivision brake position of brake mode
"P", for rapid (express) services with high brake
performances</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="4">
      <xs:annotation>
        <xs:documentation>G+E: brake position G with additional
brake=electro-dynamic brake</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="5">
      <xs:annotation>
        <xs:documentation>G+H: brake position G with additional
brake=hydro-dynamic brake</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="6">
      <xs:annotation>
        <xs:documentation>P+E: brake position P with additional
brake=electro-dynamic brake</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="7">
      <xs:annotation>
        <xs:documentation>P+H: brake position P with additional
brake=hydro-dynamic brake</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="8">
      <xs:annotation>
        <xs:documentation>P+Mg: brake position P with additional

```

```


brake=magnetic track brake</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9">
  <xs:annotation>
    <xs:documentation>R+E: brake position R with additional
brake=electro-dynamic brake</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>R+H: brake position R with additional
brake=hydro-dynamic brake</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>R+Mg: brake position R with additional
brake=magnetic track brake</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>R+WB: brake position R with additional
brake=eddy current brake (German: Wirbelstrombremse)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>R+E+Mg: brake position R with additional
brake=electro-dynamic brake and magnetic track brake</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>R+E+WB: brake position R with additional
brake=electro-dynamic brake and eddy current brake</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **BrakingPowerVariationDevice**

diagram	 <p>BrakingPowerVariationDevice Coding in 404-2, chapter ...</p>		
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:integer		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	0	documentation no braked weight variation device
	enumeration	1	documentation empty/loaded manual or automatic device with one changeover weight

	<p>enumeration 2 documentation empty/loaded manual or automatic device with two or three changeover weights</p> <p>enumeration 8 documentation linear auto continuous device with indication of maximum braked weight</p> <p>enumeration 9 documentation non-codable variation device</p>
annotation	<p>documentation Coding in 404-2, chapter 1.8</p>
source	<pre> <xs:element name="BrakingPowerVariationDevice"> <xs:annotation> <xs:documentation>Coding in 404-2, chapter 1.8</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>no braked weight variation device</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>empty/loaded manual or automatic device with one changeover weight</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>empty/loaded manual or automatic device with two or three changeover weights</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="8"> <xs:annotation> <xs:documentation>linear auto continuous device with indication of maximum braked weight</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="9"> <xs:annotation> <xs:documentation>non-codable variation device</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **CodeOfCause**

diagram	
namespace	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
type	<p>restriction of xs:token</p>
properties	<p>content simple</p>

facets	Kind	Value	Annotation
	enumeration	1	documentation Completion of formalities required by customs or other administrative authorities (CIM Article 15)
	enumeration	2	documentation Examination of the consignment (CIM Article11)
	enumeration	3	documentation Amendment of the contract of carriage (CIM Article 18)
	enumeration	4	documentation Circumstances preventing carriage (CIM Article 20)
	enumeration	5	documentation Circumstances preventing delivery (CIM Article21)
	enumeration	6	documentation Attention to be given to the consignment
	enumeration	7	documentation Rectification of the load following unsatisfactory loading by the consignor
	enumeration	8	documentation Transshipment following unsatisfactory loading by the consignor
	enumeration	9	documentation Other causes: ...
annotation	documentation Code of reason for extension		
source	<pre data-bbox="300 857 1423 2018"> <xs:element name="CodeOfCause"> <xs:annotation> <xs:documentation>Code of reason for extension</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Completion of formalities required by customs or other administrative authorities (CIM Article 15)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Examination of the consignment (CIM Article11)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Amendment of the contract of carriage (CIM Article 18)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Circumstances preventing carriage (CIM Article 20)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>Circumstances preventing delivery (CIM Article21)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="6"> </pre>		

	<pre> <xs:annotation> <xs:documentation>Attention to be given to the consignment</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="7"> <xs:annotation> <xs:documentation>Rectification of the load following unsatisfactory loading by the consignor</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="8"> <xs:annotation> <xs:documentation>Transhipment following unsatisfactory loading by the consignor</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="9"> <xs:annotation> <xs:documentation>Other causes: ...</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **CombinedTrafficLoadProfile**

diagram	<p>CombinedTrafficLoadProfile</p> <p>This element does refer to combined load units that can be used for Freight Requests only.</p> <p>There are two entry options:</p> <ul style="list-style-type: none"> • One option refers to "P" (Semi-trailer/road semi-trailer); • The other option refers to "C" (Swap body); <p>The RUs may indicate the relevant values if they are familiar with the IMs line profiles. In case there is a path request for a train with combined traffic load, the IM should indicate the possible max. value for all 4 elements (P1, P2, C1, C2). Further information about Combined Traffic Load Profile can be seen in the UIC 596-6 Leaflet.</p> <p>P1 P1 requires the code in case the gauge of the semi-trailer is less or equal 2500 mm.</p> <p>P2 P2 requires the code in case the gauge of the semi-trailer is greater than 2500 mm less or equal 2600 mm</p> <p>C1</p> <p>C2 C2 requires the code in case the gauge of the swap body is greater than 2550 mm less or equal 2600 mm</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	P1 P2 C1 C2
annotation	<p>documentation</p> <p>This element does refer to combined load units that can be used for Freight Requests only.</p> <p>There are two entry options:</p> <ul style="list-style-type: none"> • One option refers to "P" (Semi-trailer/road semi-trailer); • The other option refers to "C" (Swap body); <p>The RUs may indicate the relevant values if they are familiar with the IMs line profiles. In case there is a path request for a train with combined traffic load, the IM should indicate the possible max. value for all 4 elements (P1, P2, C1, C2). Further information about Combined Traffic Load Profile can be seen in the UIC 596-6 Leaflet.</p>
source	<pre> <xs:element name="CombinedTrafficLoadProfile"> <xs:annotation> </pre>


```

<xs:documentation>This element does refer to combined load units that
can be used for Freight Requests only.
There are two entry options:
• One option refers to "P" (Semi-trailer/road semi-trailer):
• The other option refers to "C" (Swap body):
The RUs may indicate the relevant values if they are familiar with the IMs
line profiles. In case there is a path request for a train with combined
traffic load, the IM should indicate the possible max. value for all 4
elements (P1, P2, C1, C2). Further information about Combined Traffic Load
Profile can be seen in the UIC 596-6 Leaflet.
</xs:documentation>
</xs:annotation>
<xs:complexType>
  <xs:sequence>
    <xs:element name="P1" minOccurs="0">
      <xs:annotation>
        <xs:documentation>P1 requires the code in case the gauge of the
semi-trailer is less or equal 2500 mm.</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:pattern value="\d{3}"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="P2" minOccurs="0">
      <xs:annotation>
        <xs:documentation>P2 requires the code in case the gauge of the
semi-trailer is greater than 2500 mm less or equal 2600
mm</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:pattern value="\d{3}"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="C1" minOccurs="0">
      <xs:simpleType>
        <xs:annotation>
          <xs:documentation>C1 requires the code in case the gauge of the
swap body is less or equal 2550 mm.</xs:documentation>
        </xs:annotation>
        <xs:restriction base="xs:string">
          <xs:pattern value="\d{3}"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
    <xs:element name="C2" minOccurs="0">
      <xs:annotation>
        <xs:documentation>C2 requires the code in case the gauge of the
swap body is greater than 2550 mm less or equal 2600 mm</xs:documentation>
      </xs:annotation>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:pattern value="\d{3}"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>


```

	<pre> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	---

element **CombinedTrafficLoadProfile/P1**

diagram	 <p>P1 requires the code in case the gauge of the semi-trailer is less or equal 2500 mm.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation pattern \d{3}
annotation	documentation P1 requires the code in case the gauge of the semi-trailer is less or equal 2500 mm.
source	<pre> <xs:element name="P1" minOccurs="0"> <xs:annotation> <xs:documentation>P1 requires the code in case the gauge of the semi- trailer is less or equal 2500 mm.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:pattern value="\d{3}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **CombinedTrafficLoadProfile/P2**

diagram	 <p>P2 requires the code in case the gauge of the semi-trailer is greater than 2500 mm less or equal 2600 mm.</p>
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation pattern \d{3}
annotation	documentation P2 requires the code in case the gauge of the semi-trailer is greater than 2500 mm less or equal 2600 mm
source	<pre> <xs:element name="P2" minOccurs="0"> <xs:annotation> <xs:documentation>P2 requires the code in case the gauge of the semi- trailer is greater than 2500 mm less or equal 2600 mm</xs:documentation> </xs:annotation> <xs:simpleType> </pre>

	<pre> <xs:restriction base="xs:string"> <xs:pattern value="\d{3}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **CombinedTrafficLoadProfile/C1**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation pattern \d{3}
source	<pre> <xs:element name="C1" minOccurs="0"> <xs:simpleType> <xs:annotation> <xs:documentation>C1 requires the code in case the gauge of the swap body is less or equal 2550 mm.</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:pattern value="\d{3}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **CombinedTrafficLoadProfile/C2**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
type	restriction of xs:string
properties	minOcc 0 maxOcc 1 content simple
facets	Kind Value Annotation pattern \d{3}
annotation	documentation C2 requires the code in case the gauge of the swap body is greater than 2550 mm less or equal 2600 mm
source	<pre> <xs:element name="C2" minOccurs="0"> <xs:annotation> <xs:documentation>C2 requires the code in case the gauge of the swap body is greater than 2550 mm less or equal 2600 mm</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:string"> <xs:pattern value="\d{3}"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>


	<pre></xs:simpleType> </xs:element></pre>
--	---

element **CommercialSpecificationCode**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	1	documentation Route ...
	enumeration	2	documentation Traffic flow ...
	enumeration	3	documentation Carriers mandated to perform the carriage, section, status
	enumeration	4	documentation Defined frontier stations..... (for exceptional consignments)
	enumeration	5	documentation Other conditions requested....(for example: EDI contract number if an electronic consignment note is used.)
annotation	documentation Commercial specifications code		
source	<pre><xs:element name="CommercialSpecificationCode"> <xs:annotation> <xs:documentation>Commercial specifications code</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Route ...</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Traffic flow ...</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Carriers mandated to perform the carriage, section, status</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Defined frontier stations..... (for exceptional consignments)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>Other conditions requested....(for example: EDI</pre>		

	<pre> contract number if an electronic consignment note is used.)</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **ConsignmentOrderType**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content simple		
facets	Kind	Value	Annotation
	enumeration	ECN	documentation ECN: Electronic consignment note. MessageType will be sent up to the interchange point where the transport is handed over to the next carrier involved in the transport (being ECN capable).
	enumeration	NACK	documentation NotAcknowledged. Message is only sent out by the CDS, in case an ECN is received and the next carrier who is to receive this ECN is not ECN-capable
	enumeration	PRN	documentation At the beginning of an ECN transport the shipping carrier sends the prior notification as preannouncement to all participating carriers (as far as they are able to process an ECN)
	enumeration	INFE	documentation Information ECN: This MessageType has only informative character and can be used to inform other participating carriers about changes before hand-over of the ECN.
	enumeration	INFP	documentation Information PCN: This MessageType has only informative character and may only be used to inform other participating carriers about the change from electronic transport to paper accompanied transport.
	enumeration	CANCEL	documentation The CANCEL message can only be send by the lead/contractual or the shipping carrier BEFORE the first hand-over of the ECN. By doing so, all participating carriers will receive a DEL message to inform them about the cancellation of their part of the transport.
	enumeration	DEL	documentation This message is being created by the central application, only. The receiving carrier is being informed, that his part of the transport has been cancelled.
	enumeration	ECTD	documentation Basic message type for transports accompanied by a paper consignment note message.
	enumeration	EUTD	documentation Basic update message type for transports accompanied by a paper consignment note message
	enumeration	EDTD	documentation Basic deletion message type for transports accompanied by a paper consignment note message.
	enumeration	ECOM	documentation Electronic consignment order message for carriers in role 3.Used for paperless


	<p>enumeration ECOU transport only. documentation Update message for ECOM</p> <p>enumeration ECOD documentation Deletion message for ECOM</p>
annotation	<p>documentation Preliminary list of messages, by now restricted on different types of consignment orders. Message types PRN, NACK, ECN, DEL, INFE, INFP, ECOM, ECOD and ECOM are only used in communication within Raildata ECN members.</p>
source	<pre> <xs:element name="ConsignmentOrderType"> <xs:annotation> <xs:documentation>Preliminary list of messages, by now restricted on different types of consignment orders. Message types PRN, NACK, ECN, DEL, INFE, INFP, ECOM, ECOD and ECOM are only used in communication within Raildata ECN members. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="ECN"> <xs:annotation> <xs:documentation>ECN: Electronic consignment note. MessageType will be sent up to the interchange point where the transport is handed over to the next carrier involved in the transport (being ECN capable). </xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="NACK"> <xs:annotation> <xs:documentation>NotAcknowledged. Message is only sent out by the CDS, in case an ECN is received and the next carrier who is to receive this ECN is not ECN-capable</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="PRN"> <xs:annotation> <xs:documentation>At the beginning of an ECN transport the shipping carrier sends the prior notification as preannouncement to all participating carriers (as far as they are able to process an ECN)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="INFE"> <xs:annotation> <xs:documentation>Information ECN: This MessageType has only informative character and can be used to inform other participating carriers about changes before hand-over of the ECN.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="INFP"> <xs:annotation> <xs:documentation>Information PCN: This MessageType has only informative character and may only be used to inform other participating carriers about the change from electronic transport to paper accompanied transport.</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

```

<xs:enumeration value="CANCEL">
  <xs:annotation>
    <xs:documentation>The CANCEL message can only be send by the
lead/contractual or the shipping carrier BEFORE the first hand-over of the
ECN. By doing so, all participating carriers will receive a DEL message to
inform them about the cancellation of their part of the
transport.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DEL">
  <xs:annotation>
    <xs:documentation>This message is being created by the central
application, only. The receiving carrier is being informed, that his part of
the transport has been cancelled.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ECTD">
  <xs:annotation>
    <xs:documentation>Basic message type for transports accompanied by
a paper consignment note message.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="EUTD">
  <xs:annotation>
    <xs:documentation>Basic update message type for transports
accompanied by a paper consignment note message</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="EDTD">
  <xs:annotation>
    <xs:documentation>Basic deletion message type for transports
accompanied by a paper consignment note message.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ECOM">
  <xs:annotation>
    <xs:documentation>Electronic consignment order message for
carriers in role 3.Used for paperless transport only.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ECOU">
  <xs:annotation>
    <xs:documentation>Update message for ECOM</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="ECOD">
  <xs:annotation>
    <xs:documentation>Deletion message for ECOM</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **ConsignorDeclarationCode**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content simple		
facets	Kind	Value	Annotation
	enumeration	1	documentation Consignee not-authorized to take control of the goods
	enumeration	2	documentation Authorised consignee (within the meaning of customs law)
	enumeration	3	documentation Escort(s) ... [name(s), first name(s)]
	enumeration	4	documentation Filled mass [weight]: ... (for tank-wagons refilled without having been cleaned - see RID section 5.4.1.2.2c)
	enumeration	5	documentation Emergency telephone number for irregularities or accidents with dangerous goods
	enumeration	6	documentation Not to be passed to a substitute carrier
	enumeration	7	documentation Loading by the carrier
	enumeration	8	documentation Unloading by the carrier
	enumeration	9	documentation Agreed transit period: ...
	enumeration	10	documentation Completion of administrative formalities: ... (see CIM Article 15)
	enumeration	11	documentation Exceptional consignment: ... (reference number for each of the rail carriers/infrastructure managers involved)
	enumeration	12	documentation Number of flat pallets marked "EUR" and exchangeable in the European Pallet Pool
	enumeration	13	documentation Number of box-pallets marked "EUR" and exchangeable in the European Box-Pallet Pool
	enumeration	14	documentation If the carrier's wagon sheets are used: number of sheets, abbreviation for the carrier and wagon sheet number(s)
	enumeration	15	documentation If the carrier's straps are used: number of straps and abbreviation for the carrier
	enumeration	16	documentation Other declarations: ... (designation of a representative, designation of a substitute carrier, request for attention to be given to the consignment en route, etc.)
	enumeration	17	documentation Shipment details for port traffic: ...
	enumeration	18	documentation Used for CUV transports, only. Restrictions on the operation of the wagon known to the consignor (e.g. limited speed, etc.)
	enumeration	24	documentation Dangerous goods packed in limited quantities the total gross mass of which exceeds eight tonnes per transport unit.
	enumeration	25	documentation Wagon keeper according to article 17 AVV (Name)
	enumeration	31	documentation CH import declaration by DB Cargo
	enumeration	32	documentation CH import declaration by SBB Cargo
	enumeration	33	documentation CH import declaration by third parties

annotation	documentation Carrier declaration code.
source	<pre> <xs:element name="ConsignorDeclarationCode"> <xs:annotation> <xs:documentation>Carrier declaration code.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Consignee not-authorized to take control of the goods</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Authorized consignee (within the meaning of customs law)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Escort(s) ... [name(s), first name(s)]</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Filled mass [weight]: ... (for tank-wagons refilled without having been cleaned - see RID section 5.4.1.2.2c)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>Emergency telephone number for irregularities or accidents with dangerous goods</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="6"> <xs:annotation> <xs:documentation>Not to be passed to a substitute carrier</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="7"> <xs:annotation> <xs:documentation>Loading by the carrier</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="8"> <xs:annotation> <xs:documentation>Unloading by the carrier</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="9"> <xs:annotation> </pre>

```

    <xs:documentation>Agreed transit period: ...</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>Completion of administrative formalities: ...
(see CIM Article 15)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>Exceptional consignment: ... (reference number
for each of the rail carriers/infrastructure managers
involved)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>Number of flat pallets marked "EUR" and
exchangeable in the European Pallet Pool</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>Number of box-pallets marked "EUR" and
exchangeable in the European Box-Pallet Pool</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>If the carrier's wagon sheets are used: number
of sheets, abbreviation for the carrier and wagon sheet
number(s)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>If the carrier's straps are used: number of
straps and abbreviation for the carrier</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>Other declarations: ... (designation of a
representative, designation of a substitute carrier, request for attention
to be given to the consignment en route, etc.)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>Shipment details for port traffic:
...</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>Used for CUV transports, only. Restrictions on
the operation of the wagon known to the consignor (e.g. limited speed,


```



```


etc.)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="24">
  <xs:annotation>
    <xs:documentation>Dangerous goods packed in limited quantities the
total gross mass of which exceeds eight tonnes per transport
unit.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>Wagon keeper according to article 17 AVV
(Name)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="31">
  <xs:annotation>
    <xs:documentation>CH import declaration by DB
Cargo</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="32">
  <xs:annotation>
    <xs:documentation>CH import declaration by SBB
Cargo</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="33">
  <xs:annotation>
    <xs:documentation>CH import declaration by third
parties</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **CouplingType**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content simple		
facets	Kind	Value	Annotation
	enumeration	0	documentation without coupler
	enumeration	1	documentation non-reinforced coupler less than 85t
	enumeration	2	documentation reinforced coupler equals to 85t
	enumeration	3	documentation ultra-reinforced coupler greater than 85t
	enumeration	4	documentation


	automatic coupling
annotation	documentation Classification of coupling
source	<pre> <xs:element name="CouplingType"> <xs:annotation> <xs:documentation>Classification of coupling</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>without coupler</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>non-reinforced coupler less than 85t</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>reinforced coupler equals to 85t</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>ultra-reinforced coupler greater than 85t</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>automatic coupling</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **CustomerType**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:token												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>CR</td> <td>documentation Consignor</td> </tr> <tr> <td>enumeration</td> <td>CE</td> <td>documentation Consignee</td> </tr> <tr> <td>enumeration</td> <td>FPCR</td> <td>documentation Freight payer</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	CR	documentation Consignor	enumeration	CE	documentation Consignee	enumeration	FPCR	documentation Freight payer
Kind	Value	Annotation											
enumeration	CR	documentation Consignor											
enumeration	CE	documentation Consignee											
enumeration	FPCR	documentation Freight payer											

	enumeration FPCE documentation Freight payer CE
annotation	documentation Type of participation
source	<pre> <xs:element name="CustomerType"> <xs:annotation> <xs:documentation>Type of participation</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="CR"> <xs:annotation> <xs:documentation>Consignor</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="CE"> <xs:annotation> <xs:documentation>Consignee</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="FPCR"> <xs:annotation> <xs:documentation>Freight payer</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="FPCE"> <xs:annotation> <xs:documentation>Freight payer CE</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **DangerLabel**

diagram	 <p>All Danger Label of this dangerous good according to the RID chapter 3.2, table A, column 5, excepting the shunting labels Model 13 and 15 (CODE: OTIF RID-Specification).</p>																		
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																		
type	restriction of xs:token																		
properties	content simple																		
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td>documentation Explosive materials, divisions 1.1, 1.2 and 1.3</td> </tr> <tr> <td>enumeration</td> <td>1.4</td> <td>documentation Explosive materials, division 1.4</td> </tr> <tr> <td>enumeration</td> <td>1.5</td> <td>documentation Explosive materials, division 1.5</td> </tr> <tr> <td>enumeration</td> <td>1.6</td> <td>documentation Explosive materials, division 1.6</td> </tr> <tr> <td>enumeration</td> <td>2.1</td> <td>documentation Flammable gases</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1	documentation Explosive materials, divisions 1.1, 1.2 and 1.3	enumeration	1.4	documentation Explosive materials, division 1.4	enumeration	1.5	documentation Explosive materials, division 1.5	enumeration	1.6	documentation Explosive materials, division 1.6	enumeration	2.1	documentation Flammable gases
Kind	Value	Annotation																	
enumeration	1	documentation Explosive materials, divisions 1.1, 1.2 and 1.3																	
enumeration	1.4	documentation Explosive materials, division 1.4																	
enumeration	1.5	documentation Explosive materials, division 1.5																	
enumeration	1.6	documentation Explosive materials, division 1.6																	
enumeration	2.1	documentation Flammable gases																	

	enumeration 2.2	documentation Non-flammable, non-toxic gases
	enumeration 2.3	documentation Toxic gases
	enumeration 3	documentation Flammable liquids
	enumeration 4.1	documentation Flammable solids , self-reactive substances and solid desensitized explosives
	enumeration 4.2	documentation Substances liable to spontaneous combustion
	enumeration 4.3	documentation Substances which, in contact with water, emit flammable gases
	enumeration 5.1	documentation Oxidizing substances
	enumeration 5.2	documentation Organic peroxides
	enumeration 6.1	documentation Toxic substances
	enumeration 6.2	documentation Infectious substances
	enumeration 7A	documentation Radioactive material, category I
	enumeration 7B	documentation Radioactive material, category II
	enumeration 7C	documentation Radioactive material, category III
	enumeration 7D	documentation (obsolete) should be used for general information about class 7
	enumeration 7E	documentation Fissile radioactive material
	enumeration 8	documentation Corrosive substances
	enumeration 9	documentation Miscellaneous dangerous substances and articles
annotation	documentation	All Danger Label of this dangerous good according to the RID chapter 3.2, table A, column 5, excepting the shunting labels Model 13 and 15 (CODE: OTIF RID-Specification).
source		<pre> <xs:element name="DangerLabel"> <xs:annotation> <xs:documentation>All Danger Label of this dangerous good according to the RID chapter 3.2, table A, column 5, excepting the shunting labels Model 13 and 15 (CODE: OTIF RID-Specification).</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Explosive materials, divisions 1.1, 1.2 and 1.3</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1.4"> <xs:annotation> <xs:documentation>Explosive materials, division 1.4</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1.5"> <xs:annotation> <xs:documentation>Explosive materials, division </pre>

```

1.5</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1.6">
  <xs:annotation>
    <xs:documentation>Explosive materials, division
1.6</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="2.1">
  <xs:annotation>
    <xs:documentation>Flammable gases</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="2.2">
  <xs:annotation>
    <xs:documentation>Non-flammable, non-toxic
gases</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="2.3">
  <xs:annotation>
    <xs:documentation>Toxic gases</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="3">
  <xs:annotation>
    <xs:documentation>Flammable liquids</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4.1">
  <xs:annotation>
    <xs:documentation>Flammable solids , self-reactive substances and
solid desensitized explosives</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4.2">
  <xs:annotation>
    <xs:documentation>Substances liable to spontaneous
combustion</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4.3">
  <xs:annotation>
    <xs:documentation>Substances which, in contact with water, emit
flammable gases</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="5.1">
  <xs:annotation>
    <xs:documentation>Oxidizing substances</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="5.2">
  <xs:annotation>
    <xs:documentation>Organic peroxides</xs:documentation>
  </xs:annotation>
</xs:enumeration>


```

```

<xs:enumeration value="6.1">
  <xs:annotation>
    <xs:documentation>Toxic substances</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="6.2">
  <xs:annotation>
    <xs:documentation>Infectious substances</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7A">
  <xs:annotation>
    <xs:documentation>Radioactive material, category
I</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7B">
  <xs:annotation>
    <xs:documentation>Radioactive material, category
II</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7C">
  <xs:annotation>
    <xs:documentation>Radioactive material, category
III</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7D">
  <xs:annotation>
    <xs:documentation>(obsolete) should be used for general
information about class 7</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7E">
  <xs:annotation>
    <xs:documentation>Fissile radioactive material</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="8">
  <xs:annotation>
    <xs:documentation>Corrosive substances</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9">
  <xs:annotation>
    <xs:documentation>Miscellaneous dangerous substances and
articles</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **EmptyPackingCode**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content simple		
facets	Kind	Value	Annotation
	enumeration	01	documentation EMPTY PACKAGING
	enumeration	02	documentation EMPTY CONTAINER
	enumeration	03	documentation EMPTY IBC
	enumeration	04	documentation EMPTY LARGE PACKAGING
	enumeration	05	documentation EMPTY TANK-VEHICLE
	enumeration	06	documentation EMPTY TANK-WAGON
	enumeration	07	documentation EMPTY DETACHABLE TANK
	enumeration	08	documentation EMPTY DEMOUNTABLE TANK
	enumeration	09	documentation EMPTY TANK-CONTAINER
	enumeration	10	documentation EMPTY PORTABLE TANK
	enumeration	11	documentation EMPTY BATTERY-VEHICLE
	enumeration	12	documentation EMPTY BATTERY-WAGON
	enumeration	13	documentation EMPTY LARGE CONTAINER WITH MULTIPLE LINKED ELEMENTS
	enumeration	14	documentation EMPTY VEHICLE
	enumeration	15	documentation EMPTY WAGON
	enumeration	16	documentation EMPTY RECEPTACLE le 1000L
	enumeration	17	documentation EMPTY RECEPTACLE gt 1000L
	enumeration	18	documentation EMPTY
annotation	documentation Code of empty packing as described in RID 5.4.1.1.6.2 documentation CODE: OTIF RID-Specification, element EMPTY has been added as 'dummy' until the code list has been finished and approved.		
source	<pre> <xs:element name="EmptyPackingCode"> <xs:annotation> <xs:documentation>Code of empty packing as described in RID 5.4.1.1.6.2</xs:documentation> <xs:documentation>CODE: OTIF RID-Specification, element EMPTY has been added as 'dummy' until the code list has been finished and approved. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> </pre>		

```

<xs:enumeration value="01">
  <xs:annotation>
    <xs:documentation>EMPTY PACKAGING</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="02">
  <xs:annotation>
    <xs:documentation>EMPTY CONTAINER</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="03">
  <xs:annotation>
    <xs:documentation>EMPTY IBC</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="04">
  <xs:annotation>
    <xs:documentation>EMPTY LARGE PACKAGING</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="05">
  <xs:annotation>
    <xs:documentation>EMPTY TANK-VEHICLE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="06">
  <xs:annotation>
    <xs:documentation>EMPTY TANK-WAGON</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="07">
  <xs:annotation>
    <xs:documentation>EMPTY DETACHABLE TANK</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="08">
  <xs:annotation>
    <xs:documentation>EMPTY DEMOUNTABLE TANK</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="09">
  <xs:annotation>
    <xs:documentation>EMPTY TANK-CONTAINER</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>EMPTY PORTABLE TANK</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>EMPTY BATTERY-VEHICLE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>EMPTY BATTERY-WAGON</xs:documentation>
  </xs:annotation>


```



```


</xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>EMPTY LARGE CONTAINER WITH MULTIPLE LINKED
ELEMENTS</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>EMPTY VEHICLE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>EMPTY WAGON</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>EMPTY RECEPTACLE le 1000L</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>EMPTY RECEPTACLE gt 1000L</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>EMPTY</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **HandBrakeType**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:token												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td>documentation No hand brake</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation Ground-operated hand brake</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Platform-operated hand brake</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0	documentation No hand brake	enumeration	1	documentation Ground-operated hand brake	enumeration	2	documentation Platform-operated hand brake
Kind	Value	Annotation											
enumeration	0	documentation No hand brake											
enumeration	1	documentation Ground-operated hand brake											
enumeration	2	documentation Platform-operated hand brake											
annotation	documentation Classification of hand brake												
source	<xs:element name="HandBrakeType">												

	<pre> <xs:annotation> <xs:documentation>Classification of hand brake</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>No hand brake</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Ground-operated hand brake</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Platform-operated hand brake</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--


element **ILU_TypeDetail**

diagram																																																				
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																																			
type	restriction of xs:token																																																			
properties	content simple																																																			
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>BX</td><td></td></tr> <tr><td>enumeration</td><td>BK</td><td></td></tr> <tr><td>enumeration</td><td>FL</td><td></td></tr> <tr><td>enumeration</td><td>HT</td><td></td></tr> <tr><td>enumeration</td><td>HC</td><td></td></tr> <tr><td>enumeration</td><td>IN</td><td></td></tr> <tr><td>enumeration</td><td>OT</td><td></td></tr> <tr><td>enumeration</td><td>HH</td><td></td></tr> <tr><td>enumeration</td><td>PW</td><td></td></tr> <tr><td>enumeration</td><td>OS</td><td></td></tr> <tr><td>enumeration</td><td>RF</td><td></td></tr> <tr><td>enumeration</td><td>SD</td><td></td></tr> <tr><td>enumeration</td><td>SL</td><td></td></tr> <tr><td>enumeration</td><td>VE</td><td></td></tr> <tr><td>enumeration</td><td>TC</td><td></td></tr> <tr><td>enumeration</td><td>RH</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	BX		enumeration	BK		enumeration	FL		enumeration	HT		enumeration	HC		enumeration	IN		enumeration	OT		enumeration	HH		enumeration	PW		enumeration	OS		enumeration	RF		enumeration	SD		enumeration	SL		enumeration	VE		enumeration	TC		enumeration	RH	
Kind	Value	Annotation																																																		
enumeration	BX																																																			
enumeration	BK																																																			
enumeration	FL																																																			
enumeration	HT																																																			
enumeration	HC																																																			
enumeration	IN																																																			
enumeration	OT																																																			
enumeration	HH																																																			
enumeration	PW																																																			
enumeration	OS																																																			
enumeration	RF																																																			
enumeration	SD																																																			
enumeration	SL																																																			
enumeration	VE																																																			
enumeration	TC																																																			
enumeration	RH																																																			
source	<pre> <xs:element name="ILU_TypeDetail"> <xs:simpleType> <xs:restriction base="xs:token"> </pre>																																																			

```

<xs:enumeration value="BX"/>
<xs:enumeration value="BK"/>
<xs:enumeration value="FL"/>
<xs:enumeration value="HT"/>
<xs:enumeration value="HC"/>
<xs:enumeration value="IN"/>
<xs:enumeration value="OT"/>
<xs:enumeration value="HH"/>
<xs:enumeration value="PW"/>
<xs:enumeration value="OS"/>
<xs:enumeration value="RF"/>
<xs:enumeration value="SD"/>
<xs:enumeration value="SL"/>
<xs:enumeration value="VE"/>
<xs:enumeration value="TC"/>
<xs:enumeration value="RH"/>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```


element **IncotermCode**

diagram																															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																														
type	restriction of xs:token																														
properties	content simple																														
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>CIP</td> <td>documentation Carriage Insurance Paid</td> </tr> <tr> <td>enumeration</td> <td>CPT</td> <td>documentation Carriage Paid To</td> </tr> <tr> <td>enumeration</td> <td>DAF</td> <td>documentation Delivered At Frontier (deprecated in 2011-01-01)</td> </tr> <tr> <td>enumeration</td> <td>DDP</td> <td>documentation Delivered Duty Paid</td> </tr> <tr> <td>enumeration</td> <td>DDU</td> <td>documentation Delivered Duty Unpaid (deprecated in 2011-01-01)</td> </tr> <tr> <td>enumeration</td> <td>EXW</td> <td>documentation EX Works</td> </tr> <tr> <td>enumeration</td> <td>FCA</td> <td>documentation Free Carrier</td> </tr> <tr> <td>enumeration</td> <td>DAP</td> <td>documentation Delivered At Place</td> </tr> <tr> <td>enumeration</td> <td>DAT</td> <td>documentation Delivered At Terminal</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	CIP	documentation Carriage Insurance Paid	enumeration	CPT	documentation Carriage Paid To	enumeration	DAF	documentation Delivered At Frontier (deprecated in 2011-01-01)	enumeration	DDP	documentation Delivered Duty Paid	enumeration	DDU	documentation Delivered Duty Unpaid (deprecated in 2011-01-01)	enumeration	EXW	documentation EX Works	enumeration	FCA	documentation Free Carrier	enumeration	DAP	documentation Delivered At Place	enumeration	DAT	documentation Delivered At Terminal
Kind	Value	Annotation																													
enumeration	CIP	documentation Carriage Insurance Paid																													
enumeration	CPT	documentation Carriage Paid To																													
enumeration	DAF	documentation Delivered At Frontier (deprecated in 2011-01-01)																													
enumeration	DDP	documentation Delivered Duty Paid																													
enumeration	DDU	documentation Delivered Duty Unpaid (deprecated in 2011-01-01)																													
enumeration	EXW	documentation EX Works																													
enumeration	FCA	documentation Free Carrier																													
enumeration	DAP	documentation Delivered At Place																													
enumeration	DAT	documentation Delivered At Terminal																													
annotation	documentation Incoterm (given by the client)																														
source	<pre> <xs:element name="IncotermCode"> <xs:annotation> <xs:documentation>Incoterm (given by the client)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="CIP"> <xs:annotation> </pre>																														

```

        <xs:documentation>Carriage Insurance Paid</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="CPT">
    <xs:annotation>
        <xs:documentation>Carriage Paid To</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DAF">
    <xs:annotation>
        <xs:documentation>Delivered At Frontier (deprecated in 2011-01-
01)</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DDP">
    <xs:annotation>
        <xs:documentation>Delivered Duty Paid</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DDU">
    <xs:annotation>
        <xs:documentation>Delivered Duty Unpaid (deprecated in 2011-01-
01)</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="EXW">
    <xs:annotation>
        <xs:documentation>EX Works</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="FCA">
    <xs:annotation>
        <xs:documentation>Free Carrier</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DAP">
    <xs:annotation>
        <xs:documentation>Delivered At Place</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DAT">
    <xs:annotation>
        <xs:documentation>Delivered At Terminal</xs:documentation>
    </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **InfoOnGoodsShapeTypeDanger**

<p>diagram</p>	 <p>InfoOnGoodsShapeTypeDan...</p> <p>Additional codified information on the load. Coding Structures as defined in 404-2 chapter 4.1</p>
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>

type	restriction of xs:token		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	01	documentation Container
	enumeration	02	documentation Other intermodal traffic
	enumeration	03	documentation Rolling road (RR)
	enumeration	06	documentation Semi-Trailer on bogies
	enumeration	10	documentation 1 - danger of explosion (subclass 1.1, 1.2, 1.3)
	enumeration	14	documentation 1.4 - danger of explosion (subclass 1.4)
	enumeration	15	documentation 1.5 - danger of explosion (subclass 1.5)
	enumeration	16	documentation 1.6 - danger of explosion (subclass 1.6)
	enumeration	21	documentation 2.1 - inflammable gases
	enumeration	22	documentation 2.2 - non inflammable,non-toxic gases
	enumeration	23	documentation 2.3 - toxic gases
	enumeration	30	documentation 3 - fire hazard (inflammable liquids)
	enumeration	41	documentation 4.1 - fire hazard (inflammable solids)
	enumeration	42	documentation 4.2 - spontaneously inflammable
	enumeration	43	documentation 4.3 - gives off inflammable gas on contact with water
	enumeration	51	documentation 5.1 - combustible substance
	enumeration	52	documentation 5.2 - organic peroxide
	enumeration	61	documentation 6.1 - toxic substance
	enumeration	62	documentation 6.2 - infectious substance
	enumeration	71	documentation 7A - radioactive substance in category I packing WHITE
	enumeration	72	documentation 7B - radioactive substance in category II packing YELLOW
	enumeration	73	documentation 7C - radioactive substance in category III packing YELLOW
	enumeration	74	documentation 7D - Common label for radioactive substances included under 7A, 7B + 7C
	enumeration	75	documentation 7E - fissible substance
	enumeration	80	documentation 8 - corrosive substance
	enumeration	90	documentation Various dangerous substance and objects not covered by the other classes
	enumeration	96	documentation Environmentally hazardous substance (RID 5.2.1.8)
	enumeration	97	documentation More than 8 tons of dangerous goods packaged in limited quantities (LQ)
	enumeration	98	documentation Livestock
	enumeration	99	documentation

Perishables	
annotation	documentation Additional codified information on the load. Coding Structures as defined in 404-2 chapter 4.1
source	<pre> <xs:element name="InfoOnGoodsShapeTypeDanger"> <xs:annotation> <xs:documentation>Additional codified information on the load. Coding Structures as defined in 404-2 chapter 4.1</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="01"> <xs:annotation> <xs:documentation>Container</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="02"> <xs:annotation> <xs:documentation>Other intermodal traffic</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="03"> <xs:annotation> <xs:documentation>Rolling road (RR)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="06"> <xs:annotation> <xs:documentation>Semi-Trailer on bogies</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="10"> <xs:annotation> <xs:documentation>1 - danger of explosion (subclass 1.1, 1.2, 1.3)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="14"> <xs:annotation> <xs:documentation>1.4 - danger of explosion (subclass 1.4)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="15"> <xs:annotation> <xs:documentation>1.5 - danger of explosion (subclass 1.5)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="16"> <xs:annotation> <xs:documentation>1.6 - danger of explosion (subclass 1.6)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="21"> <xs:annotation> <xs:documentation>2.1 - inflammable gases</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre> </pre>

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="22">
  <xs:annotation>
    <xs:documentation>2.2 - non inflammable,non-toxic
gases</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="23">
  <xs:annotation>
    <xs:documentation>2.3 - toxic gases</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="30">
  <xs:annotation>
    <xs:documentation>3 - fire hazard (inflammable
liquids)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="41">
  <xs:annotation>
    <xs:documentation>4.1 - fire hazard (inflammable
solids)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>4.2 - spontaneoulsy
inflammable</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>4.3 - gives off inflammable gas on contact with
water</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="51">
  <xs:annotation>
    <xs:documentation>5.1 - combustible substance</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="52">
  <xs:annotation>
    <xs:documentation>5.2 - organic peroxide</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="61">
  <xs:annotation>
    <xs:documentation>6.1 - toxic substance</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="62">
  <xs:annotation>
    <xs:documentation>6.2 - infectious substance</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="71">

```

```

    <xs:annotation>
      <xs:documentation>7A - radioactive substance in category I packing
WHITE</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="72">
    <xs:annotation>
      <xs:documentation>7B - radioactive substance in category II
packing YELLOW</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="73">
    <xs:annotation>
      <xs:documentation>7C - radioactive substance in category III
packing YELLOW</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="74">
    <xs:annotation>
      <xs:documentation>7D - Common label for radioactive substances
included under 7A, 7B + 7C</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="75">
    <xs:annotation>
      <xs:documentation>7E - fissible substance</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="80">
    <xs:annotation>
      <xs:documentation>8 - corrosive substance</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="90">
    <xs:annotation>
      <xs:documentation>Various dangerous substance and objects not
covered by the other classes</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="96">
    <xs:annotation>
      <xs:documentation>Environmentally hazardous substance (RID
5.2.1.8)</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="97">
    <xs:annotation>
      <xs:documentation>More than 8 tons of dangerous goods packaged in
limited quantities (LQ)</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="98">
    <xs:annotation>
      <xs:documentation>Livestock</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="99">
    <xs:annotation>


```



```

<xs:documentation>Perishables</xs:documentation>
</xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **InteropCapability**


diagram	 <p>InteropCapability Identification of the general interoperability capability of the wagon.</p>																											
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																											
type	restriction of xs:integer																											
properties	content simple																											
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>2</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation National</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Bi-/Multilateral (with agreement or authorisation grid)</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation RIV</td> </tr> <tr> <td>enumeration</td> <td>5</td> <td>documentation TEN</td> </tr> <tr> <td>enumeration</td> <td>6</td> <td>documentation TEN-GE</td> </tr> <tr> <td>enumeration</td> <td>7</td> <td>documentation TEN-CW</td> </tr> <tr> <td>enumeration</td> <td>8</td> <td>documentation TEN RIV</td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	2		enumeration	1	documentation National	enumeration	2	documentation Bi-/Multilateral (with agreement or authorisation grid)	enumeration	3	documentation RIV	enumeration	5	documentation TEN	enumeration	6	documentation TEN-GE	enumeration	7	documentation TEN-CW	enumeration	8	documentation TEN RIV
Kind	Value	Annotation																										
totalDigits	2																											
enumeration	1	documentation National																										
enumeration	2	documentation Bi-/Multilateral (with agreement or authorisation grid)																										
enumeration	3	documentation RIV																										
enumeration	5	documentation TEN																										
enumeration	6	documentation TEN-GE																										
enumeration	7	documentation TEN-CW																										
enumeration	8	documentation TEN RIV																										
annotation	documentation Identification of the general interoperability capability of the wagon.																											
source	<pre> <xs:element name="InteropCapability"> <xs:annotation> <xs:documentation>Identification of the general interoperability capability of the wagon.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:totalDigits value="2"/> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>National</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Bi-/Multilateral (with agreement or authorisation grid)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>RIV</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>																											

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="5">
  <xs:annotation>
    <xs:documentation>TEN</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="6">
  <xs:annotation>
    <xs:documentation>TEN-GE</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7">
  <xs:annotation>
    <xs:documentation>TEN-CW</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="8">
  <xs:annotation>
    <xs:documentation>TEN RIV</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

element **JourneyLocationTypeCode**


diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	01	documentation Origin
	enumeration	02	documentation Intermediate
	enumeration	03	documentation Destination
	enumeration	04	documentation Handover
	enumeration	05	documentation Interchange
	enumeration	06	documentation Handover and Interchange
	enumeration	07	documentation State Border
	enumeration	08	documentation None
	enumeration	09	documentation Network border
	enumeration	99	documentation Mutually Defined
source	<pre> <xs:element name="JourneyLocationTypeCode"> <xs:annotation> </pre>		

```


    <xs:documentation/>
  </xs:annotation>
</xs:simpleType>
<xs:simpleType>
  <xs:restriction base="xs:token">
    <xs:enumeration value="01">
      <xs:annotation>
        <xs:documentation>Origin</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="02">
      <xs:annotation>
        <xs:documentation>Intermediate</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="03">
      <xs:annotation>
        <xs:documentation>Destination</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="04">
      <xs:annotation>
        <xs:documentation>Handover</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="05">
      <xs:annotation>
        <xs:documentation>Interchange</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="06">
      <xs:annotation>
        <xs:documentation>Handover and Interchange</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="07">
      <xs:annotation>
        <xs:documentation>State Border</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="08">
      <xs:annotation>
        <xs:documentation>None</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="09">
      <xs:annotation>
        <xs:documentation>Network border</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="99">
      <xs:annotation>
        <xs:documentation>Mutually Defined</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
  </xs:restriction>
</xs:simpleType>
</xs:element>

```

element **LivestockOrPeopleIndicator**

diagram	 <p>Indicates that livestock and people (other than train crew) will be carried. Coding: if live animals or people are transported = 1, in opposite case = 0. If code = 1, then at the wagon level for at least one wagon Info- Goods Shape, Type and Danger has to include the code '98' or Restrictions due to Load or Damage has to inclu...</p>									
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0		enumeration	1	
Kind	Value	Annotation								
enumeration	0									
enumeration	1									
annotation	<p>documentation</p> <p>Indicates that livestock and people (other than train crew) will be carried. Coding: if live animals or people are transported = 1, in opposite case = 0. If code = 1, then at the wagon level for at least one wagon Info- Goods Shape, Type and Danger has to include the code '98' or Restrictions due to Load or Damage has to include code '09.'</p>									
source	<pre><xs:element name="LivestockOrPeopleIndicator"> <xs:annotation> <xs:documentation>Indicates that livestock and people (other than train crew) will be carried. Coding: if live animals or people are transported = 1, in opposite case = 0. If code = 1, then at the wagon level for at least one wagon Info- Goods Shape, Type and Danger has to include the code '98' or Restrictions due to Load or Damage has to include code '09.'<!--</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"/> <xs:enumeration value="1"/> </xs:restriction> </xs:simpleType> </xs:element></pre--> </pre>									

element **LoadTableStars**

diagram	 <p>Number of load table st...</p>												
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:integer												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation Authorised to run in trains up to 100 km/h with a brake that does not meet all the requirements for S (100 km/h) conditions.</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Authorised to run in trains up to 120 km/h with a brake that does not meet all the</td> </tr> </tbody> </table>	Kind	Value	Annotation	totalDigits	1		enumeration	1	documentation Authorised to run in trains up to 100 km/h with a brake that does not meet all the requirements for S (100 km/h) conditions.	enumeration	2	documentation Authorised to run in trains up to 120 km/h with a brake that does not meet all the
Kind	Value	Annotation											
totalDigits	1												
enumeration	1	documentation Authorised to run in trains up to 100 km/h with a brake that does not meet all the requirements for S (100 km/h) conditions.											
enumeration	2	documentation Authorised to run in trains up to 120 km/h with a brake that does not meet all the											


	<p>enumeration 3 requirements for SS (120 km/h) conditions. documentation Authorised to run in trains up to 120 km/h with a brake that does not meet all the requirements for SS (120 km/h) conditions. The wagons must be fitted with an automatic load-proportional braking system.</p>
annotation	<p>documentation Number of load table stars.</p>
source	<pre> <xs:element name="LoadTableStars"> <xs:annotation> <xs:documentation>Number of load table stars.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:totalDigits value="1"/> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Authorised to run in trains up to 100 km/h with a brake that does not meet all the requirements for S (100 km/h) conditions.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Authorised to run in trains up to 120 km/h with a brake that does not meet all the requirements for SS (120 km/h) conditions.</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Authorised to run in trains up to 120 km/h with a brake that does not meet all the requirements for SS (120 km/h) conditions. The wagons must be fitted with an automatic load-proportional braking system.</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **MessageStatus**

diagram													
namespace	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>												
type	<p>restriction of xs:token</p>												
properties	<p>content simple</p>												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td>documentation creation</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation modification</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation deletion</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1	documentation creation	enumeration	2	documentation modification	enumeration	3	documentation deletion
Kind	Value	Annotation											
enumeration	1	documentation creation											
enumeration	2	documentation modification											
enumeration	3	documentation deletion											


annotation	documentation Assigned by the Sender 1=creation, 2=modification, 3=deletion
source	<pre> <xs:element name="MessageStatus"> <xs:annotation> <xs:documentation>Assigned by the Sender 1=creation, 2=modification, 3=deletion</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>creation</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>modification</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>deletion</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

element **MRN_Type**

diagram																			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																		
type	restriction of xs:token																		
properties	content simple																		
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>MRN-E</td> <td>documentation if an EXPORT declaration has been lodged</td> </tr> <tr> <td>enumeration</td> <td>MRN-T</td> <td>documentation if a TRANSIT declaration has been lodged</td> </tr> <tr> <td>enumeration</td> <td>MRN-TS</td> <td>documentation if a TRANSIT declaration with SECURITY data has been lodged</td> </tr> <tr> <td>enumeration</td> <td>MRN-EXS</td> <td>documentation if the EXIT SUMMARY declaration has been made separately by the consignor</td> </tr> <tr> <td>enumeration</td> <td>MRN-ENS</td> <td>documentation if the ENTRY SUMMARY declaration has been made separately by the consignor</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	MRN-E	documentation if an EXPORT declaration has been lodged	enumeration	MRN-T	documentation if a TRANSIT declaration has been lodged	enumeration	MRN-TS	documentation if a TRANSIT declaration with SECURITY data has been lodged	enumeration	MRN-EXS	documentation if the EXIT SUMMARY declaration has been made separately by the consignor	enumeration	MRN-ENS	documentation if the ENTRY SUMMARY declaration has been made separately by the consignor
Kind	Value	Annotation																	
enumeration	MRN-E	documentation if an EXPORT declaration has been lodged																	
enumeration	MRN-T	documentation if a TRANSIT declaration has been lodged																	
enumeration	MRN-TS	documentation if a TRANSIT declaration with SECURITY data has been lodged																	
enumeration	MRN-EXS	documentation if the EXIT SUMMARY declaration has been made separately by the consignor																	
enumeration	MRN-ENS	documentation if the ENTRY SUMMARY declaration has been made separately by the consignor																	
annotation	documentation Type of MRN given, CODE: CIT GLV-CIM appendix 2																		
source	<pre> <xs:element name="MRN_Type"> <xs:annotation> <xs:documentation>Type of MRN given, CODE: CIT GLV-CIM appendix 2</xs:documentation> </xs:annotation> <xs:simpleType> </pre>																		


	<pre> <xs:restriction base="xs:token"> <xs:enumeration value="MRN-E"> <xs:annotation> <xs:documentation>if an EXPORT declaration has been lodged</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MRN-T"> <xs:annotation> <xs:documentation>if a TRANSIT declaration has been lodged</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MRN-TS"> <xs:annotation> <xs:documentation>if a TRANSIT declaration with SECURITY data has been lodged</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MRN-EXS"> <xs:annotation> <xs:documentation>if the EXIT SUMMARY declaration has been made separately by the consignor</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MRN-ENS"> <xs:annotation> <xs:documentation>if the ENTRY SUMMARY declaration has been made separately by the consignor</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **NormalLoadingGauge**

diagram	 <p>All codes are defined in the UIC leaflet 505-1 and 503, as well as in the EN 15273-2:2013. For details please refer to EN 15273-2:2013 (Railway applications - Gauges - Part 2: Rolling stock gauge). For the existing gauges in the list, th...</p>																		
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																		
type	restriction of xs:token																		
properties	content simple																		
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>G1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>G2</td> <td></td> </tr> <tr> <td>enumeration</td> <td>GA</td> <td></td> </tr> <tr> <td>enumeration</td> <td>GB</td> <td></td> </tr> <tr> <td>enumeration</td> <td>GC</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	G1		enumeration	G2		enumeration	GA		enumeration	GB		enumeration	GC	
Kind	Value	Annotation																	
enumeration	G1																		
enumeration	G2																		
enumeration	GA																		
enumeration	GB																		
enumeration	GC																		

	<p>enumeration GB1</p> <p>enumeration GB2</p> <p>enumeration GB-M6</p> <p>enumeration GHE16</p> <p>enumeration W6-A</p> <p>enumeration SEa</p>
annotation	<p>documentation</p> <p>All codes are defined in the UIC leaflet 505-1 and 503, as well as in the EN 15273-2:2013. For details please refer to EN 15273-2:2013 (Railway applications - Gauges - Part 2: Rolling stock gauge). For the existing gauges in the list, the Annex B.3 should be used.</p>
source	<pre><xs:element name="NormalLoadingGauge"> <xs:annotation> <xs:documentation> All codes are defined in the UIC leaflet 505-1 and 503, as well as in the EN 15273-2:2013. For details please refer to EN 15273- 2:2013 (Railway applications - Gauges - Part 2: Rolling stock gauge). For the existing gauges in the list, the Annex B.3 should be used. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="G1"/> <xs:enumeration value="G2"/> <xs:enumeration value="GA"/> <xs:enumeration value="GB"/> <xs:enumeration value="GC"/> <xs:enumeration value="GB1"/> <xs:enumeration value="GB2"/> <xs:enumeration value="GB-M6"/> <xs:enumeration value="GHE16"/> <xs:enumeration value="W6-A"/> <xs:enumeration value="SEa"/> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **PackingGroup**

diagram	 <p>The Packing Group according to the RID chapter 3.2, table A, column 4. Possible values are "I", "II" or "III", otherwise the Packing Group have to be omitted. Mandatory, if it's foreseen in column 4, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC..."</p>						
namespace	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>						
type	<p>restriction of xs:token</p>						
properties	<p>content simple</p>						
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>enumeration</td> <td>I</td> <td>documentation</td> </tr> </table>	Kind	Value	Annotation	enumeration	I	documentation
Kind	Value	Annotation					
enumeration	I	documentation					

	<p>enumeration II High danger documentation Medium danger</p> <p>enumeration III documentation Low danger</p>
annotation	<p>documentation The Packing Group according to the RID chapter 3.2, table A, column 4. Possible values are "I", "II" or "III", otherwise the Packing Group have to be omitted. Mandatory, if it's foreseen in column 4, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING".</p>
source	<pre><xs:element name="PackingGroup"> <xs:annotation> <xs:documentation>The Packing Group according to the RID chapter 3.2, table A, column 4. Possible values are "I", "II" or "III", otherwise the Packing Group have to be omitted. Mandatory, if it's foreseen in column 4, except it concerns a declaration of an empty packaging of the type "EMPTY PACKAGING", "EMPTY RECEPTACLE &lt;=1000L", "EMPTY IBC" or "EMPTY LARGE PACKAGING".</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="I"> <xs:annotation> <xs:documentation>High danger</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="II"> <xs:annotation> <xs:documentation>Medium danger</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="III"> <xs:annotation> <xs:documentation>Low danger</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element></pre>

element **PrepaidcodeCarrier**

diagram																
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:token															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>10</td> <td>documentation prepaid freight</td> </tr> <tr> <td>enumeration</td> <td>11</td> <td>documentation prepaid freight including...</td> </tr> <tr> <td>enumeration</td> <td>12</td> <td>documentation prepaid freight including...up to border of origin country</td> </tr> <tr> <td>enumeration</td> <td>13</td> <td>documentation</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	10	documentation prepaid freight	enumeration	11	documentation prepaid freight including...	enumeration	12	documentation prepaid freight including...up to border of origin country	enumeration	13	documentation
Kind	Value	Annotation														
enumeration	10	documentation prepaid freight														
enumeration	11	documentation prepaid freight including...														
enumeration	12	documentation prepaid freight including...up to border of origin country														
enumeration	13	documentation														

	<p>enumeration 14 prepaid freight including...up to exit border of last transit country documentation</p> <p>enumeration 15 prepaid freight including...up to exit border of other countries documentation</p> <p>enumeration 16 prepaid freight up to border of origin country documentation</p> <p>enumeration 17 prepaid freight up to exit border of last transit country documentation</p> <p>enumeration 20 prepaid freight up to exit border of other countries documentation</p> <p>enumeration 42 prepaid all costs documentation</p> <p>enumeration 43 Free carrier documentation</p> <p>enumeration 44 Carriage paid to... documentation</p> <p>enumeration 45 Delivered duty unpaid documentation</p> <p>enumeration 46 Carriage insurance paid documentation</p> <p>enumeration 47 Delivered at terminal documentation</p> <p>enumeration 90 Delivered at place documentation</p> <p>not prepaid</p>
annotation	<p>documentation Prepaidcode (given by the railway)</p>
source	<pre> <xs:element name="PrepaidcodeCarrier"> <xs:annotation> <xs:documentation>Prepaidcode (given by the railway)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="10"> <xs:annotation> <xs:documentation>prepaid freight</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="11"> <xs:annotation> <xs:documentation>prepaid freight including... </xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="12"> <xs:annotation> <xs:documentation>prepaid freight including...up to border of origin country</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="13"> <xs:annotation> <xs:documentation>prepaid freight including...up to exit border of last transit country </xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="14"> <xs:annotation> <xs:documentation>prepaid freight including...up to exit border of other countries </xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>

```

</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>prepaid freight up to border of origin country
  </xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>prepaid freight up to exit border of last
transit country</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>prepaid freight up to exit border of other
countries </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="20">
  <xs:annotation>
    <xs:documentation>prepaid all costs</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>Free carrier </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>Carriage paid to...</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="44">
  <xs:annotation>
    <xs:documentation>Delivered duty unpaid</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="45">
  <xs:annotation>
    <xs:documentation>Carriage insurance paid </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="46">
  <xs:annotation>
    <xs:documentation>Delivered at terminal</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="47">
  <xs:annotation>
    <xs:documentation>Delivered at place</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="90">
  <xs:annotation>
    <xs:documentation>not prepaid</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **PrepaidCodeCustomer**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	10	documentation prepaid freight
	enumeration	11	documentation prepaid freight including...
	enumeration	12	documentation prepaid freight including...up to border of origin country
	enumeration	13	documentation prepaid freight including...up to exit border of last transit country
	enumeration	14	documentation prepaid freight including...up to exit border of other countries
	enumeration	15	documentation prepaid freight up to border of origin country
	enumeration	16	documentation prepaid freight up to exit border of last transit country
	enumeration	17	documentation prepaid freight up to exit border of other countries
	enumeration	20	documentation prepaid all costs
	enumeration	42	documentation Free carrier
	enumeration	43	documentation Carriage paid to...
	enumeration	44	documentation Delivered duty unpaid
	enumeration	45	documentation Carriage insurance paid
	enumeration	46	documentation Delivered at terminal
	enumeration	47	documentation Delivered at place
	enumeration	90	documentation not prepaid
annotation	documentation	Prepaidcode (given by the customer)	
source	<pre> <xs:element name="PrepaidCodeCustomer"> <xs:annotation> <xs:documentation>Prepaidcode (given by the customer)</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="10"> <xs:annotation> <xs:documentation>prepaid freight</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>		

```


</xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>prepaid freight including... </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>prepaid freight including...up to border of
origin country</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>prepaid freight including...up to exit border of
last transit country </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>prepaid freight including...up to exit border of
other countries </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>prepaid freight up to border of origin country
</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>prepaid freight up to exit border of last
transit country</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>prepaid freight up to exit border of other
countries </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="20">
  <xs:annotation>
    <xs:documentation>prepaid all costs</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>Free carrier </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>Carriage paid to...</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

<xs:enumeration value="44">
  <xs:annotation>
    <xs:documentation>Delivered duty unpaid</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="45">
  <xs:annotation>
    <xs:documentation>Carriage insurance paid </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="46">
  <xs:annotation>
    <xs:documentation>Delivered at terminal</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="47">
  <xs:annotation>
    <xs:documentation>Delivered at place</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="90">
  <xs:annotation>
    <xs:documentation>not prepaid</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **ProcessType**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	0	documentation New Path Request and allocation process for annual timetable
	enumeration	1	documentation Late Path Request and allocation process for annual timetable
	enumeration	2	documentation Short-term path request and allocation process
	enumeration	3	documentation Rolling Planning path request and allocation process
	enumeration	4	documentation Feasibility Study process
	enumeration	5	documentation Path Modification process (triggered by applicant)
	enumeration	6	documentation Path Alteration process (triggered by IM)
	enumeration	7	documentation Pre-arranged Path publication by RFC
	enumeration	8	documentation Catalogue Path publication by IM

annotation	<p>documentation Process type to further distinguish among type of requests.</p>
source	<pre> <xs:element name="ProcessType"> <xs:annotation> <xs:documentation>Process type to further distinguish among type of requests.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>New Path Request and allocation process for annual timetable</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Late Path Request and allocation process for annual timetable</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Short-term path request and allocation process</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Rolling Planning path request and allocation process</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Feasibility Study process</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>Path Modification process (triggered by applicant)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="6"> <xs:annotation> <xs:documentation>Path Alteration process (triggered by IM)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="7"> <xs:annotation> <xs:documentation>Pre-arranged Path publication by RFC</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="8"> </pre>

	<pre><xs:annotation> <xs:documentation>Catalogue Path publication by IM</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element></pre>
--	--

element **ReasonOfReference**

diagram

Annex D.2

1. Introduction
2. Scope
3. References
4. Definitions
5. Abbreviations
6. Symbols
7. Data and Message Model
8. Data and Message Model
9. Data and Message Model
10. Data and Message Model
11. Data and Message Model
12. Data and Message Model
13. Data and Message Model
14. Data and Message Model
15. Data and Message Model
16. Data and Message Model
17. Data and Message Model
18. Data and Message Model
19. Data and Message Model
20. Data and Message Model
21. Data and Message Model
22. Data and Message Model
23. Data and Message Model
24. Data and Message Model
25. Data and Message Model
26. Data and Message Model
27. Data and Message Model
28. Data and Message Model
29. Data and Message Model
30. Data and Message Model
31. Data and Message Model
32. Data and Message Model
33. Data and Message Model
34. Data and Message Model
35. Data and Message Model
36. Data and Message Model
37. Data and Message Model
38. Data and Message Model
39. Data and Message Model
40. Data and Message Model
41. Data and Message Model
42. Data and Message Model
43. Data and Message Model
44. Data and Message Model
45. Data and Message Model
46. Data and Message Model
47. Data and Message Model
48. Data and Message Model
49. Data and Message Model
50. Data and Message Model
51. Data and Message Model
52. Data and Message Model
53. Data and Message Model
54. Data and Message Model
55. Data and Message Model
56. Data and Message Model
57. Data and Message Model
58. Data and Message Model
59. Data and Message Model
60. Data and Message Model
61. Data and Message Model
62. Data and Message Model
63. Data and Message Model
64. Data and Message Model
65. Data and Message Model
66. Data and Message Model
67. Data and Message Model
68. Data and Message Model
69. Data and Message Model
70. Data and Message Model
71. Data and Message Model
72. Data and Message Model
73. Data and Message Model
74. Data and Message Model
75. Data and Message Model
76. Data and Message Model
77. Data and Message Model
78. Data and Message Model
79. Data and Message Model
80. Data and Message Model
81. Data and Message Model
82. Data and Message Model
83. Data and Message Model
84. Data and Message Model
85. Data and Message Model
86. Data and Message Model
87. Data and Message Model
88. Data and Message Model
89. Data and Message Model
90. Data and Message Model
91. Data and Message Model
92. Data and Message Model
93. Data and Message Model
94. Data and Message Model
95. Data and Message Model
96. Data and Message Model
97. Data and Message Model
98. Data and Message Model
99. Data and Message Model
100. Data and Message Model

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:string		
properties	content simple		
facets	Kind	Value	Annotation
	minLength	4	
	maxLength	4	
	enumeration	1000	documentation Same path offer is desired as for stated PathRequestMessage
	enumeration	1001	documentation Same path is desired as for stated train/path
	enumeration	1002	documentation Full replacement of stated previous path
	enumeration	1003	documentation Partial replacement of stated previous path
	enumeration	1004	documentation Reference to sub train of Y-train bundle
	enumeration	1005	documentation Reference to main train of Y-train bundle
	enumeration	1006	documentation Reference to another PathRequestMessage after interruption train's journey by a foreign infrastructure area
	enumeration	1007	documentation Reference to another PathRequestMessage before interruption train's journey by a foreign infrastructure area
	enumeration	1008	documentation Reference to further path offer for the PathRequestMessage
	enumeration	1009	documentation Reference to booked path before interruption by railway replacement traffic by bus
	enumeration	1010	documentation Reference to a PreArrangedPath
	enumeration	1011	documentation Only the new train object shall be linked with the existing booked path for the specified validity period; no new path elaboration is needed
	enumeration	1012	documentation New final offer to former draft offer
	enumeration	1013	documentation Replaced path after modification by ResponsibleApplicant
	enumeration	1014	documentation New Route
	enumeration	1015	documentation Updated Route
	enumeration	5001	documentation Reference to another object on the basis of incident management in operations phase
	enumeration	DE01	documentation Reference to an associated empty/transfer train
	enumeration	DE02	documentation Reference to an associated main run
	enumeration	DE03	documentation Notice stated PathRequestMessage
	enumeration	DE04	documentation Replacement of stated train
	enumeration	DE05	documentation Reference to a reserved capacity
	enumeration	DE06	documentation Use of same OTN as of stated train
annotation	documentation Indicates the reason/purpose of usage of element RelatedPlannedTransportIdentifier. List of codes for element ReasonOfReference: 1000 = Same path offer is desired as for stated PathRequestMessage		

	<p>(Additional information: For a train requested with more than one PathRequestMessage (all with different bitmaps) the same (or nearly the same) routing and timing at location in path offers for all PathRequestMessages (PathRequestIDs) is desired by Responsible Applicant (if it is possible). RPTID: All other PathRequestIDs).</p> <p>1001 = Same path is desired as for stated train/path (Additional information: For that path request the same (or nearly the same) routing/path elaboration/offer is desired by Responsible Applicant (if it is possible) as for stated train/path (may be in a previous period). RPTID: TrainID or PathID).</p> <p>1002 = Full replacement of stated previous path (Additional information: The current path given in PathDetailsMessage will replace the stated path fully after confirming the path offer. The code is used to mark an alternative offer after PathNotAvailableMessage/PathCanceledMessage or path alteration by IM. Calendar of previous path and offered path contain the same dates. The previous path doesn't exist anymore. RPTID: PathID).</p> <p>1003 = Partial replacement of stated previous path (Additional information: The current path given in PathDetailsMessage will replace the stated path partially after confirming the path offer. The code is used to mark an alternative offer after PathNotAvailableMessage/PathCanceledMessage or path alteration by IM only for a part of the previous calendar/traffic days. Calendar of offered path is only part of the calendar of former and changed path. The calendar of the previous path has to be changed (less days and shorter validity period) after confirmation of the offered path. RPTID: PathID).</p> <p>1004 = Reference to sub train of Y-train bundle (Additional information: The current PathRequestMessage contains the main train of a Y-train bundle; the TrainID stated in RPTID is for the sub train which will be joined with or splitted of the main train.)</p> <p>1005 = Reference to main train of Y-train bundle (Additional information: The current PathRequestMessage contains the sub train of a Y-train bundle. The TrainID stated in RPTID is for the main train with which the sub train will be joined with or splitted of.)</p> <p>1006 = Reference to another PathRequestMessage after interruption train's journey by a foreign infrastructure area (Additional information: The referencing indicates that another PathRequestMessage (specifying PathRequestID as RPTID) for the same train exists after passing a foreign infrastructure area to continue train's journey.)</p> <p>1007 = Reference to another PathRequestMessage before interruption train's journey by a foreign infrastructure area (Additional information: The referencing indicates that another PathRequestMessage (specifying PathRequestID as RPTID) for the same train exists before passing a foreign infrastructure area.)</p> <p>1008 = Reference to further path offer for the PathRequestMessage (Additional information: There are more than one path offers for the PathRequestMessage. RPTID: All other PathID's.)</p> <p>1009 = Reference to booked path before interruption by railway replacement traffic by bus (Additional information: The stated train/path is continued following a railway replacement traffic with that new requested train/path. RPTID: PathID).</p> <p>1010 = Reference to a PreArrangedPath (Additional information: Reference to a PathID of existing PAP, which is to be used by an annual train requested with that PRM. RPTID: PathID).</p> <p>1011 = Only the new train object shall be linked with the existing booked path for the specified validity period; no new path elaboration is needed (Additional information: The code is used, when a new train object has to be linked with an existing booked path for a specified validity period and no new path elaboration is needed. It is used in modification process of planning phase only instead of using UpdateLinkMessage and ObjectInfoMessage. Result: Internal path modification (reduce of validity period of calendar) for previous Path. New path with new PathID for the specified validity period. RPTID: Previous TrainID and PathID).</p> <p>1012 = New final offer to former draft offer (Additional information: Reference to (old) draft offer in case of IM is making a (different) new offer (TypeOfInformation : Final offer). Code is used only in process PathRequest (annual timetable); RPTID : PathID of draft offer.)</p> <p>1013 = Replaced path after modification by ResponsibleApplicant</p>
--	--

	<p>(Additional information: Reference to replaced path when IM is making an offer after receiving PathRequestMessage sent by RA for modification of booked path. Code is used only in Path Modification process in PathDetailsMessage. RPTID: PathID.)</p> <p>1014 = New Route (Additional information: Reference to previous Route replaced by the new Route)</p> <p>1015 = Updated Route (Additional information: Reference to the Route that is updated)</p> <p>5001 = Reference to another object on the basis of incident management in operations phase Specific code only for one IM/national codes:</p> <p>DE01 = Reference to an associated empty/transfer train (Additional information: Stated train is a related train without passengers before or behind the current requested path for a train with passengers. RPTID: TrainID.)</p> <p>DE02 = Reference to an associated main run (Additional information: Stated train is a related train with passengers before or behind the current requested path for a train without passengers. RPTID: TrainID.)</p> <p>DE03 = Notice stated PathRequestMessage (Additional information: For path elaboration of current PathRequestMessage the stated PathRequestMessage should be considered. RPTID: PathRequestID.)</p> <p>DE04 = Replacement of stated train (Additional information: Full or partial replacement of the named former train; example: Change of passenger trainset (like ICE or TGV) by set of loco and wagons in case of technical problems, delay or other reasons. It is not only change of TrainID. RPTID: TrainID.)</p> <p>DE05 = Reference to a reserved capacity (Additional information: This code can be used to refer to a study offer (with booking option) as a result of the KFB process (internal process for a specific product of DB Netz). RPTID: PathID.)</p> <p>DE06 = Use of same OTN as of stated train (Additional information: Responsible Applicant wants to use same OTN as in stated train because of all trains are part of same family. The trains have only slightly differences on various days. RPTID: TrainID.)</p>
source	<pre><xs:element name="ReasonOfReference"> <xs:annotation> <xs:documentation>Indicates the reason/purpose of usage of element RelatedPlannedTransportIdentifier.</pre> <p>List of codes for element ReasonOfReference:</p> <p>1000 = Same path offer is desired as for stated PathRequestMessage (Additional information: For a train requested with more than one PathRequestMessage (all with different bitmapdays) the same (or nearly the same) routing and timing at location in path offers for all PathRequestMessages (PathRequestIDs) is desired by Responsible Applicant (if it is possible). RPTID: All others PathRequestIDs).</p> <p>1001 = Same path is desired as for stated train/path (Additional information: For that path request the same (or nearly the same) routing/path elaboration/offer is desired by Responsible Applicant (if it is possible) as for stated train/path (may be in a previous period). RPTID: TrainID or PathID).</p> <p>1002 = Full replacement of stated previous path (Additional information: The current path given in PathDetailsMessage will replace the stated path fully after confirming the path offer. The code is used to mark an alternative offer after</p>

PathNotAvailableMessage/PathCanceledMessage or path alteration by IM.
 Calendar of
 previous path and offered path contain the same dates. The previous path doesn't exist anymore. RPTID: PathID).

1003 = Partial replacement of stated previous path
 (Additional information: The current path given in PathDetailsMessage will replace the stated path partially after confirming the path offer.
 The code is used to mark an alternative offer after PathNotAvailableMessage/PathCanceledMessage or path alteration by IM only for a part of
 the previous calendar/traffic days. Calendar of offered path is only part of the calendar of former and changed path. The calendar of the previous
 path has to changed (less days and shorter validity period) after confirmation of the offered path. RPTID: PathID).

1004 = Reference to sub train of Y-train bundle
 (Additional information: The current PathRequestMessage contains the main train of a Y-train bundle; the TrainID stated in RPTID is for the sub train which will be joined with or splitted of the main train.)

1005 = Reference to main train of Y-train bundle
 (Additional information: The current PathRequestMessage contains the sub train of a Y-train bundle. The TrainID stated in RPTID is for the main train with which the sub train will be joined with or splitted of.)

1006 = Reference to another PathRequestMessage after interruption train's journey by a foreign infrastructure area
 (Additional information: The referencing indicates that another PathRequestMessage (specifying PathRequestID as RPTID) for the same train exists after passing a foreign infrastructure area to continue train's journey.)

1007 = Reference to another PathRequestMessage before interruption train's journey by a foreign infrastructure area
 (Additional information: The referencing indicates that another PathRequestMessage (specifying PathRequestID as RPTID) for the same train exists before passing a foreign infrastructure area.)

1008 = Reference to further path offer for the PathRequestMessage
 (Additional information: There are more than one path offers for the PathRequestMessage. RPTID: All other PathID's.)

1009 = Reference to booked path before interruption by railway replacement traffic by bus
 (Additional information: The stated train/path is continued following a railway replacement traffic with that new requested train/path. RPTID: PathID).

1010 = Reference to a PreArrangedPath
 (Additional information: Reference to a PathID of existing PAP, which is to be used by an annual train requested with that PRM. RPTID: PathID).

1011 = Only the new train object shall be linked with the existing booked path for the specified validity period; no new path elaboration is needed
 (Additional information: The code is used, when a new train object has to be linked with an existing booked path for a specified validity period and no new path elaboration is needed. It is used in modification process of planning phase only instead of using UpdateLinkMessage and ObjectInfoMessage. Result: Internal path modification (reduce of validity period of calendar) for previous Path. New path with new PathID for the specified validity period. RPTID: Previous TrainID and PathID).

1012 = New final offer to former draft offer
 (Additional information: Reference to (old) draft offer in case of IM is making a (different) new offer (TypeOfInformation : Final offer).

Code is used only in process PathRequest (annual timetable); RPTID : PathID of draft offer.)

1013 = Replaced path after modification by ResponsibleApplicant
 (Additional information: Reference to replaced path when IM is making an offer after receiving PathRequestMessage sent by RA for modification of booked path. Code is used only in Path Modification process in PathDetailsMessage. RPTID: PathID.)

1014 = New Route
 (Additional information: Reference to previous Route replaced by the new Route)

1015 = Updated Route
 (Additional information: Reference to the Route that is updated)

5001 = Reference to another object on the basis of incident management in operations phase
 Specific code only for one IM/national codes:

DE01 = Reference to an associated empty/transfer train
 (Additional information: Stated train is a related train without passengers before or behind the current requested path for a train with passengers. RPTID: TrainID.)

DE02 = Reference to an associated main run
 (Additional information: Stated train is a related train with passengers before or behind the current requested path for a train without passengers. RPTID: TrainID.)

DE03 = Notice stated PathRequestMessage
 (Additional information: For path elaboration of current PathRequestMessage the stated PathRequestMessage should be considered. RPTID: PathRequestID.)

DE04 = Replacement of stated train
 (Additional information: Full or partial replacement of the named former train; example: Change of passenger trainset (like ICE or TGV) by set of loco and wagons in case of technical problems, delay or other reasons. It is not only change of TrainID. RPTID: TrainID.)

DE05 = Reference to a reserved capacity
 (Additional information: This code can be used to refer to a study offer (with booking option) as a result of the KFB process (internal process for a specific product of DB Netz). RPTID: PathID.)

DE06 = Use of same OTN as of stated train
 (Additional information: Responsible Applicant wants to use same OTN as in stated train because of all trains are part of same family. The trains have only slightly differences on various days. RPTID: TrainID.)

```

</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="4"/>
    <xs:maxLength value="4"/>
    <xs:enumeration value="1000">
      <xs:annotation>
        <xs:documentation>Same path offer is desired as for stated
PathRequestMessage</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="1001">
      <xs:annotation>

```

```

    <xs:documentation>Same path is desired as for stated
train/path</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1002">
  <xs:annotation>
    <xs:documentation>Full replacement of stated previous
path</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1003">
  <xs:annotation>
    <xs:documentation>Partial replacement of stated previous
path</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1004">
  <xs:annotation>
    <xs:documentation>Reference to sub train of Y-train
bundle</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1005">
  <xs:annotation>
    <xs:documentation>Reference to main train of Y-train
bundle</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1006">
  <xs:annotation>
    <xs:documentation>Reference to another PathRequestMessage after
interruption train's journey by a foreign infrastructure
area</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1007">
  <xs:annotation>
    <xs:documentation>Reference to another PathRequestMessage before
interruption train's journey by a foreign infrastructure
area</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1008">
  <xs:annotation>
    <xs:documentation>Reference to further path offer for the
PathRequestMessage</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1009">
  <xs:annotation>
    <xs:documentation>Reference to booked path before interruption by
railway replacement traffic by bus</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1010">
  <xs:annotation>
    <xs:documentation>Reference to a
PreArrangedPath</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```




```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="1011">
  <xs:annotation>
    <xs:documentation>Only the new train object shall be linked with
the existing booked path for the specified validity period; no new path
elaboration is needed</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1012">
  <xs:annotation>
    <xs:documentation>New final offer to former draft
offer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1013">
  <xs:annotation>
    <xs:documentation>Replaced path after modification by
ResponsibleApplicant</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1014">
  <xs:annotation>
    <xs:documentation>New Route</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="1015">
  <xs:annotation>
    <xs:documentation>Updated Route</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="5001">
  <xs:annotation>
    <xs:documentation>Reference to another object on the basis of
incident management in operations phase</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DE01">
  <xs:annotation>
    <xs:documentation>Reference to an associated empty/transfer
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DE02">
  <xs:annotation>
    <xs:documentation>Reference to an associated main
run</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DE03">
  <xs:annotation>
    <xs:documentation>Notice stated
PathRequestMessage</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="DE04">
  <xs:annotation>
    <xs:documentation>Replacement of stated train</xs:documentation>


```

	<pre> </xs:annotation> </xs:enumeration> <xs:enumeration value="DE05"> <xs:annotation> <xs:documentation>Reference to a reserved capacity</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="DE06"> <xs:annotation> <xs:documentation>Use of same OTN as of stated train</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **RefusalCode**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td>documentation Data not authorised by Wagon Keeper</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Wagon number freight unknown</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1	documentation Data not authorised by Wagon Keeper	enumeration	2	documentation Wagon number freight unknown
Kind	Value	Annotation								
enumeration	1	documentation Data not authorised by Wagon Keeper								
enumeration	2	documentation Wagon number freight unknown								
annotation	documentation Code List Candidate									
source	<pre> <xs:element name="RefusalCode"> <xs:annotation> <xs:documentation>Code List Candidate</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Data not authorised by Wagon Keeper</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Wagon number freight unknown</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **RollingRoadUnitType**

diagram																
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:token															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>HGZ</td> <td>documentation articulated lorry</td> </tr> <tr> <td>enumeration</td> <td>SAL</td> <td>documentation semi-trailer</td> </tr> <tr> <td>enumeration</td> <td>MW</td> <td>documentation motor vehicle</td> </tr> <tr> <td>enumeration</td> <td>ANH</td> <td>documentation trailer</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	HGZ	documentation articulated lorry	enumeration	SAL	documentation semi-trailer	enumeration	MW	documentation motor vehicle	enumeration	ANH	documentation trailer
Kind	Value	Annotation														
enumeration	HGZ	documentation articulated lorry														
enumeration	SAL	documentation semi-trailer														
enumeration	MW	documentation motor vehicle														
enumeration	ANH	documentation trailer														
annotation	documentation Type of Rolling Road unit on Wagon															
source	<pre> <xs:element name="RollingRoadUnitType"> <xs:annotation> <xs:documentation>Type of Rolling Road unit on Wagon</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="HGZ"> <xs:annotation> <xs:documentation>articulated lorry</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="SAL"> <xs:annotation> <xs:documentation>semi-trailer</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="MW"> <xs:annotation> <xs:documentation>motor vehicle</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ANH"> <xs:annotation> <xs:documentation>trailer</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>															

element **RouteClass**

<p>diagram</p>																																																																																		
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>																																																																																	
<p>type</p>	<p>restriction of xs:string</p>																																																																																	
<p>properties</p>	<p>content simple</p>																																																																																	
<p>facets</p>	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>minLength</td><td>1</td><td></td></tr> <tr><td>maxLength</td><td>3</td><td></td></tr> <tr><td>enumeration</td><td>A</td><td></td></tr> <tr><td>enumeration</td><td>B</td><td></td></tr> <tr><td>enumeration</td><td>B1</td><td></td></tr> <tr><td>enumeration</td><td>B2</td><td></td></tr> <tr><td>enumeration</td><td>C</td><td></td></tr> <tr><td>enumeration</td><td>C2</td><td></td></tr> <tr><td>enumeration</td><td>C3</td><td></td></tr> <tr><td>enumeration</td><td>C4</td><td></td></tr> <tr><td>enumeration</td><td>CM</td><td></td></tr> <tr><td>enumeration</td><td>CM2</td><td></td></tr> <tr><td>enumeration</td><td>CM3</td><td></td></tr> <tr><td>enumeration</td><td>CM4</td><td></td></tr> <tr><td>enumeration</td><td>CE</td><td></td></tr> <tr><td>enumeration</td><td>D</td><td></td></tr> <tr><td>enumeration</td><td>D2</td><td></td></tr> <tr><td>enumeration</td><td>D3</td><td></td></tr> <tr><td>enumeration</td><td>D4</td><td></td></tr> <tr><td>enumeration</td><td>D5</td><td></td></tr> <tr><td>enumeration</td><td>E</td><td></td></tr> <tr><td>enumeration</td><td>E4</td><td></td></tr> <tr><td>enumeration</td><td>E5</td><td></td></tr> <tr><td>enumeration</td><td>E6</td><td></td></tr> <tr><td>enumeration</td><td>F</td><td></td></tr> <tr><td>enumeration</td><td>G</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	minLength	1		maxLength	3		enumeration	A		enumeration	B		enumeration	B1		enumeration	B2		enumeration	C		enumeration	C2		enumeration	C3		enumeration	C4		enumeration	CM		enumeration	CM2		enumeration	CM3		enumeration	CM4		enumeration	CE		enumeration	D		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	E		enumeration	E4		enumeration	E5		enumeration	E6		enumeration	F		enumeration	G	
Kind	Value	Annotation																																																																																
minLength	1																																																																																	
maxLength	3																																																																																	
enumeration	A																																																																																	
enumeration	B																																																																																	
enumeration	B1																																																																																	
enumeration	B2																																																																																	
enumeration	C																																																																																	
enumeration	C2																																																																																	
enumeration	C3																																																																																	
enumeration	C4																																																																																	
enumeration	CM																																																																																	
enumeration	CM2																																																																																	
enumeration	CM3																																																																																	
enumeration	CM4																																																																																	
enumeration	CE																																																																																	
enumeration	D																																																																																	
enumeration	D2																																																																																	
enumeration	D3																																																																																	
enumeration	D4																																																																																	
enumeration	D5																																																																																	
enumeration	E																																																																																	
enumeration	E4																																																																																	
enumeration	E5																																																																																	
enumeration	E6																																																																																	
enumeration	F																																																																																	
enumeration	G																																																																																	
<p>annotation</p>	<p>documentation Indication of the route class (based on CEN EN 15528: line categories for managing the interface between load limits of vehicles on infrastructure). All the codes in this code list refer to CEN EN 15528: line categories for managing the interface between load limits of vehicles on infrastructure. CM2, CM3 and CM 4 equal M2, M3 and M4 which might be used in some legacy systems which only support two character codes.</p>																																																																																	
<p>source</p>	<pre><xs:element name="RouteClass"> <xs:annotation> <xs:documentation>Indication of the route class (based on CEN EN 15528: line categories for managing the interface between load limits of vehicles</pre>																																																																																	

```

on infrastructure). All the codes in this code list refer to CEN EN 15528:
line categories for managing the interface between load limits of vehicles
on infrastructure.
CM2, CM3 and CM 4 equal M2, M3 and M4 which might be used in some legacy
systems which only support two character codes.</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="3"/>
    <xs:enumeration value="A"/>
    <xs:enumeration value="B"/>
    <xs:enumeration value="B1"/>
    <xs:enumeration value="B2"/>
    <xs:enumeration value="C"/>
    <xs:enumeration value="C2"/>
    <xs:enumeration value="C3"/>
    <xs:enumeration value="C4"/>
    <xs:enumeration value="CM"/>
    <xs:enumeration value="CM2"/>
    <xs:enumeration value="CM3"/>
    <xs:enumeration value="CM4"/>
    <xs:enumeration value="CE"/>
    <xs:enumeration value="D"/>
    <xs:enumeration value="D2"/>
    <xs:enumeration value="D3"/>
    <xs:enumeration value="D4"/>
    <xs:enumeration value="D5"/>
    <xs:enumeration value="E"/>
    <xs:enumeration value="E4"/>
    <xs:enumeration value="E5"/>
    <xs:enumeration value="E6"/>
    <xs:enumeration value="F"/>
    <xs:enumeration value="G"/>
  </xs:restriction>
</xs:simpleType>
</xs:element>

```

element **RU_DeclarationCode**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	content simple		
facets	Kind	Value	Annotation
	enumeration	1	documentation Without packing
	enumeration	2	documentation Unsatisfactory packaging: ...(give details)
	enumeration	3	documentation Insufficient packaging: ... (give details)
	enumeration	4.1	documentation Goods clearly in poor condition: ... (give details)
	enumeration	4.2	documentation

	<p>enumeration 4.3 Goods damaged:(give details) documentation</p> <p>enumeration 4.4 Goods wet: ... (give details) documentation</p> <p>enumeration 5 Goods frozen: ... (give details) documentation</p> <p>enumeration 6 Loaded by the consignor documentation</p> <p>enumeration 7 Loaded by the carrier in inclement weather at the request of the consignor documentation</p> <p>enumeration 8 Unloaded by the consignee documentation</p> <p>enumeration 9.1 Unloaded by the carrier in ... documentation</p> <p>enumeration 9.2 Inclement weather, at the request of the consignee Impossible to make the examination in accordance with CIM Article 11 section 3, because of inclement weather documentation</p> <p>enumeration 9.3 Inclement weather, at the request of the consignee Impossible to make the examination in accordance with CIM Article 11 section 3, because of sealing of the wagon or ITU documentation</p> <p>enumeration 10 Inclement weather, at the request of the consignee Impossible to make the examination in accordance with CIM Article 11 section 3, because of load in the wagon or ITU inaccessible documentation</p> <p>enumeration 11 Request for examination in accordance with CIM Article 11 section 3 presented late by the consignor documentation</p> <p>enumeration 12 Examination not made because of a shortage of resources: ... (give details) documentation</p> <p>enumeration 13 Other reserves: ... (give details) documentation</p> <p>Code used for declarations, which are no reservations. This code is not included in the official CIT code list and is not to be printed on the paper consignment note.</p>
annotation	<p>documentation Carrier declaration code.</p>
source	<pre><xs:element name="RU_DeclarationCode"> <xs:annotation> <xs:documentation>Carrier declaration code. </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Without packing</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Unsatisfactory packaging: ...(give details)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Insufficient packaging: ... (give details)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4.1"> <xs:annotation></pre>

```


    <xs:documentation>Goods clearly in poor condition: ... (give
details)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4.2">
  <xs:annotation>
    <xs:documentation>Goods damaged:(give details)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4.3">
  <xs:annotation>
    <xs:documentation>Goods wet: ... (give details)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="4.4">
  <xs:annotation>
    <xs:documentation>Goods frozen: ... (give
details)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="5">
  <xs:annotation>
    <xs:documentation>Loaded by the consignor</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="6">
  <xs:annotation>
    <xs:documentation>Loaded by the carrier in inclement weather at
the request of the consignor </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7">
  <xs:annotation>
    <xs:documentation>Unloaded by the consignee</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="8">
  <xs:annotation>
    <xs:documentation>Unloaded by the carrier in
...</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9.1">
  <xs:annotation>
    <xs:documentation>Inclement weather, at the request of the
consignee Impossible to make the examination in accordance with CIM Article
11 section 3, because of inclement weather </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9.2">
  <xs:annotation>
    <xs:documentation>Inclement weather, at the request of the
consignee Impossible to make the examination in accordance with CIM Article
11 section 3, because of sealing of the wagon or ITU </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9.3">
  <xs:annotation>

```

```

<xs:documentation>Inclement weather, at the request of the
consignee Impossible to make the examination in accordance with CIM Article
11 section 3, because of load in the wagon or ITU inaccessible
</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
<xs:annotation>
<xs:documentation>Request for examination in accordance with CIM
Article 11 section 3 presented late by the consignor</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
<xs:annotation>
<xs:documentation>Examination not made because of a shortage of
resources: ... (give details)</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
<xs:annotation>
<xs:documentation>Other reserves: ... (give
details)</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
<xs:annotation>
<xs:documentation>Code used for declarations, which are no
reservations. This code is not included in the official CIT code list and is
not to be printed on the paper consignment note.</xs:documentation>
</xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **TractionMode**

diagram			
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:integer		
properties	content	simple	
facets	Kind	Value	Annotation
	minInclusive	11	
	maxInclusive	99	
	enumeration	11	documentation Train traction - 1st traction unit in the group
	enumeration	21	documentation Intermediate traction - 1st traction unit in the group
	enumeration	31	documentation Banking locomotive - 1st traction unit in the group

	enumeration 41	documentation Banking locomotive not coupled - 1st traction unit in the group
	enumeration 51	documentation No Leading Engine - 1st traction unit in the group
	enumeration 12	documentation Train traction - 2nd traction unit in the group
	enumeration 22	documentation Intermediate traction - 2nd traction unit in the group
	enumeration 32	documentation Banking locomotive - 2nd traction unit in the group
	enumeration 42	documentation Banking locomotive not coupled - 2nd traction unit in the group
	enumeration 52	documentation No Leading Engine - 2nd traction unit in the group
	enumeration 13	documentation Train traction - 3rd traction unit in the group
	enumeration 23	documentation Intermediate traction - 3rd traction unit in the group
	enumeration 33	documentation Banking locomotive - 3rd traction unit in the group
	enumeration 43	documentation Banking locomotive not coupled - 3rd traction unit in the group
	enumeration 53	documentation No Leading Engine - 3rd traction unit in the group
	enumeration 14	documentation Train traction - 4th traction unit in the group
	enumeration 24	documentation Intermediate traction - 4th traction unit in the group
	enumeration 34	documentation Banking locomotive - 4th traction unit in the group
	enumeration 44	documentation Banking locomotive not coupled - 4th traction unit in the group
	enumeration 54	documentation No Leading Engine - 4th traction unit in the group
	enumeration 15	documentation Train traction - 5th traction unit in the group
	enumeration 25	documentation Intermediate traction - 5th traction unit in the group
	enumeration 35	documentation Banking locomotive - 5th traction unit in the group
	enumeration 45	documentation Banking locomotive not coupled - 5th traction unit in the group
	enumeration 55	documentation No Leading Engine - 5th traction unit in the group
	enumeration 16	documentation Train traction - 6th traction unit in the group
	enumeration 26	documentation Intermediate traction - 6th traction unit in the group
	enumeration 36	documentation Banking locomotive - 6th traction unit in the group
	enumeration 46	documentation Banking locomotive not coupled - 6th traction unit in the group
	enumeration 56	documentation No Leading Engine - 6th traction unit in the group
annotation		documentation Identifies the mode of deployment of a traction within a train First digit – traction role Second digit – position in group of traction units with the same role
source		<xs:element name="TractionMode"> <xs:annotation> <xs:documentation>Identifies the mode of deployment of a traction within a train

```

First digit - traction role
Second digit - position in group of traction units with the same role
</xs:documentation>
</xs:annotation>
<xs:simpleType>
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="11"/>
    <xs:maxInclusive value="99"/>
    <xs:enumeration value="11">
      <xs:annotation>
        <xs:documentation>Train traction - 1st traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="21">
      <xs:annotation>
        <xs:documentation>Intermediate traction - 1st traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="31">
      <xs:annotation>
        <xs:documentation>Banking locomotive - 1st traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="41">
      <xs:annotation>
        <xs:documentation>Banking locomotive not coupled - 1st traction
unit in the group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="51">
      <xs:annotation>
        <xs:documentation>No Leading Engine - 1st traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="12">
      <xs:annotation>
        <xs:documentation>Train traction - 2nd traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="22">
      <xs:annotation>
        <xs:documentation>Intermediate traction - 2nd traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="32">
      <xs:annotation>
        <xs:documentation>Banking locomotive - 2nd traction unit in the
group</xs:documentation>
      </xs:annotation>
    </xs:enumeration>
    <xs:enumeration value="42">
      <xs:annotation>

```

```

    <xs:documentation>Banking locomotive not coupled - 2nd traction
unit in the group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="52">
  <xs:annotation>
    <xs:documentation>No Leading Engine - 2nd traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>Train traction - 3rd traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="23">
  <xs:annotation>
    <xs:documentation>Intermediate traction - 3rd traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="33">
  <xs:annotation>
    <xs:documentation>Banking locomotive - 3rd traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>Banking locomotive not coupled - 3rd traction
unit in the group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="53">
  <xs:annotation>
    <xs:documentation>No Leading Engine - 3rd traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>Train traction - 4th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="24">
  <xs:annotation>
    <xs:documentation>Intermediate traction - 4th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="34">
  <xs:annotation>
    <xs:documentation>Banking locomotive - 4th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```


<xs:enumeration value="44">
  <xs:annotation>
    <xs:documentation>Banking locomotive not coupled - 4th traction
unit in the group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="54">
  <xs:annotation>
    <xs:documentation>No Leading Engine - 4th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>Train traction - 5th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>Intermediate traction - 5th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="35">
  <xs:annotation>
    <xs:documentation>Banking locomotive - 5th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="45">
  <xs:annotation>
    <xs:documentation>Banking locomotive not coupled - 5th traction
unit in the group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="55">
  <xs:annotation>
    <xs:documentation>No Leading Engine - 5th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>Train traction - 6th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="26">
  <xs:annotation>
    <xs:documentation>Intermediate traction - 6th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="36">
  <xs:annotation>
    <xs:documentation>Banking locomotive - 6th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="46">
  <xs:annotation>
    <xs:documentation>Banking locomotive not coupled - 6th traction
unit in the group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="56">
  <xs:annotation>
    <xs:documentation>No Leading Engine - 6th traction unit in the
group</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```


element **TractionType**

<p>diagram</p>	 <p>Identifies the type of a locomotive: First digit: "0" = not specified "1" = external electric power supply for traction (catenary and pantograph, third rail or other such as maglev) "2" = on-board traction power supply for traction without external electrical or other power supply available "3" = hybrid traction (both on-board or electric traction available) Second digit (definitions in chapter 2.2.2 of the LOC and PA5 TSI 1302/2014): "0" = not specified "1" = locomotive or power unit "2" = trainset or multiple unit or railcar "3" = shunter "4" = on track machine or infrastructure inspection vehicle</p>																																										
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>																																										
<p>type</p>	<p>restriction of xs:token</p>																																										
<p>properties</p>	<p>content simple</p>																																										
<p>facets</p>	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>00</td><td></td></tr> <tr><td>enumeration</td><td>01</td><td></td></tr> <tr><td>enumeration</td><td>02</td><td></td></tr> <tr><td>enumeration</td><td>03</td><td></td></tr> <tr><td>enumeration</td><td>04</td><td></td></tr> <tr><td>enumeration</td><td>10</td><td></td></tr> <tr><td>enumeration</td><td>11</td><td></td></tr> <tr><td>enumeration</td><td>12</td><td></td></tr> <tr><td>enumeration</td><td>13</td><td></td></tr> <tr><td>enumeration</td><td>14</td><td></td></tr> <tr><td>enumeration</td><td>20</td><td></td></tr> <tr><td>enumeration</td><td>21</td><td></td></tr> <tr><td>enumeration</td><td>22</td><td></td></tr> </tbody> </table>	Kind	Value	Annotation	enumeration	00		enumeration	01		enumeration	02		enumeration	03		enumeration	04		enumeration	10		enumeration	11		enumeration	12		enumeration	13		enumeration	14		enumeration	20		enumeration	21		enumeration	22	
Kind	Value	Annotation																																									
enumeration	00																																										
enumeration	01																																										
enumeration	02																																										
enumeration	03																																										
enumeration	04																																										
enumeration	10																																										
enumeration	11																																										
enumeration	12																																										
enumeration	13																																										
enumeration	14																																										
enumeration	20																																										
enumeration	21																																										
enumeration	22																																										


	<p>enumeration 23 enumeration 24 enumeration 30 enumeration 31 enumeration 32 enumeration 33 enumeration 34</p>
<p>annotation</p>	<p>documentation Identifies the type of a locomotive: First digit: "0" = not specified "1" = external electric power supply for traction (catenary and pantograph, third rail or other such as maglev) "2" = on-board traction power supply for traction without external electrical or other power supply available "3" = hybrid traction (both on-board or electric traction available) Second digit (definitions in chapter 2.2.2 of the LOC and PAS TSI 1302/2014): "0" = not specified "1" = locomotive or power unit "2" = trainset or multiple unit or railcar "3" = shunter "4" = on track machine or infrastructure inspection vehicle</p>
<p>source</p>	<pre> <xs:element name="TractionType"> <xs:annotation> <xs:documentation>Identifies the type of a locomotive: First digit: "0" = not specified "1" = external electric power supply for traction (catenary and pantograph, third rail or other such as maglev) "2" = on-board traction power supply for traction without external electrical or other power supply available "3" = hybrid traction (both on-board or electric traction available) Second digit (definitions in chapter 2.2.2 of the LOC and PAS TSI 1302/2014): "0" = not specified "1" = locomotive or power unit "2" = trainset or multiple unit or railcar "3" = shunter "4" = on track machine or infrastructure inspection vehicle </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="00"/> <xs:enumeration value="01"/> <xs:enumeration value="02"/> <xs:enumeration value="03"/> <xs:enumeration value="04"/> <xs:enumeration value="10"/> <xs:enumeration value="11"/> <xs:enumeration value="12"/> <xs:enumeration value="13"/> <xs:enumeration value="14"/> <xs:enumeration value="20"/> <xs:enumeration value="21"/> <xs:enumeration value="22"/> <xs:enumeration value="23"/> <xs:enumeration value="24"/> </xs:restriction> </xs:simpleType> </pre>

	<pre> <xs:enumeration value="30"/> <xs:enumeration value="31"/> <xs:enumeration value="32"/> <xs:enumeration value="33"/> <xs:enumeration value="34"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	--

element **TrainRadioSystem**


diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:token									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1		enumeration	2	
Kind	Value	Annotation								
enumeration	1									
enumeration	2									
annotation	documentation The on board radio system of the train in coded format									
source	<pre> <xs:element name="TrainRadioSystem"> <xs:annotation> <xs:documentation>The on board radio system of the train in coded format</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"/> <xs:enumeration value="2"/> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

element **TrainRunningInterruptionStatus**

diagram	
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3
properties	content complex
children	TrainInterrupted
source	<pre> <xs:element name="TrainRunningInterruptionStatus"> <xs:complexType> <xs:sequence> <xs:element name="TrainInterrupted"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> </pre>

	<pre> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>Not Interrupted</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Interrupted at location (default)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Will be interrupted, not yet at location</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </xs:sequence> </xs:complexType> </xs:element> </pre>
--	--


element **TrainRunningInterruptionStatus/TrainInterrupted**

diagram													
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:integer												
properties	content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td>documentation Not Interrupted</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation Interrupted at location (default)</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Will be interrupted, not yet at location</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0	documentation Not Interrupted	enumeration	1	documentation Interrupted at location (default)	enumeration	2	documentation Will be interrupted, not yet at location
Kind	Value	Annotation											
enumeration	0	documentation Not Interrupted											
enumeration	1	documentation Interrupted at location (default)											
enumeration	2	documentation Will be interrupted, not yet at location											
source	<pre> <xs:element name="TrainInterrupted"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>Not Interrupted</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Interrupted at location (default)</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>												


```


<xs:enumeration value="2">
  <xs:annotation>
    <xs:documentation>Will be interrupted, not yet at
location</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:element>
    
```

element **TrainType**

diagram	 <p>Element TrainType defines the main purpose of the train in a fundamental way. These purposes are: Transport of passengers Transport of freight/goods Transport of passengers and freight/goods Train only for run of traction unit/locomotive Train of the IM in case of emergency The element is not repeatable, and it does not support any overlapping meaning.</p>																								
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																								
type	restriction of xs:integer																								
properties	content simple																								
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>0</td> <td>documentation Other train</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td>documentation Passenger train</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Freight train</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation Light engine (locomotive train)</td> </tr> <tr> <td>enumeration</td> <td>4</td> <td>documentation Engineering train</td> </tr> <tr> <td>enumeration</td> <td>5</td> <td>documentation Emergency train</td> </tr> <tr> <td>enumeration</td> <td>6</td> <td>documentation Mixed train (passenger and freight train in combination)</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	0	documentation Other train	enumeration	1	documentation Passenger train	enumeration	2	documentation Freight train	enumeration	3	documentation Light engine (locomotive train)	enumeration	4	documentation Engineering train	enumeration	5	documentation Emergency train	enumeration	6	documentation Mixed train (passenger and freight train in combination)
Kind	Value	Annotation																							
enumeration	0	documentation Other train																							
enumeration	1	documentation Passenger train																							
enumeration	2	documentation Freight train																							
enumeration	3	documentation Light engine (locomotive train)																							
enumeration	4	documentation Engineering train																							
enumeration	5	documentation Emergency train																							
enumeration	6	documentation Mixed train (passenger and freight train in combination)																							
annotation	<p>documentation Element TrainType defines the main purpose of the train in a fundamental way. These purposes are: Transport of passengers Transport of freight/goods Transport of passengers and freight/goods Train only for run of traction unit/locomotive Train of the IM in case of emergency The element is not repeatable, and it does not support any overlapping meaning.</p>																								
source	<pre> <xs:element name="TrainType"> <xs:annotation> <xs:documentation>Element TrainType defines the main purpose of the train in a fundamental way. These purposes are: Transport of passengers Transport of freight/goods Transport of passengers and freight/goods Train only for run of traction unit/locomotive </pre>																								

	<p>Train of the IM in case of emergency The element is not repeatable, and it does not support any overlapping meaning.</p> <pre> </xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:integer"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>Other train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Passenger train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Freight train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Light engine (locomotive train)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Engineering train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>Emergency train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="6"> <xs:annotation> <xs:documentation>Mixed train (passenger and freight train in combination)</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **TypeOfRemovableAccessories**

<p>diagram</p>	
<p>namespace</p>	<p>http://www.era.europa.eu/schemes/TAFTSI/3.3</p>
<p>type</p>	<p>restriction of xs:token</p>

properties	content	simple	
facets	Kind	Value	Annotation
	enumeration	01	documentation Removable stanchion
	enumeration	02	documentation Removable side flap of flat wagon
	enumeration	03	documentation Removable end flap of flat wagon
	enumeration	04	documentation Removable side rail
	enumeration	05	documentation Removable intermediate upright for securing the load
	enumeration	06	documentation Stanchion chain
	enumeration	07	documentation Removable handle and wheel for winch on car-carrying wagon
	enumeration	08	documentation Swivelling bolster (with stanchions)
	enumeration	09	documentation Coupling rod (rigid coupling)
	enumeration	10	documentation Ice bunker
	enumeration	11	documentation Ice bunker screen
	enumeration	12	documentation Ice bunker frame
	enumeration	13	documentation Trestle or bar with hooks for hanging meat
	enumeration	14	documentation Movable cross-member of wagon with low loading plane
	enumeration	15	documentation Removable support
	enumeration	16	documentation Mooring cross-member on wagon for special loads
	enumeration	17	documentation Movable floor panel on wagon for special loads
	enumeration	18	documentation Scotch
	enumeration	19	documentation Skid bar with or without shoes on car-carrying wagon
	enumeration	20	documentation Mooring strap on car-carrying wagon
	enumeration	21	documentation Beam for movable ramp on car-carrying wagon
	enumeration	22	documentation Spare heating half-coupling
	enumeration	23	documentation Fire extinguisher
	enumeration	24	documentation Wheel scotches (for cars) on car-carrying wagon
	enumeration	25	documentation Gangway loading ramp on car-carrying wagon
	enumeration	26	documentation Metal cradles for rolls of metal sheeting
	enumeration	27	documentation Panel for covering markings
	enumeration	28	documentation Loading frame for special types of goods
enumeration	29	documentation Headstock for "rolling roads"	
enumeration	99	documentation Other wagon accessories	

annotation	<p>documentation Specification of removable accessory. Should be added to Code List. Values refer to UIC Leaflet 920-13</p>
source	<pre> <xs:element name="TypeOfRemovableAccessories"> <xs:annotation> <xs:documentation>Specification of removable accessory. Should be added to Code List. Values refer to UIC Leaflet 920- 13</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="01"> <xs:annotation> <xs:documentation>Removable stanchion</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="02"> <xs:annotation> <xs:documentation>Removable side flap of flat wagon</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="03"> <xs:annotation> <xs:documentation>Removable end flap of flat wagon</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="04"> <xs:annotation> <xs:documentation>Removable side rail</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="05"> <xs:annotation> <xs:documentation>Removable intermediate upright for securing the load</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="06"> <xs:annotation> <xs:documentation>Stanchion chain</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="07"> <xs:annotation> <xs:documentation>Removable handle and wheel for winch on car- carrying wagon</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="08"> <xs:annotation> <xs:documentation>Swivelling bolster (with stanchions)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="09"> </pre>

```

    <xs:annotation>
      <xs:documentation>Coupling rod (rigid coupling)</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="10">
    <xs:annotation>
      <xs:documentation>Ice bunker</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="11">
    <xs:annotation>
      <xs:documentation>Ice bunker screen</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="12">
    <xs:annotation>
      <xs:documentation>Ice bunker frame</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="13">
    <xs:annotation>
      <xs:documentation>Trestle or bar with hooks for hanging
meat</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="14">
    <xs:annotation>
      <xs:documentation>Movable cross-member of wagon with low loading
plane</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="15">
    <xs:annotation>
      <xs:documentation>Removable support</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="16">
    <xs:annotation>
      <xs:documentation>Mooring cross-member on wagon for special
loads</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="17">
    <xs:annotation>
      <xs:documentation>Movable floor panel on wagon for special
loads</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="18">
    <xs:annotation>
      <xs:documentation>Scotch</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="19">
    <xs:annotation>
      <xs:documentation>Skid bar with or without shoes on car-carrying
wagon</xs:documentation>
    </xs:annotation>
  </xs:enumeration>

```


```

</xs:enumeration>
<xs:enumeration value="20">
  <xs:annotation>
    <xs:documentation>Mooring strap on car-carrying
wagon</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="21">
  <xs:annotation>
    <xs:documentation>Beam for movable ramp on car-carrying
wagon</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="22">
  <xs:annotation>
    <xs:documentation>Spare heating half-coupling</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="23">
  <xs:annotation>
    <xs:documentation>Fire extinguisher</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="24">
  <xs:annotation>
    <xs:documentation>Wheel scotches (for cars) on car-carrying
wagon</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>Gangway loading ramp on car-carrying
wagon</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="26">
  <xs:annotation>
    <xs:documentation>Metal cradles for rolls of metal
sheeting</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="27">
  <xs:annotation>
    <xs:documentation>Panel for covering markings</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="28">
  <xs:annotation>
    <xs:documentation>Loading frame for special types of
goods</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="29">
  <xs:annotation>
    <xs:documentation>Headstock for "rolling roads"</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="99">

```


	<pre> <xs:annotation> <xs:documentation>Other wagon accessories</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **TypeOfUsedHybridPowerunit**

diagram	 <p>information about the type of power unit in case of using a hybrid locomoti...</p>															
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3															
type	restriction of xs:token															
properties	content simple															
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td>documentation electric (pantograph, conductor rail)</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation liquid fuel (benzine, diesel, gasoline)</td> </tr> <tr> <td>enumeration</td> <td>3</td> <td>documentation battery</td> </tr> <tr> <td>enumeration</td> <td>4</td> <td>documentation hydrogen</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1	documentation electric (pantograph, conductor rail)	enumeration	2	documentation liquid fuel (benzine, diesel, gasoline)	enumeration	3	documentation battery	enumeration	4	documentation hydrogen
Kind	Value	Annotation														
enumeration	1	documentation electric (pantograph, conductor rail)														
enumeration	2	documentation liquid fuel (benzine, diesel, gasoline)														
enumeration	3	documentation battery														
enumeration	4	documentation hydrogen														
annotation	documentation information about the type of power unit in case of using a hybrid locomotive															
source	<pre> <xs:element name="TypeOfUsedHybridPowerunit"> <xs:annotation> <xs:documentation>information about the type of power unit in case of using a hybrid locomotive</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>electric (pantograph, conductor rail)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>liquid fuel (benzine, diesel, gasoline)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>battery</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>hydrogen</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>															

	<pre> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>
--	---

element **WheelSetTransformationMethod**

diagram										
namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:token									
properties	content simple									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td>documentation Automatic</td> </tr> <tr> <td>enumeration</td> <td>2</td> <td>documentation Bogie/axle change</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	1	documentation Automatic	enumeration	2	documentation Bogie/axle change
Kind	Value	Annotation								
enumeration	1	documentation Automatic								
enumeration	2	documentation Bogie/axle change								
annotation	documentation Description of the wheel set transformation method for wagons with a changeable wheel set gauge.									
source	<pre> <xs:element name="WheelSetTransformationMethod"> <xs:annotation> <xs:documentation>Description of the wheel set transformation method for wagons with a changeable wheel set gauge.</xs:documentation> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Automatic</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Bogie/axle change</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:element> </pre>									

simpleType **ConsignmentTypeCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:token									
properties	base xs:token									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>CIM</td> <td>documentation CIM Convention Internationale Marchandises (OTIF) Source: CIM (OTIF)</td> </tr> <tr> <td>enumeration</td> <td>Other</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	CIM	documentation CIM Convention Internationale Marchandises (OTIF) Source: CIM (OTIF)	enumeration	Other	
Kind	Value	Annotation								
enumeration	CIM	documentation CIM Convention Internationale Marchandises (OTIF) Source: CIM (OTIF)								
enumeration	Other									
annotation	documentation Identifies the type of a waybill.									

source	<pre> <xs:simpleType name="ConsignmentTypeCode"> <xs:annotation> <xs:documentation>Identifies the type of a waybill.</xs:documentation> </xs:annotation> <xs:restriction base="xs:token"> <xs:enumeration value="CIM"> <xs:annotation> <xs:documentation>CIM Convention Internationale Marchandises (OTIF) Source: CIM (OTIF)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="Other"/> </xs:restriction> </xs:simpleType> </pre>
--------	---

simpleType **DelayCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	base	xs:token	
facets	Kind	Value	Annotation
	enumeration	11	documentation Formation of trains if managed by infrastructure manager
	enumeration	10	documentation Timetable compilation
	enumeration	12	documentation Mistakes in operational procedures
	enumeration	13	documentation Wrong application of priority rules
	enumeration	14	
	enumeration	18	documentation Staff
	enumeration	19	documentation Other causes related to the operational planning and management
	enumeration	20	documentation Signalling installations
	enumeration	21	documentation Signalling installations at level crossings
	enumeration	22	documentation Telecommunication installations
	enumeration	23	documentation Power supply equipment
	enumeration	24	documentation Track
	enumeration	25	documentation Structures
	enumeration	28	documentation Staff
	enumeration	29	documentation Other causes related to infrastructure installations
	enumeration	31	documentation Irregularities in execution of construction work
	enumeration	30	documentation Planned construction work
	enumeration	32	documentation Speed restrictions due to defective track
	enumeration	39	documentation Other causes related to Civil engineering

	enumeration 40	documentation Delay caused by next IM
	enumeration 41	documentation Delay caused by previous IM
	enumeration 50	documentation exceeding the stop time
	enumeration 51	documentation Request of the RU
	enumeration 52	documentation Loading operations
	enumeration 53	documentation Loading irregularities
	enumeration 54	documentation Commercial preparation of the train
	enumeration 58	documentation Staff
	enumeration 59	documentation Other causes related to commercial causes
	enumeration 60	documentation Roster planning/re-rostering
	enumeration 61	documentation Formation of trains by the RU
	enumeration 62	documentation Problems affecting coaches
	enumeration 63	documentation Problems affecting wagons
	enumeration 64	documentation Problems affecting traction units
	enumeration 68	documentation Staff
	enumeration 69	documentation Other causes related to Rolling Stock
	enumeration 70	documentation Delay caused by next RU
	enumeration 71	documentation Delay caused by previous RU
	enumeration 80	documentation Strike
	enumeration 81	documentation Administrative formalites
	enumeration 82	documentation Outside influence
	enumeration 83	documentation Effects of weather and natural causes
	enumeration 84	documentation Delay caused by external reasons on the next network
	enumeration 89	documentation Other external causes
	enumeration 90	documentation Dangerous incidents, accidents and hazards
	enumeration 91	documentation Track occupation caused by the lateness of the same train
	enumeration 92	documentation Track occupation caused by the lateness of another train
	enumeration 93	documentation Turn round
	enumeration 94	documentation Connection
	enumeration 95	documentation Further investigation needed
annotation	documentation	Reason for a delay or interruption. UIC Leaflet 450-2, Appendix C.
source	<xs:simpleType name="DelayCode">	

```

<xs:annotation>
  <xs:documentation>Reason for a delay or interruption. UIC Leaflet 450-
2, Appendix C.</xs:documentation>
</xs:annotation>
<xs:restriction base="xs:token">
  <xs:enumeration value="11">
    <xs:annotation>
      <xs:documentation>Formation of trains if managed by infrastructure
manager</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="10">
    <xs:annotation>
      <xs:documentation>Timetable compilation</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="12">
    <xs:annotation>
      <xs:documentation>Mistakes in operational
procedures</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="13">
    <xs:annotation>
      <xs:documentation>Wrong application of priority
rules</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="14"/>
  <xs:enumeration value="18">
    <xs:annotation>
      <xs:documentation>Staff</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="19">
    <xs:annotation>
      <xs:documentation>Other causes related to the operational planning
and management</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="20">
    <xs:annotation>
      <xs:documentation>Signalling installations</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="21">
    <xs:annotation>
      <xs:documentation>Signalling installations at level
crossings</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="22">
    <xs:annotation>
      <xs:documentation>Telecommunication installations</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="23">
    <xs:annotation>

```

```

    <xs:documentation>Power supply equipment</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="24">
  <xs:annotation>
    <xs:documentation>Track</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>Structures</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="28">
  <xs:annotation>
    <xs:documentation>Staff</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="29">
  <xs:annotation>
    <xs:documentation>Other causes related to infrastructure
installations</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="31">
  <xs:annotation>
    <xs:documentation>Irregularities in execution of construction
work</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="30">
  <xs:annotation>
    <xs:documentation>Planned construction work</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="32">
  <xs:annotation>
    <xs:documentation>Speed restrictions due to defective
track</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="39">
  <xs:annotation>
    <xs:documentation>Other causes related to Civil
engineering</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="40">
  <xs:annotation>
    <xs:documentation>Delay caused by next IM</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="41">
  <xs:annotation>
    <xs:documentation>Delay caused by previous IM</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="50">

```

```

    <xs:annotation>
      <xs:documentation>exceeding the stop time</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="51">
    <xs:annotation>
      <xs:documentation>Request of the RU</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="52">
    <xs:annotation>
      <xs:documentation>Loading operations</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="53">
    <xs:annotation>
      <xs:documentation>Loading irregularities</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="54">
    <xs:annotation>
      <xs:documentation>Commercial preparation of the
train</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="58">
    <xs:annotation>
      <xs:documentation>Staff</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="59">
    <xs:annotation>
      <xs:documentation>Other causes related to commercial
causes</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="60">
    <xs:annotation>
      <xs:documentation>Roster planning/re-rostering</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="61">
    <xs:annotation>
      <xs:documentation>Formation of trains by the RU</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="62">
    <xs:annotation>
      <xs:documentation>Problems affecting coaches</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="63">
    <xs:annotation>
      <xs:documentation>Problems affecting wagons</xs:documentation>
    </xs:annotation>
  </xs:enumeration>
  <xs:enumeration value="64">
    <xs:annotation>

```

```

    <xs:documentation>Problems affecting traction
units</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="68">
  <xs:annotation>
    <xs:documentation>Staff</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="69">
  <xs:annotation>
    <xs:documentation>Other causes related to Rolling
Stock</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="70">
  <xs:annotation>
    <xs:documentation>Delay caused by next RU</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="71">
  <xs:annotation>
    <xs:documentation>Delay caused by previous RU</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="80">
  <xs:annotation>
    <xs:documentation>Strike</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="81">
  <xs:annotation>
    <xs:documentation>Administrative formalites</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="82">
  <xs:annotation>
    <xs:documentation>Outside influence</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="83">
  <xs:annotation>
    <xs:documentation>Effects of weather and natural
causes</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="84">
  <xs:annotation>
    <xs:documentation>Delay caused by external reasons on the next
network</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="89">
  <xs:annotation>
    <xs:documentation>Other external causes</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="90">

```

	<pre> <xs:annotation> <xs:documentation>Dangerous incidents, accidents and hazards</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="91"> <xs:annotation> <xs:documentation>Track occupation caused by the lateness of the same train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="92"> <xs:annotation> <xs:documentation>Track occupation caused by the lateness of another train</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="93"> <xs:annotation> <xs:documentation>Turn round</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="94"> <xs:annotation> <xs:documentation>Connection</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="95"> <xs:annotation> <xs:documentation>Further investigation needed</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>
--	--

simpleType InfoIndex

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:string												
properties	base xs:string												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>10</td> <td></td> </tr> <tr> <td>enumeration</td> <td>20</td> <td></td> </tr> <tr> <td>enumeration</td> <td>30</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	10		enumeration	20		enumeration	30	
Kind	Value	Annotation											
enumeration	10												
enumeration	20												
enumeration	30												
annotation	documentation indicates additional information												
source	<pre> <xs:simpleType name="InfoIndex"> <xs:annotation> <xs:documentation>indicates additional information</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="10"/> <xs:enumeration value="20"/> <xs:enumeration value="30"/> </xs:restriction> </xs:simpleType> </pre>												

```
</xs:restriction>
</xs:simpleType>
```

simpleType **MessageCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	base xs:integer									
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>minInclusive</td> <td>1</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>9999</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	minInclusive	1		maxInclusive	9999	
Kind	Value	Annotation								
minInclusive	1									
maxInclusive	9999									
annotation	documentation Identifies the type of message									
source	<pre><xs:simpleType name="MessageCode"> <xs:annotation> <xs:documentation>Identifies the type of message</xs:documentation> </xs:annotation> <xs:restriction base="xs:integer"> <xs:minInclusive value="1"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType></pre>									

simpleType **RestrictionCodes**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3																																							
type	restriction of xs:token																																							
properties	base xs:token																																							
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>07</td> <td>documentation F - Shunt only when hand brake operable with ground staff</td> </tr> <tr> <td>enumeration</td> <td>08</td> <td>documentation F - Tank wagon loaded with liquid</td> </tr> <tr> <td>enumeration</td> <td>09</td> <td>documentation F - Wagon loaded with people</td> </tr> <tr> <td>enumeration</td> <td>11</td> <td>documentation F - Wagon other than bogie wagon with wheelbase of more than 9 metres</td> </tr> <tr> <td>enumeration</td> <td>12</td> <td>documentation F - Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres</td> </tr> <tr> <td>enumeration</td> <td>13</td> <td>documentation F - Bogie wagon with distance between wheels of more than 17,50 metres</td> </tr> <tr> <td>enumeration</td> <td>15</td> <td>documentation F - Wagon not allowed over the hump</td> </tr> <tr> <td>enumeration</td> <td>16</td> <td>documentation F - Do not fly shunt or gravity shunt (3 red triangles)</td> </tr> <tr> <td>enumeration</td> <td>18</td> <td>documentation F - Must not use active braking equipment</td> </tr> <tr> <td>enumeration</td> <td>25</td> <td>documentation F - Gas carrying tank wagon with orange side stripe</td> </tr> <tr> <td>enumeration</td> <td>30</td> <td>documentation P (+F) - CCS fault (see CCS coding list)</td> </tr> <tr> <td>enumeration</td> <td>31</td> <td>documentation P (+F) - Braking system fault</td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	07	documentation F - Shunt only when hand brake operable with ground staff	enumeration	08	documentation F - Tank wagon loaded with liquid	enumeration	09	documentation F - Wagon loaded with people	enumeration	11	documentation F - Wagon other than bogie wagon with wheelbase of more than 9 metres	enumeration	12	documentation F - Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres	enumeration	13	documentation F - Bogie wagon with distance between wheels of more than 17,50 metres	enumeration	15	documentation F - Wagon not allowed over the hump	enumeration	16	documentation F - Do not fly shunt or gravity shunt (3 red triangles)	enumeration	18	documentation F - Must not use active braking equipment	enumeration	25	documentation F - Gas carrying tank wagon with orange side stripe	enumeration	30	documentation P (+F) - CCS fault (see CCS coding list)	enumeration	31	documentation P (+F) - Braking system fault
Kind	Value	Annotation																																						
enumeration	07	documentation F - Shunt only when hand brake operable with ground staff																																						
enumeration	08	documentation F - Tank wagon loaded with liquid																																						
enumeration	09	documentation F - Wagon loaded with people																																						
enumeration	11	documentation F - Wagon other than bogie wagon with wheelbase of more than 9 metres																																						
enumeration	12	documentation F - Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres																																						
enumeration	13	documentation F - Bogie wagon with distance between wheels of more than 17,50 metres																																						
enumeration	15	documentation F - Wagon not allowed over the hump																																						
enumeration	16	documentation F - Do not fly shunt or gravity shunt (3 red triangles)																																						
enumeration	18	documentation F - Must not use active braking equipment																																						
enumeration	25	documentation F - Gas carrying tank wagon with orange side stripe																																						
enumeration	30	documentation P (+F) - CCS fault (see CCS coding list)																																						
enumeration	31	documentation P (+F) - Braking system fault																																						

08	F	Tank wagon loaded with liquid			x			x
09	F	Wagon loaded with people				x		
11	F	Wagon other than bogie wagon with wheelbase of more than 9 metres					x	
12	F	Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres					x	
13	F	Bogie wagon with distance between wheels of more than 17,50 metres						
15	F	Wagon not allowed over the hump						
16	F	Do not fly shunt or gravity shunt (3 red triangles)						
18	F	Must not use active braking equipment						
18	F	Must not use active braking equipment						
25	F	Gas carrying tank wagon with orange side stripe						
30	P (+F)	CCS fault (see CCS coding list)						
31	P (+F)	Braking system fault						
32	P (+F)	Wheelset, bogie fault						
33	P (+F)	Headlighting or back lighting fault						
34	P (+F)	Front glass broken						
35	P (+F)	Horn fault						
36	P (+F)	Radio fault						
37	P (+F)	Energy supply fault						

<p>source</p>	<pre><xs:simpleType name="RestrictionCodes"> <xs:annotation> <xs:documentation></pre> <p style="text-align: right;">All codes of Transport restrictions for Freight Traffic (cf. UIC 920-13) and Passengers Traffic are in the same list.</p> <p style="text-align: right;">F = Freight</p> <p>P = Passenger T = Technical D = Damage L = Load</p> <table border="0"> <thead> <tr> <th>Code</th> <th>F or P</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>07</td> <td>F</td> <td style="text-align: right;">T D L Shunt only when hand brake operable with ground staff</td> </tr> <tr> <td>08</td> <td>F</td> <td style="text-align: center;">x Tank wagon loaded with liquid</td> </tr> <tr> <td>09</td> <td>F</td> <td style="text-align: right;">x Wagon loaded with people</td> </tr> <tr> <td>11</td> <td>F</td> <td style="text-align: right;">x Wagon other than bogie wagon with wheelbase of more than 9 metres</td> </tr> <tr> <td>12</td> <td>F</td> <td style="text-align: right;">x Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres</td> </tr> <tr> <td>13</td> <td>F</td> <td style="text-align: right;">x Bogie wagon with distance between wheels of more than 17,50 metres</td> </tr> <tr> <td>15</td> <td>F</td> <td style="text-align: right;">x Wagon not allowed over the hump</td> </tr> <tr> <td>16</td> <td>F</td> <td style="text-align: center;">x x x Do not fly shunt or gravity shunt (3 red triangles)</td> </tr> <tr> <td>18</td> <td>F</td> <td style="text-align: center;">x x x Must not use active braking equipment</td> </tr> <tr> <td>25</td> <td>F</td> <td style="text-align: center;">x Gas carrying tank wagon with orange side stripe</td> </tr> <tr> <td>30</td> <td>P (+F)</td> <td style="text-align: center;">x CCS fault (see CCS coding list)</td> </tr> </tbody> </table>	Code	F or P	Description	07	F	T D L Shunt only when hand brake operable with ground staff	08	F	x Tank wagon loaded with liquid	09	F	x Wagon loaded with people	11	F	x Wagon other than bogie wagon with wheelbase of more than 9 metres	12	F	x Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres	13	F	x Bogie wagon with distance between wheels of more than 17,50 metres	15	F	x Wagon not allowed over the hump	16	F	x x x Do not fly shunt or gravity shunt (3 red triangles)	18	F	x x x Must not use active braking equipment	25	F	x Gas carrying tank wagon with orange side stripe	30	P (+F)	x CCS fault (see CCS coding list)
Code	F or P	Description																																			
07	F	T D L Shunt only when hand brake operable with ground staff																																			
08	F	x Tank wagon loaded with liquid																																			
09	F	x Wagon loaded with people																																			
11	F	x Wagon other than bogie wagon with wheelbase of more than 9 metres																																			
12	F	x Bogie wagon with distance between wheels of more than 14 metres and up to and including a distance of 17,50 metres																																			
13	F	x Bogie wagon with distance between wheels of more than 17,50 metres																																			
15	F	x Wagon not allowed over the hump																																			
16	F	x x x Do not fly shunt or gravity shunt (3 red triangles)																																			
18	F	x x x Must not use active braking equipment																																			
25	F	x Gas carrying tank wagon with orange side stripe																																			
30	P (+F)	x CCS fault (see CCS coding list)																																			

31	P (+F)	Braking system fault	x		
32	P (+F)	Wheelset, bogie fault		x	
33	P (+F)	Headlighting or back lighting fault		x	
34	P (+F)	Front glass broken	x		
35	P (+F)	Horn fault		x	
36	P (+F)	Radio fault			x
37	P (+F)	Energy supply fault			x
38	P (+F)	Traction or motor fault		x	
39	P	Access door fault		x	
41	F	Place this wagon at the front of the train			x
42	F	Place this wagon at the rear of the train	x	x	x
50	P (+F)	Speed restriction	x	x	x
52	P (+F)	Diesel locomotive instead of electric locomotive		x	x
61	x (X) F	Wagon forming part of a consignment of several wagons			
62	x F	Wagon forming part of a group of wagons from which it must not			


```

<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>F - Wagon other than bogie wagon with wheelbase of
more than 9 metres</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>F - Bogie wagon with distance between wheels of
more than 14 metres and up to and including a distance of 17,50
metres</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>F - Bogie wagon with distance between wheels of
more than 17,50 metres</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>F - Wagon not allowed over the
hump</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>F - Do not fly shunt or gravity shunt (3 red
triangles)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>F - Must not use active braking
equipment</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>F - Gas carrying tank wagon with orange side
stripe</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="30">
  <xs:annotation>
    <xs:documentation>P (+F) - CCS fault (see CCS coding
list)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="31">
  <xs:annotation>
    <xs:documentation>P (+F) - Braking system fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="32">
  <xs:annotation>
    <xs:documentation>P (+F) - Wheelset, bogie fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

</xs:enumeration>
<xs:enumeration value="33">
  <xs:annotation>
    <xs:documentation>P (+F) - Headlighting or back lighting
fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="34">
  <xs:annotation>
    <xs:documentation>P (+F) - Front glass broken</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="35">
  <xs:annotation>
    <xs:documentation>P (+F) - Horn fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="36">
  <xs:annotation>
    <xs:documentation>P (+F) - Radio fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="37">
  <xs:annotation>
    <xs:documentation>P (+F) - Energy supply fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="38">
  <xs:annotation>
    <xs:documentation>P (+F) - Traction or motor
fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="39">
  <xs:annotation>
    <xs:documentation>P - Access door fault</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="41">
  <xs:annotation>
    <xs:documentation>F - Place this wagon at the front of the
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>F - Place this wagon at the rear of the
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="50">
  <xs:annotation>
    <xs:documentation>P (+F) - Speed restriction</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="52">
  <xs:annotation>
    <xs:documentation>P (+F) - Diesel locomotive instead of electric

```



```

locomotive</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="61">
  <xs:annotation>
    <xs:documentation>F - Wagon forming part of a consignment of several
wagons</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="62">
  <xs:annotation>
    <xs:documentation>F - Wagon forming part of a group of wagons from
which it must not be separated</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="63">
  <xs:annotation>
    <xs:documentation>F (+P) - Special consignment or (for Passengers
trains) loading/cinematic gauge larger than the planned
one</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="68">
  <xs:annotation>
    <xs:documentation>F - First or last wagon of a wagon group from
which it must not be separated</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="70">
  <xs:annotation>
    <xs:documentation>F - Shunt with care (1 red
triangle)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="71">
  <xs:annotation>
    <xs:documentation>F - Shunt with special care (2 red
triangle)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="90">
  <xs:annotation>
    <xs:documentation>P - Train planned with passengers operated without
passengers</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="91">
  <xs:annotation>
    <xs:documentation>P - Train planned without passengers operated with
passengers</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="92">
  <xs:annotation>
    <xs:documentation>P - Train planned with hauled rolling stock and
operated without any coaches (light engine)</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

<xs:enumeration value="94">
  <xs:annotation>
    <xs:documentation>F - Gas carrying wagon without orange side
stripe</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="99">
  <xs:annotation>
    <xs:documentation>P - Other</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
    
```

simpleType **RunningStatus**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	base xs:token		
facets	Kind	Value	Annotation
	enumeration	00	documentation Not specified
	enumeration	01	documentation Arrival at destination
	enumeration	02	documentation Departure at origin
	enumeration	03	documentation Intermediate arrival
	enumeration	04	documentation Intermediate departure
	enumeration	05	documentation Pass through
	enumeration	06	documentation NEW CODES: Some IMs are transmitting these codes (6 - 9)
	enumeration	07	
	enumeration	08	
	enumeration	09	
	enumeration	10	documentation Not specified for wagon
	enumeration	11	documentation Wagon arrival at its destination by train
	enumeration	12	documentation Wagon departure from its station of origin by train
	enumeration	13	documentation Wagon arrival at reporting point by train
	enumeration	14	documentation Wagon departure from reporting point by train
	enumeration	15	documentation Wagon run-through at reporting point by train
	enumeration	16	documentation Wagon parked at reporting point
	enumeration	17	documentation Wagon shunted at reporting point
	enumeration	18	documentation Wagon arrived at reporting point
	enumeration	19	documentation Wagon departure from reporting point

annotation	<p>documentation</p> <p>Identifies the status of a train related to the actual time at the reporting point.</p>
source	<pre> <xs:simpleType name="RunningStatus"> <xs:annotation> <xs:documentation>Identifies the status of a train related to the actual time at the reporting point.</xs:documentation> </xs:annotation> <xs:restriction base="xs:token"> <xs:enumeration value="00"> <xs:annotation> <xs:documentation>Not specified</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="01"> <xs:annotation> <xs:documentation>Arrival at destination</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="02"> <xs:annotation> <xs:documentation>Departure at origin</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="03"> <xs:annotation> <xs:documentation>Intermediate arrival</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="04"> <xs:annotation> <xs:documentation>Intermediate departure</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="05"> <xs:annotation> <xs:documentation>Pass through</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="06"> <xs:annotation> <xs:documentation>NEW CODES: Some IMs are transmitting these codes (6 - 9)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="07"> <xs:annotation> <xs:documentation/> </xs:annotation> </xs:enumeration> <xs:enumeration value="08"> <xs:annotation> <xs:documentation/> </xs:annotation> </xs:enumeration> <xs:enumeration value="09"> <xs:annotation> <xs:documentation/> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>Not specified for wagon</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>Wagon arrival at its destination by
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>Wagon departure from its station of origin by
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>Wagon arrival at reporting point by
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>Wagon departure from reporting point by
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>Wagon run-through at reporting point by
train</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>Wagon parked at reporting point</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>Wagon shunted at reporting
point</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>Wagon arrived at reporting
point</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="19">
  <xs:annotation>
    <xs:documentation>Wagon departure from reporting
point</xs:documentation>

```

```

</xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
    
```

simpleType **TrainCC_SystemCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	base	xs:token	
facets	Kind	Value	Annotation
	enumeration	01	
	enumeration	02	
	enumeration	03	
	enumeration	04	
	enumeration	05	
	enumeration	06	
	enumeration	07	
	enumeration	08	
	enumeration	09	
	enumeration	10	
	enumeration	11	
	enumeration	12	
	enumeration	13	
	enumeration	14	
	enumeration	15	
	enumeration	16	
	enumeration	17	
	enumeration	18	
	enumeration	19	
	enumeration	20	
	enumeration	21	
	enumeration	22	
	enumeration	23	
	enumeration	24	
	enumeration	25	
	enumeration	26	
	enumeration	27	
	enumeration	28	
	enumeration	29	
	enumeration	30	
	enumeration	31	
	enumeration	32	
	enumeration	33	
	enumeration	34	
	enumeration	35	
	enumeration	36	
	enumeration	37	

	<p>enumeration 38</p> <p>enumeration 39</p> <p>enumeration 40</p> <p>enumeration 41</p> <p>enumeration 42</p> <p>enumeration 43</p> <p>enumeration 44</p> <p>enumeration 45</p> <p>enumeration 46</p> <p>enumeration 47</p> <p>enumeration 48</p> <p>enumeration 49</p> <p>enumeration 50</p> <p>enumeration 51</p> <p>enumeration 52</p> <p>enumeration 53</p> <p>enumeration 54</p>
<p>annotation</p>	<p>documentation</p> <p>Type of Train Control System</p> <p>Identifies the command control system of the train in coded values.</p> <ol style="list-style-type: none"> 1 ALSN 2 ASFA 3 ATB 1st Gen 4 ATB Next Gen 5 ATC 6 ATP 7 CIR 1 (traction unit is equipped with LZB CIR-ELKE I) 8 CIR 1+2 (traction unit is equipped with LZB CIR-ELKE I + II) 9 CIR 2 (traction unit is equipped with LZB CIR-ELKE II) 10 Crocodile 11 DAAT 12 EBICAB 700 13 EBICAB 900 14 EFA (all traction units/driving cabins of the train are equipped with an electronic drivers cab display (EFA)) 15 ETCS L1 LS plus EuroZUB 16 ETCS L1 SRS 2.3.0d (traction unit is equipped with ETCS Level 1 version 2.3.0d) 17 ETCS L2 SRS 2.3.0d (traction unit is equipped with ETCS Level 2 version 2.3.0d) 18 ETCS L2 SRS 3.3.0 (traction unit is equipped with ETCS Level 2 version 3.3.0) 19 ETCS L2 SRS 3.4.0 (traction unit is equipped with ETCS Level 2 version 3.4.0) 20 ETCS L2 SRS 3.6.0 (traction unit is equipped with ETCS Level 2 version 3.6.0) 21 ETCS Level 0 22 ETCS Level 1 23 ETCS Level 2 24 ETCS Level 3 25 ETCS Level NSC 26 EVM 27 Indusi 54 28 Indusi 60 R 29 Indusi PZ 80 30 KBS-E 31 KCVB 32 KCVP 33 KVB 34 KVBP 35 LS 36 LS 90 37 LS I 38 LS III

	39 LS IV 40 LZB 41 Mirel 42 NEXTEO 43 PZB 44 PZB90 45 SCMT 46 SHP 47 SIFA 48 STM ASFA 49 STM LZB 50 TBL 1 51 TBL 2 52 TVM 300 53 TVM 430 54 ZUB
source	<pre><xs:simpleType name="TrainCC_SystemCode"> <xs:annotation> <xs:documentation>Type of Train Control System Identifies the command control system of the train in coded values. 1 ALSN 2 ASFA 3 ATB 1st Gen 4 ATB Next Gen 5 ATC 6 ATP 7 CIR 1 (traction unit is equipped with LZB CIR-ELKE I) 8 CIR 1+2 (traction unit is equipped with LZB CIR-ELKE I + II) 9 CIR 2 (traction unit is equipped with LZB CIR-ELKE II) 10 Crocodile 11 DAAT 12 EBICAB 700 13 EBICAB 900 14 EFA (all traction units/driving cabins of the train are equipped with an electronic drivers cab display (EFA)) 15 ETCS L1 LS plus EuroZUB 16 ETCS L1 SRS 2.3.0d (traction unit is equipped with ETCS Level 1 version 2.3.0d) 17 ETCS L2 SRS 2.3.0d (traction unit is equipped with ETCS Level 2 version 2.3.0d) 18 ETCS L2 SRS 3.3.0 (traction unit is equipped with ETCS Level 2 version 3.3.0) 19 ETCS L2 SRS 3.4.0 (traction unit is equipped with ETCS Level 2 version 3.4.0) 20 ETCS L2 SRS 3.6.0 (traction unit is equipped with ETCS Level 2 version 3.6.0) 21 ETCS Level 0 22 ETCS Level 1 23 ETCS Level 2 24 ETCS Level 3 25 ETCS Level NSC 26 EVM 27 Indusi 54 28 Indusi 60 R 29 Indusi PZ 80 30 KBS-E 31 KCVB 32 KCVP 33 KVB</pre>

```
34   KVBP
35   LS
36   LS 90
37   LS I
38   LS III
39   LS IV
40   LZB
41   Mirel
42   NEXTE0
43   PZB
44   PZB90
45   SCMT
46   SHP
47   SIFA
48   STM ASFA
49   STM LZB
50   TBL 1
51   TBL 2
52   TVM 300
53   TVM 430
54   ZUB</xs:documentation>
</xs:annotation>
<xs:restriction base="xs:token">
  <xs:enumeration value="01"/>
  <xs:enumeration value="02"/>
  <xs:enumeration value="03"/>
  <xs:enumeration value="04"/>
  <xs:enumeration value="05"/>
  <xs:enumeration value="06"/>
  <xs:enumeration value="07"/>
  <xs:enumeration value="08"/>
  <xs:enumeration value="09"/>
  <xs:enumeration value="10"/>
  <xs:enumeration value="11"/>
  <xs:enumeration value="12"/>
  <xs:enumeration value="13"/>
  <xs:enumeration value="14"/>
  <xs:enumeration value="15"/>
  <xs:enumeration value="16"/>
  <xs:enumeration value="17"/>
  <xs:enumeration value="18"/>
  <xs:enumeration value="19"/>
  <xs:enumeration value="20"/>
  <xs:enumeration value="21"/>
  <xs:enumeration value="22"/>
  <xs:enumeration value="23"/>
  <xs:enumeration value="24"/>
  <xs:enumeration value="25"/>
  <xs:enumeration value="26"/>
  <xs:enumeration value="27"/>
  <xs:enumeration value="28"/>
  <xs:enumeration value="29"/>
  <xs:enumeration value="30"/>
  <xs:enumeration value="31"/>
  <xs:enumeration value="32"/>
  <xs:enumeration value="33"/>
  <xs:enumeration value="34"/>
  <xs:enumeration value="35"/>
```


	<pre> <xs:enumeration value="36"/> <xs:enumeration value="37"/> <xs:enumeration value="38"/> <xs:enumeration value="39"/> <xs:enumeration value="40"/> <xs:enumeration value="41"/> <xs:enumeration value="42"/> <xs:enumeration value="43"/> <xs:enumeration value="44"/> <xs:enumeration value="45"/> <xs:enumeration value="46"/> <xs:enumeration value="47"/> <xs:enumeration value="48"/> <xs:enumeration value="49"/> <xs:enumeration value="50"/> <xs:enumeration value="51"/> <xs:enumeration value="52"/> <xs:enumeration value="53"/> <xs:enumeration value="54"/> </xs:restriction> </xs:simpleType> </pre>
--	--

simpleType TypeOfIMHarmonizationCode

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:string									
properties	base xs:string									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>enumeration</td> <td>Full</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Part</td> <td></td> </tr> </table>	Kind	Value	Annotation	enumeration	Full		enumeration	Part	
Kind	Value	Annotation								
enumeration	Full									
enumeration	Part									
annotation	documentation Enumeration of Type of IM harmonization: Full, Part									
source	<pre> <xs:simpleType name="TypeOfIMHarmonizationCode"> <xs:annotation> <xs:documentation>Enumeration of Type of IM harmonization: Full, Part </xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Full"/> <xs:enumeration value="Part"/> </xs:restriction> </xs:simpleType> </pre>									

simpleType TypeOfInformationCode

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3									
type	restriction of xs:integer									
properties	base xs:integer									
facets	<table border="0"> <tr> <td>Kind</td> <td>Value</td> <td>Annotation</td> </tr> <tr> <td>minInclusive</td> <td>0</td> <td></td> </tr> <tr> <td>maxInclusive</td> <td>99</td> <td></td> </tr> </table>	Kind	Value	Annotation	minInclusive	0		maxInclusive	99	
Kind	Value	Annotation								
minInclusive	0									
maxInclusive	99									

enumeration	1	documentation harmonisation - in process
enumeration	2	documentation harmonisation - accepted
enumeration	3	documentation harmonisation - rejected
enumeration	4	documentation Request ready
enumeration	5	documentation path study request
enumeration	6	documentation pre-arranged path/reserve capacity
enumeration	7	documentation create offer
enumeration	8	documentation coordination update
enumeration	9	documentation draft offer
enumeration	10	documentation draft alternative offer
enumeration	11	documentation observation - in process
enumeration	12	documentation observation - complete
enumeration	13	documentation preparation of final offer - in process
enumeration	14	documentation preparation of final offer - accepted
enumeration	15	documentation preparation of final offer - rejected
enumeration	16	documentation final offer
enumeration	17	documentation final offer - accepted
enumeration	18	documentation alternative offer accepted
enumeration	19	documentation pre-accepted offer
enumeration	20	documentation Final Offer rejected
enumeration	21	documentation no alternative available
enumeration	22	documentation booked
enumeration	23	documentation preparation of draft alternative offer is in progress
enumeration	24	documentation alternative offer triggered by IM
enumeration	25	documentation offer/final offer rejected (without revision)
enumeration	26	documentation alternative offer rejected (without revision)
enumeration	27	documentation offer/final offer rejected (revision required)
enumeration	28	documentation alternative offer rejected (revision required)
enumeration	29	documentation withdrawal
enumeration	30	documentation Create Dossier
enumeration	31	documentation Close Dossier
enumeration	32	documentation

	<p>enumeration 33 Path canceled full documentation</p> <p>enumeration 40 Path canceled partial documentation</p> <p>enumeration 42 Fully Assembled Path (FAP, constructed path) documentation</p> <p>enumeration 43 Preparation of draft offer – accepted documentation</p> <p>enumeration 44 Preparation of draft offer – rejected documentation</p> <p>enumeration 45 Draft offer rejected documentation</p> <p>enumeration 50 Draft no alternative available documentation</p> <p>enumeration 51 activate path (utilisation notification) documentation</p> <p>enumeration 52 deactivate path (utilisation notification) documentation</p> <p>enumeration 53 confirmation of utilisation notification documentation</p> <p>enumeration 65 Path and train cancelled documentation</p> <p>enumeration 66 Preparation of alternative offer in progress due to route update (used in PathNotAvailableMessage) documentation</p> <p>Booked after route update (used in PathDetailsMessage)</p>
annotation	<p>documentation</p> <p>Enumeration indicating to which process step / process type in the planning does the message belong</p>
source	<pre> <xs:simpleType name="TypeOfInformationCode"> <xs:annotation> <xs:documentation>Enumeration indicating to which process step / process type in the planning does the message belong</xs:documentation> </xs:annotation> <xs:restriction base="xs:integer"> <xs:maxInclusive value="99"/> <xs:minInclusive value="0"/> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>harmonisation - in process</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>harmonisation - accepted</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>harmonisation - rejected</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Request ready</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="5"> <xs:annotation> <xs:documentation>path study request</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>

```

</xs:enumeration>
<xs:enumeration value="6">
  <xs:annotation>
    <xs:documentation>pre-arranged path/reserve
capacity</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7">
  <xs:annotation>
    <xs:documentation>create offer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="8">
  <xs:annotation>
    <xs:documentation>coordination update</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9">
  <xs:annotation>
    <xs:documentation>draft offer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>draft alternative offer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>observation - in process</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>observation - complete</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>preparation of final offer - in
process</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>preparation of final offer -
accepted</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>preparation of final offer -
rejected</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>final offer</xs:documentation>

```

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>final offer - accepted</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>alternative offer accepted</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="19">
  <xs:annotation>
    <xs:documentation>pre-accepted offer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="20">
  <xs:annotation>
    <xs:documentation>Final Offer rejected</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="21">
  <xs:annotation>
    <xs:documentation>no alternative available</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="22">
  <xs:annotation>
    <xs:documentation>booked</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="23">
  <xs:annotation>
    <xs:documentation>preparation of draft alternative offer is in
progress</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="24">
  <xs:annotation>
    <xs:documentation>alternative offer triggered by
IM</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>offer/final offer rejected (without
revision)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="26">
  <xs:annotation>
    <xs:documentation>alternative offer rejected (without
revision)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="27">
  <xs:annotation>

```

```

    <xs:documentation>offer/final offer rejected (revision
required)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="28">
  <xs:annotation>
    <xs:documentation>alternative offer rejected (revision
required)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="29">
  <xs:annotation>
    <xs:documentation>withdrawal</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="30">
  <xs:annotation>
    <xs:documentation>Create Dossier</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="31">
  <xs:annotation>
    <xs:documentation>Close Dossier</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="32">
  <xs:annotation>
    <xs:documentation>Path canceled full</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="33">
  <xs:annotation>
    <xs:documentation>Path canceled partial</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="40">
  <xs:annotation>
    <xs:documentation>Fully Assembled Path (FAP, constructed
path)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>Preparation of draft offer -
accepted</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>Preparation of draft offer -
rejected</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="44">
  <xs:annotation>
    <xs:documentation>Draft offer rejected</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

<xs:enumeration value="45">
  <xs:annotation>
    <xs:documentation>Draft no alternative available</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="50">
  <xs:annotation>
    <xs:documentation>activate path (utilisation
notification)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="51">
  <xs:annotation>
    <xs:documentation>deactivate path (utilisation
notification)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="52">
  <xs:annotation>
    <xs:documentation>confirmation of utilisation
notification</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="53">
  <xs:annotation>
    <xs:documentation>Path and train cancelled </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="65">
  <xs:annotation>
    <xs:documentation>Preparation of alternative offer in progress due
to route update (used in PathNotAvailableMessage)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="66">
  <xs:annotation>
    <xs:documentation>Booked after route update (used in
PathDetailsMessage)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
    
```

simpleType **TypeOfRequestCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:short		
properties	base	xs:short	
facets	Kind	Value	Annotation
	minInclusive	1	
	enumeration	1	documentation Study
	enumeration	2	documentation Request
	enumeration	3	documentation

Modification	
annotation	documentation Enumeration for 3 different basic types of the processes in the planning: Study (1), Request (2), Modification (3)
source	<pre> <xs:simpleType name="TypeOfRequestCode"> <xs:annotation> <xs:documentation> Enumeration for 3 different basic types of the processes in the planning: Study (1), Request (2), Modification (3)</xs:documentation> </xs:annotation> <xs:restriction base="xs:short"> <xs:minInclusive value="1"/> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Study</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Request</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Modification</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </pre>

simpleType TypeOfRUHarmonizationCode

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3												
type	restriction of xs:string												
properties	base xs:string												
facets	<table border="0"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Full</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Part</td> <td></td> </tr> <tr> <td>enumeration</td> <td>None</td> <td></td> </tr> </tbody> </table>	Kind	Value	Annotation	enumeration	Full		enumeration	Part		enumeration	None	
Kind	Value	Annotation											
enumeration	Full												
enumeration	Part												
enumeration	None												
annotation	documentation Type of RU harmonization: Full, Part, None.												
source	<pre> <xs:simpleType name="TypeOfRUHarmonizationCode"> <xs:annotation> <xs:documentation>Type of RU harmonization: Full, Part, None.</xs:documentation> </xs:annotation> <xs:restriction base="xs:string"> <xs:enumeration value="Full"/> <xs:enumeration value="Part"/> <xs:enumeration value="None"/> </xs:restriction> </xs:simpleType> </pre>												

simpleType **UnitType**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
properties	base xs:token		
facets	Kind	Value	Annotation
	enumeration	1	documentation Container
	enumeration	2	documentation Other intermodal traffic
	enumeration	4	documentation Rolling road (RR)
	enumeration	6	documentation Semi-trailer on bogies
	enumeration	10	documentation Container less than 20'
	enumeration	11	documentation Container 20'
	enumeration	12	documentation Container 30'
	enumeration	13	documentation Container 40'
	enumeration	40	documentation Semi-trailer truck/articulated lorry
	enumeration	41	documentation Road tractor
	enumeration	42	documentation Lorry without trailer
	enumeration	43	documentation Lorry with trailer
	enumeration	50	documentation Semi-trailer/road semi-trailer
	enumeration	51	documentation Swap bodies
annotation	documentation Indicates the type of a Transportation unit.		
source	<pre> <xs:simpleType name="UnitType"> <xs:annotation> <xs:documentation>Indicates the type of a Transportation unit.</xs:documentation> </xs:annotation> <xs:restriction base="xs:token"> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Container</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Other intermodal traffic</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Rolling road (RR)</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="6"> <xs:annotation> </pre>		

```

    <xs:documentation>Semi-trailer on bogies</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>Container less than 20'</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>Container 20'</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>Container 30'</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>Container 40'</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="40">
  <xs:annotation>
    <xs:documentation>Semi-trailer truck/articulated
lorry</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="41">
  <xs:annotation>
    <xs:documentation>Road tractor</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>Lorry without trailer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>Lorry with trailer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="50">
  <xs:annotation>
    <xs:documentation>Semi-trailer/road semi-trailer</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="51">
  <xs:annotation>
    <xs:documentation>Swap bodies</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>

```

attribute **LocationSubsidiaryTypeCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
facets	Kind	Value	Annotation
	enumeration	0	documentation Not Defined
	enumeration	1	documentation not used
	enumeration	2	documentation Track The track is a uniquely defined part of location
	enumeration	3	documentation Private Siding Tracks are not for open access
	enumeration	4	documentation Border Point Code Special code for the Border Points are allocated at the country border and the points between different IM networks. Location of these points sometimes are not geographically same with the station or yard. Therefore these points are "logical point"
	enumeration	5	documentation Sorting Code Destination station of the wagon has a code in order to provide shunting technology.
	enumeration	6	documentation Vehicle Parking Points All points (tracks) Public Loading Places
	enumeration	7	documentation Is a type of physical location on the open access network where consignor or consignee can load or unload wagons Private Loading Places
	enumeration	8	documentation Is a type of physical location outside the open access network where consignor or consignee can load or unload wagons IM Path Tariff Point
	enumeration	9	documentation Price Segment change between two IM Networks. Depot / Maintenance workshop. Place for overhaul or maintenance of the rolling stock.
	enumeration	10	documentation Switch/turnout
	enumeration	11	documentation The location where two tracks meet or diverge. Grade Crossing
	enumeration	12	documentation The location where two tracks on the same level cross each other. Section of the track

	enumeration	13	Section is inside of the location considered part of a track. documentation Twin track point documentation
	enumeration	14	The spot where is end or start of the twinned track section. documentation Retarder (rail brake) documentation Trackside equipment to control the speed of the wagons running from the shunting hump.
	enumeration	15	documentation Platform documentation The area next to the track which has been raised to make access to railway vehicles easier.
	enumeration	16	documentation Railing documentation barrier Safety equipment used to prevent access to the track by people and animals.
	enumeration	17	documentation Movable scotch block documentation Safety equipment across the track avoiding any unnecessary moving beyond that point.
	enumeration	18	documentation Derailing stop / Trap points / Catch points documentation Safety equipment is on one rail avoiding any unnecessary moving beyond that point.
	enumeration	19	documentation Loading equipment documentation Special equipment to facilitate the loading and unloading on the Public Loading Places.
	enumeration	20	documentation Weighbridge documentation Special equipment is to facilitate the measure of the weight of the wagon.
	enumeration	21	documentation Building documentation Those buildings where IM placed his staff for direct communication with RU staff or the IM buildings serve RU activities as well.
	enumeration	22	documentation Level crossing documentation Place where rail and road crossing in level. on the same level (grade)
	enumeration	23	documentation Bridge documentation Special built structure is over the road
	enumeration	24	documentation Tunnel documentation Structure to to allow a railway line to pass under the surface.
	enumeration	25	documentation Underpass documentation Undercrossing or underground passage under the railway track. (Not used by trains)
	enumeration	26	documentation Block section documentation Block section outside of the location with primary code. In other words: a section on the open track between stations defined by signalling system.
	enumeration	27	documentation Signal

		documentation	A signal is a mechanical or electrical device erected beside a railway line to pass information relating to the state of the line ahead to train drivers/engineers.
enumeration	28	documentation	Sign and board
		documentation	Equipment to inform the board staff for train traffic and shunting.
enumeration	29	documentation	Phase break
		documentation	Border of the power supply systems (catenary).
enumeration	30	documentation	Leap in kilometer
		documentation	The section has deviation in length i. e. the section more or less than called.
enumeration	32	documentation	Balise
		documentation	A balise is an electronic beacon or transponder placed between the rails of a railway as part of an Automatic Train Protection (ATP) system.
enumeration	33	documentation	Hot spot detector
		documentation	Trackside equipment which detects hot wheels or axle-box on passing trains.
enumeration	34	documentation	Flat wheel detector
		documentation	Trackside equipment which detects flat spots on wheels on passing trains.
enumeration	35	documentation	Dynamic wheel load
		documentation	detector Special equipment is in trackside for inspect of the overloaded wagons.
enumeration	36	documentation	Freight yard
		documentation	A freight yard is commercial usage of a physical location which can be used as a sending or a destination station in freight orders of rail freight transports. The freight yard can have his own codification
enumeration	37	documentation	Loading point
		documentation	A loading point is a commercial usage of a physical location. Each loading point is assigned to a yard.
enumeration	38	documentation	IM Network link
		documentation	It allows to link two locations from different IM Networks
enumeration	39	documentation	Reservation code
enumeration	40	documentation	Metastation
		documentation	To mark a meta location that forms the link between different stations that are considered as equal (for the traveller)
enumeration	41	documentation	CompanySpecificIdentifier
		documentation	Company specific identifier of the primary location
enumeration	42	documentation	
			DIUM stations - Places of acceptance/delivery Station open into international traffic of goods (tariff point included in DIUM) – consignment acceptance/delivery station (loading points are excluded and covered by

		TypeCode 37).	
enumeration	43	documentation	
			Passengers cars public loadings Is a type of physical location on the open access network where passengers can put their car on a carrying train
enumeration	44	documentation	
			Passengers cars private loading Is a type of physical location outside the open access network where passengers can put their car on a carrying train
enumeration	45	documentation	
			Sewage dump Place for cleaning purposes - disposal of the waste
enumeration	46	documentation	
			Refuelling Point Location where refuelling takes place
enumeration	47	documentation	
			Mains Supply Location where energy supply can be provided for the rolling stock e.g. preheating
enumeration	48	documentation	
			Water Supply Location where water supply can be provided for the rolling stock
enumeration	49	documentation	
			Compressed plant Train on a track with motion stabled with external air supply for braking systems
enumeration	50	documentation	
			Indoor cleaning platform Cleaning point - interior
enumeration	51	documentation	
			Car-wash plant Cleaning point -outdoor
enumeration	52	documentation	
			Short dry-cleaning track Cleaning point
enumeration	53	documentation	
			Pollution protective plate Track where floor that avoids pollution of the earth below
enumeration	54	documentation	
			Sand-filling station Location where sand is

		filled		
enumeration	55	documentation	Repair track	Location where a train/wagon/engine can be repaired
enumeration	56	documentation	Signal box	The location of a building containing signalling equipment
enumeration	57	documentation		Intermodal Terminal
		documentation		Intermodal Terminal is a location which provides the space, equipment and operational environment under which the transfer of loading units (freight containers, swap bodies, semi-trailers or trailers) takes place
enumeration	58	documentation		OSJD system based location
		documentation		Location code used within OSJD
enumeration	59	documentation		Train Service Substitute Stop
		documentation		Place outside of railway station or railway stop, where passengers board or leave bus or any other transport mean as substitution of train service. Physical part of Primary Location.
enumeration	60	documentation		Multifunctional rail terminal
		documentation		Facilities for conventional and/or intermodal rail/road transshipment principally open for public use and for all types of cargo. This kind of facility does not only provide transshipment, but also additional services like storage, consignment or road pre/end haulage. Physical part of Primary Location.
enumeration	61	documentation		Relief facility
		documentation		Facilities providing equipment and infrastructure used to overcome a disruption (derailment, collision or other accidents). Physical part of Primary Location.
enumeration	66	documentation		Location ENEE Code
		documentation		Legacy ENEE code of the parent primary location. Different coding of primary location.
enumeration	70	documentation		Network Border
		documentation		Network border between two neighboring IM's; first or last Primary Location on a network. Attribute of primary location.
enumeration	71	documentation		State border
		documentation		Political border between two member states. Attribute of primary location.
enumeration	72	documentation		Administrative border
		documentation		Border point inside a member state to define federal structures or administrative districts or local areas. Attribute of primary location.
enumeration	74	documentation		Operational handover
		documentation		Location where the responsibility for operation changes or can change between two

	<p>enumeration 75 involved IMs. Attribute of primary location. documentation Planning handover documentation Location where the responsibility for timetable planning and path allocation changes or can change between two involved IMs. Attribute of primary location.</p> <p>enumeration 76 documentation Other technical facility documentation All technical installations and services that are not included in other facility types. E.g. Pre heating, de icing, air conditioning, Washing/cleaning of rolling stock, Disinfection of rolling stock, Sewage removal and Stationary brake test facilities. Physical part of Primary Location.</p> <p>enumeration 90 documentation Test Loc</p> <p>enumeration 99 documentation Relation to Station documentation An indicator used to show that this location is a subsidiary of another location.</p>
<p>source</p>	<pre> <xs:attribute name="LocationSubsidiaryTypeCode"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="0"> <xs:annotation> <xs:documentation>Not Defined</xs:documentation> <xs:documentation>not used</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="1"> <xs:annotation> <xs:documentation>Track</xs:documentation> <xs:documentation>The track is a uniquely defined part of location</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="2"> <xs:annotation> <xs:documentation>Private Siding</xs:documentation> <xs:documentation>Tracks are not for open access</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="3"> <xs:annotation> <xs:documentation>Border Point Code</xs:documentation> <xs:documentation>Special code for the Border Points are allocated at the country border and the points between different IM networks. Location of these points sometimes are not geographically same with the station or yard. Therefore these points are "logical point"</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="4"> <xs:annotation> <xs:documentation>Sorting Code</xs:documentation> <xs:documentation>Destination station of the wagon has a code in order to provide shunting technology.</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:attribute> </pre>


```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="5">
  <xs:annotation>
    <xs:documentation>Vehicle Parking Points</xs:documentation>
    <xs:documentation>All points (tracks)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="6">
  <xs:annotation>
    <xs:documentation>Public Loading Places</xs:documentation>
    <xs:documentation>Is a type of physical location on the open
access network where consignor or consignee can load or unload
wagons</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="7">
  <xs:annotation>
    <xs:documentation>Private Loading Places</xs:documentation>
    <xs:documentation>Is a type of physical location outside the open
access network where consignor or consignee can load or unload
wagons</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="8">
  <xs:annotation>
    <xs:documentation>IM Path Tariff Point</xs:documentation>
    <xs:documentation>Price Segment change between two IM
Networks.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="9">
  <xs:annotation>
    <xs:documentation>Depot / Maintenance workshop.
Place for overhaul or maintenance of the rolling stock.

</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="10">
  <xs:annotation>
    <xs:documentation>Switch/turnout</xs:documentation>
    <xs:documentation>The location where two tracks meet or
diverge.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="11">
  <xs:annotation>
    <xs:documentation>Grade Crossing</xs:documentation>
    <xs:documentation>The location where two tracks on the same level
cross each other.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="12">
  <xs:annotation>
    <xs:documentation>Section of the track</xs:documentation>
    <xs:documentation>Section is inside of the location considered
part of a track.</xs:documentation>

```

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="13">
  <xs:annotation>
    <xs:documentation>Twin track point</xs:documentation>
    <xs:documentation>The spot where is end or start of the twinned
track section.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="14">
  <xs:annotation>
    <xs:documentation>Retarder (rail brake)</xs:documentation>
    <xs:documentation>Trackside equipment to control the speed of the
wagons running from the shunting hump.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="15">
  <xs:annotation>
    <xs:documentation>Platform</xs:documentation>
    <xs:documentation>The area next to the track which has been raised
to make access to railway vehicles easier.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="16">
  <xs:annotation>
    <xs:documentation>Railing</xs:documentation>
    <xs:documentation>barrier Safety equipment used to prevent access
to the track by people and animals.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="17">
  <xs:annotation>
    <xs:documentation>Movable scotch block</xs:documentation>
    <xs:documentation>Safety equipment across the track avoiding any
unnecessary moving beyond that point.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="18">
  <xs:annotation>
    <xs:documentation>Derailing stop / Trap points / Catch
points</xs:documentation>
    <xs:documentation>Safety equipment is on one rail avoiding any
unnecessary moving beyond that point.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="19">
  <xs:annotation>
    <xs:documentation>Loading equipment</xs:documentation>
    <xs:documentation>Special equipment to facilitate the loading and
unloading on the Public Loading Places.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="20">
  <xs:annotation>
    <xs:documentation>Weighbridge</xs:documentation>
    <xs:documentation>Special equipment is to facilitate the measure
of the weight of the wagon.</xs:documentation>
  </xs:annotation>
</xs:enumeration>

```

```

</xs:enumeration>
<xs:enumeration value="21">
  <xs:annotation>
    <xs:documentation>Building</xs:documentation>
    <xs:documentation>Those buildings where IM placed his staff for
direct communication with RU staff or the IM buildings serve RU activities
as well.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="22">
  <xs:annotation>
    <xs:documentation>Level crossing</xs:documentation>
    <xs:documentation>Place where rail and road crossing in level. on
the same level (grade)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="23">
  <xs:annotation>
    <xs:documentation>Bridge</xs:documentation>
    <xs:documentation>Special built structure is over the
road</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="24">
  <xs:annotation>
    <xs:documentation>Tunnel</xs:documentation>
    <xs:documentation>Structure to to allow a railway line to pass
under the surface.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="25">
  <xs:annotation>
    <xs:documentation>Underpass</xs:documentation>
    <xs:documentation>Undercrossing or underground passage under the
railway track. (Not used by trains)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="26">
  <xs:annotation>
    <xs:documentation>Block section</xs:documentation>
    <xs:documentation>Block section outside of the location with
primary code. In other words: a section on the open track between stations
defined by signalling system.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="27">
  <xs:annotation>
    <xs:documentation>Signal</xs:documentation>
    <xs:documentation>A signal is a mechanical or electrical device
erected beside a railway line to pass information relating to the state of
the line ahead to train drivers/engineers.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="28">
  <xs:annotation>
    <xs:documentation>Sign and board</xs:documentation>
    <xs:documentation>Equipment to inform the board staff for train
traffic and shunting.</xs:documentation>

```

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="29">
  <xs:annotation>
    <xs:documentation>Phase break</xs:documentation>
    <xs:documentation>Border of the power supply systems
(catenary).</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="30">
  <xs:annotation>
    <xs:documentation>Leap in kilometer</xs:documentation>
    <xs:documentation>The section has deviation in length i. e. the
section more or less than called.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="32">
  <xs:annotation>
    <xs:documentation>Balise</xs:documentation>
    <xs:documentation>A balise is an electronic beacon or transponder
placed between the rails of a railway as part of an Automatic Train
Protection (ATP) system.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="33">
  <xs:annotation>
    <xs:documentation>Hot spot detector</xs:documentation>
    <xs:documentation>Trackside equipment which detects hot wheels or
axle-box on passing trains.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="34">
  <xs:annotation>
    <xs:documentation>Flat wheel detector</xs:documentation>
    <xs:documentation>Trackside equipment which detects flat spots on
wheels on passing trains.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="35">
  <xs:annotation>
    <xs:documentation>Dynamic wheel load</xs:documentation>
    <xs:documentation>detector Special equipment is in trackside for
inspect of the overloaded wagons.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="36">
  <xs:annotation>
    <xs:documentation>Freight yard</xs:documentation>
    <xs:documentation>A freight yard is commercial usage of a physical
location which can be used as a sending or a destination station in freight
orders of rail freight transports. The freight yard can have his own
codification</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="37">
  <xs:annotation>
    <xs:documentation>Loading point</xs:documentation>
    <xs:documentation>A loading point is a commercial usage of a

```

```

physical location. Each loading point is assigned to a
yard.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="38">
  <xs:annotation>
    <xs:documentation>IM Network link</xs:documentation>
    <xs:documentation>It allows to link two locations from different
IM Networks</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="39">
  <xs:annotation>
    <xs:documentation>Reservation code</xs:documentation>
    <xs:documentation/>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="40">
  <xs:annotation>
    <xs:documentation>Metastation</xs:documentation>
    <xs:documentation>To mark a meta location that forms the link
between different stations that are considered as equal (for the
traveller)</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="41">
  <xs:annotation>
    <xs:documentation>CompanySpecificIdentifier</xs:documentation>
    <xs:documentation>Company specific identifier of the primary
location</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="42">
  <xs:annotation>
    <xs:documentation>
      DIUM stations - Places of acceptance/delivery
      Station open into international traffic of goods (tariff point
included in DIUM) - consignment acceptance/delivery station (loading points
are excluded and covered by TypeCode 37).
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="43">
  <xs:annotation>
    <xs:documentation>
      Passengers cars public loading Is a type of
physical location on the open access network where passengers can put their
car on a carrying train
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="44">
  <xs:annotation>
    <xs:documentation>
      Passengers cars private loading Is a type of
physical location outside the open access network where passengers can put
their car on a carrying train
    </xs:documentation>
  </xs:annotation>
</xs:documentation>

```

```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="45">
  <xs:annotation>
    <xs:documentation>
      Sewage dump Place for cleaning purposes -
disposal of the waste
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="46">
  <xs:annotation>
    <xs:documentation>
      Refuelling Point Location where refuelling
takes place
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="47">
  <xs:annotation>
    <xs:documentation>
      Mains Supply Location where energy supply can be
provided for the rolling stock e.g. preheating
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="48">
  <xs:annotation>
    <xs:documentation>
      Water Supply Location where water supply can be
provided for the rolling stock
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="49">
  <xs:annotation>
    <xs:documentation>
      Compressed plant Train on a track with motion
stabled with external air supply for braking systems
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="50">
  <xs:annotation>
    <xs:documentation>
      Indoor cleaning platform Cleaning point -interior
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="51">
  <xs:annotation>
    <xs:documentation>
      Car-wash plant Cleaning point -outdoor
    </xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="52">
  <xs:annotation>

```

```

        <xs:documentation>
            Short dry-cleaning track Cleaning point
        </xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="53">
    <xs:annotation>
        <xs:documentation>
            Pollution protective plateTrack where floor that
            avoids pollution of the earth below
        </xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="54">
    <xs:annotation>
        <xs:documentation>
            Sand-filling station Location where sand is
            filled
        </xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="55">
    <xs:annotation>
        <xs:documentation>
            Repair track Location where a train/wagon/engine
            can be repaired
        </xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="56">
    <xs:annotation>
        <xs:documentation>
            Signal box The location of a building containing
            signalling equipment
        </xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="57">
    <xs:annotation>
        <xs:documentation>Intermodal Terminal</xs:documentation>
        <xs:documentation> Intermodal Terminal is a location which
        provides the space, equipment and operational environment under which the
        transfer of loading units (freight containers, swap bodies, semi-trailers or
        trailers) takes place </xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="58">
    <xs:annotation>
        <xs:documentation>OSJD system based location</xs:documentation>
        <xs:documentation>Location code used within
        OSJD</xs:documentation>
    </xs:annotation>
</xs:enumeration>
<xs:enumeration value="59">
    <xs:annotation>
        <xs:documentation>Train Service Substitute Stop</xs:documentation>
        <xs:documentation>Place outside of railway station or railway
        stop, where passengers board or leave bus or any other transport mean as
    
```

```

substitution of train service. Physical part of Primary
Location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="60">
<xs:annotation>
<xs:documentation>Multifunctional rail terminal</xs:documentation>
<xs:documentation>Facilities for conventional and/or intermodal
rail/road transshipment principally open for public use and for all types of
cargo. This kind of facility does not only provide transshipment, but also
additional services like storage, consignment or road pre/end haulage.
Physical part of Primary Location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="61">
<xs:annotation>
<xs:documentation>Relief facility</xs:documentation>
<xs:documentation>Facilities providing equipment and
infrastructure used to overcome a disruption (derailment, collision or other
accidents). Physical part of Primary Location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="66">
<xs:annotation>
<xs:documentation>Location ENEE Code</xs:documentation>
<xs:documentation>Legacy ENEE code of the parent primary location.
Different coding of primary location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="70">
<xs:annotation>
<xs:documentation>Network Border</xs:documentation>
<xs:documentation>Network border between two neighboring IM's;
first or last Primary Location on a network. Attribute of primary
location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="71">
<xs:annotation>
<xs:documentation>State border</xs:documentation>
<xs:documentation>Political border between two member states.
Attribute of primary location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="72">
<xs:annotation>
<xs:documentation>Administrative border</xs:documentation>
<xs:documentation>Border point inside a member state to define
federal structures or administrative districts or local areas. Attribute of
primary location.</xs:documentation>
</xs:annotation>
</xs:enumeration>
<xs:enumeration value="74">
<xs:annotation>
<xs:documentation>Operational handover</xs:documentation>
<xs:documentation>Location where the responsibility for operation
changes or can change between two involved IMs. Attribute of primary
location.</xs:documentation>

```



```

</xs:annotation>
</xs:enumeration>
<xs:enumeration value="75">
  <xs:annotation>
    <xs:documentation>Planning handover</xs:documentation>
    <xs:documentation>Location where the responsibility for timetable
    planning and path allocation changes or can change between two involved IMs.
    Attribute of primary location.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="76">
  <xs:annotation>
    <xs:documentation>Other technical facility</xs:documentation>
    <xs:documentation>All technical installations and services that
    are not included in other facility types. E.g. Pre heating, de icing, air
    conditioning, Washing/cleaning of rolling stock, Disinfection of rolling
    stock, Sewage removal and Stationary brake test facilities. Physical part of
    Primary Location.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="90">
  <xs:annotation>
    <xs:documentation>Test Loc</xs:documentation>
    <xs:documentation/>
  </xs:annotation>
</xs:enumeration>
<xs:enumeration value="99">
  <xs:annotation>
    <xs:documentation>Relation to Station</xs:documentation>
    <xs:documentation>An indicator used to show that this location is
    a subsidiary of another location.</xs:documentation>
  </xs:annotation>
</xs:enumeration>
</xs:restriction>
</xs:simpleType>
</xs:attribute>

```

attribute **TimingQualifierCode**

namespace	http://www.era.europa.eu/schemes/TAFTSI/3.3		
type	restriction of xs:token		
facets	Kind	Value	Annotation
	enumeration	PLA	documentation Public Location Arrival
	enumeration	PLD	documentation Public Location Departure
	enumeration	ELA	documentation Earliest Location Arrival
	enumeration	ELD	documentation Earliest Location Departure
	enumeration	LLA	documentation Latest Location Arrival
	enumeration	LLD	documentation Latest Location Departure
	enumeration	ALA	documentation Actual Location Arival
	enumeration	ALD	documentation

	Actual Location Departure
source	<pre> <xs:attribute name="TimingQualifierCode"> <xs:annotation> <xs:documentation/> </xs:annotation> <xs:simpleType> <xs:restriction base="xs:token"> <xs:enumeration value="PLA"> <xs:annotation> <xs:documentation>Public Location Arrival</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="PLD"> <xs:annotation> <xs:documentation>Public Location Departure</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ELA"> <xs:annotation> <xs:documentation>Earliest Location Arrival</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ELD"> <xs:annotation> <xs:documentation>Earliest Location Departure</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="LLA"> <xs:annotation> <xs:documentation>Latest Location Arrival</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="LLD"> <xs:annotation> <xs:documentation>Latest Location Departure</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ALA"> <xs:annotation> <xs:documentation>Actual Location Arrival</xs:documentation> </xs:annotation> </xs:enumeration> <xs:enumeration value="ALD"> <xs:annotation> <xs:documentation>Actual Location Departure</xs:documentation> </xs:annotation> </xs:enumeration> </xs:restriction> </xs:simpleType> </xs:attribute> </pre>