

# ERTMS/ETCS FIS for the RBC/RBC Handover involving a Baseline 2 RBC REF : SUBSET-129 ISSUE : 1.0.0 DATE : 01-12-2017

Company	Technical Approval	Management approval
ALSTOM		
ANSALDO		
AZD		
BOMBARDIER		
CAF		
SIEMENS		
THALES		



## 1. MODIFICATION HISTORY

Issue Number Date	Section Number	Modification / Description	Author
v.0.01		New document	Unisig WP RBC-
03-07-2014			RBC Handover
v.0.02		Updates according to the	Unisig WP RBC-
29-07-2014		agreed WP comments	RBC Handover
v.0.0.3		Updates following SG	Unisig WP RBC-
14-10-2014		review	RBC Handover
v.0.0.4	3.2, 4.2	Updates for Baseline 3	Unisig WP RBC-
31-03-2016		Release 2	RBC Handover
v.0.1.0	Version updated to	SG approval, version for	Unisig WP RBC-
14-04-2016	0.1.0	external review	RBC Handover
v.0.1.1	4.2.1.22, 4.2.1.23,	Update according ERA	Unisig WP RBC-
05-10-2017	4.2.1.24,	review sheet as agreed in	RBC Handover
	5.2.2.1	EECT April 2017	
v.1.0.0	Version updated to	Version for publication in	Unisig WP RBC-
01-12-2017	1.0.0	Application Guide	RBC Handover



## 2. TABLE OF CONTENTS

Modi	FICATION HISTORY	2
TABLE	E OF CONTENTS	3
INTRO	DDUCTION	4
3.1	Scope and Purpose	4
3.2	References	4
Requ	JIREMENTS ON A B3 RBC INTERFACING WITH A B2 RBC	5
4.1	General Requirements	5
4.2	Amendments to [Subset-039] when interfacing with a B2 RBC	5
ISSUE	ES REQUIRING PROJECT SPECIFIC CONSIDERATION	8
5.1	Introduction	8
5.2	Pre-Announcement	8
5.2.	.1 Repetition of Pre-Announcement	8
5.2.	.2 Acknowledgement of Pre-Announcement	8
5.2.	.3 Pre-Announcement of the train with OBU in LS mode	8
5.3	Receiving RRI before the first RRI Request	8
5.4	Updating of Train Data	8
5.5	Definition of the variables Q_RRIMACHANGE and Q_TDCHANGE	9
5.6	Handling of life sign messages	9
	TABL INTRO 3.1 3.2 REQU 4.1 4.2 ISSUE 5.1 5.2 5.2 5.2 5.2 5.2 5.2 5.2 5.2 5.2 5.2	<ul> <li>3.2 References</li> <li>3.2 References</li> <li>REQUIREMENTS ON A B3 RBC INTERFACING WITH A B2 RBC</li> <li>4.1 General Requirements</li> <li>4.2 Amendments to [Subset-039] when interfacing with a B2 RBC</li> <li>ISSUES REQUIRING PROJECT SPECIFIC CONSIDERATION</li> <li>5.1 Introduction</li> <li>5.2 Pre-Announcement</li> <li>5.2.1 Repetition of Pre-Announcement</li> <li>5.2.2 Acknowledgement of Pre-Announcement</li> <li>5.2.3 Pre-Announcement of the train with OBU in LS mode</li> <li>5.3 Receiving RRI before the first RRI Request</li> <li>5.4 Updating of Train Data</li> <li>5.5 Definition of the variables Q_RRIMACHANGE and Q_TDCHANGE</li> </ul>



### 3. INTRODUCTION

#### 3.1 Scope and Purpose

- 3.1.1.1 This document specifies the functional interface for the RBC/RBC communication to perform an RBC/RBC handover between a Baseline 3 (B3) RBC and a Baseline 2 (B2) RBC according to the principles and procedures in the SRS [Subset-026].
- 3.1.1.2 The requirements contained in this document are specified for the B3 RBC, i.e. there are no requirements on a B2 RBC.
- 3.1.1.3 The B2 RBC operates with system version 1.0 and implements [Subset-039 v2.3.0].
- 3.1.1.4 To be compliant with this specification all the requirements of this specification shall be implemented in the B3 RBC.
- 3.1.1.5 The purpose of this specification is to enable a B3 RBC and a B2 RBC to be interconnected so that RBC/RBC handovers can be performed, independently of service performance and safety of the concerned RBCs, which are outside the scope of this specification.
- 3.1.1.6 Chapter 5 describes RBC/RBC handover issues for which this document does not provide harmonised solutions.

#### 3.2 References

Reference	Title
Subset-023	Glossary of Terms and Abbreviations
Subset-026	System Requirements Specification
Subset-039	FIS for the RBC/RBC Handover
Subset-039 v2.3.0	FIS for the RBC/RBC Handover v2.3.0



# 4. REQUIREMENTS ON A B3 RBC INTERFACING WITH A B2 RBC

#### 4.1 General Requirements

- 4.1.1.1 The [Subset-039] shall apply with the amendments specified in the following section 4.2.
- 4.1.1.1.1 Note: Any B3 RBC exchanging information with a B2 RBC has to comply with the requirements of [Subset-039] applicable to an interface according to system version 1.0 with the additional exceptions following in this specification in section 4.2.
- 4.1.1.2 Note: The statements in chapter 5 of the current document must be taken into account to avoid possible operational and/or safety problems caused by functional aspects which were not harmonised in the framework of the ETCS Baseline 2 specification.

#### 4.2 Amendments to [Subset-039] when interfacing with a B2 RBC

- 4.2.1.1 [Subset-039] clause 4.5.1.6 shall not apply.
- 4.2.1.2 [Subset-039] clause 4.5.2.6 shall not apply.
- 4.2.1.3 In [Subset-039] clause 6.2.2.9 the incoming event "New train data received" specified in Table B2 of Annex B shall not apply.
- 4.2.1.4 In [Subset-039] clause 6.2.2.9 the outgoing event "New train data" specified in Table B3 of Annex B shall not apply.
- 4.2.1.5 In [Subset-039] clause 6.2.2.9 the event "New train data received" specified in Table B4 of Annex B shall not apply.
- 4.2.1.6 In [Subset-039] clause 6.2.2.10 the incoming event "New train data received" specified in Table B6 of Annex B shall not apply.
- 4.2.1.7 In [Subset-039] clause 6.2.2.10 the event "New train data received" specified in Table B8 of Annex B shall not apply.
- 4.2.1.8 In [Subset-039] Table 13 additional configuration item shall apply:

Configuration items	Description
RRI confirmation implemented in the neighbouring RBC	Yes/No



4.2.1.9 In [Subset-039] Table 13 additional configuration item shall apply:

Configuration items	Description
TSR revocation implemented in the neighbouring RBC	Yes/No

- 4.2.1.10 In [Subset-039] Table 14, message with identifier 207 shall not apply.
- 4.2.1.11 [Subset-039] clause 5.2.5 shall not apply.
- 4.2.1.12 In [Subset-039] clause 6.2.3.20 message identifier 207 shall not apply.
- 4.2.1.13 If the configuration item added in clause 4.2.1.9 has the value "No" then packet 66 shall be excluded from the list of optional packets specified in [Subset-039] clause 6.2.3.10.
- 4.2.1.14 If the configuration item added in clause 4.2.1.8 has the value "No" then [Subset-039] clause 5.3.3 shall not apply.
- 4.2.1.15 If the configuration item added in clause 4.2.1.9 has the value "No" then packet 66 shall be excluded from the list of track-to-train packets specified in [Subset-039] clause 6.2.3.16.
- 4.2.1.16 If the configuration item added in clause 4.2.1.8 has the value "No" then message identifier 224 shall be excluded from the list specified in [Subset-039] clause 6.2.3.20.
- 4.2.1.17 [Subset-039] clause 5.2.1.1 shall be replaced with: "Note: Pre-Announcement is only supported for on-boards in modes FS, OS, SR, TR, PT or NL because in other modes either the Accepting RBC cannot forward any information to the on-board or the on-board cannot handle an RBC/RBC handover."
- 4.2.1.18 If the configuration item added in clause 4.2.1.9 of this document has the value "No" then [Subset-039] clause 6.2.3.2 shall be modified to read "Clause 5.1.1.7 shall be replaced with: "It shall be forbidden to send more instances of the same packet type in the same message, except for Packet 65 (TSR)."
- 4.2.1.19 In [Subset-039] clause 6.2.3.7 mode LS shall not apply.
- 4.2.1.20 In [Subset-039] clause 6.2.4.4.1 shall be replaced with: "In case an engine has to be pre-announced to an RBC X=1 then packet 11 shall be translated as follows:". The tables and translations related to this clause remain unchanged.
- 4.2.1.21 In [Subset-039] clause 6.2.4.4.2 shall be replaced with: "Note In case an engine is preannounced to an RBC X=1 the train running number cannot be sent in packet 5 but only as part of the train data in packet 11."
- 4.2.1.22 In [Subset-039] clause 4.5.2.1 shall be replaced with: "If acknowledgement of preannouncement is requested by the Handing Over RBC then the Accepting RBC is allowed to send route related information to the Handing Over RBC after the



acknowledgement of the pre-announcement. If acknowledgement of preannouncement is not requested by the Handing Over RBC then the Accepting RBC is allowed to send route related information after reception of the pre-announcement from the Handing Over RBC."

- 4.2.1.23 In [Subset-039] clause 5.1.1.6.b) an additional rule shall apply: "Value 0 of variable M\_ACK in a pre-announcement message shall be regarded as valid value.".
- 4.2.1.24 In [Subset-039] clause B.2.1.5 row 1 of table 8 shall be replaced by

Pre-Announcement received	If M_ACK=1: Send "Acknowledgement"→ ACC	If M_ACK=1: Send "Acknowledgement"→ ACC
	If M_ACK=0:	If M_ACK=0:
	$\rightarrow ACC$	$\rightarrow ACC$



### 5. ISSUES REQUIRING PROJECT SPECIFIC CONSIDERATION

#### 5.1 Introduction

- 5.1.1.1 The points described in this chapter may lead to operation and/or safety issues unless they are addressed in the framework of a specific project.
- 5.1.1.2 The following sections identify each issue, but do not propose mitigations as these cannot be generic.

#### 5.2 **Pre-Announcement**

#### 5.2.1 Repetition of Pre-Announcement

5.2.1.1 The management of Pre-Announcement during an ongoing handover is not clearly defined in B2. No functional equivalent of [Subset-039] clauses 4.3.1.4, 4.3.1.5, 4.3.1.6 and 4.3.1.7 exists for B2 RBCs.

#### 5.2.2 Acknowledgement of Pre-Announcement

5.2.2.1 In B2 the acknowledgement request (M\_ACK = 1) for a Pre-Announcement message is not mandatory, and it is not mandatory for a B2 RBC to acknowledge the Preannouncement before sending RRI. This raises the issue for a B3 Handing Over RBC that it could receive an RRI message before the acknowledgement of a Pre-Announcement.

#### 5.2.3 **Pre-Announcement of the train with OBU in LS mode**

5.2.3.1 A train in LS mode cannot be pre-announced to a B2 RBC because the value for this mode is not allowed in the Pre-Announcement to a B2 RBC.

#### 5.3 Receiving RRI before the first RRI Request

5.3.1.1 No functional equivalent of [Subset-039] clauses 4.3.1.8 exists for B2 RBCs.

#### 5.4 Updating of Train Data

5.4.1.1 In B2 there is no harmonised means to update train data and train running number during an ongoing handover.



# 5.5 Definition of the variables Q\_RRIMACHANGE and Q\_TDCHANGE

5.5.1.1 The rules for the usage of variables Q\_RRIMACHANGE and Q\_TDCHANGE are different between the baselines.

#### 5.6 Handling of life sign messages

5.6.1.1 Resolution and range of cycle times for transmission/reception of life sign messages are not defined in B2.