

Moving Europe towards a sustainable and safe railway system without frontiers.

## Guide for the application of the WAG TSI

*In accordance with Article 19(3) of Regulation (EU) 2016/796 of the European Parliament and of the Council of 11 May 2016*

### *Document History*

<i>Version date</i>	<i>Section number</i>	<i>Modification description</i>
Version 1.0 15/04/2013	All	First publication
Version 2.0 03/03/2015	1.1, 2.1, 2.3, 2.4, 2.8, 2.10, 2.11	Second publication incorporating amendments brought by Regulation (EU) No 1236/2013 and Regulation (EU) 2015/924
Version 3.0 15/02/2021	All	Third publication incorporating amendments brought by Commission Implementing Regulation (EU) 2019/776 (4th Railway Package amendment)
Version 4.0 8/12/2023	All	Fourth publication incorporating amendments brought by Commission Implementing Regulation (EU) 2023/1694

## Table of Contents

1	SCOPE OF THIS GUIDE .....	4
1.1	Content of the guide .....	4
1.2	Document reference/s .....	4
1.3	Definitions and abbreviations .....	4
2	GUIDANCE ON THE APPLICATION OF THE WAG TSI.....	4
2.1	Scope and definition of the subsystem.....	4
2.2	Essential requirements .....	11
2.3	Characterisation of the subsystem .....	11
2.3.1	Section 4.1: Introduction .....	11
2.3.2	Point 4.2.1 General .....	12
2.3.3	Point 4.2.2.1.1: End coupling and point 4.2.2.1.2: Inner coupling.....	12
2.3.4	Point 4.2.2.2: Strength of unit.....	13
2.3.5	Point 4.2.2.3: Integrity of the unit - Requirements applicable to units used for combined transport .....	13
2.3.6	Point 4.2.3.1: Gauging.....	14
2.3.7	Point 4.2.3.3: Compatibility with train detection systems .....	14
2.3.8	Point 4.2.3.4: Axle bearing condition monitoring.....	15
2.3.9	Points 4.2.3.5.2, 6.1.2.1 and 6.2.2.3: Running dynamic behaviour/Running gear .....	15
2.3.10	Point 4.2.3.5.3: Derailment detection and prevention function .....	17
2.3.11	Points 4.2.3.6.2 and 6.1.2.2: Characteristics of wheelsets .....	18
2.3.12	Points 4.2.3.6.3 and 6.1.2.3: Characteristics of wheels .....	18
2.3.13	Points 4.2.3.6.4 and 6.1.2.4: Characteristics of axles.....	20
2.3.14	Points 4.2.3.6.5 and 6.2.2.4: Axle boxes/bearings.....	20
2.3.15	Points 4.2.3.6.6, 6.1.2.6 and 6.2.2.4a: Automatic variable gauge systems .....	21
2.3.16	Points 4.2.3.6.7 and 6.2.2.5: Running gear for manual change of wheelsets.....	22
2.3.17	Point 4.2.4.2: Brake - Safety requirements.....	22
2.3.18	Point 4.2.4.3.2: Brake - Brake performance.....	23
2.3.19	Point 4.2.4.3.3: Brake - Thermal capacity .....	24
2.3.20	Point 4.2.4.3.4: Brake - Wheel slide protection .....	24
2.3.21	Points 4.2.4.3.5 and 6.1.2.5: Friction elements for wheel tread brakes.....	25
2.3.22	Point 4.2.5: Environmental conditions.....	26
2.3.23	Point 4.2.6.1.1: Fire safety - General .....	27
2.3.24	Point 4.2.6.1.2.1: Fire safety - Barriers .....	27
2.3.25	Points 4.2.6.1.2.2 and 6.2.2.8.2: Fire safety – Materials.....	28
2.3.26	Point 4.5.3: Maintenance description file.....	28
2.3.27	Section 4.7: Health and Safety conditions .....	29
2.3.28	Section 4.8: Parameters to be recorded in the technical file and European register of authorised types of vehicles .....	30
2.4	Interoperability constituent(s).....	30
2.4.1	Point 5.3.3: Wheel.....	30
2.5	Conformity assessment and EC verification.....	30
2.5.1	Section 6.1: Conformity assessment procedures.....	30

2.5.2	Section 6.3: Subsystem containing components corresponding to interoperability constituents not holding an EC declaration.....	31
3	IMPLEMENTATION .....	31
3.1	General rules on application.....	31
3.1.1	Point 7.1: Authorisation for placing on the market .....	31
3.1.2	Point 7.1.1 Application to ongoing projects.....	32
3.2	Point 7.1.2: Mutual recognition of the first authorisation for placing on the market.....	32
3.3	Point 7.2.1: Substitution of constituents .....	34
3.4	Point 7.2.2 Changes to an existing unit or to an existing unit type, point 7.2.2.1 Introduction .....	34
3.5	Point 7.2.2.2: Rules to manage changes in both a unit or a unit type.....	35
3.6	Point 7.2.2.4: Rules for the extension of the area of use for units having an authorisation in accordance with Directive 2008/57/EC or in operation before 19 July 2010 .....	36
3.7	Point 7.2.3.1.1: Rules related to the EC type or design examination certificates - Definitions.....	40
3.8	Point 7.1.3.1.2: Rules related to the EC type or design examination certificate .....	41
3.8.1	Example 1.....	41
3.8.2	Other examples can be added according to the return of experience– currently left blank intentionally .....	42
4	APPENDICES OF THE WAG TSI.....	42
4.1	Appendix C: Additional optional conditions .....	42
4.2	Appendix D – List of referenced standards.....	43
5	PRACTICAL CASES.....	43
5.1	Example of a unit to carry lorries (‘Rollende Landstrasse’) .....	43
6	TRANSITION PHASES CONCERNING FRICTION ELEMENTS FOR WHEEL TREAD BRAKES.....	44
6.1	ERA technical document ERA/TD/2013-02/INT .....	45
6.1.1	Chapter 4 ‘Dynamic friction coefficient’ of the ERA TD .....	45
6.1.2	Chapter 5 ‘Static friction coefficient’ of the ERA TD .....	46
6.1.3	Chapter 6 ‘Mechanical characteristics’ of the ERA TD.....	47
6.1.4	Chapter 7 ‘Suitability for train detection by systems based on track circuits’ of the ERA TD .....	47
6.1.5	Chapter 8 ‘Suitability for severe environmental conditions’ of the ERA TD.....	48
6.1.6	Section 8.1 ‘Test run’ .....	49
6.1.7	Section 8.2 ‘Dynamometer test’ .....	49
6.1.8	Chapter 9 ‘Thermo mechanical characteristics’ of the ERA TD .....	50
7	APPLICABLE SPECIFICATIONS AND STANDARDS .....	51
7.1	Explanation of the use of the specifications and standards .....	51
7.2	Annex 1 Voluntary standards.....	51
7.3	Annex 2 Guidance on marking.....	57

## 1 SCOPE OF THIS GUIDE

This document is an annex to the ‘Guide for the application of TSIs’. It provides information on the application of **Commission Regulation (EU) No 321/2013 of 13 March 2013 concerning the technical specification for interoperability relating to the subsystem ‘rolling stock – freight wagons’** (further referred to as ‘WAG TSI’).

This version 2023 of the guide is updated based on the **Commission Implementing Regulation (EU) 2023/1694 of 10 August 2023 amending Regulations (EU) No 321/2013, (EU) No 1299/2014, (EU) No 1300/2014, (EU) No 1301/2014, (EU) No 1302/2014, (EU) No 1304/2014 and Implementing Regulation (EU) 2019/777**.

The guide should be read and used only in conjunction with the WAG TSI. It is intended to facilitate its application, but does not replace it. The general part of the ‘Guide for the application of TSIs’ should also be considered.

### 1.1 Content of the guide

In section 2 of this document, extracts of the original text of the WAG TSI are provided in shaded text boxes, which are followed by a text that gives guidance.

Guidance is not provided for clauses where the original WAG TSI requires no further explanation.

Guidance is of voluntary application. It does not mandate any requirement in addition to those set out in the WAG TSI.

Guidance is given by means of further explanatory text and, where relevant, by reference to standards that demonstrate compliance with the WAG TSI. Relevant standards are listed in Appendix 1 of this document, and their purpose is indicated in the column ‘purpose’ of the table.

### 1.2 Document reference/s

Reference documents are listed in the general part of the ‘Guide for the application of TSIs’.

### 1.3 Definitions and abbreviations

Definitions and abbreviations are given in the “Guide for the Application of TSIs”

## 2 GUIDANCE ON THE APPLICATION OF THE WAG TSI

### 2.1 Scope and definition of the subsystem

Sections 2.1: Scope and 7.1: Authorisation for placing on the market

*2.1. Scope*

*(...)*

*The other vehicles listed in Section 2 of Annex I to Directive (EU) 2016/797 are excluded from the scope of this TSI; this is especially the case for:*

- (a) *special vehicles;*
- (b) *vehicles designed to carry:*
- *motor vehicles with their passengers on board, or*
  - *motor vehicles without passengers on board but intended to be integrated in passenger trains (car carriers):*
- (c) *vehicles which*
- *increase their length in loaded configuration, and*
  - *their payload itself is part of the vehicle structure.*

*Note: See also section 7.1 for particular cases.*

#### *7.1. Authorisation for placing on the market*

*(1) This TSI is applicable to the subsystem ‘rolling stock — freight wagons’ within the scope set out in its Sections 1.1, 1.2 and 2.1, which are placed on the market after the date of application of this TSI, except where point 7.1.1 ‘Application to ongoing projects’ applies.*

*(2) This TSI is also applicable on a voluntary basis to:*

- *units referred to in section 2.1 point (a) in running mode, in case they correspond to a ‘unit’ as defined in this TSI, and*
- *units as defined in section 2.1 point (c), in case they are in empty configuration.*

*In case the applicant chooses to apply this TSI, the corresponding EC declaration of verification shall be recognised as such by Member States.*

In case of special vehicles in running mode, the applicant can apply either the WAG TSI (only when hauled) or the LOC&PAS TSI for conformity assessment; a vehicle may be assessed under either of the TSIs depending on the characteristics and the intended use of the vehicle in question in comparison with the technical scope of the respective TSIs.

The following Figure 1 and Figure 2 provide examples of vehicles that increase their length in loaded configuration and which payload is part of the vehicle structure.



Figure 1 - Example of a vehicle that increases its length in loaded configuration and its payload is part of the vehicle structure (in loaded configuration)




Figure 2 - Two examples of vehicles that increase their length in loaded configuration and their payload is part of the vehicle structure (in unloaded configuration)

## Section 2.2: Definitions

(a) A 'unit' is the generic term used to name the rolling stock. It is subject to the application of this TSI, and therefore subject to the EC verification procedure.

A unit can consist of:

- a 'wagon' that can be operated separately, featuring an individual frame mounted on its own set of wheels, or
- a rake of permanently connected 'elements', those elements cannot be operated separately, or
- 'separate rail bogies connected to compatible road vehicle(s)' the combination of which forms a rake of a rail compatible system.

The following figures clarify these definitions.



Figure 3 - Example of a unit consisting of a (freight) wagon that can be operated separately, featuring an individual frame mounted on its own set of wheels



Figure 4 - Example 1 of a unit consisting of a rake of permanently connected two elements (blue and orange), those elements cannot be operated separately (articulated wagon)



Figure 5 - Example 2 of a unit consisting of a rake of permanently connected two elements; those elements cannot be operated separately



Figure 6 - Example 3 of a unit consisting of a rake of permanently connected elements, those elements cannot be operated separately (self-discharging train)



Figure 7 - Example 1 of a unit consisting of separate rail bogies connected to compatible road vehicles



Figure 8 - Example 2 of a unit consisting of separate rail bogies connected to compatible road vehicles

*(c) The ‘design operating state’ covers all conditions under which the unit is intended to operate and its technical boundaries. This design operating state may go beyond the specifications of this TSI in order that units may be used together in a train on the network under the safety management system of a railway undertaking.*

According to Article 2 (31) of the Interoperability Directive, “‘design operating state’ means the normal operating mode and the foreseeable degraded conditions (including wear) within the range and the conditions of use specified in the technical and maintenance files.”

The foreseeable degraded conditions can be divided into the following categories, in accordance with point 4.2.4.5.2 of the TSI LOC&PAS:

1. Degraded condition = unfavourable external influence on the subsystem or on the interoperability constituent.
2. Degraded mode = failure, or wear limit reached, in the subsystem or in the interoperability constituent.

The NoBo scope of assessment is limited to the TSI requirements, i.e. the effects of those degraded modes and conditions that are explicitly mentioned in the TSIs and/or the referred sections of mandatory standards, on the TSI requirements under assessment.

## 2.2 Essential requirements

*The essential requirements 1.3.1, 1.4.1, 1.4.3, 1.4.4 and 1.4.5 of Annex III of the Directive (EU) 2016/797 fall under the scope of other Union legislation.*

The following essential requirements have not been dealt with at all within the drafting process of the WAG TSI because they are in the scope of other mandatory EU legislation:

**1.3.1** *Materials likely, by virtue of the way they are used, to constitute a health hazard to those having access to them must not be used in trains and railway infrastructures.* (Directive 2006/42/EC on machinery)

**1.4.1** *The environmental impact of establishment and operation of the rail system must be assessed and taken into account at the design stage of the system in accordance with the Community provisions in force.* (Directive 2011/92/EU on the assessment of the effects of certain public and private projects on the environment and Directive 2008/68/EC on the inland transport of dangerous goods)

**1.4.3** *The rolling stock and energy-supply systems must be designed and manufactured in such a way as to be electromagnetically compatible with the installations, equipment and public or private networks with which they might interfere.* (Directive 2014/30/EU on the harmonisation of the laws of the Member States relating to electromagnetic compatibility)

**1.4.4** *The design and operation of the rail system must not lead to an inadmissible level of noise generated by it:*

- *in areas close to railway infrastructure, as defined in Article 3 of Directive 2012/34/EU, and*
- *in the driver's cab. (Commission Regulation (EU) No 1304/2014 on the technical specification for interoperability relating to the subsystem 'rolling stock – noise')*

**1.4.5** *Operation of the rail system must not give rise to an inadmissible level of ground vibrations for the activities and areas close to the infrastructure and in a normal state of maintenance.* (Directive 2002/44/EC on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (vibration))

## 2.3 Characterisation of the subsystem

### 2.3.1 Section 4.1: Introduction

*The rail system, to which the Directive (EU) 2016/797 applies and of which freight wagons form a part, is an integrated system whose consistency shall be verified. This consistency shall be checked in particular with regard to the specifications of the rolling stock subsystem and the compatibility with the network (section 4.2), its interfaces in relation to the other subsystems of the rail system in which it is integrated (sections 4.2 and 4.3), as well as the initial operating and maintenance rules (sections 4.4 and 4.5) as requested by Article 15(4) of Directive (EU) 2016/797. The technical file, as set out in Article 15(4) of Directive (EU) 2016/797 and in point 2.4 of Annex IV to that Directive, shall contain in particular design related values concerning the compatibility with the network.*

The WAG TSI covers the harmonisation of all subsystem-related

- *basic parameters necessary to achieve interoperability and safe integration including the*

- *basic parameters needed for the RU to establish together with the IM the compatibility of a unit with the network.*

The WAG TSI sets out in addition how the values of the compatibility relevant basic parameters must be determined (calculation method, tests, simulations). Concerning the safe integration the applicant has to compile the initial documentation containing in particular all the elements relating to the conditions and limits of use and to the instructions concerning servicing, constant or routine monitoring, adjustment and maintenance. This documentation has to accompany the unit and enables the RUs to take their responsibility concerning the safe operation as per Article 4.1(d) of the Railway Safety Directive (Directive (EU) 2016/798) and the OPE TSI.

The process of establishing the compatibility with infrastructure may be centralised, performed once giving restrictions of use line per line, or performed for each time slot allocated by the infrastructure manager. Whichever is the case, the railway undertaking has to control that all the wagons in its train composition are capable and suitable of going on the line the train is slotted for in respect of loading (axle load), loading gauge, brake performance (brake weight), etc.

### 2.3.2 Point 4.2.1 General

*In light of the essential requirements in Chapter 3, the functional and technical specifications of the subsystem ‘rolling stock — freight wagons’ are grouped and sorted out in the following points of this Chapter:*

- *Structures and mechanical parts*
- *Gauging and vehicle track interaction*
- *Brake*
- *Environmental conditions*
- *System protection.*

*Except where this is strictly necessary for the interoperability of the rail system and to meet the relevant essential requirements, the functional and technical specifications of the freight wagon and its interfaces do not impose the use of any particular technical solutions.*

*[...]*

Measures to ensure that the load do not leave the freight wagon are not covered by this TSI. The TSI is not intended to be a design guide including good practice and advice; this type of requirements belongs to the people who are professional freight forwarders. Therefore not any load securing requirements are considered in the TSI, including design hints for the doors, specific requirements for the attachment of Semi-Trailers to Railcar Trailer, side and end walls such as these “shall be designed to carry the maximum load they will experience in performing their intended function”

### 2.3.3 Point 4.2.2.1.1: End coupling and point 4.2.2.1.2: Inner coupling

*End couplings shall be resilient and capable of withstanding the forces in accordance with the defined design operating state of the unit.*

*The inner coupling shall be resilient and capable of withstanding the forces in accordance with the defined design operating state of the unit. The joint between two elements sharing the same running gear, is covered by point 4.2.2.2.*

*The longitudinal strength of the inner coupling(s) shall be equal to or higher than the one of the end coupling(s) of the unit.*

The input parameters coming from the intended operation of the wagon (e.g. train weight, acceleration/deceleration of the train, etc.) determines the load (dynamic traction and compressive forces, etc.) the coupling must be designed for. The longitudinal direction is to be taken as the travel direction of the train.

#### 2.3.4 Point 4.2.2.2: Strength of unit

*The structure of a unit body, any equipment attachments and lifting and jacking points shall be designed such that no cracks, no significant permanent deformation or ruptures occur under the load cases defined in the specification referenced in Appendix D Index [1].*

*In case of a rake of a rail compatible system composed of separate rail bogies connected to compatible road vehicles, the load cases may differ from those mentioned above, due to their bi-modal specification; in such a case, the load cases considered shall be described by the applicant based on a consistent set of specifications with consideration of the specific conditions of use related to train composition, shunting and operation.*

‘Equipment attachments’ include loading devices.

In case of a rake of a rail compatible system composed of separate rail bogies connected to compatible road vehicles, the road vehicles are also subject to the requirements of point 4.2.2.2.

For tank wagons which fall under the scope of point 6.8.2.1.2 of RID, the following is to be taken into account in the load cases to assess the strength of the wagon:

- *The maximum working pressure of the tank has been superimposed on the load cases*
- *The operating temperature range of the shell and*
- *The minimum wall thickness of the shell in accordance to RID 6.8.2.1 and 6.8.2.6.*

#### 2.3.5 Point 4.2.2.3: Integrity of the unit - Requirements applicable to units used for combined transport

*(...)*

*Units intended to be used for combined transport and requiring a wagon compatibility code shall be equipped with devices for securing the Intermodal Loading Unit.*

The following standards provide acceptable means of compliance to the requirements:

- *Units for the conveyance of containers and swap bodies with a compatibility code respectively ISO and C:*
  - (a) are equipped with fixed, foldable or removable devices compliant with points 2.3, 2.4 and 2.6 of IRS 50571-4:2022.
  - (b) The position of these devices complies with points 2.7, 2.7.1 and 2.7.2 of IRS 50571-4:2021.
  - (c) Point 2.8 of IRS 50571-4:2021 applies additionally to wagons intended to be used for the carriage of heavy duty containers.

- *Units for the conveyance of semi-trailers with a compatibility code P:*
  - (a) equipped with a seating device compliant with points 3.4.2 and 3.4.4 to 3.4.9 of IRS 50571-4:2022 clause 3.4:
  
- *Units for the conveyance of roller units for horizontal transshipment with a compatibility code B:*
  - (a) equipped with a pivoting frame compliant to points 2.2 to 2.7 of IRS 50571-5:2021 2

### 2.3.6 Point 4.2.3.1: Gauging

*The compliance of a unit with the intended reference profile including the reference profile for the lower part shall be established by one of the methods set out in the specification referenced in Appendix D index [4].*

*The kinematic method, as described in the specification referenced in Appendix D Index [4] shall be used to establish conformity, if any, between the reference profile established for the unit and the respective target reference profiles G1, GA, GB and GC including those used for the lower part GI1 and GI2.*

The compliance with the requirements is used by the RU for the establishment of the compatibility with the structure gauge of the infrastructure.

This compliance shall be demonstrated in any case, not only for the interoperable gauges.

Furthermore the EN 15273-2:2013+A1:2016 contains requirements on the minimum vertical convex / concave curve radius capability which have to be registered in ERATV as these are a basic design characteristic and part of the route compatibility check.

### 2.3.7 Point 4.2.3.3: Compatibility with train detection systems

- *If the unit is intended to be compatible with one or more of the following train detection systems, this compatibility shall be established according to the provisions of the technical document referenced in Appendix D.2 Index [A]: Train detection systems based on track circuits (the electrical resistance of the wheelset can be assessed at IC level or at vehicle level);*
- *Train detection systems based on axle counters;*
- *Train detection systems based on loop equipment.*

The set of parameters in order to be compatible with train detection systems, such as track circuits, axle counters and loop systems, have been identified in the TSI with references to the CCS TSI for each parameter and type of train detection system. The related specific cases are defined in point 7.7 of TSI CCS.

The TSI requirement for rolling stock regarding compatibility with CCS TSI is that the train detection system(s) which the rolling stock has been assessed as being compatible with is (are) declared and recorded in the technical documentation.

As referred into article 13 of TSI CCS, By 31 December 2024, Member States that operate non-TSI-compliant train-detection systems must request a specific case and shall notify the Agency of these systems by informing it about:

- the interference current limits for track circuits including the evaluation methods and vehicle impedance in accordance with point 3.2.2 of index 77 of CCS TSI
- field limits for axle counters in X, Y, Z axis including the evaluation methods in accordance with point 3.2.1 of index 77 of CCS TSI

For non TSI compliant train detection system, pending that parameters above are specified in the specific cases or in the technical documents referred in Article 13 of CCS TSI , national rules remain applicable.

- National rules are assessed by Designated Bodies.
- Assessment by NoBo can be performed only when the parameters above will be specified in the specific cases or in the technical documents referred in Article 13 of CCS TSI

The assessment of the rolling stock regarding train detection systems requirements specified in index 77 of TSI CCS referred in point 4.2.3.3.1 of this TSI is part of EC verification for the Rolling Stock subsystem and is to be assessed by the RST NoBo, this include the relevant specific cases defined in point 7.7 of CCS TSIs.

If the brake system requires friction elements for wheel tread brakes, compliance with chapter 7 of ERA technical document ERA/TD/2013-02/INT published on the ERA website (<http://www.era.europa.eu>) fulfils the requirements on compatibility with train detection systems based on track circuits set out in ERA/ERTMS/033281 rev. 3.0 for use of composite brake blocks.

The assessment of the rolling stock regarding train detection systems requirements specified in index 77 of TSI CCS referred in point 4.2.3.3.1 of this TSI is part of EC verification for the Rolling Stock subsystem and is to be assessed by the RST NoBo, this include the relevant specific cases defined in point 7.7 of CCS TSIs.

#### 2.3.8 Point 4.2.3.4: Axle bearing condition monitoring

*If the unit is intended to be capable of being monitored by on-board equipment, the following requirements shall apply:*

- *This equipment shall be able to detect a deterioration of any of the axle box bearings of the unit.*
- *The bearing condition shall be evaluated either by monitoring its temperature, or its dynamic frequencies or some other suitable bearing condition characteristic.*
- *The detection system shall be located entirely on board the unit, and diagnosis messages shall be available on board the unit.*
- *The diagnosis messages delivered and how they are made available shall be described in the operating documentation set out in section 4.4 of this TSI, and in the maintenance rules described in section 4.5 of this TSI.*

Some technical solutions complying with the requirements of this point are:

- *Train bus including the locomotive and other units forming a train*
- *Radio communication to an operational centre that may send the received messages to the driver by radio (similarly to what is done currently with fixed detection systems)*
- *Fusible plug*
- *Other solutions*

#### 2.3.9 Points 4.2.3.5.2, 6.1.2.1 and 6.2.2.3: Running dynamic behaviour/Running gear

*The running dynamic behaviour of a unit shall be proven either by*

- *following the procedures set out in the specification referenced in Appendix D Index [7], or*

- *performing simulations using a validated model.*

*The demonstration of conformity is described in point 6.2.2.3.*

*Running dynamic behaviour is permitted to be assessed at interoperability constituent level in accordance with point 6.1.2.1. In this case a specific test or simulation at subsystem level is not required.*

The TSI sets out several possibilities to verify the running dynamic behaviour of a wagon as set out in Figure 9.




Figure 9 – Flow chart of all the possibilities to prove the running dynamic behaviour in the TSI

*6.2.2.3. Running dynamic behaviour**On-track tests*

*The demonstration of conformity shall be carried out in accordance with the specification referenced in Appendix D Index [7].*

EN 14363:2016+A2:2022 applies to vehicles intended for circulation on 1435 mm track gauge networks; however, it is permissible to apply this standard by analogy for vehicles intended for circulation on other track gauges. The related test conditions and limit values are specified in this TSI.

*The combination of the highest equivalent conicity and speed for which the unit meets the stability criterion in the specification referenced in Appendix D Index [7] shall be recorded in the report.*

The recorded combination of the highest equivalent conicity and speed enables the implementation of operational measures where necessary due to infrastructure characteristics.

*2.3.10 Point 4.2.3.5.3: Derailment detection and prevention function*

*If a unit is fitted with the derailment detection and prevention function, the requirements below shall be met.*

It is not mandatory to fit a unit with the derailment prevention and detection function in order to fulfil the requirements of this TSI. However, it might be, that EU legislation requires to fit some particular types of freight wagons with this function at some point in time.

*Points 4.2.3.5.3.2 Derailment prevention function and 4.2.3.5.3.3. Derailment detection function**‘4.2.3.5.3.2 Derailment prevention function (DPF)*

*The DPF shall send a signal to the driver’s cab of the locomotive hauling the train once a precursor to derailment is detected in the unit.*

*The signal enabling the DPF to be available at train level and its transmission between the unit, the locomotive and the other coupled unit(s) in a train shall be documented in the technical file.*

*4.2.3.5.3.3. Derailment detection function (DDF)*

*The DDF shall send a signal to the driver’s cab of the locomotive hauling the train once the derailment is detected in the unit.*

*The signal enabling the DDF to be available at train level and its transmission between the unit, the locomotive and the other coupled unit(s) in a train shall be documented in the technical file.’*

It is possible to send the signal to the driver’s cab of the locomotive via an electronic tool (e.g, a tablet) outside the scope of the TSI LOC&PAS. In such case, the requirements of signal processing set out in TSI LOC&PAS do not apply.

*Point 4.2.3.5.3.4 Derailment detection and actuation function (DDAF)*

*The DDAF shall automatically activate a brake application when the derailment is detected without possibility of overriding by the driver.*

*The risk of false derailment detections shall be limited to an acceptable level.*

*Therefore, the DDAF shall be subject to a risk assessment in accordance with Implementing Regulation (EU) No 402/2013.*

If the DDAF consists of standard devices according to the requirements of chapter 4.2.3.5.3.4 fitted in the freight wagon, this risk assessment can be carried out generically at device level. This safety analysis might conclude that additional operational conditions/restrictions for use are required in order to grant the safety at freight train level.

Additional guidance is available in the Agency webpage:

[https://www.era.europa.eu/sites/default/files/activities/docs/guidelines\\_from\\_eu\\_agency\\_for\\_railways\\_use\\_derailment\\_detectors\\_en.pdf](https://www.era.europa.eu/sites/default/files/activities/docs/guidelines_from_eu_agency_for_railways_use_derailment_detectors_en.pdf)

Additional information on design specifications regarding purely pneumatic DDAF are available in UIC 541-08:2007, Chapter 1.

#### 2.3.11 Points 4.2.3.6.2 and 6.1.2.2: Characteristics of wheelsets

*The demonstration of conformity for the mechanical behaviour of the wheelset assembly shall be carried out in accordance with the specification referenced in Appendix D Index [10], which defines limit values for the axial assembly force and the associated verification test.*

The requirement of the wheelset mechanical behaviour of the assembly as expressed in the TSI is intended to ensure the ability of 'transmitting the forces and a torque between the fitted elements' as stated in clause 4.2.1 of EN 13260:2020.

#### 2.3.12 Points 4.2.3.6.3 and 6.1.2.3: Characteristics of wheels

*The mechanical characteristics of the wheels shall ensure the transmission of forces and torque as well as the resistance against thermal load where so required in accordance with the area of use.*

- ...

*If the wheel is intended to be used with brake blocks acting on the wheel running surface, the wheel shall be thermo mechanically proven by taking into account the maximum braking energy foreseen.*

According to the mentioned clauses, the wheel is required to be resistant against thermal effects - requirements on thermal aspects of the interoperability constituent 'wheel' are herewith specified and assessment is performed according to point 6.1.2.3. Furthermore, in accordance with point 4.2.4.3.3, the brake equipment is required to be able to withstand one emergency brake application without any loss of brake performance due to thermal effects - requirements on thermal aspects of the brake at the level of the subsystem are therefore defined and assessment is performed according to point 6.2.2.6.

ERA technical document ERA/TD/2013-02/INT additionally specifies in chapter 9 the voluntary performance of a 'locked brake test' of a friction element for wheel tread brakes (according to EN 16452: 2015+A1:2019).

The objective of this test is to determine from the temperature of a wheel tread measured after being braked by defined brake force during defined time the conformity/non-conformity of the friction element. This test represents a possibility for the friction element manufacturer to test thermal aspects of the friction element in addition to the mandatory verification, as specified in the previous paragraph, of thermal aspects of wheels (by the wheels manufacturer) and the brake system of the wagon (by the applicant). If the manufacturer of the friction element decides to perform this additional test, he has to record the evidence of it in the technical documentation as part of the area of use.

- *Forged and rolled wheels: The mechanical characteristics shall be proven following the procedure as described in the specification referenced in Appendix D Index [11].*

The wheel is required to be designed following the methodology set out in clause 8 of EN 13979-1:2020 , which requires calculations to be performed and subsequent tests if design criteria are not met.

For tread braked wheels the requirements of clause 6.2.1 of EN 13979-1:2020 are fulfilled only by using the values of Table C.4.

The design criteria, the permissible range of dynamic stress, are defined for forged and rolled wheels. The test to be performed in case of exceeding the criteria is a bench test where it is required that no fatigue cracks must be observed after the test.

- ...  
*The decision criteria of residual stresses for forged and rolled wheels are set out in the same specification .*

The decision criteria of the thermo mechanical behaviour of wheels for materials other than ER6 and ER7 which are presented in EN 13979-1:2020 have to be extrapolated from known data. Furthermore, any other type of wheel than those set out in the TSI, are permitted for (and restricted to) national use.

- *A verification procedure shall exist to ensure at the production phase that no defects may adversely affect safety due to any change in the mechanical characteristics of the wheels.*

The wheel is a component, which needs to be checked and controlled, not only for the design criteria, but also for ensuring end quality of the product. EN 13262:2020 sets out the verification procedure to be followed for the parameters stated in the TSI; the material characteristics and the number of samples to be checked in production, the procedures to follow for any changes in the design of the axle or changes of manufacturer of the material of the axle, etc.

The verification of the fatigue characteristics of the wheel material, as set out in the TSI, is only intended to be performed if there is a change of supplier of the raw material for the production of the wheel or there are any changes to the manufacturing process or the design of the wheel is appreciably changed.

### 2.3.13 Points 4.2.3.6.4 and 6.1.2.4: Characteristics of axles

*In addition to the requirement on the assembly above, the demonstration of conformity of the mechanical resistance and fatigue characteristics of the axle shall be based on the specification referenced in Appendix D, index [12].*

*That specification includes the decision criteria for the permissible stress.*

The verification of the axle is supposed to be done by calculation as set out in EN 13103-1:2017+A1:2021 which defines the load cases to consider, the specific calculation methods for the design of the axle and the decision criteria, the permissible stress, for steel grade EA1N and the methodology for arriving to permissible stress with other materials.

*A verification procedure shall exist to ensure at the production phase that no defects may adversely affect safety due to any change in the mechanical characteristics of the axles. The tensile strength of the material in the axle, the resistance to impact, the surface integrity, the material characteristics and the material cleanliness shall be verified. The verification procedure shall specify the batch sampling used for each characteristic to be verified.*

The axle is a component, which needs to be checked and controlled, not only for the design criteria, but also for ensuring end quality of the product. EN 13261:2020 sets out the verification procedure to be followed for the parameters stated in the TSI; the number of samples to be checked in production, the procedures to follow for any changes in the design of the axle or changes of manufacturer of the material of the axle, etc.

### 2.3.14 Points 4.2.3.6.5 and 6.2.2.4: Axle boxes/bearings

*The axle box and the rolling bearing shall be designed with consideration of mechanical resistance and fatigue characteristics.*

*(...) the demonstration of conformity for mechanical resistance and fatigue characteristics of the rolling bearing shall be in accordance with the specification referenced in Appendix D, index [13].*

Clause 7 of EN 12082:2017+A1:2021 consists of a rig test for an assembly composed of axle box housing, rolling bearing(s), sealing and grease.

A suitable demonstration of conformity for the axle box assembly may be performed by the applicant and checked by the notified body.

*It is permitted to use other standards for the above demonstration of conformity where the EN standards do not cover the proposed technical solution; in that case the notified body shall verify that the alternative standards form part of a technically consistent set of standards applicable to the design, construction and testing of the bearings.*

The paragraph above is also applicable in cases where the assembly does not have an axle box.

## 2.3.15 Points 4.2.3.6.6, 6.1.2.6 and 6.2.2.4a: Automatic variable gauge systems

*The failure of the locking of the position of the wheels and braking equipment (if relevant) during operation has typical credible potential to lead directly to a catastrophic accident (resulting in multiple fatalities); considering this severity of the failure consequence, it shall be demonstrated that the risk is controlled to an acceptable level.*

*The safety analysis required in point 4.2.3.6.6, and performed at IC level, shall be consolidated at the level of the unit; in particular, the assumptions made in accordance with point 6.1.2.6 may need to be reviewed to take into account the unit and its mission profile.*

The latest revision of the common safety method for risk evaluation and assessment (Commission Implementing Regulation (EU) 402/2013) clarifies in point 2.5.6 of its Annex I that the harmonised design targets needed to apply the 'explicit risk estimation and evaluation' cannot be used neither for purely mechanical systems nor for purely mechanical part of mixed systems.

Taking into account that the safety target is fixed in the TSI for the locking of the position of the wheels and braking equipment in the variable gauge system, as long as this system is

- *purely mechanical or*
- *composed of both a purely mechanical part and an electrical, electronic and programmable electronic part*

a safety demonstration referred to in points 4.2.3.6.6, 6.1.2.6 and 6.2.2.4a of the TSI should use as risk acceptance principles 'codes of practice' or 'similar reference systems'. This means that the manufacturer will have to compare the proposed solution to similar existing ones (e.g. mechanical systems subject to similar forces); a risk analysis based on 'explicit risk estimation and evaluation' should not be acceptable for the purely mechanical part.

The existing codes of practice for the validation of these systems are:

- *EN 17069-1:2019 'Railway applications - Systems and procedures for change of track gauge'*
- *National rules (e.g. Annex G of ETH de Material Rodante Ferroviario. Vagones, DGF-MFOM, 2009 – Spanish Technical Rule)*

Existing systems already in service can be referred to as reference systems.

*The automatic variable gauge system may be subject to an assessment of suitability for use (module CV). Before commencing in-service tests, a suitable module (CB or CH1) shall be used to certify the design of the interoperability constituent. The in-service tests shall be organised on request from the manufacturer, who must obtain an agreement from a railway undertaking for its contribution to such assessment.*

The manufacturer has the ultimate responsibility to meeting all the essential requirements applicable to automatic variable gauge system. The WAG TSI further specifies mandatory in-service testing if there is insufficient return of experience for the proposed design of the system. The notion of return of experience is to be understood in this context. The manufacturer is the best placed actor to decide (under his sole responsibility) on its own maturity taking into account the area of use of the automatic variable gauge system on the one hand and the previous experience with similar types of systems on the other hand. The safety analysis required in point 4.2.3.6.6 may be used for this purpose.

According to Decision 2010/713/EU, it is the manufacturer who defines the programme for validation of an automatic variable gauge system by in-service experience using module CV. The on-track tests described in

EN 17069-1:2019 'Railway applications - Systems and procedures for change of track gauge' may be taken as reference. The provisions of this draft standard may be altered by the manufacturer taken into account the area of use of the automatic variable gauge system and the level of experience that the manufacturer possesses with similar designs of this equipment. The objective of in-service testing is to perform the tests under real conditions and tailored to match the area of use of the automatic variable gauge system.

#### 2.3.16 Points 4.2.3.6.7 and 6.2.2.5: Running gear for manual change of wheelsets

*Changeover between 1 435 mm and 1 668 mm track gauges*

*The technical solutions described in the specification referenced in Appendix D Index [14] for axle units and for bogie units are deemed to be compliant with the requirements in point 4.2.3.6.7.*

*Changeover between 1 435 mm and 1 524 mm track gauges*

*The technical solution described in the specification referenced in Appendix D Index [15] is deemed to be compliant with the requirements in point 4.2.3.6.7.*

At the present time, only one approach for the manual change of wheelsets exists. The requirements concerning the interface between the unit and the current facilities carrying out the manual change of wheelsets can be found in UIC leaflet 430-1:2012 (1 435 mm/1 668 mm) and in UIC leaflet 430-3:1995 (1 435 mm/1 524 mm).

Should alternatives become available these will be addressed within the revision of this Application Guide.

#### 2.3.17 Point 4.2.4.2: Brake - Safety requirements

*The braking system contributes to the safety level of the railway system. Therefore the design of the braking system of a unit has to undergo a risk assessment in accordance with Commission Implementing Regulation (EU) No 402/2013 considering the hazard of complete loss of the brake capability of the unit. The severity level shall be deemed as catastrophic when:*

- *it affects the unit alone (combination of failures), or*
- *it affects the brake capability of more than the unit (single fault).*

*The fulfilment of the conditions of C.9 and C.14 of Appendix C is presumed to be in conformity with this requirement.*

The brake system contributes significantly to the safety level of the railway system. Therefore, point 4.2.4.2 of the TSI requires a risk assessment in accordance with Commission Implementing Regulation (EU) No 402/2013 on risk evaluation and assessment (CSM regulation). The risk assessment is based on the following commonly accepted risk acceptance principles:

- the application of codes of practice and risk evaluation, and/or
- use of reference system and risk evaluation, and/or
- an explicit risk estimation and evaluation.

The applicant/proposer may choose which of the principles he wants to apply.

The hazard to be covered by this risk assessment is the complete loss of the brake capability of the unit. The following two scenarios are required to be controlled:

- The failure or combination of failures is affecting only the brake capability of the unit itself.
- One single failure leads to a loss of the brake capability of another unit or of other units in a train.

Both scenarios are allocated to the severity level ‘catastrophic’ which means that the associated risk does not have to be reduced further if the rate of that failure or combination of failures is less than or equal to  $10^{-9}$  per operating hour. All failures and the causes which may lead to one of these scenarios are to be analysed and identified.

The CSM regulation in its Article 15(1) obliges the assessment body to provide the applicant/proposer with a safety assessment report which must contain e.g. all made assumptions.

The applicant has to record in the technical file all corresponding operating and maintenance rules which shall be met (see section 4.4 and 4.5 of the TSI) in order to control the given scenarios. This information enables the RUs and ECMs to take their responsibility in accordance with Article 4(3) of the Railway Safety Directive (Directive 2004/49/EC).

One possibility to carry out the risk assessment can be the application of a code of practise, such as the CENELEC standards EN 50126-1:2017, EN 50128:2011+A1:2019+A2:2020 4, EN 50129:2018+AC:2019-04 and 50367:2020+A1:2022, or some others, including the compliance with their applicable ‘reliability, availability maintainability and safety (RAMS)’ requirements. In this case, the corresponding RAMS performance must be recorded in the technical file as well.

#### The Brake block

The brake block (i.e. friction element for wheel tread brakes) is a part of the brake system and is assessed together with it. Therefore, the proposer/applicant has to follow the CSM approach also for the brake block. The corresponding codes of practise should be considered as applied if brake blocks:

- *are part of those listed in Appendix G of the TSI, or*
- *fulfil the requirements set out in point 4.2.4.3.5 and are assessed in accordance with the procedure set out in point 6.1.2.5 of the TSI, or*
- *are part of those listed in Appendix M of UIC leaflet 541-4:2010, or*
- *other agreed publicly available codes of practice for wagons restricted to national use only.*

#### 2.3.18 Point 4.2.4.3.2: Brake - Brake performance

*The brake performance of a unit shall be calculated in accordance with one of the specifications referenced in Appendix D, either Index [16], Index [37], Index [58] or Index [17]. The calculation shall be validated by tests. Brake performance calculation in accordance with the specification referenced in Appendix D Index [17] shall be validated as set out in the same specification or in the specification referenced in Appendix D, Index [58].*

A brake performance calculation performed in accordance with the standard quoted in TSI has to be validated as set out in the UIC leaflet. If UIC leaflet is used, the UIC leaflet describes some exemptions, for which tests are not always necessary<sup>1</sup>.

<sup>1</sup> The UIC leaflet refers also to the document ‘Design rules of composite (k) brake blocks’ where describes more exemptions, therefore for which tests are not necessary.

**2.3.19 Point 4.2.4.3.3: Brake - Thermal capacity**

*The braking equipment shall be able to withstand one emergency brake application without any loss of brake performance due to thermal or mechanical effects.*

The essential requirement is fulfilled as soon as the wagon complies with this requirement. The operative rules, depending on the design of the wagon, have to set out how to continue following a standstill after an emergency brake application. It could be necessary to check the brake equipment or to take time restrictions into account before the train is allowed to continue its journey (risk: immediate second emergency brake).

This requirement on thermal aspects of the brake equipment is defined at the level of the subsystem. It means that if the brake system requires friction elements for wheel tread brakes, the friction elements are required to comply because they are part of the brake.

*The thermal load that the unit is capable of withstanding without any adverse loss of brake performance due to thermal or mechanical effects, shall be defined and expressed in terms of speed, axle load, gradient and brake distance.*

This thermal load should be consistent with the resistance against thermal load of the wheel as set out in point 4.2.3.6.3.

*A slope of 21 ‰ at 70 km/h during 40 km may be considered as the reference case for the thermal capacity which results in a braking power of 45 kW per wheel during 34 minutes for a nominal wheel diameter of 920 mm and an axle load of 22,5 t.*

The requirement allows for any thermal capacity of the brake equipment. The reference case sets out a combination of values considered representative for a major part of the European network. The fulfilment of the brake components with the reference case is to be recorded in the technical file and in ERATV.

**2.3.20 Point 4.2.4.3.4: Brake - Wheel slide protection**

*The following types of units shall be fitted with WSP:*

- *types of units equipped with all types of brake blocks except composite brake blocks, for which the maximum mean utilisation of adhesion is greater than 0,12,*
- *types of units equipped with brake discs only and/or with composite brake blocks, for which the maximum mean utilisation of adhesion is greater than 0,11.*

The maximum mean utilisation of adhesion is the maximum mean utilisation of adhesion after response time (in accordance with clause 4.6.10 of EN 14478:2017) considering the speed range between 30 km/h and maximum intended operating speed of the wagon.

For wagons fulfilling the TSI including section 9 of Appendix C and with a maximum braking performance not exceeding a brake percentage calculated in accordance with UIC 544-1:2014 of

- 125%, or
- 130% for empty wagons as defined in Table C.3 of Appendix C,

the requirement is deemed to be fulfilled without WSP.

### 2.3.21 Points 4.2.4.3.5 and 6.1.2.5: Friction elements for wheel tread brakes

*The demonstration of conformity of friction elements for wheel tread brakes shall be carried out by determining the following friction element properties in accordance with ERA technical document ERA/TD/2013-02/INT version 3.0 of 27.11.2015 published on the ERA website (<http://www.era.europa.eu>):*

- *dynamic friction performance (chapter 4);*
- *static friction coefficient (chapter 5);*
- *mechanical characteristics including properties in respect with shear strength test and flexural strength test (chapter 6).*

*Demonstration of the following suitabilities shall be carried out in accordance with chapters 7 and/or 8 of the ERA technical document ERA/TD/2013-02/INT version 3.0 of 27.11.2015 published on the ERA website (<http://www.era.europa.eu>), if the friction element is intended to be suitable for:*

- *train detection by systems based on track circuits; and/or*
- *severe environmental conditions.*

The tests specified in chapters 4, 5 and 6 of the ERA technical document ERA/TD/2013-02/INT are mandatory. The results of these tests have to be recorded in the technical documentation in order to define the area of use of a friction element for wheel tread brakes.

Tests specified in chapters 7 ‘Suitability for train detection by systems based on track circuits’ and 8 ‘Suitability for severe environmental conditions’ are not mandatory. It is up to the manufacturer of the friction element to decide whether his product should be suitable for train detection by systems based on track circuits and/or severe environmental conditions and to perform these tests accordingly. If these tests are not performed, the friction element is considered as ‘not suitable for train detection by systems based on track circuits’ or ‘not suitable for severe environmental conditions’ respectively; the non-suitability for train detection by systems based on track circuits and/or severe environmental conditions should be mentioned in the technical documentation of the interoperability constituent.

A reference to the non-mandatory locked brake test specified in EN 16452:2015+A1:2019 is done in chapter 9 ‘Thermo mechanical characteristics’. Additional guidance is provided in this Application Guide (see section 2.4 providing guidance on points 4.2.3.6.3 and 6.1.2.3 of the TSI).

Please refer to section 2.11 of this Application Guide for further information on the ERA technical document ERA/TD/2013-02/INT.

*If a manufacturer does not have sufficient return of experience (according with its own judgment) for the proposed design, the type validation by in-service experience procedure (module CV) shall be part of the assessment procedure for suitability for use. Before commencing in-service tests, a suitable module (CB or CH1) shall be used to certify the design of the interoperability constituent.*

The manufacturer has the ultimate responsibility to meeting all the essential requirements applicable to a friction element. The WAG TSI further specifies mandatory in-service testing if there is insufficient return of experience for the proposed design of the friction element. The notion of return of experience is to be understood in this context. The manufacturer is the best placed actor to decide (under his sole responsibility) on its own maturity taking into account the area of use of the friction element on the one hand and the

previous experience with similar types of friction elements on the other hand. The manufacturer may use the CSM Regulation for this purpose.

According to Decision 2010/713/EU, it is the manufacturer who defines the programme for validation of a friction element by in-service experience using module CV. Annex V of EN 16452:2015 may be taken as reference. The provisions of this annex may be altered by the manufacturer taken into account the area of use of the friction element and the level of experience that the manufacturer possesses with similar designs of friction elements. The objective of in-service testing is to perform the tests under real conditions and tailored to match the area of use of the friction element.

### 2.3.22 Point 4.2.5: Environmental conditions

*The design of the unit, as well as its constituents shall take into account the environmental conditions to which this rolling stock will be subjected to.*

*The environmental parameters are described in the clauses below. For each environmental parameter, a nominal range is defined, which is the most commonly encountered in Europe, and is the basis for the interoperable unit.*

*For certain environmental parameters ranges other than the nominal one are defined. In that case, a range shall be selected for the design of the unit.*

*For the functions identified in the clauses below, design and/or testing provisions taken to ensure that the rolling stock is meeting the TSI requirements in this range shall be described in the technical file.*

*Depending on the ranges selected and on provisions taken (described in the technical file), appropriate operating rules could be necessary when the unit designed for the nominal range is operated on a particular line where the nominal range is exceeded at certain periods of the year.*

*The ranges, if different from the nominal one, to be selected to avoid any restrictive operating rule(s) linked to environmental conditions, are specified by the Member States and are listed in section 7.4.*

*The unit and its constituents shall be designed under consideration of one or several of the following external air temperature ranges*

- T1: – 25 °C to + 40 °C (nominal),
- T2: – 40 °C to + 35 °C, and
- T3: – 25 °C to + 45 °C.

*The unit shall meet the requirements of this TSI without degradation for snow, ice and hail conditions as defined in the specification referenced in Appendix D Index [18], which correspond to the nominal range.*

*Where more severe ‘snow, ice and hail’ conditions are selected, the unit and its constituents shall then be designed to meet TSI requirements considering the combined effect with low temperature according to the temperature range chosen.*

*In relation with the temperature range T2 and with the severe conditions for snow, ice and hail, the provisions taken to meet TSI requirements in these severe conditions shall be identified and verified, in particular design and/or testing provisions considering the following functions:*

- Coupling function, restricted to the resiliency of couplings.
- Brake function, including brake equipment.

The TSI mandates that environmental conditions of temperature and snow/ice/hail be taken into account in the design of the wagon. Therefore, nominal conditions are set out (temperature range T1 and snow/ice/hail conditions in EN 50125-1:2014).

However, a few MSs have concerns because they meet more severe conditions in some periods of the year. To cover that, severe conditions are specified for the parameters temperature and snow/ice/hail. Concerning the temperature, the ranges T2 (– 40 °C to + 35 °C) and T3 (– 25 °C to + 45 °C) have been introduced, concerning the snow/ice/hail conditions the WAG TSI refers to section 7.4 in case of more severe conditions than those set out in EN 50125-1:2014.

The design and the assessment of a wagon may be completely assessed under nominal conditions or under consideration of one or both of the severe conditions.

The provisions in design and/or in testing taken to meet the chosen conditions are to be reported in the technical file and can be used to establish operating rules e.g. operating rules to take into account the more severe conditions during certain periods of the year in certain Member States.

For unrestricted access concerning the environmental conditions in the MS concerned the conditions set out in section 7.4 of the WAG TSI have to be fulfilled.

The term ‘coupling function’ in the TSI text covers the function of drawing and buffing equipment.

#### 2.3.23 Point 4.2.6.1.1: Fire safety - General

*All significant potential fire sources (high risk components) on the unit shall be identified. The fire safety aspects of the unit design shall be aimed at:*

- *preventing a fire from occurring,*
- *limiting the effects if a fire occurs.*

*The goods carried on the unit are not part of the unit and do not have to be taken into account in the conformity assessment.*

Significant potential fire sources and high-risk components include: contact surfaces of brake blocks, tanks containing flammable liquids, electrical equipment (including cables), combustion engines, heat exchanging equipment like air-conditioning systems.

The fire safety requirements in this TSI are not aimed at the transport of dangerous goods. In case of dangerous goods carried on freight wagons, RID requirements are to be applied in all aspects of fire safety.

#### 2.3.24 Point 4.2.6.1.2.1: Fire safety - Barriers

*In order to limit the effects of fire, fire barriers with integrity of at least 15 minutes shall be installed between the identified potential fire sources (high risk components) and the carried load.*

According to the general experience, a likely fire source on wheel tread braked wagons can be brake blocks.

Technical solutions in accordance with UIC leaflets 430-1:2012 and 543:2018, which contain elements to be fitted above wheels, give presumption of conformity to the requirement in point “4.2.6.1.2.1 Barriers”, for the area above the brake blocks, e.g. wooden floor and running gear.

## 2.3.25 Points 4.2.6.1.2.2 and 6.2.2.8.2: Fire safety – Materials

*All permanent materials used on the unit shall have limited ignitability and flame spread properties, unless:*

- *the material is separated from all potential fire risks on the unit by a fire barrier and the safe application is supported by a risk assessment, or*
- *the component has a mass < 400 g, and is located within a horizontal distance of ≥ 40 mm and a vertical distance of ≥ 400 mm to other non-tested components.*

*The demonstration of conformity is described in point 6.2.2.8.2.*

E.g. rubber parts and synthetic or plastic material of bogies are not to be tested when their main surface is surrounded of a fire barrier compliant with point 6.2.2.8.1 of this TSI and they are supported by a risk assessment.

The expression in point 4.2.6.1.2.2 ‘the component has a mass less than 400 g’ refers to the mass of the material without proven limited ignitability and flame spread properties.

## 2.3.26 Point 4.5.3: Maintenance description file

*The maintenance description file includes the following:*

- ...
- *Parts list which shall contain the technical and functional descriptions of the spare parts (replaceable units). The list shall include all parts specified for changing based on condition, which may require a replacement following electrical or mechanical malfunction or which will foreseeable require a replacement after an accidental damage. Interoperability constituents shall be indicated and referenced to their corresponding declaration of conformity.*
- ...

It is recommended to add to the parts list also the references from the spare part provider and manufacturer, in order to allow identification and procurement of the correct spare parts.

*The maintenance description file includes the following:*

- ...
- *Maintenance plan i.e. the structured set of tasks to perform the maintenance including the activities, procedures and means. The description of this set of tasks includes:*
  - *Disassembly/assembly instructions drawings necessary for correct assembly/disassembly of replaceable parts.*
  - *Maintenance criteria.*
  - *Checks and tests in particular of safety relevant parts; these include visual inspection and non-destructive tests (where appropriate e.g. to detect deficiencies that may impair safety).*
  - *Tools and materials required to undertake the task.*
  - *Consumables required to undertake the task.*
  - *Personal protective safety provision and equipment.*
- ...

It is recommended that the following results of the Task Force on Freight Wagon Maintenance are included in the maintenance description file as they are considered as good practice:

- The harmonised maintenance program of inspection of axles, EVIC that is effective to reduce risks related to corrosion but insufficient to eliminate them completely. (See Annex III of Final report on the activities of the Task Force Freight Wagon Maintenance)
- The identification of the data that needs to be collected in the European Wheelset Traceability Catalogue, EWT (See Annex IV of Final report on the activities of the Task Force Freight Wagon Maintenance)
- The European Common Criteria for Maintenance for freight wagon axles, ECCM (See Annex V of Final report on the activities of the Task Force Freight Wagon Maintenance)

These three documents on railway maintenance, which were developed by the railway sector, should be taken into account by the applicant in the maintenance description file respectively for:

- The development and update of visual inspections on axles (EVIC)
- Defining the content of the part of the configuration file addressing wheelsets (EWT)
- Harmonising the maintenance plans (ECCM) when appropriate

Regarding visual inspections there might be different understandings if they also belong to visual inspections carried out in the operational field outside of a maintenance workshop (see the final report 'certification of maintenance workshops' 01.08.2008, clause 5.1 first steps of maintenance). It is up to the RU and keeper/ECM to carry out the visual inspection, for example as agreed in the GCU.

Visual inspections may be carried out in maintenance workshops or in the operational field, for example by inspectors.

If the applicant can demonstrate through experience and risk assessment that it has more effective maintenance rules than the here-above recommended good practises, it should better introduce these in its maintenance description file.

### 2.3.27 Section 4.7: Health and Safety conditions

*If the unit is fitted with a manual coupling system, a free space for shunters during coupling and uncoupling shall be provided.*

The free space for shunter as defined in clause 6.2.1 of EN 16116-2:2021 is deemed to be in conformity with this requirement of the TSI.

*All protruding parts deemed a hazard to operational staff shall be clearly indicated and/or fitted with protective devices.*

Protective devices as described in clause 1.3 of UIC 535-2:2006 are deemed to be in conformity with this requirement of the TSI.

*The unit shall be equipped with footsteps and handrails except in those cases it is not intended to be operated with staff on-board, e.g. for shunting.*

Footsteps and handrails in accordance with chapter 4 and 5 of EN 16116-2:2021 are deemed to be in conformity with the requirement of the TSI.

### 2.3.28 Section 4.8: Parameters to be recorded in the technical file and European register of authorised types of vehicles

*The technical file shall contain at least the following parameters:*

- ...
- *Position of the axles along the unit and number of axles*
- ...

The position of the axle along the unit and number of axles is the geometrical position of the axles in the unit according to EN 15528:2021.

## 2.4 Interoperability constituent(s)

An IC can be defined if its requirements in the TSI can be assessed independently from the subsystem on constituent level and if its area of use can be specified.

The area of use covers all conditions under which the constituents are intended to be used and their technical boundaries.

### 2.4.1 Point 5.3.3: Wheel

*A wheel shall be designed and assessed for an area of use defined by:*

- *nominal tread diameter,*
- *maximum vertical static force,*
- *maximum speed,*
- *in-service limits, and*
- *maximum braking energy.*

The in-service limits may be defined by the minimum tread diameter.

The last bullet point indicates also the capability to be combined with a certain brake principle. For example, when the brake force is not acting directly on the tread a very low braking energy or zero is stated for this parameter.

## 2.5 Conformity assessment and EC verification

Explanations concerning the conformity assessment in section 6.1 and 6.2 of the WAG TSI are incorporated in section 2.4 of this application guide.

### 2.5.1 Section 6.1: Conformity assessment procedures

*‘(\*) Modules CA1, CA2 or CH may be used only in the case of products placed on the market, and therefore developed, before the entry into force of this TSI, [...]’*

Modules CA1, CA2 or CH may be used only in the case of products manufactured according to a design developed and already used to place products on the market before the entry into force of relevant TSIs applicable to those products.

### 2.5.2 Section 6.3: Subsystem containing components corresponding to interoperability constituents not holding an EC declaration

*A Notified Body is permitted to issue an EC certificate of verification of a subsystem, even if one or more of the components corresponding to interoperability constituents incorporated within the subsystem are not covered by a relevant EC declaration of conformity...*

When a constituent is considered as an IC, the use of a constituent holding an EC declaration is mandatory to get an EC declaration of verification for a RST subsystem unless the conditions set out in section 6.3 of the WAG TSI are applied.

Only components corresponding to an IC not holding an EC certificate (non-certified ICs as defined in point 7.2.1 of the TSI), which are produced before or within the transitional period referred to in section 6.3 as well as in Article 8 of the Commission Regulation (EU) No 321/2013 are allowed to be incorporated in the subsystem. Within this period the manufacturer must obtain an EC certificate otherwise he has to stop the production. Exemption is the running gear, where point 4.2.3.5.2 of the TSI always allows the applicant to choose for the assessment on subsystem level in accordance with point 6.2.2.3 or on interoperability constituent level in accordance with point 6.1.2.1.

The distinction between 'component' and 'interoperability constituent' had to be made because the 'component' means a tangible part of the subsystem and the 'interoperability constituent' is defined by a function.

## 3 IMPLEMENTATION

### 3.1 General rules on application

#### 3.1.1 Point 7.1: Authorisation for placing on the market

*(3) Compliance with this Annex in its version applicable before 28 September 2023 is deemed equivalent to compliance with this TSI, except for changes listed in Appendix A.*

The TSI package 2022 introduces new principles for the transition between TSIs. One of these principles is that the TSI assessment basis is no longer defined at the time of appointment of a NoBo (formerly known as the beginning of phase A).

With the new transition regime, the TSI assessment basis is defined at the time the NoBo delivers the EC type examination certificate (module SB) or the EC design examination certificate (module SH1). In order for an applicant to identify the changes between the TSIs in force at that time and the TSIs in force at the beginning of a project, those changes are identified and categorised as follows:

1. For some changes, compliance with the previous TSI systematically implies compliance with the revised TSI (for instance editorial changes, changes resulting in a softer requirement): those changes aren't listed; the point (3) of the TSI quoted above covers those changes;
2. For some other changes compliance with the previous TSI does not systematically imply compliance with the revised TSI. Those changes are listed in Appendix A and are divided in two subcategories: changes with a generic transition regime and changes with a specific transition regime.

### 3.1.2 Point 7.1.1 Application to ongoing projects

*(1) The application of this TSI applicable from 28 September 2023 is not mandatory for projects that, on that date, are in phase A or phase B as defined in points 7.2.3.1.1 and 7.2.3.1.2 of the ‘previous TSI’ (i.e. this Regulation, as amended by Commission Implementing Regulation (EU) 2020/387)*

For projects that are already in phase A (or in phase B), the application of the revised TSI isn't mandatory. The consequence of not-applying the new TSI is that the type certificate will be delivered according to a previous version of the TSI and will have therefore a 10-year validity. The consequence of applying the new TSI is that the requirements listed in appendix A will be applicable to the project according to their transition regime, but then the validity of the type certificate will not be limited to 10 years.

#### **Case of projects in phase B (type certificate issued before 28 September 2023):**

A modification of the type certificate without modification of the type is to be considered as a correction, without the need to establish a new type certificate under the TSI 2023 framework. The limit of validity of the type certificate isn't changed.

### 3.2 Point 7.1.2: Mutual recognition of the first authorisation for placing on the market

*In accordance with Article 21(3)(b) of Directive (EU) 2016/797 the authorisation for placing on the market of a vehicle (as defined in this TSI) is granted on the basis of:*

*in accordance with point (a) of Article 21(3): the ‘EC’ declaration of verification as provided for in Article 15 of the same directive, and*

*in accordance with (d) of Article 21(3): evidence of the technical compatibility of the unit with the network in the area of use covering the EU network.*

*Points (b) and (c) of Article 21(3) of Directive (EU) 2016/797 do not represent any additional requirement. The technical compatibility of the vehicle with the network being covered by rules (TSIs or national rules), this aspect is also considered at the level of the ‘EC’ verification.*

*Therefore, the conditions for having an area of use not limited to particular national networks are specified below as additional requirements to be covered in the EC verification of the subsystem rolling stock. These conditions shall be seen as complementary to the requirements in Section 4.2 and must be fulfilled in their entirety:*

The precondition to apply the point 7.1.2 of the WAG TSI is that the unit is conforming to all the requirements of chapter 4 of the TSI.

The conditions in the bullet point (b) define the way to deal with the specific case of Sweden. All other specific cases in section 7.3 of the WAG TSI are alleviations solely applicable to domestic traffic, therefore not touching interoperability and subsequently not relevant for the mutual recognition.

Nevertheless, some Member States/NSAs requested for additional conditions for the mutual recognition of the first authorisation with regard to concerns related to the application of the new approach. In (c) and (d) two conditions are to be found related to the compatibility with the network, and the points (e) to (f) refer to technical solutions coming from the former RIV world.

The conditions in bullet point (g) and (h) relates to the marking of the vehicle. The applicable markings as defined in the EN 15877-1: 2012+A1:2018 may be:

- the allocated interoperable gauge,
- the vehicle tare weight,
- the vehicle load table,
- the length over buffers,
- the lifting and re-railing signs,
- the distance between end axles or bogie centres,
- the brake weight,
- wagons built for running between networks with different track gauges.

Units authorised in accordance with this TSI including the additional conditions set out in point 7.1.2 should be marked 'TEN' in accordance with OPE TSI, point 4.2.2.3 and Appendix H thereof.

For existing units, which have been authorised in accordance with Commission Decision 2006/861/EC as amended by Commission Decision 2009/107/EC, and meeting the conditions set out in point 7.6.4 of Commission Decision 2009/107/EC but not fulfilling at least one of the following requirements:

- point 7.6.4 (c) of Commission Decision 2009/107/EC,
- point 7.6.4 (d) of Commission Decision 2009/107/EC,
- Annex Z of Commission Decision 2006/861/EC.

may apply the provisions on modifications to an existing unit covered by an EC certificate of verification set out in point 7.2.2.3 of this TSI in order to demonstrate that they may receive the CW marking.

The EVN (European Vehicle Number) of the wagon should not change after receiving the new marking.

*(d1) If the unit has electronic equipment on board emitting interference current via the rail, the 'influencing unit' (as defined in the technical document referenced in Appendix D.2 Index [A]) of which the unit is planned to be part shall be compliant with specific cases for track circuits notified under Article 13 of CCS TSI by applying the harmonised vehicle test methods and vehicle impedance referred in the technical document referenced in Appendix D.2 Index [A]. Compliance of the unit can be demonstrated based on the technical document referred in Article 13 of CCS TSI and is checked by the Notified Body as part of EC verification.*

*(d2) If the unit has electrical or electronic equipment on board emitting interference electromagnetic fields:*

- *close to the wheel sensor of an axle counter, or*
- *induced by the return current via the rail if applicable.*

*The 'influencing unit' (as defined in the technical document referenced in Appendix D.2 Index [A]) of which the unit is planned to be part shall be compliant with specific cases for axle counters notified under Article 13 of CCS TSI by applying the harmonised vehicle test methods referred in the technical document referenced in appendix D.2 index [A]. Compliance of the unit can be demonstrated based on the technical document referred in Article 13 of CCS TSI and is checked by the Notified Body as part of EC verification.*

See further explanations relative to the Article 13 of CCS TSI in point 2.3.7.

Note: In case electronic equipment according to d1 and/or d2 is on-board in preparation of a future upgrade of the unit, but with the condition of use that it will be switched off, mutual recognition is not impacted.

*(e) The unit must be equipped with the manual coupling system in accordance with the prescriptions set out in Appendix C, Section 1, including the fulfilment of Section 8 or with any semi-automatic or automatic coupling system.*

The requirement was changed to open the possibility for a semi-automatic or automatic coupler. The intention behind the change is to enable the testing of the Digital Automatic Coupler (DAC) in a large scale without the need for multiple authorizations.

### 3.3 Point 7.2.1: Substitution of constituents

*The word ‘check’ in Table 11 means that the entity in charge of maintenance (ECM) may under its responsibility substitute a component by another one utilising the same function and performance in accordance with the relevant TSI requirements...*

When a component is considered as an interoperability constituent (IC) in chapter 5 of the TSI, its use within the context of substitution, renewal and upgrading is set out in point 7.2.1 of the WAG TSI.

The clarification in the TSI about ICs in the context of substitution, renewal and upgrading was necessary because these rules are needed for the WP members to assess whether or not a constituent should be declared as an IC. They are strictly based on the ECM regulation.

Only components corresponding to an IC not holding an EC certificate (non-certified ICs as defined in point 7.2.1 of the TSI), which are produced before or within the transitional period referred to in section 6.3 and indicated in this TSI, are allowed to be used for substitution.

The distinction between ‘component’ and ‘interoperability constituent’ had to be made because the ‘component’ means a tangible part of the subsystem and the ‘interoperability constituent’ is defined by functions.

The text following table 11 in the WAG TSI explains when the ECM has a role to play and what the checks consist of.

### 3.4 Point 7.2.2 Changes to an existing unit or to an existing unit type, point 7.2.2.1 Introduction

*[...] The holder of the vehicle type authorisation shall provide, under reasonable conditions, the information necessary for assessing the changes to the entity managing the change.*

Each entity managing the change needs to ensure, that all relevant information for the intended changes are available before changing any existing rolling stock. If the holder of the type authorisation is not the same as the entity managing the change, the entity managing the change should request the holder of type authorisation all necessary information to perform the change. Contractual arrangements may be needed between the holder of the vehicle type and entity managing the change to facilitate the information needed.

Other possibilities (e.g. that the holder of type authorisation performs the change) are analysed in the guidance to Article 15 of Implementing regulation (EU) 2018/545.

Implementing regulation (EU) 2018/545 requires in case of changes of authorised vehicles that the changes shall be categorised according to its Article 15 (1). Even for the small changes it has to be checked if there is a “deviation from the technical files accompanying the EC declarations for verification for the subsystems”, see Article 15(1)(a) and (b). Therefore, each entity managing the change needs this technical file or all documents related to the change.

Further explanation is provided in the Guidance for the application of Regulation 2018/545.

### 3.5 Point 7.2.2.2: Rules to manage changes in both a unit or a unit type

*The safety judgement mandated in Article 21(12)(b) of Directive (EU) 2016/797 shall cover changes concerning basic parameters of the table of section 3.1, related to all the essential requirements, in particular the requirements “Safety” and “Technical compatibility”*

The general safety judgement mandated in Article 21(12)(b) of Directive (EU) 2016/797 should cover all aspects related to the change. Article 13 of the Commission Implementing Regulation (EU) 2018/545 further explains how the essential requirements ‘safety’ and ‘technical compatibility’ impacted by the change are to be dealt with.

*The replacement of a whole element within a rake of permanently connected elements after a severe damage does not require a conformity assessment against this TSI, as long as the element is identical to the one it replaces. Such element must be traceable and certified in accordance with any national or international rule, or any code of practice widely acknowledged in the railway domain.*

In case of two units each consisting of two permanently connected elements which need to be reconfigured, e.g. due to an accident, it may be possible to form a new unit from two elements of the different units. If the European Vehicle Number (EVN) applies to the whole unit, the EVN of one of the units may be retained without requiring new authorisation.

*In order to establish the EC type or design examination certificate, the notified body selected by the entity managing the change may refer to:*

- *the original EC type or design examination certificate for parts of the design that are unchanged or those that are changed but do not affect the conformity of the subsystem, as far as it is still valid,*
- *additional EC type or design examination certificate (amending the original certificate) for modified parts of the design that affect the conformity of the subsystem with the TSIs referred to in the certification framework defined in point 7.2.3.1.1.*

*In case the validity period of the EC type or design examination certificate for the original type is limited to 10 years (due to the application of the former Phase A/B concept), the validity period of the EC type or design examination certificate for the modified type, type variant or type version shall be limited to 14 years after the date of appointment of a notified body by the applicant for the initial rolling stock type (beginning of phase A of the original EC type or design examination certificate).*

Projects of changes in a unit or a unit type that are ongoing (i.e. in phase A) on 28 September 2023 are to be considered as ongoing projects as specified in the TSI point 7.1.1. Accordingly, the application of the revised TSI isn't mandatory.

The consequence of not-applying the new TSI is that the type certificate will be delivered according to a previous version of the TSI. The EC type examination certificate will be delivered according to that previous version of the TSI (rules in previous version of WAG TSI point 7.2.3).

When applying the new TSI for the modified parts, the EC type examination certificate will be delivered according to the TSI 2023 (rules in point 7.2.3), but its validity will be limited as specified in point 7.2.2.2.

### 3.6 Point 7.2.2.4: Rules for the extension of the area of use for units having an authorisation in accordance with Directive 2008/57/EC or in operation before 19 July 2010

*(1) In the absence of full conformity with this TSI, point 2 applies to units that fulfil the following conditions when requesting an extension of their area of use in accordance with Article 21(13) of Directive (EU) 2016/797:*

*1. they have been authorised in accordance with Directive 2008/57/EC or put in operation before 19 July 2010;*

*2. they are registered with 'Valid' registration code '00', in the National Vehicle Register in accordance with Commission Decision 2007/756/EC ( 11 ) or in the European Vehicle Register in accordance with Commission Implementing Decision (EU) 2018/1614 ( 12 ) and maintained in a safe state of running in accordance with Commission Implementing Regulation (EU) 2019/779 ( 13 ).*

*The following provisions for extension of area of use apply also in combination with a new authorisation as defined in point (a) of Article 14(3) of Regulation (EU) 2018/545.*

The point 7.2.2.4 applies to units that **are not compliant to the TSIs in force** (including all amendments) : TSI NOISE 1304/2014 and TSI WAG 321/2013.

Note. Regarding 7.2.2.4(1), please refer to Vehicle Authorisation guideline (sections 3.11.1.8 evidence concerning previous authorisations and/or 3.11.1.9 Evidence concerning the area of use of vehicles used under RIC/RIV agreements)

*(2) Authorisation for an extended area of use of the units referred to in point 1 shall be based on the existing authorisation, if any, the technical compatibility between the unit and the network in accordance with point (d) of Article 21(3) of Directive (EU) 2016/797 and compliance with the Basic Design Characteristics of Table 11a of this TSI, taking into account any restrictions or limitations.*

*The applicant shall provide an 'EC declaration of verification' accompanied by technical files giving evidence of compliance with the requirements set out in this TSI, or with provisions having equivalent effect, for each basic parameter referred to in column 1 of Table 11a of this TSI, through one or a combination of the following:*

*(a) compliance with requirements of this TSI as referred above;*

*(b) compliance with corresponding requirements set out in a previous TSI as referred above;*

*(c) compliance with alternative specifications deemed to have equivalent effect to the relevant requirements set out in this TSI as referred above;*

*(d) evidence that the requirements for technical compatibility with the network of the extended area of use are equivalent to the requirements for technical compatibility with the network for which the unit is already authorised or in operation. Such evidence shall be provided by the applicant and may be based on the information in the register of railway infrastructure (RINF).*

For the extension of area of use of unit having an authorization in accordance with Directive 2008/57/EC or in operation before 19 July 2010, the basic parameters to be checked correspond mainly to technical compatibility between the rolling stock and the extended area of use.

The basic parameters to be checked are those referred to in point 7.2.2.4 (2) of WAG, and the EC verification procedure shall cover the compliance with the requirements set out in this TSI, or with provisions having equivalent effect, for each basic parameter referred to in point 7.2.2.4 (2).

The table below provides the list of related TSIs basic parameters :

<i>Compliance with requirements defined in following TSIs basic parameters</i>
4.2.2.1.1 End coupling
4.2.3.1 Gauging
4.2.3.2. Compatibility with load carrying capacity of lines
4.2.3.3 Compatibility with train detection systems
4.2.3.4 Axle bearing condition monitoring
4.2.3.5 Running safety
4.2.3.6.2 Characteristics of wheelsets
4.2.3.6.3 Characteristics of wheels
4.2.3.6.6 Automatic variable gauge systems
4.2.4.3.2.1 Service brake
4.2.4.3.2.2 Parking brake
4.2.4.3.3 Thermal capacity
4.2.4.3.4 Wheel slide protection (WSP)
4.2.5 Environmental conditions

The demonstration of compliance of unit with the requirements defined in basic parameters referred to in point 7.2.2.4 (2) can be performed through one or a combination of the following:

- compliance with TSIs in force: in this case the checks are performed by a Notified Body (who shall establish the relevant EC certificates and accompanying file).
- compliance with previous TSIs: in this case, the checks are performed by a Notify Body (who shall establish the relevant EC certificates and accompanying file).
- compliance with alternative specifications deemed to have equivalent effect to the relevant requirements of this TSI: the alternative specifications are proposed by the applicant, they can refer to standards, specifications (e.g UIC 518 regarding running dynamics, UIC 505-1 for vehicle gauge ...). The alternative specifications may have been already used come from the previous authorisation.
- evidence that the requirements for technical compatibility with the network of the extended area of use are equivalent to the requirements for technical compatibility with the network for which the rolling stock is already authorised or in operation.: such evidence may be based on the information of the RINF.

*(3) The equivalent effect of alternative specifications to the requirements of this TSI (point 2(c)) and the equivalence of requirements for technical compatibility with the network (point 2(d)) shall be justified and documented by the Applicant by applying the risk management process set out in Annex I of Regulation (EU) No 402/2013. The applicant shall provide a positive assessment by an assessment body (CSM RA).*

When the demonstration is not based on TSIs requirements (point 7.2.2.4(2)(c) ,point 7.2.2.4 (2)(d)), the independent assessment of conformity is not carried out by a notified body. In that case, when the applicant's demonstration of compliance is based on alternative specifications and/or equivalence of requirements for technical compatibility with the networks:

- The applicant applies the risk management process set out in annex I of regulation 402/2013, justifies and documents for every TSI basic parameter listed in point 7.2.2.4(2) of this TSI that the demonstrations proposed have an equivalent effect to the application of requirements of this TSI.
- The assessment body (CSM RA) assesses the evidences provided by the applicant for every TSI basic parameter listed in in point 7.2.2.4 (2) of this TSI, and confirms the equivalent effect of compliance with alternative specifications and/or the equivalence of requirements for technical compatibility with the network.

Notes: in relation with annex I of regulation 402/2013:

- Alternative specifications correspond to “code of practices”.
- Equivalence of requirements for technical compatibility with the networks correspond to “ use of reference system”.

This requirement on the assessment body (CSM RA) for assessing the capability of existing rolling stock, authorised in accordance with Directive 2008/57/EC or in operation before 19 July 2010, fully matches with both of the following :

- The definition in Article 3(14) and Article 6(1) of Regulation (EU) No 402/2013 on the CSM for risk assessment request the assessment body (CSM RA) to assess the applicant’s risk management process and demonstration that existing rolling stock can be operated safely for the considered extension of the area of use;
- Article 13(1) and 13(3) of regulation 2018/545 regarding the independent assessment by the assessment body (CSM RA) of the applicant’s process for vehicle requirement capture, including thus the applicant’s demonstration of the safe integration of the rolling stock within an extension of the area of use.

Clause I.D of the recommendation for use N°03 (RFU 03) ensures that the assessment body (CSM RA), accredited, or recognised, according to Annex II of Regulation (EU) No 402/2013, has the necessary technical knowledge and competences for carrying out those assessments.

Point 6 in clause IV.E of RFU 03 addresses the capability of the assessment body (CSM RA) to independently assess the applicant’s process for the vehicle requirement capture.

Point 3 of section I.D of RFU 03 explicitly requires that the assessment body (CSM RA) has “... access to a sufficient number of in-house or external railway technical experts, who are fully qualified to provide ... the safety specialists ...” of the assessment body (CSM RA) “... with railway technical opinions/advices on the quality and the robustness of the proposer’s work”.

Note . The task of the AsBo referred above is without prejudice to the AsBo responsibility to independently assess the applicant’s compliance with Article 13(3) of Regulation 2018/545, regarding the applicant’s methodology for the requirements capture of the essential requirements ‘safety’ related to the vehicle and subsystems, as well as safe integration between subsystems.

*(4) In addition to the requirements referred to in point 2 and where applicable, the applicant shall provide an ‘EC declaration of verification’ accompanied by technical files giving evidence of compliance with the following:*

*(a) specific cases relating to any part of the extended area of use, listed in this TSI, TSI NOI and CCS TSI*

*(b) the national rules referred to in points (a), (c) and (d) of Article 13(2) of Directive (EU) 2016/797 as notified in accordance with Article 14 of that Directive.*

The EC declaration of verification and the accompanying files shall also cover:

- The compliance with the relevant specific cases of the extended area of use. The compliance is subject to a Notify Body assessment when the specific cases are described in TSI. Regarding the specific cases in TSI CCS and in relation to point 7.2.2.4.4(4)(a), they are limited to train detection systems and can be found in point 7.7 of TSI CCS.
- The compliance with the national rules on top of TSIs related to:
  - o Open points in the TSIs (article 13(2)(a) of Directive (EU) 2016/797),
  - o Specific cases not described in the TSIs (article 13(2)(b) of Directive (EU) 2016/797),
  - o Technical compatibility of the vehicle with existing network (Article 13(2)(d) of Directive (EU) 2016/797)

The corresponding national rules can be found in the Reference Document Database (RDD) through the report : *List of National Technical Rules – Detailed – Criteria – TSI*. The national rules in addition to TSIs are identified in the column named : “Applicable for authorisation of railway vehicles as defined in Art. 2 of Commission Regulation (EU) No 1302/2014 and Art. 2 of Commission Regulation (EU) No 321/2013”.

  - o The Designated Body assesses compliance of the rolling stock with the national rules referred above.

The applicant is responsible to compile the technical files accompanying the EC declaration of verification that should include evidences of compliance with point 7.2.2.4 of TSI WAG:

- NoBo certificates and accompanying files, when assessment is performed against TSIs,
- Justification and Documentation including AsBo report, when assessment is performed using alternative specification and/or the equivalence of requirements for technical compatibility with the network.
- DeBo certificates and technical files regarding assessment of national rules.

*(5) The authorising entity shall make publicly available through the Agency website details of the alternative specifications referred to in point 2(c) and of the requirements for technical compatibility with the network referred to in point 2(d) on the basis of which it granted authorisations for the extended area of use.*

The Agency should make available through its website a report providing information on alternative specifications and on technical compatibility that may provide equivalent effect to TSI requirements defined in basic parameters referred to in point 7.2.2.4(2) of WAG TSI. The published information will be based on granted authorisations for the extended area of use delivered by the Agency. Information are provided for information purpose, this do not prevent the applicant, for its application, to justify and document the use of alternative specifications and / or equivalence of requirements for technical compatibility as required by points 7.2.2.4 of WAG TSI.

*(6) Where an authorised vehicle benefited from non-application of TSIs or part of them pursuant to Article 9 of Directive 2008/57/EC, the applicant shall seek derogation(s) in the Member States of the extended area of use in accordance to Article 7 of Directive (EU) 2016/797.*

**Non-applications of TSIs are exceptional measures** and non-application decisions have to follow a procedure involving the MS(s) and the Commission. **Non-applications can only be granted for a defined scope** in

relation to identifiable vehicles, a number of vehicles and a defined network of an area of use, in order to ensure compatibility with the non-application cases.

### 3.7 Point 7.2.3.1.1: Rules related to the EC type or design examination certificates - Definitions

*(1) Initial assessment framework*

*The initial assessment framework is the set of TSIs (i.e. this TSI, the NOI TSI) applicable at the beginning of the design phase when the notified body is contracted by the applicant.*

*(2) Certification framework*

*The certification framework is the set of TSIs (i.e. this TSI, the NOI TSI) applicable at the time of issuing the EC type or design examination certificate. It is the initial assessment framework amended with the revisions of TSIs that came into force during the design phase.*

*(3) Design phase*

*The design phase is the period starting once a notified body, which is responsible for EC verification, is contracted by the applicant and ending when the EC type or design examination certificate is issued.*

*A design phase can cover a type and one or several type variant(s) and type version(s). For all type variant(s) and type version(s), the design phase is considered as starting at the same time as for the main type.*

*(4) Production phase*

*The production phase is the period during which rolling stock subsystems may be placed on the market on the basis of an EC declaration of verification referring to a valid EC type or design examination certificate.*

*(5) Rolling stock in operation :*

*Rolling stock is in operation when it is registered with ‘Valid’ registration code ‘00’, in the National Vehicle Register in accordance with Commission Decision 2007/756/EC (1) or in the European Vehicle Register in accordance with Commission Implementing Decision (EU) 2018/1614 (2) and maintained in a safe state of running in accordance with Commission Implementing Regulation (EU) 2019/779.*

The ‘design phase’ as defined in the TSI can basically be compared to the former ‘phase A’ as it has the same starting point (appointment of the NoBo) and ending point (delivery by the NoBo of the EC type certificate or EC design examination certificate). There are however major differences that are:

- The design phase isn’t limited in time, while the phase A was limited to 4 years,
- All TSIs and amendments entering in force during the design phase shall be considered, there is no “freezing” of the requirements as for the former phase A; this is the reason for the categorisation of all TSI changes and of the transition regime defined per TSI change.

At the beginning of the design phase, the ‘initial assessment framework’ is determined, i.e. the set of applicable TSIs and amendments. This initial assessment framework is generally not the same as the ‘certification framework’ which is the set of TSIs and amendments applicable at the end of the design phase (note: both frameworks can be the same only if no applicable TSI or TSI amendment is published during the design phase). Changes made to the TSIs being categorised and listed with an associated transition regime,

the evolution between the initial assessment framework and the certification framework can be traced and documented.

Similarly to the design phase, the ‘production phase’ can be compared to the former ‘phase B’ as it represents the period during which vehicles can be authorised in conformity to the type. However, there is a difference in its duration, as the production phase isn’t limited in time like the phase B was.

### 3.8 Point 7.1.3.1.2: Rules related to the EC type or design examination certificate

- (1) *The notified body shall issue the EC type or design examination certificate referring to the certification framework*
- (2) *When a revision of this TSI or of the TSI Noise comes into force during the design phase, the notified body shall issue the EC type or design examination certificate according to the following rules:*
- *For changes in the TSIs that are not referenced in appendix A, conformity with the initial assessment framework leads to conformity to the certification framework. The Notified Body shall issue the EC type or design examination certificate referring to the certification framework without additional assessment.*
  - *For changes in the TSIs that are referenced in appendix A, their application is mandatory according to the transition regime defined in the appendix. During the defined transition period, the Notified Body may issue the EC type or design examination certificate referring to the certification framework without additional assessment. The Notified Body shall list in the EC type or design examination certificate all the clauses assessed according to the initial assessment framework*

An applicant can decide to upgrade existing certificates to the newest TSIs. In this case, the applicant should consider the possible impact on :

- vehicle authorisation, for example:
  - Is an authorisation needed, is the rolling stock type modified?
  - does the rolling stock modification affect safety or impacts a basic design characteristics, requiring a new authorisation?
- registers as ERADIS, ERATV.

Renewed authorisation : As referred in article 24(3) of Directive 2016/797, renewed authorisation is needed when changes to any relevant provisions in TSIs (or national rules) require that a vehicle type authorisation already granted needs to be renewed (further explanation can be found in the vehicle authorisation guideline).

To illustrate the principles of the new transition regime, several examples are illustrated below.

#### 3.8.1 Example 1


In this example, a project starts in January 2023, and the set of TSIs applicable at that time are identified as TSI n; this is the initial assessment framework as defined in point 7.1.3.1.1 of the TSI.

During the design phase (after 2 years in the example below), new revisions of TSIs enter into force, identified as TSI n+1. These TSIs include a statement that compliance with TSI n implies compliance with TSI n+1 except

for the requirements listed in Appendix A. Those requirements are of two categories: those with a generic transition and those with a specific transition. The first ones will be applicable to the project 7 years after entry into force of TSI n+1 and the second ones will be applicable according to their specific transition regime.

In the example below, the design phase continues for another 2 years before the delivery of the EC type or design examination certificate. At that time, the certification framework is the set of TSIs n+1. As specified in the TSI point 7.1.3.1.2 (see point (1) above), the notified body shall issue the EC type or design examination certificate referring to the certification framework, i.e. TSI n+1, and list in the certificate all requirements for which TSI n was applied, as permitted by the transition regime.

In the example below, for all requirements with a generic transition regime, the requirements of TSI n can still apply because the design phase is ending 2 years only after entry into force of TSI n+1.



EIF Entry into force  
IAF Initial assessment framework  
CF Certification framework

3.8.2 Other examples can be added according to the return of experience– currently left blank intentionally

## 4 APPENDICES OF THE WAG TSI

### 4.1 Appendix C: Additional optional conditions

Appendix C consists of a set of detailed prescriptions of conditions and technical solutions optimised for the free exchange of wagons and its adhered operative regime and maintenance concept of the incumbent railway undertakings.

Next to the compliance with the core TSI requirements in chapter 4 and the fulfilment of the complete set of conditions in point 7.1.2 the wagon may also fulfil the conditions of Appendix C. The fulfilment of the Appendix C conditions is optional and not needed to achieve TSI conformity.

If an applicant chooses for the application of Appendix C the fulfilment of all conditions become mandatory and shall be assessed by a notified body. Appendix C.5 allows for a limited fulfilment where the conditions C.3 and/or C.6 and/or C.7b are excluded.

The responsibility for safe operation and in particular under which conditions a certain wagon can be operated remains always with the transporting RUs. These RUs may decide that particular wagons of the existing fleet could be operated like wagons marked TEN GE or TEN CW. In this case the RUs are free to indicate this in an appropriate way as part of their SMS.

Article 3 of the enacting part of the WAG TSI allows for wagons authorised according to the previous technical specification for interoperability relating to the subsystem ‘rolling stock — freight wagons’ (Decision 2006/861/EC and its amendments) and fulfilling the conditions set out in point 7.6.4 thereof to obtain ‘GE’ marking without any additional assessment or new authorisation for placing in service. Although conditions specified in point 7.6.4 of the previous WAG TSI are not the same as those specified in point 7.1.2 and Appendix C of this WAG TSI, RUs may use the ‘GE’ marking for freight wagons authorised in accordance with both TSIs. The RUs should check the technical file of the wagon in order to verify that the ‘GE’ marking is suitable considering the intended conditions of use of the wagon. In any case, the interpretation of this marking for operational purposes remains under the responsibility of the RUs.

## 4.2 Appendix D – List of referenced standards

Appendix D lists all the clauses of standards that are made mandatory by a direct reference in the TSI. Each natural index number (marked [n]) corresponds to one standard. All occurrences of that standard in the TSI are identified with the marking [n.m].

## 5 PRACTICAL CASES

### 5.1 Example of a unit to carry lorries (‘Rollende Landstrasse’)

In general several units to carry lorries are forming a block train. At each end of the block train the unit is fitted with movable head stocks which are equipped with footsteps and handrails (see Figure 10 and Figure 11).




Figure 10 - Example of a unit to carry lorries ('Rollende Landstrasse') – end vehicle



Figure 11 - Example of a unit to carry lorries ('Rollende Landstrasse') – intermediate vehicles

## 6 TRANSITION PHASES CONCERNING FRICTION ELEMENTS FOR WHEEL TREAD BRAKES

WAG TSI provides transition phases for friction elements for wheel tread brakes.

Before the application of Commission Regulation (EU) 2015/924 fully approved composite brake blocks were listed in Appendix G (in the form of a link to the list of fully approved composite brake blocks for international transport published on the ERA website) and used in case the text of the WAG TSI made a reference to this appendix.

With the application of Commission Regulation (EU) 2015/924 a new interoperability constituent 'friction element for wheel tread brakes' has been created. This interoperability constituent comprises any friction element that acts on wheel's tread including composite brake blocks as well as cast iron brake blocks.

Appendix G will be managed by ERA until the friction elements listed in it are not yet covered by EC declarations of conformity (cf. Article 10). Transition period in Article 8b is provided for friction elements that have already been listed in Appendix G before the application of Regulation 2015/924 in the sense that they are deemed TSI compliant until the end of their current approval period. This transition period should be used by the manufacturer to obtain EC certificate of conformity from a notified body and subsequently to issue EC declaration of conformity.

For obtaining EC certificate of conformity for a friction element for wheel tread brakes the manufacturer or his authorised representative established within the European Union should choose conformity assessment modules according to Table 9 of the WAG TSI. As technical documentation the manufacturer may provide notified body with the proof of compliance to the UIC requirements based on which the friction element has been included in Appendix G plus documentation regarding the manufacturing process. The notified body should make sure among other things that all the parameters specifying the area of use of the friction element according to point 5.3.4a of the WAG TSI are provided by the manufacturer before issuing EC certificate of conformity.

On top of the already explained transition phase for friction elements listed in Appendix G there are two other transition phases concerning components corresponding to the designs of friction elements for wheel tread brakes:

- *components manufactured before the application of Regulation 2015/924 (e.g. according to notified national technical rules) and*
- *components corresponding to Appendix G designs of friction elements and manufactured before the expiry of the approval period.*

For these components transition phase of 10 years is provided for their use in subsystem provided conditions of Article 8a and Article 8c respectively are fulfilled.

This means that since the date of application of Regulation 2015/924 no new friction elements are to be produced according to NNTRs with exception of friction elements intended for substitution in the framework of maintenance.

Since the date of application of Regulation 2015/924 no new friction elements will be newly listed in Appendix G. The reason for that is that since 1st July 2015 an EU procedure for friction elements will be used.

## 6.1 ERA technical document ERA/TD/2013-02/INT

The ERA technical document ERA/TD/2013-02/INT 'Friction elements for wheel tread brakes for freight wagons' published on the ERA website (<http://www.era.europa.eu>) is based on EN 16452:2015 'Railway applications — Braking — Brake blocks'. The tests defined in the technical document are more generic than those of EN 16452:2015, because the technical document cover more braking systems than UIC.

In the following text the link between these two documents is described.

### 6.1.1 Chapter 4 'Dynamic friction coefficient' of the ERA TD

*The dynamometer test program for friction elements for wheel tread brakes to determine the dynamic friction coefficient  $\mu_{dyn}$  is set out in table 1.*

Dynamic friction coefficients and their tolerance bands form part of the parameters that characterise the area of use of the friction element for wheel tread brakes. The dynamometer test programme to determine these values is mandatory within the assessment procedure of friction elements.

Normative Annexes C, D and E and informative Annex J of EN 16452:2015+A1:2019 provide basis for the dynamometer test programme set out in table 1. The dynamometer test programme is generic to allow a wide range of designs of friction elements for wheel tread brakes to be tested.

*During the tests described in table 1 the following conditions shall be respected:*

The conditions to be respected while performing dynamometer test programme to determine the dynamic friction coefficient are set out in the ERA TD. They represent a generalisation of the conditions described in Annex B of EN 16452:2015+A1:2019.

*In relation to the characteristics described in this chapter, in case the manufacturer chooses to apply some of the harmonised acceptance criteria for dynamic friction performance as specified in EN 16452:2015, the compliance to these harmonised acceptance criteria have to be stated in the technical documentation as part of the area of use of the friction element for wheel tread brakes.*

There are no acceptance criteria for dynamic friction coefficients and their tolerance bands specified in the ERA TD. The reasoning behind is to allow for different values of the characterising friction elements' parameters; the values need to be recorded in the technical documentation. Based on these values the applicant can choose the ones that suit the characteristics of his project. The intention is to widen the possible technical solutions pertaining to friction elements in order to allow for a technical development of the sector.

Nevertheless, a link is established with the harmonised acceptance criteria defined in EN 16452:2015 in Annex J.4 of EN 16452:2015+A1:2019. If a friction element fulfils some of these harmonised acceptance criteria and if the manufacturer intends to point out this conformity he can do so in the technical documentation of the friction element.

#### 6.1.2 Chapter 5 'Static friction coefficient' of the ERA TD

*The dynamometer test program to determine the static friction coefficient  $\mu_{stat}$  of friction elements for wheel tread brakes is set out in table 4.*

Minimum static friction coefficient form part of the parameters that characterise the area of use of the friction element for wheel tread brakes. The dynamometer test programme to determine this value is mandatory within the assessment procedure of friction elements.

Annex Q of EN 16452:2015+A1:2019 provides basis for the dynamometer test programme set out in table 4. The dynamometer test programme is generic to allow a wide range of designs of friction elements for wheel tread brakes to be tested.

*For each brake application ( $n^{\circ}$  1 to 20) the static friction coefficient shall be determined which is the value of the instantaneous friction coefficient at the time corresponding to the commencement of sliding (mean value calculated from the measurement records for the intersection between the linearised characteristic line of the rotation angle and the time axis) as described in figure 1.*

The definition of the static friction coefficient corresponds to Annex Q.4.1 of EN 16452:2015+A1:2019.

*During the tests described in table 4 the following conditions shall be respected:*

The conditions to be respected while performing dynamometer test programme to determine the static friction coefficient are set out in the ERA TD. They represent a generalisation of the conditions described in Annex Q.4.3 of EN 16452:2015+A1:2019.

*For each force the average value of the 5 measurements shall be determined. The lowest average value is the characterising static friction coefficient.*

There are no acceptance criteria for static friction coefficient specified in the ERA TD. The reasoning behind is to allow for different values of the characterising friction elements' parameters; the values need to be recorded in the technical documentation. Based on these values the applicant can choose the ones that suit the characteristics of his project. The intention is to widen the possible technical solutions pertaining to friction elements in order to allow for a technical development of the sector.

#### 6.1.3 Chapter 6 'Mechanical characteristics' of the ERA TD

*The mechanical characteristics of the assembly between back plate and friction element for wheel tread brakes shall be tested with the test procedures set out in sections 6.1 and 6.2.*

Mechanical characteristics in respect with the maximum permitted brake forces applied on the friction element form part of the parameters that characterise the area of use of the friction element for wheel tread brakes. The tests to determine these values are mandatory within the assessment procedure of friction elements.

Annex T of EN 16452:2015 provides basis for the shear strength and flexural strength tests described in the ERA TD. These tests use the value of the maximum permissible braking force applied at the friction element to determine its conformity in respect with mechanical characteristics resistance.

#### 6.1.4 Chapter 7 'Suitability for train detection by systems based on track circuits' of the ERA TD

This chapter specifies a rig test programme to determine the suitability of friction elements for wheel tread brakes for train detection by systems based on track circuits. Annex O of EN 16452:2015 provides basis for this test. The demonstration of this suitability within the assessment procedure is not mandatory. Nevertheless, the suitability/non-suitability of the friction element has to be recorded in the technical documentation.

*The following rig test to demonstrate the suitability for train detection by systems based on track circuits is only applicable if the friction element is intended to be used in subsystems which fall under the following scope:*

- *Nominal wheel diameters of 680 mm to 920 mm*
- *Friction element configurations 1Bg, 1Bgu, 2Bg, 2Bgu*
- *Mass per wheel  $\geq 1.8$  t*

The restriction of the scope of the rig test is caused by a lack of experience with testing friction elements of other parameters than those specified. If a manufacturer would like to test such friction element he has to use the procedure for innovative solutions (Article 10a and point 6.1.2.5 of the WAG TSI). Nevertheless, the manufacturer may propose the same rig test as specified in chapter 7 of the ERA TD if he considers that he has already gained sufficient experience to be sure that the test may be used even outside the prescribed scope.

*Cast iron brake blocks are deemed to be suitable for train detection by systems based on track circuits.*

Cast iron brake blocks need not be tested and their suitability for train detection by systems based on track circuits is deemed to be fulfilled.

#### 6.1.5 Chapter 8 'Suitability for severe environmental conditions' of the ERA TD

*The suitability of the friction element acting on wheel tread brakes for severe environmental conditions shall be tested in accordance with the test procedures set out in sections 8.1 or 8.2.*

If the friction element is supposed to be suitable for severe environmental conditions, the demonstration of this suitability is carried out according to chapter 8 of the ERA TD. This chapter provides two possibilities: either a test run (based on Annex M of EN 16452:2015) or a dynamometer test (based on Annex L of EN 16452:2015+A1:2019).

The demonstration of this suitability within the assessment procedure is not mandatory. Nevertheless, the suitability/non-suitability of the friction element has to be recorded in the technical documentation.

*Cast iron brake blocks are deemed to be suitable for severe environmental conditions.*

Cast iron brake blocks need not be tested and their suitability for severe environmental conditions is deemed to be fulfilled.

#### 6.1.6 Section 8.1 'Test run'

*The average braking distances of the 'winter tests' at each speed and the average braking distances of the 'reference tests' shall be determined.*

There are no acceptance criteria specified for the test run. The reasoning behind is to allow for different values of the characterising friction elements' parameters; the values need to be recorded in the technical documentation. Based on these values the applicant can choose the ones that suit the characteristics of his project. The intention is to widen the possible technical solutions pertaining to friction elements in order to allow for a technical development of the sector.

Harmonised acceptance criterion is defined in Annex M.4 of EN 16452:2015+A1:2019. If a friction element fulfils some of these harmonised acceptance criteria the manufacturer can optionally point out this conformity in the technical documentation relating to the friction element.

#### 6.1.7 Section 8.2 'Dynamometer test'

*The dynamometer test program to demonstrate the extreme winter braking properties is set out in table 6 and table 7 and is only applicable if the friction element...*

The restriction of the scope of the dynamometer test is caused by a lack of experience with testing friction elements of other parameters than those specified. If a manufacturer would like to test such friction element he has to use the procedure for innovative solutions (Article 10a and point 6.1.2.5 of the WAG TSI). Nevertheless, the manufacturer may propose the same dynamometer test as specified in section 8.2 of the ERA TD if he considers that he has already gained sufficient experience to be sure that the test may be used even outside the prescribed scope.

*During the tests described in tables 6 and 7 the following conditions shall be respected:*

The conditions to be respected while performing dynamometer test programme to determine the suitability of a friction element for severe environmental conditions are set out in the ERA TD. They represent a generalisation of the conditions described in Annex L.3 of EN 16452:2015.

*The test program shall be carried out three times and the establishment of the suitability shall be done for a maximum test speed of 100 km/h and 120 km/h as follows:*

There are no acceptance criteria specified for the dynamometer test. The reasoning behind is to allow for different values of the characterising friction elements' parameters; the values need to be recorded in the technical documentation. The applicant can choose the ones that suit the characteristics of his project. The intention is to widen the possible technical solutions pertaining to friction elements in order to allow for a technical development of the sector.

Harmonised acceptance criteria are defined in EN 16452: 2015+A1:2019 - Annex L.4. If a friction element fulfils some of these harmonised acceptance criteria the manufacturer can optionally point out this conformity in the technical documentation relating to the friction element.

#### 6.1.8 Chapter 9 'Thermo mechanical characteristics' of the ERA TD

*At the interoperability constituent level (friction element for wheel tread brakes), in case the manufacturer chooses to perform the test to simulate 'locked brake' as specified in EN 16452:2015, the result of this test has to be recorded in the technical documentation as part of the area of use of the friction element for wheel tread brakes.*

Locked brake test is described in Annex N of EN 16452:2015 +A1:2019. The performance of this test by the manufacturer is not mandatory. Please read the guidance in this Application Guide provided for points 4.2.3.6.3 and 4.2.4.3.3 of the WAG TSI.

## 7 APPLICABLE SPECIFICATIONS AND STANDARDS

### 7.1 Explanation of the use of the specifications and standards

For general use of standards in the TSI application guide please refer to the “Guide for the Application of TSIs”

Standards of voluntary use which have been identified during the drafting process of the TSI are listed in the Annex 1, column “Voluntary ref to clause(s) of Standard N”; as far as possible, the clause of the standard which is relevant for the conformity assessment of the TSI requirement should be identified. In addition, the column “Voluntary ref – Purpose” should give a written explanation regarding the purpose of the reference to the standard.

Where relevant, an additional explanation is given in the chapter 2 above.

### 7.2 Annex 1 Voluntary standards

REFERENCE IN THE WAG TSI		VOLUNTARY STANDARD	
Element of the subsystem	Point	Standard reference	Purpose
<b>Structures and mechanical parts</b>	<b>4.2.2</b>		
End coupling	4.2.2.1.1		
Inner coupling	4.2.2.1.2	UIC 572:2011	The fulfilment of UIC 572:2011 gives presumption of conformity with the requirement in clause 4.2.21.2, for UIC couplings designed according to the design operating states considered in the leaflet.
Strength of unit	4.2.2.2 6.2.2.1	EN 15085-5:2023	Where applicable the fulfilment of the verification procedure of the EN 15085-5:2023 gives the presumption of conformity with the requirement in point 6.2.2.1 concerning joint techniques.
Integrity of the unit	4.2.2.3		
<b>Gauging and track interaction</b>	<b>4.2.3</b>		
Gauging	4.2.3.1	EN 15273-2 2013+A1:2016	minimum vertical convex / concave curve radius capability

<i>REFERENCE IN THE WAG TSI</i>		<i>VOLUNTARY STANDARD</i>	
<i>Element of the subsystem</i>	<i>Point</i>	<i>Standard reference</i>	<i>Purpose</i>
Compatibility with load carrying capacity of lines	4.2.3.2		
Compatibility with train detection systems	4.2.3.3		
Axle bearing condition monitoring	4.2.3.4	EN 15437-2:2012+A1:2022	On-board system
Safety against derailment running on twisted track	4.2.3.5.1 6.2.2.2		
Running dynamic behaviour	4.2.3.5.2 6.2.2.3 6.1.2.1		
Derailment detection and actuation function (DDAF)	4.2.3.5.3.4	UIC 541-08:2007, Chapter 1.	Additional information on design specifications regarding purely pneumatic DDAF
Structural design of bogie frame	4.2.3.6.1 6.1.2.1		
Characteristics of wheelsets	4.2.3.6.2 6.1.2.2	EN 13260:2020 clause 2.1	'transmitting the forces and a torque between the fitted elements'
Characteristics of wheels	4.2.3.6.3 6.1.2.3	EN 16452:2015 +A1:2019 EN 13262:2020	locked brake test  end quality of the product
Characteristics of axles	4.2.3.6.4 6.1.2.4	EN 13261:2020	end quality of the product

REFERENCE IN THE WAG TSI		VOLUNTARY STANDARD	
Element of the subsystem	Point	Standard reference	Purpose
Variable gauge systems	4.2.3.6.6	EN 15827:2011	The methodology for the validation of bogie and running gear can be used for some aspects of the validation of the variable gauge systems.
	6.1.2.6	EN 17069-1:2019 Annex G of 'ETH de Material Rodante Ferroviario. Vagones, DGF-MFOM, 2009'	The validation plan defined in the EN 17069-1:2019 or in the Annex G of 'ETH de Material Rodante Ferroviario. Vagones, DGF-MFOM, 2009' could be used as a "code of practice" in order to perform the safety analysis resulting in the definition of the validation plan. The area and conditions of use of this validation plan should be taken into account.
Running gear for manual change of wheelsets	4.2.3.6.7 6.2.2.5:	UIC 430-1:2012 UIC 430-3:1995	interface between the unit and the current facilities carrying out the manual change of wheelsets
<b>Brake</b>	<b>4.2.4</b>		
Safety requirements	4.2.4.2	EN 50126-1:2017 EN 50128:2011 +A1:2019+A2:2020 EN 50129:2018 +AC:2019-04 EN 50367:2020 +A1:2022	
Brake performance - Service brake	4.2.4.3.2.1		
Brake performance - Parking brake	4.2.4.3.2.2		
Thermal capacity	4.2.4.3.3		
Wheel slide protection (WSP)	4.2.4.3.4	UIC 544-1:2014	

<i>REFERENCE IN THE WAG TSI</i>		<i>VOLUNTARY STANDARD</i>	
<i>Element of the subsystem</i>	<i>Point</i>	<i>Standard reference</i>	<i>Purpose</i>
Friction elements for wheel tread brakes	4.2.4.3.5 6.1.2.5	EN16452:2015+A1:2019	non-mandatory locked brake test
<b>Environmental conditions</b>	<b>4.2.5</b>		
Environmental conditions	4.2.5 6.2.2.7		
<b>System protection</b>	<b>4.2.6</b>		
Fire safety – - Barriers	4.2.6.1.2.1 6.2.2.8.1	UIC 430-1:2012 UIC 543:2018	The fulfilment of UIC leaflets 430-1:2012 and 543:2018 gives presumption of conformity with the requirement in point 4.2.6.1.2.2, for providing protection to the area above the brake blocks (e.g. wooden floor and running gear) in wagons fitted with cast iron wheel tread brakes
Fire safety - Materials	4.2.6.1.2.2 6.2.2.8.2		
Fire safety - Cables	4.2.6.1.2.3 6.2.2.8.3		
Fire safety - Flammable liquids	4.2.6.1.2.4 6.2.2.8.4		
Protection against electric hazard	4.2.6.2		
Attachment devices for rear-end signal	4.2.6.3		
<b>Operating rules</b>	<b>4.4</b>		
<b>Maintenance rules</b>	<b>4.5</b>		

<i>REFERENCE IN THE WAG TSI</i>		<i>VOLUNTARY STANDARD</i>	
<i>Element of the subsystem</i>	<i>Point</i>	<i>Standard reference</i>	<i>Purpose</i>
<b>General - Marking</b>	-		
<b>Longitudinal compressive forces</b>	-	EN 15839:2012+A1:2015	Pass/fail criteria of longitudinal compressive forces effects for certain design of wagons and under certain operative regimes.
<b>Health and Safety conditions</b>	<b>4.5</b>		
		clause 6.2.1 of EN 16116-2: 2021	free space for shunter
		UIC 535-2:2006	Protective devices
		EN 16116-2:2021	Footsteps and handrails
<b>Parameters to be recorded in the technical file and European register of authorised types of vehicles</b>	<b>4.8</b>		
		EN15528:2021	position of the axle along the unit and number of axles
<b>Implementation</b>	<b>7</b>		
<b>Mutual recognition of the first authorisation for placing on the market</b>	<b>7.1.2:</b>	EN15877-1: 2012+A1:2018	Markings (see also Annex 2 of this guide)
<b>2.10. ERA technical document</b>	<b>ERA/TD/2013-02/INT</b>		

<i>REFERENCE IN THE WAG TSI</i>		<i>VOLUNTARY STANDARD</i>	
<i>Element of the subsystem</i>	<i>Point</i>	<i>Standard reference</i>	<i>Purpose</i>
<b>Dynamic friction coefficient</b>	<b>4</b>	EN16452:2015+A 1:2019 EN16452:2015+A 1:2019 EN16452:2015+A 1:2019 EN16452:2015+A 1:2019	
<b>Suitability for severe environmental conditions</b>	<b>8</b>	EN16452:2015+A 1:2019	tests
<b>Thermo mechanical characteristics</b>	<b>9</b>	EN16452:2015+A 1:2019	

### 7.3 Annex 2 Guidance on marking

The table below provides further guidance on wagon markings taking into account the provisions laid down in WAG TSI, in particular with the view on the markings 'GE', 'CW' and the gauge marking according to clause 4.5.2 of EN 15877-1:2012.

<i>COLUMN</i>	<i>A</i>	<i>B</i>	<i>C 1</i>	<i>C 2</i>
Requirement	Fulfils section 4.2 of the TSI	Fulfils column A and point 7.1.2 of the TSI	Fulfils columns A and B and complete Appendix C of the TSI	Fulfils columns A and B and partly Appendix C of the TSI (see condition C.5)
Interoperability marking	Authorisation plate	TEN	TEN GE	TEN CW
Additional gauge marking(s)	Section 4.2 does not require a specific gauge marking	Point 7.1.2 (d): 'The reference profile must be allocated to one of the target reference profile(s) G1, GA, GB and GC including those used for the lower part GI1 and GI2.'  Point 7.1.2 (h): 'The unit must be marked with all applicable markings in accordance with EN 15877-1:2012 [...]'  EN 15877-1:2012, clause 4.5.2, requires the new gauge marking with 3 gauges defined in the keys. Key 1 is one of those required in point 7.1.2 of the TSI. Key 2 could be the same as key 1 or a smaller national or multinational gauge (e.g. G2). Key 3 is always the lower gauge.	In accordance with EN 15877-1:2012, clause 4.5.2:  Key 1 = G1  Key 2 = G1 or smaller national or multinational gauge abbreviation in accordance with EN 15273-2:2013  Key 3 = GI1	Alternative 1 (criterion C.6 fulfilled):  In accordance with EN 15877-1:2012, clause 4.5.2:  Key 1 = G1  Key 2 = key 1 or smaller national or multinational gauge abbreviation in accordance with EN 15273-2:2013  Key 3 = GI1  Alternative 2 (criterion C.6 not fulfilled):  In accordance with EN 15877-1:2012, clause 4.5.2:  Key 1 = GA or GB or GC  Key 2 = key 1 or smaller national or multinational gauge abbreviation in accordance with EN 15273-2:2013  Key 3 = GI1 or GI2
First digit EVN	4 or 8	4 or 8	0 or 1 or 2 or 3	4 or 8

Additional guidance is available in the document 'Wagon Markings – Guidelines' available in the GCU webpage: <https://gcubureau.org/recommendations/>

*(Note: version applicable at publication of this application guide: v 3.0 of 11 May 2016)*