


ERTMS 2024 Conference Workshop (WS) #10b:

„How can ETCS braking curves be adapted to a more realistic behaviour of the rolling stock?“


WS Leads:



Jakub Marek (AŽD, UNISIG) &



Maarten Bartholomeus (ProRail, EUG)



WS description/aim:

The aim of this workshop is to inform about **generic changes** on the adaptation of **ETCS Braking curves (BC) to better reflect real train behaviour**. We will look at the **changes** already **performed** and finalised for **Baseline 4 Release 1 (SV 3.0) in the CCS TSI 2023** as well as the ones already **identified and logged** into the ERTMS Change Requests' database, with the aim to **possibly** further **improve** the **performance** of the overall system (including the possibility to remove/minimise the need for usage of Release Speed when approaching the End of Movement Authority) **or** the **ergonomics** of the associated display towards the driver.

High-level description of such changes, including **videos/simulations** of possible solutions, **will be provided, followed by a short discussion**. However, experience is also demonstrating that some of the **issues** are **related to the configuration of vehicles** in order to meet the model parameters. Therefore, the discussion part will also focus on sharing experience about the setting-up of vehicles. It will be an excellent opportunity for participants to share further concerns or verified less known issues.

Braking curves WS #10b content

15:00-15:05

- Introduction of the WS & to the BC

15:05-15:15

- Why is **ETCS** a **very useful ATP** to supervise the train's movement?

- besides **interoperability**, safe and **continuous speed/distance supervision**

15:15-15:30

- What has been **done/optimised in B4R1** (SV 3.0)?

- reduction of the eq. brake build-up time (t_e), corresponding to the ΔV (CR1344)










15:30-16:15

- What **can still be done to improve** the performance **in the future** releases?

- How can the **actual deceleration** be **taken into account** during braking? (CR1385)
- How can the **worst-case gradient** under the train be **avoided**? (CR874, CR1435)
- Can the presented permitted speed displayed to the driver be improved?
 - Issue 1 „**falling hook effect of permitted speed**“ (ALE CSG V_P_DMI CR, CR1401)
 - Issue 2 „**fluctuating permitted speed**“ (Jumping V_P on DMI CR)
- Can **reduced adhesion** handling be improved? (CR1343)

16:15-16:30

- Topical discussion & WS conclusions



Braking curves WS #10b content

15:00-15:05

- Introduction of the WS & to the BC

15:05-15:15

- Why is **ETCS** a **very useful ATP** to supervise the train's movement?

- besides **interoperability**, safe and **continuous speed/distance supervision**

15:15-15:30

- What has been **done/optimised in B4R1** (SV 3.0)?

- reduction of the eq. brake build-up time (t_e), corresponding to the ΔV (CR1344)










15:30-16:15

- What **can still be done to improve** the performance **in the future** releases?

- How can the **actual deceleration** be **taken into account** during braking? (CR1385)
- How can the **worst-case gradient** under the train be **avoided**? (CR874, CR1435)
- Can the presented permitted speed displayed to the driver be improved?
 - Issue 1 „**falling hook effect of permitted speed**“ (ALE CSG V_P_DMI CR, CR1401)
 - Issue 2 „**fluctuating permitted speed**“ (Jumping V_P on DMI CR)
- Can **reduced adhesion** handling be improved? (CR1343)

16:15-16:30

- Topical discussion & WS conclusions



Braking curves WS #10b content

15:00-15:05

- Introduction of the WS & to the BC

15:05-15:15

- Why is **ETCS** a **very useful ATP** to supervise the train's movement?
 - besides interoperability, safe and continuous speed/distance supervision

15:15-15:30






- What has been **done/optimised in B4R1** (SV 3.0)?
 - reduction of the eq. brake build-up time (t_e), corresponding to the ΔV (CR1344)

15:30-16:15





- What **can still be done to improve** the performance **in the future** releases?
 - How can the **actual deceleration** be **taken into account** during braking? (CR1385)
 - How can the **worst-case gradient** under the train be **avoided**? (CR874, CR1435)
 - Can the presented permitted speed displayed to the driver be improved?
 - Issue 1 „**falling hook effect of permitted speed**“ (ALE CSG V_P_DMI CR, CR1401)
 - Issue 2 „**fluctuating permitted speed**“ (Jumping V_P on DMI CR)
 - Can **reduced adhesion** handling be improved? (CR1343)

16:15-16:30

- Topical discussion & WS conclusions



[S+D (112) 3 a 6/2020]



Braking curves WS #10b content

15:00-15:05

- Introduction of the WS & to the BC

15:05-15:15

- Why is **ETCS** a **very useful ATP** to supervise the train's movement?
 - besides **interoperability**, safe and **continuous speed/distance supervision**

15:15-15:30

- What has been **done/optimised in B4R1** (SV 3.0)?

- reduction of the eq. brake build-up time (t_e), corresponding to the ΔV (CR1344)










15:30-16:15

- What **can still be done to improve** the performance **in the future** releases?

- How can the **actual deceleration** be **taken into account** during braking? (CR1385)
- How can the **worst-case gradient** under the train be **avoided**? (CR874, CR1435)
- Can the presented permitted speed displayed to the driver be improved?
 - Issue 1 „**falling hook effect of permitted speed**“ (ALE CSG V_P_DMI CR, CR1401)
 - Issue 2 „**fluctuating permitted speed**“ (Jumping V_P on DMI CR)
- Can **reduced adhesion** handling be improved? (CR1343)

16:15-16:30

- Topical discussion & WS conclusions



Braking curves WS #10b content

15:00-15:05

- Introduction of the WS & to the BC

15:05-15:15

- Why is **ETCS** a **very useful ATP** to supervise the train's movement?
 - besides **interoperability**, safe and **continuous speed/distance supervision**

15:15-15:30

- What has been **done/optimised in B4R1** (SV 3.0)?

- reduction of the eq. brake build-up time (t_b), corresponding to the ΔV (CR1344)






15:30-16:15

- What **can still be done to improve** the performance **in the future** releases?





- How can the **actual deceleration** be **taken into account** during braking? (CR1385)
- How can the **worst-case gradient** under the train be **avoided**? (CR874, CR1435)
- Can the presented permitted speed displayed to the driver be improved?
 - Issue 1 „**falling hook effect of permitted speed**“ (ALE CSG V_P_DMI CR, CR1401)
 - Issue 2 „**fluctuating permitted speed**“ (Jumping V_P on DMI CR)
- Can **reduced adhesion** handling be improved? (CR1343)

16:15-16:30

- Topical discussion & WS conclusions



[S+D (112) 3 a 6/2020]



Braking curves WS #10b content

15:00-15:05

- Introduction of the WS & to the BC

15:05-15:15

- Why is **ETCS** a **very useful ATP** to supervise the train's movement?
 - besides **interoperability**, safe and **continuous speed/distance supervision**

15:15-15:30

- What has been **done/optimised in B4R1** (SV 3.0)?

- reduction of the eq. brake build-up time (t_b), corresponding to the ΔV (CR1344)






15:30-16:15

- What **can still be done to improve** the performance **in the future** releases?

- How can the **actual deceleration** be **taken into account** during braking? (CR1385)
- How can the **worst-case gradient** under the train be **avoided**? (CR874, CR1435)
- Can the presented permitted speed displayed to the driver be improved?
 - Issue 1 „**falling hook effect of permitted speed**“ (ALE CSG V_P_DMI CR, CR1401)
 - Issue 2 „**fluctuating permitted speed**“ (Jumping V_P on DMI CR)
- Can **reduced adhesion** handling be improved? (CR1343)

16:15-16:30

- Topical discussion & WS conclusions



[S+D (112) 3 a 6/2020]

