




AŽD Praha s.r.o.

How can the braking curves be adapted to a more realistic behaviour of the rolling stock?

Jakub Marek

UNISIG Braking curves TF Leader, representing the AŽD Praha company


UNISIG Super Group Leader, representing the AŽD Praha company




B4R1 (reduced envelope up to SV 2.2/2.1) or B3R2

- Will this train be further braked by the B3R2 ERTMS/ETCS OBU?


Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?



Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?



Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?




Will this train be braked by the B3R2 ETCS OBU?



Will this train be braked by the B3R2 ETCS OBU?



Will this train be braked by the B3R2 ETCS OBU?




B4R1 (reduced envelope up to SV 2.2/2.1) or B3R2

■ Will this train be further braked by the B3R2 ERTMS/ETCS OBU?

– Yes, it will 😞


– What can be done?

- OVL by construction (on the line)
- OVL by logic (in IXL)
- RS (computed by OBU OR given from the TRK) (+ OVL)
- Improving BC computations (the train can also already be braking) 😊



NOTE: We can also try to derive this with the audience; i.e., to remove it from here.


Will this train be braked by the B3R2 ETCS OBU?






19


Will this train be braked by the B3R2 ETCS OBU?



Release speed (RS) 40 km/h – possible risk (H0001)




Will this train be braked by the B3R2 ETCS OBU?




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs



CR1385 (better handling with the measured decel.)

- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs




CR1385 (better handling with the measured decel.)



How can the braking curves be adapted to a more realistic behaviour of the RST?
» Better consideration of the actual train's deceleration (CR1385) «

CR1385 (better handling with the measured decel.)


- Principle: For the trains braking enough (A_{est}), remove the ETCS BCs



Thank you for your attention!

J. Marek

marek.jakub@azd.cz



Žirovnická 3146/2, Záběhlice, 106 00 Praha 10

www.azd.cz